

FCC 47 CFR PART 18 TEST REPORT

Test Report No. : OT-239-RED-020

Reception No. : 2308002781

Applicant : LG Electronics USA, Inc.

Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, 07632, United States

Manufacturer : LG Electronics USA, Inc.

Address : 170, Seongsanpaechong-ro, Seongsan-gu, Changwon-si, Gyeongsangnam-do 51533 Korea

Type of Equipment : HOUSEHOLD ELECTRIC RANGE

Model Name : LSIL6336FE

Multiple Model Name : LSIL6336*E

FCC ID. : BEJS47413HB

Serial number : N/A

Total page of Report : 7 pages (including this page)

Date of Incoming : August 29, 2023

Date of Issuing : September 06, 2023

summary

The equipment complies with the requirement of FCC CFR 47 PART 18(§ 18.313).

This test report contains only the results of a single test of the sample supplied for the examination.

It is not a general valid assessment of the features of the respective products of the mass-production.

 $This \ report \ is \ not \ correlated \ with \ the \ ''KS \ Q \ ISO/IEC \ 17025 \ and \ KOLAS \ accreditation'' \ of \ Korean \ Laboratory \ Accreditation \ Scheme.$

Reviewed by:

Sun-Teak, Oh / Manager EMC Testing Div.

ONETECH Corp.

Approved by:

Seung-Hyun, Park / Senior Manager

Report No.: OT-239-RED-020

EMC Testing Div. ONETECH Corp.





CONTENTS

| | PAGE |
|---|------|
| 1. VERIFICATION OF COMPLIANCE | 4 |
| 2. GENERAL INFORMATION | 5 |
| 2.1 PRODUCT DESCRIPTION | 5 |
| 2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT. | 5 |
| 3. EUT MODIFICATIONS | 5 |
| 4. SUMMARY OF TEST RESULTS | 6 |
| 4.1 Test Equipment used. | |





Revision History

| Rev. No. | Issue Report No. | Issued Date | Revisions | Section Affected |
|----------|------------------|--------------------|-----------------|------------------|
| 0 | OT-239-RED-020 | September 06, 2023 | Initial Release | All |
| | | | | |
| | | | | |

^{*} Please contact us (e-mail: info@onetech.co.kr) for verification of this test report.





1. VERIFICATION OF COMPLIANCE

| APPLICANT | LG Electronics USA, Inc. 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, 07632, United States | |
|--------------|---|--|
| MANUFACTURER | LG Electronics USA, Inc. 170, Seongsanpaechong-ro, Seongsan-gu, Changwon-si, Gyeongsangnam-do 51533 Korea | |
| FACTORY | LG Electronics USA, Inc. 170, Seongsanpaechong-ro, Seongsan-gu, Changwon-si, Gyeongsangnam-do 51533 Korea | |

| E.U.T. DESCRIPTION | HOUSEHOLD ELECTRIC RANGE |
|---|-----------------------------|
| MEASUREMENT PROCEDURES | MP-5: 1986 |
| TYPE OF EQUIPMENT TESTED | Pre-Production |
| KIND OF EQUIPMENT AUTHORIZATION REQUESTED | Certification |
| STANDARDS | FCC Part 18, Section 18.313 |
| MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE | None |
| FINAL TEST WAS CONDUCTED ON | 10 m semi anechoic chamber |

ONETECH Corp. tested the above equipment in accordance with the requirements set forth in the above standard. The test results show that equipment tested is capable of demonstrating compliance with the requirements as documented in this report.



2. GENERAL INFORMATION

2.1 Product Description

The LG Electronics USA, Inc., Model LSIL6336FE (referred to as the EUT in this report) is a HOUSEHOLD ELECTRIC RANGE. The product specification described herein was obtained from product data sheet or user's manual.

| CHASSIS TYPE | Metal & Plastic |
|--|---|
| Temperature Range | -40 °C ~ +85 °C |
| LIST OF EACH OSC. or CRY. FREQ. (FREQ. >= 1 MHz) | 10 MHz |
| RF OPERATING FREQUENCY | Wi-Fi 2.4 GHz (Wi-Fi Module Model: LCWB-001) * Wi-Fi Module FCC ID: BEJ-LCWB001 |
| NUMBER OF PCB LAYERS | - |
| P. C. Board name | - |
| Induction cooking range Operating frequency (ISM frequency band) | 26 kHz ~ 75 kHz |
| ELECTRICAL RATING | 120/240 V, 11.9k W Or 120/208 V, 10.2 kW/ 60 Hz |
| EXTERNAL CONNECTOR | AC IN |

2.2 Alternative type(s)/model(s); also covered by this test report.

| LSIL6336FE, LSIL6336*E | | | |
|------------------------|-------------------|--------------------|--|
| Variable | Range of variable | Content | |
| 1st '*' | A to Z | Cosmetic features. | |

3. EUT MODIFICATIONS

-. None





4. Summary of Test Results

Test Date: August 31, 2023

4.1 Test Equipment used

| | Model Number | Manufacturer | Description | Serial Number | Last Cal. (Interval) |
|-----|--------------|--------------------|---------------|---------------|----------------------|
| ■ - | ESW 44 | Rohde & Schwarz | Test Receiver | 101851 | Mar. 07, 2023 (1Y) |
| ■ - | CO3000 | Innco Systems GmbH | Controller | N/A | N/A |
| ■ - | DT5000 | Innco Systems GmbH | Turn Table | N/A | N/A |
| ■ - | HLA 6121 | TESEQ | Loop Antenna | 50841 | Apr. 13, 2022 (2Y) |

All test equipment used is calibrated on a regular basis.



-. 18.313 Radio frequency exposure requirements

1.1307 (b)(3)(ii)(A)

The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those is paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

-. 447498 D04 Interim General RF Exposure Guidance v01

2.2.1 1-mW Test Exemption for Multiple Sources

As discussed in § 1.1307(b)(3)(ii)(A), the 1-mW exemption intended for single transmitters may be also applied to simultaneous transmission conditions, within the same host device, according one of the following criteria:

a) When maximum available power each individual transmitting antenna within the same time averaging period is ≤ 1 mW, and the nearest parts of the antenna structures of the simultaneously operating transmitters are separated by at least 2 cm.

b) When the aggregate maximum available power of all transmitting antennas is $\leq 1 \text{ mW}$ in the same

time-averaging period. This exemption may not be combined with any other exemption.

| Elements | Highest Emissions @ 10m [dBuV/m] | EIRP [dBm] | EIRP [mW] |
|-----------|----------------------------------|------------|-----------|
| Element 1 | 67.2 | -17.57 | 0.017 |
| Element 2 | 67.7 | -17.07 | 0.020 |
| Element 3 | 67.7 | -17.07 | 0.020 |
| Element 4 | 66.7 | -18.07 | 0.016 |

These values are most conservative values based on measured emission regardless voltage and polarization

 $EIRP[dBm] = E \left[dB\mu V/m \right] + 20 \log \left(10 \left[m \right] \right) \text{ - } 104.77$

Aggregated maximum power = 0.017 + 0.020 + 0.020 + 0.016 = 0.073 mW

Therefore, 1mW test exemption can be applied and this device complies 18.313 requirement in accordance with 1.1307(b)(3)(ii)(A).

It should not be reproduced except in full, without the written approval of ONETECH Corp.