

# TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: BEJTL1R22NR

Equipment Under Test : Telematics  
Model Name : TL1R22NR  
Variant Model Name(s) : Refer to the page 3  
Applicant : LG Electronics USA  
Manufacturer : LG Electronics Inc.  
Date of Receipt : 2022.11.04  
Date of Test(s) : 2022.11.04 ~ 2022.12.26  
Date of Issue : 2022.12.26

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.


- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
- 3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
- 4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.

We are responsible for all the information of this test report except for the data(※) provided by the customer.

Tested by:

  
Murphy Kim

Technical  
Manager:

  
Jinhyoung Cho

**SGS Korea Co., Ltd. Gunpo Laboratory**



# INDEX

<u>Table of Contents</u>	Page
1. General Information -----	3
2. RF Exposure Evaluation -----	6



**SGS Korea Co., Ltd.**

4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807  
Tel. +82 31 428 5700 / Fax. +82 31 427 2370  
<http://www.sgsgroup.kr>

## 1. General Information

### 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Telephone : +82 31 688 0901

FAX : +82 31 688 0921

### 1.2. Details of Applicant

Applicant : LG Electronics USA

Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, United States,  
07632

Contact Person : Kim, Sung-soo

Phone No. : +1 201 266 2215

### 1.3. Details of Manufacturer

Company : LG Electronics Inc.

Address : 10, Magokjungang 10-ro, Gangseo-gu, Seoul, Korea, 07796

### 1.4. Description of EUT

<b>Kind of Product</b>	Telematics
<b>Model Name</b>	TL1R22NR
<b>Variant Model Names</b>	TL1R22NE
<b>Serial Number</b>	352162110229030
<b>Power Supply</b>	DC 12.5 V
<b>Rated Power</b>	GSM 850: 33 dB m GSM 1 900: 30 dB m WCDMA II, IV, V: 24 dB m LTE Band 2, 4, 5, 7, 12, 17, 26, 41: 23 dB m
<b>Frequency Range</b>	GSM 850: 824 MHz ~ 849 MHz GSM 1 900: 1 850 MHz ~ 1 910 MHz WCDMA II: 1 850 MHz ~ 1 910 MHz WCDMA IV: 1 710 MHz ~ 1 755 MHz WCDMA V: 824 MHz ~ 849 MHz LTE Band 2: 1 850 MHz ~ 1 910 MHz LTE Band 4: 1 710 MHz ~ 1 755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2 500 MHz ~ 2 570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 17: 704 MHz ~ 716 MHz LTE Band 26(Part 90): 814 MHz ~ 824 MHz LTE Band 26(Part 22): 824 MHz ~ 849 MHz LTE Band 41: 2 496 MHz ~ 2 690 MHz
<b>Modulation Technique</b>	QPSK, 16QAM
<b>Antenna Type</b>	External antenna
<b>Antenna Gain※</b>	699 MHz ~ 716 MHz: -0.2 dB i 704 MHz ~ 716 MHz: -0.2 dB i 814 MHz ~ 824 MHz: -0.3 dB i 824 MHz ~ 849 MHz: -0.6 dB i 1 710 MHz ~ 1 755 MHz: 2 dB i 1 850 MHz ~ 1 910 MHz: 2.8 dB i 2 500 MHz ~ 2 570 MHz: 5 dB i 2 496 MHz ~ 2 690 MHz: 5 dB i
<b>H/W Version</b>	Rev.D
<b>S/W Version</b>	v001.039.026

**1.5. Test Report Revision**

Revision	Report Number	Date of Issue	Description
0	F690501-RF-RTL003661	2022.12.26	Initial

**1.6. Information of Variant Model**

Model Name		Description
Basic Model	TL1R22NR	Fully mounted module on hardware.
Variant Model	TL1R22NE	Band 21 duplexer, PA are removed.

**- Supported Cellular Band**

MODEL	GSM	WCDMA	LTE
TL1R22NR	GSM850, PCS1900	B2, B4, B5	B2, B4, B5, B7, B12, B17, B26, B41
TL1R22NE	N/A	B2, B4, B5	B2, B4, B5, B7, B12, B17

\*Difference between two models does not affect bands that can be used in the US.

## 2. RF Exposure Evaluation

### 2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	≤ 6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	<6
30-300	61.4	0.163	1.0	<6
300-1 500	-	-	f/300	<6
1 500-100 000	-	-	5	<6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
<b><u>300-1 500</u></b>	-	-	<b><u>f/1500</u></b>	<b><u>&lt;30</u></b>
<b><u>1 500-100 000</u></b>	-	-	<b><u>1.0</u></b>	<b><u>&lt;30</u></b>

#### 2.1.1. Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where  $P_d$  = power density in  $mW/cm^2$

$P_{out}$  = output power to antenna in  $mW$

$G$  = gain of antenna in linear scale

$R$  = distance between observation point and center of the radiator in  $cm$

$P_d$  the limit of MPE,  $1 mW/cm^2$ . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

### 2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data  
 Test Mode : Normal Operation

### 2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

#### GSM 850

##### - Maximum tune up tolerance

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Antenna Gain (dB i)	Duty Cycle (%)	Power Density at 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
824 ~ 849	33.0	2.5	35.5	-0.6	25.0	0.153 699	0.549 333

#### GSM 1 900

##### - Maximum tune up tolerance

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Antenna Gain (dB i)	Duty Cycle (%)	Power Density at 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
1 850 ~ 1 910	30.0	2.5	32.5	2.8	25.0	0.168 527	1

#### WCDMA - Band II

##### - Maximum tune up tolerance

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
1 850 ~ 1 910	24.0	1.7	25.7	2.8	0.140 841	1

#### WCDMA IV

##### - Maximum tune up tolerance

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
1 710 ~ 1 755	24.0	1.7	25.7	2	0.117 147	1

#### WCDMA - Band V

##### - Maximum tune up tolerance

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
824 ~ 849	24.0	1.7	25.7	-0.6	0.064 377	0.549 333

**LTE Band 2**
**- Maximum tune up tolerance**

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
1 850 ~ 1 910	23.0	2.7	25.7	2.8	0.140 841	1

**LTE Band 4**
**- Maximum tune up tolerance**

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
1 710 ~ 1 755	23.0	2.7	25.7	2	0.117 147	1

**LTE Band 7**
**- Maximum tune up tolerance**

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
2 500 ~2 570	23.0	2.7	25.7	5	0.233 738	1

**LTE Band 12/17**
**- Maximum tune up tolerance**

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
699 ~ 716	23.0	2.7	25.7	-0.2	0.070 588	0.466

**LTE Band 26/5\_Part 22**
**- Maximum tune up tolerance**

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
824 ~ 849	23.0	2.7	25.7	-0.6	0.064 377	0.549 333

**LTE Band 26\_Part 90**
**- Maximum tune up tolerance**

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
814 ~ 824	23.0	2.7	25.7	-0.3	0.068 981	0.542 667



**LTE Band 41**

**- Maximum tune up tolerance**

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
2 496 ~ 2 690	23.0	2.7	25.7	5	0.233 738	1

**Note;**

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 cm between the radiator and your body.
- The antenna gain of this transmitter is less than 6 dB i and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.
- According to KDB 447498 D01 RF Exposure Guidance 4.1.
- Maximum average target power is the manufacturer's declared rated power.
- Maximum average output power = Maximum average power target power (dB m) + Maximum tune up (dB).

**- End of the Test Report -**