


LTE band 4




1.4 MHz Low Channel - Full RB

3 MHz Low Channel - Full RB



1.4 MHz Middle Channel - Full RB


3 MHz Middle Channel - Full RB



1.4 MHz High Channel - Full RB

3 MHz High Channel - Full RB

LTE band 4



LTE band 4



15 MHz Low Channel - Full RB



20 MHz Low Channel - Full RB




15 MHz Middle Channel - Full RB



20 MHz Middle Channel - Full RB




15 MHz High Channel - Full RB



20 MHz High Channel - Full RB

LTE band 7



LTE band 7



15 MHz Low Channel - Full RB



20 MHz Low Channel - Full RB



15 MHz Middle Channel - Full RB



20 MHz Middle Channel - Full RB



15 MHz High Channel - Full RB



20 MHz High Channel - Full RB

LTE band 12



1.4 MHz Low Channel - Full RB



3 MHz Low Channel - Full RB



1.4 MHz Middle Channel - Full RB



3 MHz Middle Channel - Full RB



1.4 MHz High Channel - Full RB



3 MHz High Channel - Full RB

LTE band 12/17




5 MHz Low Channel - Full RB

10 MHz Low Channel - Full RB



5 MHz Middle Channel - Full RB

10 MHz Middle Channel - Full RB



5 MHz High Channel - Full RB

10 MHz High Channel - Full RB

LTE band 26/5_Part 22



1.4 MHz Low Channel - Full RB



3 MHz Low Channel - Full RB



1.4 MHz Middle Channel - Full RB



3 MHz Middle Channel - Full RB



1.4 MHz High Channel - Full RB



3 MHz High Channel - Full RB

LTE band 26/5_Part 22



5 MHz Low Channel - Full RB



10 MHz Low Channel - Full RB



5 MHz Middle Channel - Full RB



10 MHz Middle Channel - Full RB



5 MHz High Channel - Full RB



10 MHz High Channel - Full RB

LTE band 26_Part 22



15 MHz Low Channel - Full RB



15 MHz High Channel - Full RB

LTE band 26 Part 90




1.4 MHz Low Channel - Full RB

3 MHz Low Channel - Full RB



1.4 MHz Middle Channel - Full RB

3 MHz Middle Channel - Full RB



1.4 MHz High Channel - Full RB

3 MHz High Channel - Full RB

LTE band 26_Part 90



5 MHz Low Channel - Full RB



5 MHz Middle Channel - Full RB



5 MHz High Channel - Full RB



10 MHz Middle Channel - Full RB



15 MHz Middle Channel - Full RB

LTE band 41




5 MHz Low Channel - Full RB

10 MHz Low Channel - Full RB



5 MHz Middle Channel - Full RB

10 MHz Middle Channel - Full RB



5 MHz High Channel - Full RB

10 MHz High Channel - Full RB

LTE band 41



15 MHz Low Channel - Full RB

20 MHz Low Channel - Full RB



15 MHz Middle Channel - Full RB

20 MHz Middle Channel - Full RB



15 MHz High Channel - Full RB

20 MHz High Channel - Full RB

6. Spurious Emissions at Antenna Terminal


6.1. Limit

- §22.917(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.
- §24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.
- §27.53(g), the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB.
- §27.53(h)(1), for operations in the 1 695-1 710 MHz, 1 710-1 755 MHz, 1 755-1 780 MHz, 1 915-1 920 MHz, 1 995-2 000 MHz, 2 000-2 020 MHz, 2 110-2 155 MHz, 2 155-2 180 MHz, and 2 180-2 200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB.
- §27.53(m)(4), for mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log_{10} (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log_{10} (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log_{10} (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that $43 + 10 \log_{10} (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log_{10} (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.
- §90.691(a), out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:
 - (1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \text{Log}_{10} (f / 6.1)$ decibels or $50 + 10 \text{Log}_{10} (P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.
 - (2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \text{Log}_{10} (P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

6.2. Test Procedure

The test follows section 5.7 of ANSI C63.26-2015.

1. Start frequency was set to 9 kHz and stop frequency was set to at least 10* the fundamental frequency.
2. Detector = RMS.
3. Trace mode = Max hold.
4. Sweep time = Auto couple.
5. The trace was allowed to stabilize.
6. Please see notes below for RBW and VBW settings.
7. For plots showing conducted spurious emissions from 9 kHz to 27 GHz, all path loss of wide frequency range was investigated and compensated to spectrum analyzer as TDF function.




Note;

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for frequencies less than 1 GHz and frequencies greater than 1 GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two point, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.


6.3. Test Results

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.


- Test plots LTE band 2 (15 MHz)



QPSK Low Channel - 1 RB




QPSK Middle Channel - 1 RB




QPSK High Channel - 1 RB


LTE band 4 (20 MHz)



QPSK Low Channel - 1 RB




QPSK Middle Channel - 1 RB




QPSK High Channel - 1 RB


LTE band 7 (5 MHz)



QPSK Low Channel - 1 RB




QPSK Middle Channel - 1 RB




QPSK High Channel - 1 RB


LTE band 12/17 (5 MHz)



QPSK Low Channel - 1 RB




QPSK Middle Channel - 1 RB




QPSK High Channel - 1 RB

**LTE band 26/5 (15 MHz)
 (Part 22)**




QPSK Low Channel - 1 RB




QPSK High Channel - 1 RB

**LTE band 26 (15 MHz)
 (Part 90)**




QPSK Middle Channel - 1 RB


LTE band 41 (20 MHz)



QPSK Low Channel - 1 RB



QPSK Middle Channel - 1 RB



QPSK High Channel - 1 RB

7. Band Edge and Emission Mask


7.1. Limit

- §22.917(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.
- §24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.
- §27.53(g), the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB.
- §27.53(h)(1), for operations in the 1 695-1 710 MHz, 1 710-1 755 MHz, 1 755-1 780 MHz, 1 915-1 920 MHz, 1 995-2 000 MHz, 2 000-2 020 MHz, 2 110-2 155 MHz, 2 155-2 180 MHz, and 2 180-2 200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB.
- §27.53(m)(4), for mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log_{10} (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log_{10} (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log_{10} (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that $43 + 10 \log_{10} (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log_{10} (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.
- §90.691(a), out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:
 - (1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \text{ Log}_{10} (f / 6.1)$ decibels or $50 + 10 \text{ Log}_{10} (P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.
 - (2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \text{ Log}_{10} (P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

7.2. Test Procedure

The test follows section 5.7 of ANSI C63.26-2015.

- a. Span was set large enough so as to capture all out of band emissions near the band edge.
- b. RBW \geq 1 % of OBW
- c. VBW \geq 3 x RBW.
- d. Detector = RMS.
- e. Trace mode = Average.
- f. Sweep time = Auto.
- g. The trace was allowed to stabilize.
- h. All path loss of frequency range was investigated and compensated to spectrum analyzer as TDF function.




7.3. Test Results

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.

- Test plots

LTE band 2 (1.4 MHz)




LTE band 2 (1.4 MHz)



16QAM Low Channel - 1 RB

16QAM High Channel - 1 RB



16QAM Low Channel - Full RB


16QAM High Channel - Full RB

LTE band 2 (3 MHz)



QPSK Low Channel - 1 RB


QPSK High Channel - 1 RB




QPSK Low Channel - Full RB

QPSK High Channel - Full RB

LTE band 2 (3 MHz)



LTE band 2 (5 MHz)



QPSK Low Channel - 1 RB


QPSK High Channel - 1 RB



QPSK Low Channel - Full RB

QPSK High Channel - Full RB

LTE band 2 (5 MHz)



16QAM Low Channel - 1 RB


16QAM High Channel - 1 RB



16QAM Low Channel - Full RB

16QAM High Channel - Full RB

LTE band 2 (10 MHz)



LTE band 2 (10 MHz)



16QAM Low Channel - 1 RB

16QAM High Channel - 1 RB



16QAM Low Channel - Full RB

16QAM High Channel - Full RB