

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: BEJTLHOBDDNN0B


Equipment Under Test : Car Telematics Device
Model Name : TLHOBDDNN0B2
Variant Model Name(s) : Refer to the page 3
Applicant : LG Electronics USA
Manufacturer : LG Electronics Inc.
Date of Receipt : 2022.09.26
Date of Test(s) : 2022.10.10 ~ 2022.12.08
Date of Issue : 2022.12.14

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
- 3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
- 4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.

We are responsible for all the information of this test report except for the data(※) provided by the customer.

Tested by:



Murphy Kim

Technical
Manager:



Jinhyoung Cho

SGS Korea Co., Ltd. Gunpo Laboratory



SGS Korea Co., Ltd.

4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
Tel. +82 31 428 5700 / Fax. +82 31 427 2370
<http://www.sgsgroup.kr>

Report Number: F690501-RF-RTL003633

Page: 2 of 7

INDEX

<u>Table of Contents</u>	Page
1. General Information -----	3
2. RF Exposure Evaluation -----	5

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

 All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

 Telephone : +82 31 688 0901
 FAX : +82 31 688 0921

1.2. Details of Applicant

 Applicant : LG Electronics USA
 Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, United States, 07632
 Contact Person : Kim, Sung-soo
 Phone No. : +1 201 266 2215

1.3. Details of Manufacturer

 Company : LG Electronics Inc.
 Address : 10, Magokjungang 10-ro, Gangseo-gu, Seoul, Korea, 07796

1.4. Description of EUT

Kind of Product	Telematics Module Device
Model Name	TLHOBDDNN0B2
Variant Model Names	TLHOBDDNN0B1, TLHOBENND01
Approved Module	BEJTM03LNNAHD0
Model Serial Number	353342703000020
Power Supply	DC 13.2 V
Rated Power	WCDMA II, V: 23 dB m LTE Band 2, 4, 5, 12: 23 dB m
Frequency Range	WCDMA II: 1 850 MHz ~ 1 910 MHz WCDMA V: 824 MHz ~ 849 MHz LTE Band 2: 1 850 MHz ~ 1 910 MHz LTE Band 4: 1 710 MHz ~ 1 755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 12: 699 MHz ~ 716 MHz
Modulation Technique	QPSK, 16QAM
Antenna Type	External antenna
Antenna Gain*	699 MHz ~ 716 MHz: -2.20 dB i 824 MHz ~ 849 MHz: 0.40 dB i 1 710 MHz ~ 1 780 MHz: 0.40 dB i 1 850 MHz ~ 1 910 MHz: -0.10 dB i
H/W Version	Rev.C1
S/W Version	V3.6_20210526

1.5. Test Report Revision

Revision	Report Number	Date of Issue	Description
0	F690501-RF-RTL003633	2022.12.14	Initial

1.6. Test information of Cable Loss and Antenna Gain

Test Item	Frequency (MHz)	Cable Loss (dB)	Antenna Gain (dB i)	Final Antenna Gain (dB i)
WCDMA II	1 850 ~ 1 910	0.90	-0.10	-1
WCDMA V	824 ~ 849	0.50	0.40	-0.10
LTE - Band 2	1 850 ~ 1 910	0.90	-0.10	-1
LTE - Band 4	1 710 ~ 1 755	0.80	0.40	-0.40
LTE - Band 5	824 ~ 849	0.50	0.40	-0.10
LTE - Band 12	699 ~ 716	0.50	-2.20	-2.70

1.7. Information of Variant Model

Model Name		Description
Basic Model	TLHOBDNN0B2	D-Class AMP condition
Variant Model	TLHOBDNN0B1	Same RF module and circuit to basic model, Except below - Buffer AMP condition - De-populated to BUB (Backup battery) part
	TLHOBENN0D1	Same circuit to basic model, except below - Operating external ANT.

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	≤ 6
3.0-30	1842/f	4.89/f	*900/f ²	<6
30-300	61.4	0.163	1.0	<6
300-1 500	-	-	f/300	<6
1 500-100 000	-	-	5	<6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
<u>300-1 500</u>	-	-	<u>f/1500</u>	<u><30</u>
<u>1 500-100 000</u>	-	-	<u>1.0</u>	<u><30</u>

2.1.1. Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data
 Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

WCDMA - Band II

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
1 850 ~ 1 910	23.0	1	24.0	-1.0	0.039 694	1

WCDMA - Band V

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
824 ~ 849	23.0	1	24.0	-0.10	0.048 835	0.549 333

LTE Band 2

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
1 850 ~ 1 910	23.0	1	24.0	-1.0	0.039 694	1

LTE Band 4

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
1 710 ~ 1 755	23.0	1	24.0	-0.40	0.045 575	1

LTE Band 5

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
824 ~ 849	23.0	1	24.0	-0.10	0.048 835	0.549 333

LTE Band 12

Frequency (MHz)	Maximum Average Target Power (dB m)	Maximum Tune up (dB)	Maximum Average Output Power (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
699 ~ 716	23.0	1	24.0	-2.70	0.026 837	0.466 000

Note;

- The power density Pd (5th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 cm between the radiator and your body.
- The antenna gain of this transmitter is less than 6 dBi and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.
- According to KDB 447498 D01 RF Exposure Guidance 4.1.

- End of the Test Report -