

TEST REPORT

of

FCC Part 2 Subpart J, Part 22 Subpart C/H,
Part 24 Subpart E and Part 27 Subpart C
IC RSS-132 Issue 3, RSS-133 Issue 6,
RSS-139 Issue 3 and RSS-Gen Issue 5

FCC ID: BEJTM04ANNABM2
IC Certification: 2703H-TM04ANNABM2


Equipment Under Test : Telematics Module
Model Name : TM04ANNABM2
Variant Model Name(s) : -
Applicant : FCC: LG Electronics USA
: IC: LG ELECTRONICS INC.
Manufacturer : LG Electronics Inc.
Date of Receipt : 2022.04.26
Date of Test(s) : 2020.01.13 ~ 2022.07.04
Date of Issue : 2022.07.20

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
- 3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
- 4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.


We are responsible for all the information of this test report except for the data(※) provided by the customer.

Tested by:



Murphy Kim

Technical
Manager:



Jinhyoung Cho

SGS Korea Co., Ltd. Gunpo Laboratory



INDEX

| <u>Table of Contents</u> | Page |
|---|------|
| 1. General Information ----- | 3 |
| 2. E.R.P. / E.I.R.P. & Spurious Radiated Emission ----- | 10 |
| 3. Conducted Output Power ----- | 22 |
| 4. Occupied Bandwidth ----- | 25 |
| 5. Peak-Average Ratio ----- | 32 |
| 6. Spurious Emissions at Antenna Terminal ----- | 39 |
| 7. Band Edge ----- | 47 |
| 8. Frequency Stability ----- | 52 |

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

1.2. Details of Applicant

FCC Applicant : LG Electronics USA

FCC Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, United States, 07632

IC Applicant : LG ELECTRONICS INC.

IC Address : 222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, Korea (Republic of), 451-713

Contact Person : Kim, Sung-soo

Phone No. : +1 201 266 2215

1.3. Details of Manufacturer

Company : LG Electronics Inc.

Address : 10, Magokjungang 10-ro, Gangseo-gu, Seoul, Korea, 07796

1.4. Description of EUT

| | |
|----------------------------------|--|
| Kind of Product | Telematics Module |
| Model Name | TM04ANNABM2 |
| Serial Number | Conducted Sample: 00400152020000 Radiated Sample: Radio#01 |
| Power Supply | DC 12.5 V |
| Rated Power | GSM 850: 33 dBm GSM 1 900: 30 dBm WCDMA II, IV, V: 24 dBm |
| Frequency Range | GSM 850: 824 MHz ~ 849 MHz GSM 1 900: 1 850 MHz ~ 1 910 MHz WCDMA II: 1 850 MHz ~ 1 910 MHz WCDMA IV: 1 710 MHz ~ 1 755 MHz WCDMA V: 824 MHz ~ 849 MHz |
| Modulation Technique | QPSK, 16QAM, GMSK, 8PSK |
| Antenna Type | Planar Inverted F Antenna |
| Antenna Gain [*] | 824 MHz ~ 849 MHz: -4.33 dB i 1 710 MHz ~ 1 780 MHz: 3.76 dB i 1 850 MHz ~ 1 915 MHz: 2.23 dB i |
| H/W Version | Rev.A0 |
| S/W Version | v002.008.022 |

1.5. Introduction of Test Data Reuse

This report referenced from the FCC ID: BEJ-TM04ANNABM0 and IC Certification: 2703H-TM04ANNABM0 GSM&WCDMA.

The applicant takes full responsibility that the test data as referenced in this report represent compliance for this FCC ID and IC Certification.

1.6. Difference

The FCC ID: BEJTM04ANNABM2 and IC Certification: 2703H-TM04ANNABM2 share the same enclosure as FCC ID: BEJ-TM04ANNABM0 and 2703H-TM04ANNABM0

Applicant as the manufacturer of the following products, declared that had changed the hardware of the EUT.

Band differences between TM04ANNABM0 and TM04ANNABM2

| Band | Frequency (MHz) | | FDD/TDD | Band | TM04ANNABM0 | TM04ANNABM2 |
|----------|-----------------|---------------|---------|------|-------------|-------------|
| | Tx | Rx | | | | |
| B2 | 1 850 ~ 1 910 | 1 930 ~ 1 990 | FDD | Mid | G, W, L | G, W, L |
| B4 | 1 710 ~ 1 755 | 2 110 ~ 2 155 | FDD | Mid | W, L | W, L |
| B5 | 824 ~ 849 | 869 ~ 894 | FDD | Low | G, W, L | G, W, L |
| B7 | 2 500 ~ 2 570 | 2 620 ~ 2 690 | FDD | High | L | L |
| B12(B17) | 699 ~ 716 | 729 ~ 746 | FDD | Low | L | L |
| B13 | 777 ~ 787 | 746 ~ 756 | FDD | Low | L | L |
| B25 | 1 850 ~ 1 915 | 1 930 ~ 1 995 | FDD | Mid | L | L |
| B26 | 814 ~ 849 | 859 ~ 894 | FDD | Low | L | - |
| B29 | - | 717 ~ 728 | FDD | Low | L(RX only) | - |
| B30 | 2 305 ~ 2 315 | 2 350 ~ 2 360 | FDD | High | L(RX only) | - |
| B41 | 2 496 ~ 2 690 | | TDD | High | L | L |
| B66 | 1 710 ~ 1 780 | 2 110 ~ 2 200 | FDD | Mid | L | L |
| B71 | 663 ~ 698 | 617 ~ 652 | FDD | Low | L | L |

- G(GSM), W(WCDMA), T(TD-SCDMA), L(LTE)

After confirming through preliminary E.R.P. / E.I.R.P. and conducted power that the performance of the FCC ID: BEJ-TM04ANNABM0 and IC Certification: 2703H-TM04ANNABM0 remain representative of FCC ID: BEJTM04ANNABM2 and IC Certification: 2703H-TM04ANNABM2.

The test data of FCC ID: BEJ-TM04ANNABM0 and IC Certification: 2703H-TM04ANNABM0 being submitted for this application to cover GSM&WCDMA features.

1.7. Spot Check Data

| Band | Test item | Frequency (MHz) | Limit | Original model | | Spot check model | | Deviation (dB) | Remark |
|----------|-----------------|-----------------|-------|--|-------|---|-------|----------------|--------|
| | | | | TM04ANNABM0 | | TM04ANNABM2 | | | |
| | | | | FCC ID: BEJ-TM04ANNABM0 IC Certification: 2703H-TM04ANNABM0 | | FCC ID: BEJTM04ANNABM2 IC Certification: 2703H-TM04ANNABM2 | | | |
| | | | | (dB m) | (W) | (dB m) | (W) | | |
| GSM 850 | Conducted power | 824 ~ 849 | 7 W | 33.08 | 2.032 | 33.18 | 2.080 | 0.10 | - |
| | E.R.P. | | | 31.45 | 1.396 | 27.52 | 0.564 | -3.93 | - |
| GSM 1900 | Conducted power | 1 850 ~ 1 910 | 2 W | 29.56 | 0.904 | 29.86 | 0.968 | 0.30 | - |
| | E.I.R.P. | | | 33.00 | 1.995 | 32.73 | 1.875 | -0.27 | - |
| WCDMA II | Conducted power | 1 850 ~ 1 910 | 2 W | 23.41 | 0.219 | 23.30 | 0.214 | -0.11 | - |
| | E.I.R.P. | | | 27.70 | 0.589 | 27.23 | 0.528 | -0.47 | - |
| WCDMA IV | Conducted power | 1 710 ~ 1 755 | 1 W | 23.72 | 0.236 | 22.55 | 0.180 | -1.17 | - |
| | E.I.R.P. | | | 28.30 | 0.676 | 28.76 | 0.752 | 0.46 | - |
| WCDMA V | Conducted power | 824 ~ 849 | 7 W | 23.77 | 0.238 | 24.12 | 0.258 | 0.35 | - |
| | E.R.P. | | | 21.65 | 0.146 | 18.52 | 0.071 | -3.13 | - |

1.8. Reference Detail

Reference applicant that contains the reused reference data in the individual test reports:

| Mode | Reference FCC ID / IC Certification | Application type | Reference test report number | Exhibit type | Data reuse |
|-------|---|------------------|------------------------------|--------------|----------------|
| GSM | FCC: BEJ-TM04ANNABM0 IC: 2703H-TM04ANNABM0 | Original grant | F690501-RF-RTL000879 (GSM) | Test report | Conducted data |
| WCDMA | | | F690501-RF-RTL000880 (WCDMA) | | |

1.9. Test Equipment List

| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Interval | Cal. Due |
|---------------------|-----------------------------|-----------------------------------|------------------------|---------------|---------------|---------------|
| Signal Generator | Agilent | E8257D | MY51501169 | Mar. 04, 2022 | Annual | Mar. 04, 2023 |
| Spectrum Analyzer | R&S | FSV30 | 103210 | Dec. 08, 2021 | Annual | Dec. 08, 2022 |
| Spectrum Analyzer | Agilent | N9020A | MY53421758 | Aug. 27, 2021 | Annual | Aug. 27, 2022 |
| Mobile Test Unit | R&S | CMW500 | 144034 | Feb. 21, 2022 | Annual | Feb. 21, 2023 |
| Power Meter | Anritsu | ML2495A | 1223004 | May 25, 2022 | Annual | May 25, 2023 |
| Power Sensor | Anritsu | MA2411B | 1207272 | May 25, 2022 | Annual | May 25, 2023 |
| Temperature Chamber | ESPEC CORP. | SH-662 | 93000533 | Jul. 15, 2021 | Annual | Jul. 15, 2022 |
| Low Pass Filter | Mini-Circuits | NLP-1200+ | V9500401023-2 | May 25, 2022 | Annual | May 25, 2023 |
| High Pass Filter | Wainwright Instrument GmbH | WHKX10-900-1000-18000-40SS | 7 | Mar. 04, 2022 | Annual | Mar. 04, 2023 |
| High Pass Filter | Wainwright Instrument GmbH | WHKX1.5/15G-6SS | 4 | Jun. 09, 2022 | Annual | Jun. 09, 2023 |
| High Pass Filter | Wainwright Instrument GmbH | WHKX2.2/12.75G-10SS | 8 | Mar. 04, 2022 | Annual | Mar. 04, 2023 |
| High Pass Filter | Wainwright Instrument GmbH | WHKX3.0/18G-6SS | 21 | Jun. 09, 2022 | Annual | Jun. 09, 2023 |
| High Pass Filter | Wainwright Instrument GmbH | WHNX7.5/26.5G-6SS | 11 | Aug. 11, 2021 | Annual | Aug. 11, 2022 |
| Directional Coupler | KRYTAR | 152613 | 122661 | Mar. 04, 2022 | Annual | Mar. 04, 2023 |
| DC Power Supply | Agilent | U8002A | MY54110041 | Sep. 14, 2021 | Annual | Sep. 14, 2022 |
| Preamplifier | H.P. | 8447F | 2944A03909 | Aug. 06, 2021 | Annual | Aug. 06, 2022 |
| Preamplifier | R&S | SCU 18 | 10117 | Jun. 13, 2022 | Annual | Jun. 13, 2023 |
| Preamplifier | TESTEK | TK-PA1840H | 130016 | Jan. 10, 2022 | Annual | Jan. 10, 2023 |
| Test Receiver | R&S | ESU26 | 100109 | Jan. 18, 2022 | Annual | Jan. 18, 2023 |
| Loop Antenna | Schwarzbeck Mess-Elektronik | FMZB 1519 | 1519-039 | Aug. 23, 2021 | Biennial | Aug. 23, 2023 |
| Bilog Antenna | Schwarzbeck Mess-Elektronik | VULB9163 | 1126 | Feb. 07, 2022 | Annual | Feb. 07, 2023 |
| Horn Antenna | R&S | HF906 | 100326 | Feb. 18, 2022 | Annual | Feb. 18, 2023 |
| Horn Antenna | Schwarzbeck Mess-Elektronik | BBHA9170 | 9170-540 | Nov. 30, 2021 | Annual | Nov. 30, 2022 |
| Antenna Master | Innco systems GmbH | MM4000 | N/A | N.C.R. | N/A | N.C.R. |
| Turn Table | Innco systems GmbH | DS 1200S | N/A | N.C.R. | N/A | N.C.R. |
| Controller | Innco systems GmbH | CONTROLLER CO3000-4P | CO3000/963/383 30516/L | N.C.R. | N/A | N.C.R. |
| Anechoic Chamber | SY Corporation | L x W x H (9.6 m x 6.4 m x 6.6 m) | N/A | N.C.R. | N/A | N.C.R. |
| Coaxial Cable | RFONE | MWX221-NMSNMS (4 m) | J1023142 | Apr. 04, 2022 | Semi-annual | Oct. 04, 2022 |
| Coaxial Cable | micro-coax UTiflex | 142A SERIES 502839-8 (10 m) | 90000034 | Apr. 04, 2022 | Semi-annual | Oct. 04, 2022 |
| Coaxial Cable | RADIALL | TESTPRO 3 | 182287 | Feb. 18, 2022 | Semi-annual | Aug. 18, 2022 |
| Coaxial Cable | RADIALL | TESTPRO 3 | 182288 | Feb. 18, 2022 | Semi-annual | Aug. 18, 2022 |
| Coaxial Cable | RADIALL | TESTPRO 3 | 182291 | Feb. 18, 2022 | Semi-annual | Aug. 18, 2022 |

► Support Equipment

| Description | Manufacturer | Model | Serial Number |
|-------------|--------------|-------|---------------|
| N/A | - | - | - |

1.10. Summary of Test Results

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 2, 22, 24 and 27 / IC part RSS-132 Issue 3, RSS-133 Issue 6, RSS-139 Issue 3 and RSS-Gen Issue 5 | | | |
|--|---|---------------------------------------|----------|
| Section in FCC | Section in IC | Test Item | Result |
| §2.1046 §22.913(a)(5) §24.232(c) §27.50(d)(4) | RSS-132 Issue 3 5.4 RSS-133 Issue 6 6.4 RSS-139 Issue 3 6.5 | E.R.P. / E.I.R.P. | Complied |
| §2.1053 §22.917(a) §24.238(a) §27.53(h)(1) | RSS-132 Issue 3 5.5 RSS-133 Issue 6 6.5 RSS-139 Issue 3 6.6 | Spurious Radiated Emission | Complied |
| §2.1046 | RSS-Gen Issue 5 6.12 | Conducted Output Power | Complied |
| §2.1049 | RSS-Gen Issue 5 6.7 | Occupied Bandwidth | Complied |
| §22.913(d) §24.232(d) §27.50(d)(5) | RSS-132 Issue 3 5.4 RSS-133 Issue 6 6.4 RSS-139 Issue 3 6.5 | Peak-Average Ratio | Complied |
| §2.1051 §22.917(a) §24.238(a) §27.53(h)(1) | RSS-132 Issue 3 5.5 RSS-133 Issue 6 6.5 RSS-139 Issue 3 6.6 | Spurious Emission at Antenna Terminal | Complied |
| §22.917(a) §24.238(a) §27.53(h)(1) | RSS-132 Issue 3 5.5 RSS-133 Issue 6 6.5 RSS-139 Issue 3 6.6 | Band Edge | Complied |
| §2.1055 §22.355 §24.235 §27.54 | RSS-Gen Issue 5 6.11 RSS-132 Issue 3 5.3 RSS-133 Issue 6 6.3 RSS-139 Issue 3 6.4 | Frequency Stability | Complied |

1.11. Sample Calculation for Offset

Where relevant, the following sample calculation is provided:

1.11.1. Conducted Test

Offset value (dB) = Directional Coupler (dB) + Cable loss (dB)

1.11.2. Radiation test

- E.I.R.P. (dB m) = Measured level (dB μ V) + Antenna factor (dB/m) + Cable loss (dB) + 20 Log D - 104.8;
 where D is the measurement distance in meters.
- E.R.P (dB m) = E.I.R.P. (dB m) - 2.15 (dB)

1.12. Worst Case Configuration and Mode

GSM

The worst-case is based on the average conducted output power measurement investigation results. Output power measurements were measured on GSM, GPRS, EDGE Mode. All testing was performed using GPRS mode to represent the worst case.

The radiation test of the EUT was investigated in three orthogonal orientations X, Y, and Z, and the worst case data is reported.

WCDMA

The worst-case is based on the average conducted output power measurement investigation results. Output power measurements were measured on RMC, HSDPA, HSUPA, HSPA+ and DC-HSDPA Modulation. All testing was performed using RMC modulations to represent the worst case.

The radiation test of the EUT was investigated in three orthogonal orientations X, Y, and Z, and the worst case data is reported.

1.13. Measurement Configuration

WCDMA

| Test Items | Band | Test Channel | | | Modulation | | |
|----------------------------|---------|--------------|-----|------|------------|-------|-------|
| | | Low | Mid | High | RMC | HSUPA | HSDPA |
| Conducted Output Power | Band II | V | V | V | V | V | V |
| | Band IV | V | V | V | V | V | V |
| | Band V | V | V | V | V | V | V |
| Spurious Radiated Emission | Band II | V | V | V | V | - | - |
| | Band IV | V | V | V | V | - | - |
| | Band V | V | V | V | V | - | - |

GSM

| Test Items | Band | Test Channel | | | Modulation | | |
|----------------------------|----------|--------------|-----|------|------------|------|-------|
| | | Low | Mid | High | VOICE | GPRS | EGPRS |
| Conducted Output Power | GSM 850 | V | V | V | V | V | V |
| | GSM 1900 | V | V | V | V | V | V |
| Spurious Radiated Emission | GSM 850 | V | V | V | V | - | V |
| | GSM 1900 | V | V | V | V | - | V |

Remark;

All supported GSM and WCDMA's frequency stability, occupied bandwidth, peak to average radio, band edge and spurious emission at antenna terminal have been tested in the approved module test report.

- Module model name : TM04ANNABM0
- Test report Number : F690501-RF-RTL000879(GSM) & F690501-RF-RTL000880(WCDMA)
- Issue date : 2020.07.03
- Test Laboratory : SGS Korea Co., Ltd.

1.14. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Parameter | Uncertainty | |
|------------------------------------|-------------|---------|
| RF Output Power | 0.32 dB | |
| Radiated Emission, 9 kHz to 30 MHz | H | 3.30 dB |
| | V | 3.30 dB |
| Radiated Emission, below 1 GHz | H | 4.80 dB |
| | V | 5.20 dB |
| Radiated Emission, above 1 GHz | H | 3.90 dB |
| | V | 4.00 dB |

All measurement uncertainty values are shown with a coverage factor $k = 2$ to indicate a 95 % level of confidence.

1.15. Test Report Revision

| Revision | Report Number | Date of Issue | Description |
|----------|----------------------|---------------|-------------|
| 0 | F690501-RF-RTL003309 | 2022.07.20 | Initial |


1.16. Emission Designator and Max Power

| Band | Frequency Range (MHz) | Mode | Emission Designator | E.R.P. / E.I.R.P. | |
|----------|-----------------------|------|---------------------|-------------------|---------------|
| | | | | Max power (dB m) | Max power (W) |
| GSM 850 | 824.2 ~ 848.8 | GPRS | 241KGXW | 27.52 | 0.564 |
| | | EDGE | 246KG7W | | |
| GSM 1900 | 1 850.2 ~ 1 909.8 | GPRS | 241KGXW | 32.73 | 1.875 |
| | | EDGE | 245KG7W | | |
| WCDMA II | 1 852.4 ~ 1 907.6 | RMC | 4M15F9W | 27.23 | 0.528 |
| WCDMA IV | 1 712.4 ~ 1 752.6 | RMC | 4M15F9W | 28.76 | 0.752 |
| WCDMA V | 826.4 ~ 846.6 | RMC | 4M14F9W | 18.52 | 0.071 |


2. E.R.P. / E.I.R.P. & Spurious Radiated Emission

2.1. Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to 20 GHz Emissions.



2.2. Limit

2.2.1. Limit of E.R.P. / E.I.R.P.

FCC

- §22.913(a)(5), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

- §24.232(c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

- §27.50(d)(4), fixed, mobile, and portable (hand-held) stations operating in the 1 710-1 755 MHz band and mobile and portable stations operating in the 1 695-1 710 MHz and 1 755-1 780 MHz bands are limited to 1 watt EIRP.

IC

- RSS-132 Issue 3

5.4, the transmitter output power shall be measured in terms of average power.

The equivalent isotropically radiated power (e.i.r.p.) for mobile equipment shall not exceed 11.5 watts.

Refer to SRSP-503 for base station e.i.r.p. limits.

- RSS-133 Issue 6

6.4, the equivalent isotropically radiated power (e.i.r.p.) for transmitters shall not exceed the limits given in SRSP-510. Mobile stations and hand-held portables are limited to 2 watts maximum e.i.r.p. The equipment shall employ means to limit the power to the minimum necessary for successful communication.

- RSS-139 Issue 3

6.5, the equivalent isotropically radiated power (e.i.r.p.) for mobile and portable transmitters shall not exceed one watt. The e.i.r.p. for fixed and base stations in the band 1 710-1 780 MHz shall not exceed one watt.

2.2.2. Limit of Spurious Radiated Emission

FCC

- §22.917(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

- §24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

- §27.53(h)(1), for operations in the 1 695-1 710 MHz, 1 710-1 755 MHz, 1 755-1 780 MHz, 1 915-1 920 MHz, 1 995-2 000 MHz, 2 000-2 020 MHz, 2 110-2 155 MHz, 2 155-2 180 MHz, and 2 180-2 200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB.

IC

- RSS-132 Issue 3

5.5, Mobile and base station equipment shall comply with the limits in (i) and (ii) below.

(i) In the first 1.0 MHz band immediately outside and adjacent to each of the sub-bands specified in Section 5.1, the power of emissions per any 1 % of the occupied bandwidth shall be attenuated (in dB) below the transmitter output power P (dB W) by at least $43 + 10 \log_{10} p$ (watts).

(ii) After the first 1.0 MHz immediately outside and adjacent to each of the sub-bands, the power of emissions in any 100 kHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dB W) by at least $43 + 10 \log_{10} p$ (watts). If the measurement is performed using 1 % of the occupied bandwidth, power integration over 100 kHz is required.

- RSS-133 Issue 6

6.5, Equipment shall comply with the limits in (i) and (ii) below.

(i) In the 1.0 MHz bands immediately outside and adjacent to the equipment's operating frequency block, the emission power per any 1 % of the emission bandwidth shall be attenuated (in dB) below the transmitter output power P (dB W) by at least $43 + 10 \log_{10} p$ (watts).

(ii) After the first 1.0 MHz, the emission power in any 1 MHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dB W) by at least $43 + 10 \log_{10} p$ (watts). If the measurement is performed using 1 % of the emission bandwidth, power integration over 1.0 MHz is required.

- RSS-139 Issue 3

6.6, (i) In the first 1.0 MHz bands immediately outside and adjacent to the equipment's smallest operating frequency block, which can contain the equipment's occupied bandwidth, the emission power per any 1 % of the emission bandwidth shall be attenuated below the transmitter output power P (in dB W) by at least $43 + 10 \log_{10} p$ (watts) dB.

(ii) After the first 1.0 MHz outside the equipment's smallest operating frequency block, which can contain the equipment's occupied bandwidth, the emission power in any 1 MHz bandwidth shall be attenuated below the transmitter output power P (in dB W) by at least $43 + 10 \log_{10} p$ (watts) dB.

2.3. Test Procedure: Based on ANSI/TIA 603E: 2016 and ANSI C63.26-2015 and KDB 971168 D01 Power Meas License Digital Systems v03r01.

1. On a test site, the EUT shall be placed at 0.8 m or 1.5 m height on a turn table, and in the position close to normal use as declared by the applicant.
2. The test antenna shall be oriented initially for vertical polarization located 3 m from EUT to correspond to the fundamental frequency of the transmitter.
3. The output of the test antenna shall be connected to the measuring receiver and the peak detector is used for the measurement.
4. Radiated spurious emissions measurement method was set as follows:
RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz, VBW \geq 3 x RBW,
Detector = RMS, trace mode = max hold.
5. The transmitter shall be switched on, the measuring receiver shall be tuned to the frequency of the transmitter under test.
6. The test antenna shall be raised and lowered through the specified range of height until the maximum signal level is detected by the measuring receiver.
7. The transmitter shall be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
8. The test antenna shall be raised and lowered again through the specified range of height until the maximum signal level is detected by the measuring receiver.
9. The maximum signal level detected by the measuring receiver shall be noted.
10. In necessary, the input attenuator setting on the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
11. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
12. The measurement shall be repeated with the test antenna orientated for horizontal polarization.

2.4. Test result for E.R.P. / E.I.R.P.

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.

GSM

| Band | Frequency (MHz) | Maximum Average Power (dB m) | Maximum Average Power (W) | Antenna Gain (dB i) | Maximum E.I.R.P. (dB m) | Maximum E.I.R.P. (W) | Maximum E.R.P. (dB m) | Maximum E.R.P. (W) | Output Power Limit |
|-------|-----------------|------------------------------|---------------------------|---------------------|-------------------------|----------------------|-----------------------|--------------------|--------------------|
| 850 | 824 ~ 849 | 34.00 | 2.511 | -4.33 | 29.67 | 0.927 | 27.52 | 0.564 | 7 W E.R.P. |
| 1 900 | 1 850 ~ 1 910 | 30.50 | 1.122 | 2.23 | 32.73 | 1.875 | | | 2 W E.I.R.P. |

WCDMA

| Band | Frequency (MHz) | Maximum Average Power (dB m) | Maximum Average Power (W) | Antenna Gain (dB i) | Maximum E.I.R.P. (dB m) | Maximum E.I.R.P. (W) | Maximum E.R.P. (dB m) | Maximum E.R.P. (W) | Output Power Limit |
|------|-----------------|------------------------------|---------------------------|---------------------|-------------------------|----------------------|-----------------------|--------------------|--------------------|
| II | 1 850 ~ 1 910 | 25.00 | 0.316 | 2.23 | 27.23 | 0.528 | | | 2 W E.I.R.P. |
| IV | 1 710 ~ 1 755 | 25.00 | 0.316 | 3.76 | 28.76 | 0.752 | | | 1 W E.I.R.P. |
| V | 824 ~ 849 | 25.00 | 0.316 | -4.33 | 20.67 | 0.117 | 18.52 | 0.071 | 7 W E.R.P. |

Remark;

1. E.I.R.P. (dB m) = Maximum Average Power (dB m) + Maximum Antenna Gain (dB i)
2. E.R.P. (dB m) = E.I.R.P. (dB m) - 2.15 (dB); where E.R.P. and E.I.R.P. are expressed in consistent units.

2.5. Spurious Radiated Emission

GSM 850

| Frequency (MHz) | Measured Level (dB μ V) | Ant. Pol. | AF (dB/m) | AMP+CL (dB) | E (dB μ V/m) | CF (dB) | E.R.P. (dB m) | Limit (dB m) | Margin (dB) |
|----------------------------|-----------------------------|-----------|-----------|-------------|------------------|---------|---------------|--------------|-------------|
| Low Channel (824.2 MHz) | | | | | | | | | |
| 1 648.32 | 58.02 | H | 25.60 | -36.69 | 46.93 | -97.41 | -50.48 | -13 | 37.48 |
| 1 648.49 | 66.76 | V | 25.60 | -36.69 | 55.67 | -97.41 | -41.74 | -13 | 28.74 |
| 2 472.79 | 57.68 | H | 28.15 | -34.20 | 51.63 | -97.41 | -45.78 | -13 | 32.78 |
| 2 472.71 | 59.98 | V | 28.15 | -34.20 | 53.93 | -97.41 | -43.48 | -13 | 30.48 |
| Above 2 500.00 | Not detected | - | - | - | - | - | - | - | - |
| Middle Channel (836.6 MHz) | | | | | | | | | |
| 1 673.29 | 67.55 | H | 25.88 | -36.62 | 56.81 | -97.41 | -40.60 | -13 | 27.60 |
| 1 673.29 | 65.15 | V | 25.88 | -36.62 | 54.41 | -97.41 | -43.00 | -13 | 30.00 |
| 2 509.55 | 48.96 | H | 28.16 | -34.05 | 43.07 | -97.41 | -54.34 | -13 | 41.34 |
| 2 509.62 | 51.96 | V | 28.16 | -34.05 | 46.07 | -97.41 | -51.34 | -13 | 38.34 |
| Above 2 600.00 | Not detected | - | - | - | - | - | - | - | - |
| High Channel (848.8 MHz) | | | | | | | | | |
| 1 697.57 | 66.95 | H | 26.17 | -36.52 | 56.60 | -97.41 | -40.81 | -13 | 27.81 |
| 1 697.60 | 61.48 | V | 26.17 | -36.52 | 51.13 | -97.41 | -46.28 | -13 | 33.28 |
| 2 546.60 | 45.80 | H | 28.38 | -33.86 | 40.32 | -97.41 | -57.09 | -13 | 44.09 |
| 2 546.70 | 45.98 | V | 28.38 | -33.86 | 40.50 | -97.41 | -56.91 | -13 | 43.91 |
| Above 2 600.00 | Not detected | - | - | - | - | - | - | - | - |

EDGE 850

| Frequency (MHz) | Measured Level (dB μ V) | Ant. Pol. | AF (dB/m) | AMP+CL (dB) | E (dB μ V/m) | CF (dB) | E.R.P. (dB m) | Limit (dB m) | Margin (dB) |
|----------------------------|-----------------------------|-----------|-----------|-------------|------------------|---------|---------------|--------------|-------------|
| Low Channel (824.2 MHz) | | | | | | | | | |
| 1 648.59 | 54.12 | H | 25.60 | -36.69 | 43.03 | -97.41 | -54.38 | -13 | 41.38 |
| 1 648.49 | 51.79 | V | 25.60 | -36.69 | 40.70 | -97.41 | -56.71 | -13 | 43.71 |
| 2 472.65 | 44.76 | H | 28.15 | -34.20 | 38.71 | -97.41 | -58.70 | -13 | 45.70 |
| 2 472.78 | 48.67 | V | 28.15 | -34.20 | 42.62 | -97.41 | -54.79 | -13 | 41.79 |
| Above 2 500.00 | Not detected | - | - | - | - | - | - | - | - |
| Middle Channel (836.6 MHz) | | | | | | | | | |
| 1 673.26 | 54.84 | H | 25.88 | -36.62 | 44.10 | -97.41 | -53.31 | -13 | 40.31 |
| 1 673.13 | 52.18 | V | 25.88 | -36.62 | 41.44 | -97.41 | -55.97 | -13 | 42.97 |
| 2 510.29 | 43.57 | H | 28.16 | -34.06 | 37.67 | -97.41 | -59.74 | -13 | 46.74 |
| 2 509.71 | 46.96 | V | 28.16 | -34.05 | 41.07 | -97.41 | -56.34 | -13 | 43.34 |
| Above 2 600.00 | Not detected | - | - | - | - | - | - | - | - |
| High Channel (848.8 MHz) | | | | | | | | | |
| 1 697.78 | 52.76 | H | 26.17 | -36.52 | 42.41 | -97.41 | -55.00 | -13 | 42.00 |
| 1 697.56 | 51.60 | V | 26.17 | -36.52 | 41.25 | -97.41 | -56.16 | -13 | 43.16 |
| 2 546.43 | 44.36 | H | 28.38 | -33.86 | 38.88 | -97.41 | -58.53 | -13 | 45.53 |
| 2 546.33 | 45.46 | V | 28.38 | -33.86 | 39.98 | -97.41 | -57.43 | -13 | 44.43 |
| Above 2 600.00 | Not detected | - | - | - | - | - | - | - | - |

GSM 1 900

| Frequency (MHz) | Measured Level (dB μ V) | Ant. Pol. | AF (dB/m) | AMP+CL (dB) | E (dB μ V/m) | CF (dB) | E.I.R.P. (dB m) | Limit (dB m) | Margin (dB) |
|------------------------------|-----------------------------|-----------|-----------|-------------|------------------|---------|-----------------|--------------|-------------|
| Low Channel (1 850.2 MHz) | | | | | | | | | |
| Above 0.009 | Not detected | | - | - | - | - | - | - | - |
| Middle Channel (1 880.0 MHz) | | | | | | | | | |
| Above 0.009 | Not detected | | - | - | - | - | - | - | - |
| High Channel (1 909.8 MHz) | | | | | | | | | |
| Above 0.009 | Not detected | | - | - | - | - | - | - | - |

EDGE 1 900

| Frequency (MHz) | Measured Level (dB μ V) | Ant. Pol. | AF (dB/m) | AMP+CL (dB) | E (dB μ V/m) | CF (dB) | E.I.R.P. (dB m) | Limit (dB m) | Margin (dB) |
|------------------------------|-----------------------------|-----------|-----------|-------------|------------------|---------|-----------------|--------------|-------------|
| Low Channel (1 850.2 MHz) | | | | | | | | | |
| Above 0.009 | Not detected | | - | - | - | - | - | - | - |
| Middle Channel (1 880.0 MHz) | | | | | | | | | |
| Above 0.009 | Not detected | | - | - | - | - | - | - | - |
| High Channel (1 909.8 MHz) | | | | | | | | | |
| Above 0.009 | Not detected | | - | - | - | - | - | - | - |

WCDMA II

| Frequency (MHz) | Measured Level (dB μ V) | Ant. Pol. | AF (dB/m) | AMP+CL (dB) | E (dB μ V/m) | CF (dB) | E.I.R.P. (dB m) | Limit (dB m) | Margin (dB) |
|------------------------------|-----------------------------|-----------|-----------|-------------|------------------|---------|-----------------|--------------|-------------|
| Low Channel (1 852.4 MHz) | | | | | | | | | |
| 5 000.02 | 43.44 | H | 33.00 | -26.66 | 49.78 | -95.26 | -45.48 | -13 | 32.48 |
| 5 000.04 | 43.05 | V | 33.00 | -26.66 | 49.39 | -95.26 | -45.87 | -13 | 32.87 |
| 5 559.25 | 48.48 | H | 33.90 | -25.98 | 56.40 | -95.26 | -38.86 | -13 | 25.86 |
| 5 560.85 | 48.35 | V | 33.90 | -25.97 | 56.28 | -95.26 | -38.98 | -13 | 25.98 |
| 7 404.85 | 37.94 | H | 36.00 | -22.59 | 51.35 | -95.26 | -43.91 | -13 | 30.91 |
| 7 412.50 | 41.17 | V | 36.00 | -22.62 | 54.55 | -95.26 | -40.71 | -13 | 27.71 |
| 12 961.30 | 35.69 | H | 39.00 | -15.06 | 59.63 | -95.26 | -35.63 | -13 | 22.63 |
| Above 13 000.00 | Not detected | - | - | - | - | - | - | - | - |
| Middle Channel (1 880.0 MHz) | | | | | | | | | |
| 5 000.30 | 41.45 | H | 33.00 | -26.65 | 47.80 | -95.26 | -47.46 | -13 | 34.46 |
| 4 999.96 | 43.30 | V | 33.00 | -26.66 | 49.64 | -95.26 | -45.62 | -13 | 32.62 |
| 5 642.45 | 44.29 | H | 33.90 | -25.19 | 53.00 | -95.26 | -42.26 | -13 | 29.26 |
| 5 642.20 | 45.42 | V | 33.90 | -25.19 | 54.13 | -95.26 | -41.13 | -13 | 28.13 |
| 7 515.35 | 37.12 | H | 35.90 | -22.90 | 50.12 | -95.26 | -45.14 | -13 | 32.14 |
| 7 515.05 | 39.58 | V | 35.90 | -22.90 | 52.58 | -95.26 | -42.68 | -13 | 29.68 |
| 13 166.70 | 35.49 | H | 39.23 | -15.35 | 59.37 | -95.26 | -35.89 | -13 | 22.89 |
| Above 13 200.00 | Not detected | - | - | - | - | - | - | - | - |
| High Channel (1 907.6 MHz) | | | | | | | | | |
| 4 999.88 | 41.86 | H | 33.00 | -26.66 | 48.20 | -95.26 | -47.06 | -13 | 34.06 |
| 5 000.12 | 42.97 | V | 33.00 | -26.66 | 49.31 | -95.26 | -45.95 | -13 | 32.95 |
| 5 720.75 | 39.43 | H | 33.94 | -25.07 | 48.30 | -95.26 | -46.96 | -13 | 33.96 |
| 5 719.10 | 40.98 | V | 33.94 | -25.07 | 49.85 | -95.26 | -45.41 | -13 | 32.41 |
| 7 635.30 | 36.65 | H | 35.90 | -22.64 | 49.91 | -95.26 | -45.35 | -13 | 32.35 |
| 7 627.45 | 38.90 | V | 35.90 | -22.57 | 52.23 | -95.26 | -43.03 | -13 | 30.03 |
| Above 7 700.00 | Not detected | - | - | - | - | - | - | - | - |

WCDMA IV

| Frequency (MHz) | Measured Level (dB μ V) | Ant. Pol. | AF (dB/m) | AMP+CL (dB) | E (dB μ V/m) | CF (dB) | E.I.R.P. (dB m) | Limit (dB m) | Margin (dB) |
|------------------------------|-----------------------------|-----------|-----------|-------------|------------------|---------|-----------------|--------------|-------------|
| Low Channel (1 712.4 MHz) | | | | | | | | | |
| 3 467.25 | 41.75 | H | 31.10 | -32.66 | 40.19 | -95.26 | -55.07 | -13 | 42.07 |
| 3 426.70 | 47.88 | V | 30.91 | -32.80 | 45.99 | -95.26 | -49.27 | -13 | 36.27 |
| 4 999.92 | 41.47 | H | 33.00 | -26.66 | 47.81 | -95.26 | -47.45 | -13 | 34.45 |
| 5 000.08 | 41.11 | V | 33.00 | -26.66 | 47.45 | -95.26 | -47.81 | -13 | 34.81 |
| 5 140.55 | 42.92 | V | 33.28 | -26.46 | 49.74 | -95.26 | -45.52 | -13 | 32.52 |
| Above 5 200.00 | Not detected | - | - | - | - | - | - | - | - |
| Middle Channel (1 732.6 MHz) | | | | | | | | | |
| 3 463.40 | 41.19 | H | 31.10 | -32.75 | 39.54 | -95.26 | -55.72 | -13 | 42.72 |
| 3 463.87 | 45.95 | V | 31.10 | -32.74 | 44.31 | -95.26 | -50.95 | -13 | 37.95 |
| 4 999.84 | 41.92 | H | 33.00 | -26.66 | 48.26 | -95.26 | -47.00 | -13 | 34.00 |
| 4 999.78 | 41.14 | V | 33.00 | -26.66 | 47.48 | -95.26 | -47.78 | -13 | 34.78 |
| 5 195.65 | 42.93 | V | 33.48 | -26.07 | 50.34 | -95.26 | -44.92 | -13 | 31.92 |
| Above 5 200.00 | Not detected | - | - | - | - | - | - | - | - |
| High Channel (1 752.6 MHz) | | | | | | | | | |
| 3 503.05 | 46.44 | H | 31.09 | -32.65 | 44.88 | -95.26 | -50.38 | -13 | 37.38 |
| 3 503.75 | 49.67 | V | 31.09 | -32.66 | 48.10 | -95.26 | -47.16 | -13 | 34.16 |
| 4 999.92 | 41.34 | H | 33.00 | -26.66 | 47.68 | -95.26 | -47.58 | -13 | 34.58 |
| 4 999.98 | 41.76 | V | 33.00 | -26.66 | 48.10 | -95.26 | -47.16 | -13 | 34.16 |
| Above 5 000.00 | Not detected | - | - | - | - | - | - | - | - |

WCDMA V

| Frequency (MHz) | Measured Level (dB μ V) | Ant. Pol. | AF (dB/m) | AMP+CL (dB) | E (dB μ V/m) | CF (dB) | E.R.P. (dB m) | Limit (dB m) | Margin (dB) |
|----------------------------|-----------------------------|-----------|-----------|-------------|------------------|---------|---------------|--------------|-------------|
| Low Channel (826.4 MHz) | | | | | | | | | |
| 5 000.01 | 39.62 | H | 33.00 | -26.66 | 45.96 | -97.41 | -51.45 | -13 | 38.45 |
| 4 999.94 | 39.56 | V | 33.00 | -26.66 | 45.90 | -97.41 | -51.51 | -13 | 38.51 |
| Above 5 100.00 | Not detected | - | - | - | - | - | - | - | - |
| Middle Channel (836.6 MHz) | | | | | | | | | |
| 5 000.13 | 39.38 | H | 33.00 | -26.66 | 45.72 | -97.41 | -51.69 | -13 | 38.69 |
| 4 999.89 | 39.70 | V | 33.00 | -26.66 | 46.04 | -97.41 | -51.37 | -13 | 38.37 |
| Above 5 100.00 | Not detected | - | - | - | - | - | - | - | - |
| High Channel (846.6 MHz) | | | | | | | | | |
| 5 000.08 | 39.48 | H | 33.00 | -26.66 | 45.82 | -97.41 | -51.59 | -13 | 38.59 |
| 4 999.94 | 39.62 | V | 33.00 | -26.66 | 45.96 | -97.41 | -51.45 | -13 | 38.45 |
| Above 5 100.00 | Not detected | - | - | - | - | - | - | - | - |

Remark;

1. AF = Antenna Factor, CL = Cable Loss, CF = Conversion Factor.
2. E (dB μ V/m) = Measured Level (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB).
3. E.I.R.P. (dB m) = E (dB μ V/m) + CF (dB).
4. E.R.P. (dB m) = E (dB μ V/m) + CF (dB) - 2.15 (dB); where E.R.P. and E.I.R.P. are expressed in consistent units.
5. CF (dB) = 20 log D - 104.8; where D is the measurement distance in meters, According to ANSI C63.26-2015 5.2.7 and KDB 971168 D01 v03r01 5.8.4
6. The frequency spectrum is examined from 9 kHz to the 10th harmonic of the fundamental frequency of the transmitter. No other spurious and harmonic emissions were reported greater than listed emissions above table.

3. Conducted Output Power


3.1. Limit

CFR 47, Section FCC §2.1046 and IC RSS-Gen Issue 5 6.12.

3.2. Test Procedure

Output power shall be measured at the RF output terminals for all configurations.

1. The RF output of the transmitter was connected to the input of the mobile test unit in order to establish communication with the EUT.
2. The EUT was set up for the max. output power with pseudo random data modulation by using mobile test unit parameters.
3. The measurement performed using a wideband RF power meter.
4. This EUT was tested under all configurations and the highest power was investigated and reported.



3.3. Test Result

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.

- GSM

| Band | Channel | Frequency (MHz) | GSM | | GPRS | | | | EDGE | | | |
|-------|---------|-----------------|--------------|--------------|-----------|-------|-----------|-------|--------------|--------------|-----------|-------|
| | | | Voice | | 1 Tx slot | | 2 Tx slot | | 1 Tx slot | | 2 Tx slot | |
| | | | (dB m) | (W) | (dB m) | (W) | (dB m) | (W) | (dB m) | (W) | (dB m) | (W) |
| 850 | 128 | 824.2 | 33.18 | 2.080 | 33.14 | 2061 | 33.16 | 2.070 | 27.21 | 0.526 | 26.85 | 0.484 |
| | 190 | 836.6 | 33.08 | 2.032 | 33.12 | 2.051 | 33.10 | 2.042 | 26.76 | 0.474 | 26.21 | 0.418 |
| | 251 | 848.8 | 32.94 | 1.968 | 33.08 | 2.032 | 33.03 | 2.009 | 26.42 | 0.439 | 26.62 | 0.459 |
| 1 900 | 512 | 1 850.2 | 29.86 | 0.968 | 29.81 | 0.957 | 29.78 | 0.951 | 25.94 | 0.393 | 25.27 | 0.337 |
| | 661 | 1 880.0 | 29.85 | 0.966 | 29.79 | 0.953 | 29.70 | 0.933 | 25.89 | 0.388 | 25.44 | 0.350 |
| | 810 | 1 909.8 | 29.82 | 0.959 | 29.76 | 0.946 | 29.68 | 0.929 | 25.71 | 0.372 | 25.09 | 0.323 |

- WCDMA

| Band | 3GPP Release Version | Channel | | 9262 | | 9400 | | 9538 | |
|------|----------------------|-----------------|-----------|---------|-------|--------------|--------------|---------|-------|
| | | Frequency (MHz) | | 1 852.4 | | 1 880.0 | | 1 907.6 | |
| | | | | (dB m) | (W) | (dB m) | (W) | (dB m) | (W) |
| II | 99 | WCDMA | GPRS | 23.06 | 0.202 | 23.30 | 0.214 | 23.01 | 0.200 |
| | 5 | HSDPA | Subtest 1 | 22.03 | 0.160 | 22.35 | 0.172 | 22.06 | 0.161 |
| | 5 | | Subtest 2 | 22.05 | 0.160 | 22.34 | 0.171 | 22.06 | 0.161 |
| | 5 | | Subtest 3 | 21.53 | 0.142 | 21.77 | 0.150 | 21.56 | 0.143 |
| | 5 | | Subtest 4 | 21.53 | 0.142 | 21.81 | 0.152 | 21.59 | 0.144 |
| | 6 | HSUPA | Subtest 1 | 22.11 | 0.163 | 22.39 | 0.173 | 22.14 | 0.164 |
| | 6 | | Subtest 2 | 20.13 | 0.103 | 20.36 | 0.109 | 20.14 | 0.103 |
| | 6 | | Subtest 3 | 21.11 | 0.129 | 21.36 | 0.137 | 21.14 | 0.130 |
| | 6 | | Subtest 4 | 20.12 | 0.103 | 20.38 | 0.109 | 20.17 | 0.104 |
| | 6 | | Subtest 5 | 22.11 | 0.163 | 22.43 | 0.175 | 22.14 | 0.164 |
| | 7 | HSPA+ | | 21.68 | 0.147 | 21.76 | 0.150 | 21.49 | 0.141 |
| | 8 | DC-HSDPA | Subtest 1 | 22.28 | 0.169 | 22.31 | 0.170 | 22.02 | 0.159 |
| | 8 | | Subtest 2 | 22.28 | 0.169 | 22.29 | 0.169 | 22.02 | 0.159 |
| | 8 | | Subtest 3 | 21.68 | 0.147 | 21.78 | 0.151 | 21.11 | 0.129 |
| | 8 | | Subtest 4 | 21.70 | 0.148 | 21.80 | 0.151 | 21.07 | 0.128 |

| Band | 3GPP Release Version | Channel | | 1312 | | 1413 | | 1513 | |
|------|----------------------|-----------------|-----------|---------|-------|---------|-------|--------------|--------------|
| | | Frequency (MHz) | | 1 712.4 | | 1 732.6 | | 1 752.6 | |
| | | | | (dB m) | (W) | (dB m) | (W) | (dB m) | (W) |
| IV | 99 | WCDMA | GPRS | 22.53 | 0.179 | 22.40 | 0.174 | 22.55 | 0.180 |
| | 5 | HSDPA | Subtest 1 | 21.44 | 0.139 | 21.42 | 0.139 | 21.55 | 0.143 |
| | 5 | | Subtest 2 | 21.40 | 0.138 | 21.38 | 0.137 | 21.53 | 0.142 |
| | 5 | | Subtest 3 | 20.73 | 0.118 | 20.90 | 0.123 | 21.03 | 0.127 |
| | 5 | | Subtest 4 | 20.88 | 0.122 | 20.88 | 0.122 | 21.00 | 0.126 |
| | 6 | HSUPA | Subtest 1 | 21.63 | 0.146 | 21.64 | 0.146 | 21.72 | 0.149 |
| | 6 | | Subtest 2 | 19.62 | 0.092 | 19.62 | 0.092 | 19.79 | 0.095 |
| | 6 | | Subtest 3 | 20.61 | 0.115 | 20.67 | 0.117 | 20.76 | 0.119 |
| | 6 | | Subtest 4 | 19.65 | 0.092 | 19.67 | 0.093 | 19.77 | 0.095 |
| | 6 | | Subtest 5 | 21.60 | 0.145 | 21.65 | 0.146 | 21.75 | 0.150 |
| | 7 | HSPA+ | | 20.59 | 0.115 | 20.68 | 0.117 | 20.70 | 0.117 |
| | 8 | DC-HSDPA | Subtest 1 | 21.03 | 0.127 | 21.11 | 0.129 | 21.01 | 0.126 |
| | 8 | | Subtest 2 | 21.12 | 0.129 | 21.23 | 0.133 | 21.03 | 0.127 |
| | 8 | | Subtest 3 | 20.54 | 0.113 | 20.61 | 0.115 | 20.52 | 0.113 |
| | 8 | | Subtest 4 | 20.59 | 0.115 | 20.69 | 0.117 | 20.58 | 0.114 |

| Band | 3GPP Release Version | Channel | | 4132 | | 4182 | | 4233 | |
|------|----------------------|-----------------|-----------|--------------|--------------|--------|-------|--------|-------|
| | | Frequency (MHz) | | 826.4 | | 836.6 | | 846.6 | |
| | | | | (dB m) | (W) | (dB m) | (W) | (dB m) | (W) |
| V | 99 | WCDMA | GPRS | 24.12 | 0.258 | 23.97 | 0.249 | 23.85 | 0.243 |
| | 5 | HSDPA | Subtest 1 | 22.86 | 0.193 | 22.80 | 0.191 | 22.84 | 0.192 |
| | 5 | | Subtest 2 | 22.88 | 0.194 | 22.80 | 0.191 | 22.84 | 0.192 |
| | 5 | | Subtest 3 | 22.37 | 0.173 | 22.28 | 0.169 | 22.34 | 0.171 |
| | 5 | | Subtest 4 | 22.38 | 0.173 | 22.29 | 0.169 | 22.33 | 0.171 |
| | 6 | HSUPA | Subtest 1 | 22.88 | 0.194 | 22.93 | 0.196 | 22.89 | 0.195 |
| | 6 | | Subtest 2 | 21.03 | 0.127 | 20.90 | 0.123 | 20.94 | 0.124 |
| | 6 | | Subtest 3 | 21.97 | 0.157 | 21.92 | 0.156 | 21.95 | 0.157 |
| | 6 | | Subtest 4 | 21.04 | 0.127 | 20.96 | 0.125 | 20.98 | 0.125 |
| | 6 | | Subtest 5 | 23.00 | 0.200 | 22.98 | 0.199 | 22.95 | 0.197 |
| | 7 | HSPA+ | | 21.89 | 0.155 | 21.92 | 0.156 | 21.90 | 0.155 |
| | 8 | DC-HSDPA | Subtest 1 | 21.92 | 0.156 | 21.85 | 0.153 | 22.02 | 0.159 |
| | 8 | | Subtest 2 | 21.98 | 0.158 | 21.84 | 0.153 | 22.01 | 0.159 |
| | 8 | | Subtest 3 | 21.42 | 0.139 | 21.35 | 0.136 | 21.49 | 0.141 |
| | 8 | | Subtest 4 | 21.40 | 0.138 | 21.31 | 0.135 | 21.62 | 0.145 |

4. Occupied Bandwidth

4.1. Limit

CFR 47, Section FCC §2.1049 and IC RSS-Gen Issue 5 6.7.

4.2. Test Procedure

FCC

The test follows section 5.4.4 of ANSI C63.26-2015.

- a. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (typically a span of $1.5 \times \text{OBW}$ is sufficient).
- b. The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1 % to 5 % of the anticipated OBW, and the VBW shall be set $\geq 3 \times \text{RBW}$.
- c. Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3.
- d. Set the detection mode to peak, and the trace mode to max-hold.
- e. If the instrument does not have a 99 % OBW function, recover the trace data points and sum directly in linear power terms. Place the recovered amplitude data points, beginning at the lowest frequency, in a running sum until 0.5 % of the total is reached. Record that frequency as the lower OBW frequency. Repeat the process until 99.5 % of the total is reached and record that frequency as the upper OBW frequency. The 99 % power OBW can be determined by computing the difference these two frequencies.
- f. The OBW shall be reported and plot(s) of the measuring instrument display shall be provided with the test report. The frequency and amplitude axis and scale shall be clearly labeled. Tabular data can be reported in addition to the plot(s).


IC

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99 % emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99 % emission bandwidth).



4.3 Test Results

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.

- GSM


| Band | Frequency (MHz) | Occupied Bandwidth (MHz) | |
|-------|-----------------|--------------------------|-------|
| | | GPRS | EDGE |
| 850 | 824.2 | 0.240 | 0.246 |
| | 836.6 | 0.240 | 0.244 |
| | 848.8 | 0.241 | 0.245 |
| 1 900 | 1 850.2 | 0.240 | 0.245 |
| | 1 880.0 | 0.241 | 0.244 |
| | 1 909.8 | 0.240 | 0.241 |


- WCDMA

| Band | Frequency (MHz) | Occupied Bandwidth (MHz) |
|------|-----------------|--------------------------|
| II | 1 852.4 | 4.146 |
| | 1 880.0 | 4.136 |
| | 1 907.6 | 4.146 |
| IV | 1 712.4 | 4.146 |
| | 1 732.6 | 4.146 |
| | 1 752.6 | 4.126 |
| V | 826.4 | 4.126 |
| | 836.6 | 4.116 |
| | 846.6 | 4.136 |


- Test plots

GSM







GSM 1 900 GPRS Low Channel




GSM 1 900 EDGE Low Channel




GSM 1 900 GPRS Middle Channel



GSM 1 900 EDGE Middle Channel





GSM 1 900 GPRS High Channel




GSM 1 900 EDGE High Channel

WCDMA






WCDMA BAND V Low Channel



WCDMA BAND V Middle Channel



WCDMA BAND V High Channel