

### MPE Calculation : Bluetooth

RF function or Mode	Frequency range (MHz)	Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density(mW/cm <sup>2</sup> )	Requirment (mW/cm <sup>2</sup> )
BDR(1Mbps)	2402.00 ~ 2480.00	8.50	0.94	9.44	8.79833	0.00176	1.00000
EDR(2/3Mbps)	2402.00 ~ 2480.00	4.50	0.94	5.44	3.50268	0.00070	1.00000
	~						
	~						
	~						
	~						
	~						
	~						
	~						

Note: Please refer to the technical document(operation description) for the max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / ( 4 R^2 \pi ) \\
 &= 8.79833 / ( 4 \times 20^2 \times \pi ) \\
 &= 0.00176 \text{ mW/cm}^2
 \end{aligned}$$

- Note  
 S= Maximum power density(mW/cm<sup>2</sup>)  
 EIRP= Equivalent Isotropic Radiated Power(mW)  
 R= Distance to the center of the radiation of the antenna(20cm)

▪ Limits for General Population/Uncontrolled Exposure

Frequency range (MHz)	Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averageing time (minutes)
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19 / f	*180 / f <sup>2</sup>	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1,500			f / 1500	30
1,500 ~ 100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

**Conclusion : The exposure condition of this device is compliant with FCC**

**MPE Calculation : LE**

RF function or Mode	Frequency range (MHz)		Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density(mW/cm <sup>2</sup> )	Requirment (mW/cm <sup>2</sup> )
LE	2402.00	~ 2480.00	1.50	0.94	2.44	1.75550	0.00035	1.00000
		~						
		~						
		~						
		~						
		~						
		~						
		~						
		~						

Note: Please refer to the technical document(operation description) for the max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / ( 4 R^2 \pi ) \\
 &= 1.7555 / ( 4 \times 20^2 \times \pi ) \\
 &= 0.00035 \text{ mW/cm}^2
 \end{aligned}$$

- Note
- S= Maximum power density(mW/cm<sup>2</sup>)
- EIRP= Equivalent Isotropic Radiated Power(mW)
- R= Distance to the center of the radiation of the antenna(20cm)

**Limits for General Population/Uncontrolled Exposure**

Frequency range (MHz)	Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averageing time (minutes)
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19 / f	*180 / f <sup>2</sup>	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1,500			f / 1500	30
1,500 ~ 100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

**Conclusion : The exposure condition of this device is compliant with FCC**