




PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. 410.290.6652 / Fax 410.290.6654
<http://www.pctest.com>



RF EXPOSURE EVALUATION Maximal Permissible Exposure [MPE]

Applicant Name:
LG Electronics Inc.
10, Magokjungang 10-ro, Gangseo-gu,
Seoul, Korea 07796


Date of Testing:
4/26 - 5/2/2018
Test Site/Location:
PCTEST Lab. Columbia, MD, USA
Test Report Serial No.:
1M1804270089-01.BEJ

FCC ID:	BEJWC500MRN
APPLICANT:	LG Electronics Inc.

Application Type:	Certification
Model:	WC500M-RN
Operating Frequency:	145kHz
EUT Type:	Vehicle Installed Wireless Charging System
FCC Classification:	Part 15 Low Power Transmitter Below 1705kHz (DCD)
FCC Rule Part:	FCC Part 1 (§1.1310) and Part 2 (§2.1091)
Test Procedure(s):	KDB 680106 D01 v03

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in FCC KDB 680106 D01 v03. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President







FCC ID: BEJWC500MRN		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Quality Manager
Test Report S/N: 1M1804270089-01.BEJ	Test Dates: 4/26 - 5/2/2018	EUT Type: Vehicle Installed Wireless Charging System		Page 1 of 6

TABLE OF CONTENTS

1.0	RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)	3
1.1	Introduction	3
1.2	EUT Description.....	3
1.3	Test Equipment.....	4
1.4	Test Setup	4
1.5	Summary of Results.....	5
2.0	CONCLUSION	6

FCC ID: BEJWC500MRN		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Quality Manager
Test Report S/N: 1M1804270089-01.BEJ	Test Dates: 4/26 - 5/2/2018	EUT Type: Vehicle Installed Wireless Charging System		Page 2 of 6

1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Introduction

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations and RSS-102 of Industry Canada.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310 and RSS-102: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	f/300	6
1500-100,000	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30



Table 1-1. Limits for Maximum Permissible Exposure (MPE)

Per the guidance of KDB 680106, the E-field and H-field limits shown in the table above are extended down to 100kHz.

1.2 EUT Description

The **EUT FCC ID: BEJWC500MRN** is a wireless charging system (source) that transfers power to a client device via inductive coupling using the WPC wireless charging protocol. Wireless power transfer is initiated when the dummy load is placed on the charger system.

Output power of the charging pad is fixed to 15W in WPC mode.

FCC ID: BEJWC500MRN		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Quality Manager
Test Report S/N: 1M1804270089-01.BEJ	Test Dates: 4/26 - 5/2/2018	EUT Type: Vehicle Installed Wireless Charging System		Page 3 of 6

1.3 Test Equipment

Test equipment calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Narda	EHP-200AC	Electronic & Magnetic Field Probe	8/31/2017	Annual	8/31/2018	170WX60209

Table 1-2. Test Equipment List

1.4 Test Setup

Maximum E-field and H-field measurements were made on each of five sides of the EUT that could come in contact with a user. The five sides are defined as follows: Bottom (A), Right (B), Top (C), Left (D), and Front (E). Refer to the test position diagram below.

Mobile Condition

"Mobile Condition" section and include text instead: "All E-field and H-field measurements are performed per the guidance of KDB 680106 D01 v03. Test distance was 15cm on the surrounding sides and 20cm from the top side of the EUT.






Figure 1. Test Positions and Probe Distance

FCC ID: BEJWC500MRN		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Quality Manager
Test Report S/N: 1M1804270089-01.BEJ	Test Dates: 4/26 - 5/2/2018	EUT Type: Vehicle Installed Wireless Charging System	Page 4 of 6	

1.5 Summary of Results

The procedure used to determine the RF power density for the mobile condition was based upon E-field and H-field measurements recorded using a calibrated probe. All measurements were recorded with the EUT (the charging system) transferring power to the Rx dummy loads that support the WPC charging protocols. The pad itself was running off of a 12VDC power supply.

Care was exercised to ensure that the charging system was transferring power to the dummy loads throughout the duration of the field strength measurements.

During testing, the charging system with WPC dummy load was placed on a non-conductive (composite plastic) table top. The probe was positioned at the location where there is maximum field strength on each side of the EUT. The maximum E-field and H-field is reported below.

Distance (cm)	EUT SIDES					Limit (V/m)
	A (V/m)	B (V/m)	C (V/m)	D (V/m)	E (V/m)	
20					1.425	614.00
15	1.145	1.684	1.817	1.604	1.976	614.00



Table 1-3. E-field Measurements (15W WPC)

Distance (cm)	EUT SIDES					Limit (A/m)
	A (A/m)	B (A/m)	C (A/m)	D (A/m)	E (A/m)	
20					0.0375	1.63
15	0.0438	0.0594	0.0438	0.0375	0.0531	1.63

Table 1-4. H-field Measurements (15W WPC)



Note:

The data above show that the aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

FCC ID: BEJWC500MRN		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Quality Manager
Test Report S/N: 1M1804270089-01.BEJ	Test Dates: 4/26 - 5/2/2018	EUT Type: Vehicle Installed Wireless Charging System		Page 5 of 6

2.0 CONCLUSION

The E-field and H-field data shown in this report show that the Vehicle Installed Wireless Charger System is compliant with the MPE limits.

FCC ID: BEJWC500MRN		MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Quality Manager
Test Report S/N: 1M1804270089-01.BEJ	Test Dates: 4/26 - 5/2/2018	EUT Type: Vehicle Installed Wireless Charging System		Page 6 of 6