

# TEST REPORT

## FCC SAR Exclusion Report for WR24GA Certification

APPLICANT  
LG Electronics Inc.

REPORT NO.  
HCT-SR-2407-FC019

DATE OF ISSUE  
July 30, 2024

Technical Manager  
Yun Jeang Heo

(signature) 

Accredited by KOLAS, Republic of KOREA

**HCT CO., LTD.**  
*BongJai Huh*  
BongJai Huh / CEO

HCT CO.,LTD.

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 645 6300 Fax. +82 31 645 6401

**TEST  
REPORT**  
FCCBT LE Test for  
WR24GA

REPORT NO.  
HCT-SR-2407-FC019

DATE OF ISSUE  
July 30, 2024

Applicant **LG Electronics Inc.**  
222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do 17709, Republic of Korea

EUT Type Simple Remote  
Model Name WR24GA

FCC ID BEJWR24GA

Location of Test  Permanent Testing Lab  On Site Testing Lab  
(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si,  
Gyeonggi-do, 17383 KOREA)

Maximum Output Power 8 dBm (EIRP)

Modulation type GFSK

FCC Classification Digital Transmission System (DTS)

FCC Rule Part(s) 47CFR §2.1093

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

## REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	July 30, 2024	Initial Release

## Notice

---

### Content

---

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked \*.

Information provided by the applicant is marked \*\*.

Test results provided by external providers are marked \*\*\*.

When confirmation of authenticity of this test report is required, please contact [www.hct.co.kr](http://www.hct.co.kr)

This test report provides test result(s) under the scope accredited by the Korea Laboratory Accreditation Scheme (KOLAS), which signed the ILAC-MRA.

(KOLAS (KS Q ISO/IEC 17025) Accreditation No. KT197)

---

## CONTENTS

1. EUT DESCRIPTION	5
2. TEST METHODOLOGY	6
2.1 FCC	6

## 1. EUT DESCRIPTION

Model Name	WR24GA
EUT Type	Simple Remote
Power Supply	DC 3.0 V
Frequency Range	2 402 MHz – 2 480 MHz
Max. RF Output Power	Conducted power 4 dBm +/- 2.06 dB + peak. Antenna gain 1.94 dBi = 8 dBm (EIRP)
Modulation Type	GFSK
Bluetooth Version	4.2
Number of Channels	40 Channels
Antenna Specification	Antenna type: PCB Antenna peak. Antenna gain 1.94 dBi
EUT Serial Number	Conduction: WR24GA_C1 Radiation: WR24GA_R1
Manufacturer	222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do 17709, Republic of Korea

## 2. TEST METHODOLOGY

### 2.1 FCC

Limb SAR and Body SAR Test Exclusions Applied \_Bluetooth 4.2 LE

Since this product is a remote control product, it is used by most users in the hand, so Limb SAR standard is applied. In addition, since this product is capable of voice recognition by the user, an exception evaluation is applied at a distance of 10 mm from the Body SAR.

According to the FCC KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances  $\leq$  50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

a) For 100 MHz to 6 GHz and test separation distances  $\leq$  50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq$   
 3.0 for 1-g SAR, and  $\leq$  7.5 for 10-g extremity SAR, where

$$\frac{\text{Max Power of Channel(mW)}}{\text{Test Separation Distance (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0 \text{ For 1g SAR, } 7.5. \text{ for 10g SAR}$$

where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Calculation Result:

Tx frequency range: 2 402 MHz ~ 2 480 MHz

Limb SAR Consideration Min. test separation distance: 5 mm

Body SAR Consideration Min. test separation distance: 10 mm

Maximum Output Power: 6.06 dBm (4 mW)

The Highest RF channel frequency: 2 480 MHz

#### For Body SAR Exclusion

Mode	Frequency	Maximum Allowed Power	Separation Distance	$\leq$ 3.0 for 1 g SAR
	[MHz]	[mW]	[mm]	
Bluetooth 4.2 LE	2 480	4	10	0.6

#### For Limb SAR exclusion

Mode	Frequency	Maximum Allowed Power	Separation Distance	$\leq$ 7.5 for 10 g SAR
	[MHz]	[mW]	[mm]	
Bluetooth 4.2 LE	2 480	4	5	1.3

Based on the maximum output power of Bluetooth 4.2 LE and antenna to use separation distance, Bluetooth 4.2 LE Limb SAR and Body SAR were not required.