

FM Clip Coupler OATS measurements for Xpress

Product Description	Freq (MHz)	vert margin to spec (dB)	FAU OATS reading VERTICAL							FAU OATS reading horizontal							
			0 deg (dBuV)	90 deg (dBuV)	180 deg (dBuV)	270 deg (dBuV)	spec Limit (dBuV/m)	V factor (dB)	Max level corrected (dBuV/m)	horiz margin to spec (dB)	0 deg (dBuV)	90 deg (dBuV)	180 deg (dBuV)	270 deg (dBuV)	spec Limit (dBuV/m)	H Factor (dB)	Max level corrected (dBuV/m)
Escalade glass	88.7	-9.1	50.5	43.9	53.9	58.1	48	-19.20	38.90	-16.1	50.4	50.5	45.7	50.7	48	-18.8	31.90
	96.9	-8.1	47.9	49.1	52.9	59.9	48	-20.00	39.90	-14.5	51.7	50.8	45.8	48.5	48	-18.2	33.49
	107.1	-10.3	48.2	48.4	52.1	58.7	48	-21.00	37.70	-15.9	50.8	46.7	45.9	46.1	48	-18.7	32.10
Camary F90RYJ glass	88.7	-9.2	53.6	53.3	58.0	53.5	48	-19.20	38.80	-10.7	49.2	55.2	45.4	56.1	48	-18.8	37.30
	96.9	-10.9	53	50.9	57.1	51.7	48	-20.00	37.10	-11.6	48.1	54.2	46.9	54.6	48	-18.2	36.40
	107.1	-5.9	58.3	57.2	63.1	56.7	48	-21.00	42.10	-5.8	53.3	60.9	52.4	59.9	48	-18.7	42.20
1997 Nissan Maxima J49VKV Glass	88.7	-19.0	42.9	43.6	48.2	45.8	48	-19.20	29.00	-21.8	40.1	42.0	45.0	44.0	48	-18.8	26.20
	96.9	-19.8	48.2	44.1	45.8	45.2	48	-20.00	28.20	-18.3	46.4	47.4	47.3	47.9	48	-18.2	29.70
	107.1	-17.6	51.4	47.9	51.2	49.8	48	-21.00	30.40	-13.7	48.0	53.0	47.7	50.3	48	-18.7	34.30