

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
CERTIFICATION TO FCC PART 15 REQUIREMENTS**

for

UNINTENTIONAL RADIATOR

302 MHz RECEIVER

MODEL: EX-8000

FCC ID: BGAEX8R

REPORT NO: 99T0402-1

DATE: JULY 13, 1999

Prepared for

**AUDIOVOX CORPORATION
150 MARCUS BOULEVARD
HAUPPAUGE, NY 11788
U.S.A.**

Prepared by

**COMPLIANCE ENGINEERING SERVICES, INC.
1366 BORDEAUX DRIVE
SUNNYVALE, CA 94089, USA
TEL: (408) 752-8166
FAX: (408) 752-8168**

TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE..... 1
2. PRODUCT DESCRIPTION 2
3. TEST FACILITY 2
4. MEASUREMENT EQUIPMENT USED..... 2
5. TEST CONFIGURATION..... 3
6. TESTS CONDUCTED..... 3
7. CONDUCTED EMISSION TEST PROCEDURE..... 3
8. RADIATED EMISSION TEST PROCEDURE..... 4
9. COHERENT TESTS 4
10. EQUIPMENT MODIFICATIONS..... 4
11. TEST CONFIGURATION PHOTOS (RADIATED EMISSION TEST)..... 5

TEST DATA

- Fundamental Frequency Plot
- Radiated Emission Data

Proposed FCC ID Label.....	Exhibit 1
Agent Authorization Letter.....	Exhibit 2
User Manual.....	Attachment A
Block Diagram/Schematics.....	Attachment B

1. VERIFICATION OF COMPLIANCE

COMPANY NAME : AUDIOVOX CORPORATION
 150 MARCUS BOULEVARD
 HAUPPAUGE, NY 11788
 U.S.A.

CONTACT PERSON : PAT LAVELLE / EXECUTIVE VICE
 PRESIDENT

TELEPHONE NO. : (516) 231-7750

EUT DESCRIPTION : 302 MHz RECEIVER

MODEL NAME/NUMBER : EX-8000


FCC ID : BGAEX8R

DATE TESTED : JULY 13, 1999

REPORT NUMBER : 99T0402

TYPE OF EQUIPMENT	SECURITY EQUIPMENT (UNINTENTIONAL RADIATOR)
EQUIPMENT TYPE	302 MHz SUPERREGENERATE RECEIVER
MEASUREMENT PROCEDURE	ANSI 63.4 / 1992
LIMIT TYPE	CERTIFICATION
FCC RULE	CFR 47, PART 15.109

The above equipment was tested by Compliance Engineering Services, Inc. for compliance with the requirements set forth in CFR 47, PART 15. This said equipment in the configuration described in this report shows that maximum emission levels emanating from equipment are within the compliance requirements.



MIKE C.I. KUO / VICE PRESIDENT
 COMPLIANCE ENGINEERING SERVICES, INC.

2. PRODUCT DESCRIPTION

AUDIOVOX CORP., Model EX-8000 is the receiving portion of a multi-purpose security device. The associated Transmitter is manufactured by Audiovox Corp., Model No: FOB-OE3B, FCC ID: BGAOE3B.

3. TEST FACILITY

The 3 meter open area test site and conducted measurement facility used to collect the radiated data is located at 561F Monterey Road, Morgan Hill, California, U.S.A. A detailed description of the test facilities was submitted to the Commission on May 27, 1994.

The measuring instrument which was utilized in performing the tests documented herein has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment which is traceable to recognized national standards.

4. MEASUREMENT EQUIPMENT USED

Manufacturer	Model Number	Description	Cal Due Date
H.P.	8640B	Signal Generator (0.5 - 1024 MHz)	08/99
H.P.	8566B	Spectrum Analyzer (100Hz - 22GHz)	09/99
EMCO	3146	Antenna (200-1000 MHz)	10/99
H.P.	8447D	Preamplifier (0.1 - 1300 MHz)	09/99
ARA	DRG-18/A	Antenna(1 - 18GHZ)	12/99
H.P.	8449B	Preamplifier (1-26.5GHZ)	03/00

5. TEST CONFIGURATION

Set signal generator to transmit at 302 MHz. The receiver receives the signal.

6. TESTS CONDUCTED

CFR 47, 15.107 CONDUCTED TESTS	CONDUCTED WHEN DEVICE CONNECTED TO AC LINE
CFR 47, 15.109 RADIATED EMISSION TESTS	CONDUCTED AT 3 METERS

7. CONDUCTED EMISSION TEST PROCEDURE

The EUT is located so that the distance between the boundary of the EUT and the closest surface to the LISN is 0.8m.

Conducted disturbance shall be measured between the phase lead and the ground, and between the neutral lead and the ground. The frequency 0.450 - 30 MHz shall be investigated.

Set the EMI receiver to PEAK detector setting and sweep continuously over the frequency range to be investigated. Set resolution bandwidth to 9kHz minimum. Connect EMI receiver input cable to LINE 1 RF measurement connection on the LISN. Connect a 50ohm terminator to the unused RF connection on the LISN. For each mode of EUT operation, maximize emissions readings by manipulating cable and wire positions. Record the configuration for each EUT power cord which produces emissions closest to the limit. Repeat the same procedure for LINE 2 of each EUT power cord.

8. RADIATED EMISSION TEST PROCEDURE

The EUT and all other support equipment are placed on a wooden table 80 cm above the ground screen. Antenna to EUT distance is 3 meters. During the test, the table is rotated 360 degrees to maximize emissions and the antenna is positioned from 1 to 4 meters above the ground screen to further maximize emissions. The antenna is polarized in both vertical and horizontal positions.

Monitor the frequency range of interest at a fixed antenna height and EUT azimuth. Frequency span should be small enough to easily differentiate between broadcast stations and intermittent ambients. Rotate EUT 360 degrees to maximize emissions received from EUT. If emission increases by more than 1 dB, or if another emission appears that is greater by 1 dB, return to azimuth where maximum occurred and perform additional cable manipulation to further maximize received emission.

Move antenna up and down to further maximize suspected highest amplitude signal. If emission increased by 1 dB or more, or if another emission appears that is greater by 1dB or more, return to antenna height where maximum signal was observed and manipulate cables to produce highest emissions, noting frequency and amplitude.

9. COHERENT TESTS

During Radiated Emission Tests, H.P. signal generator model no: 8640B (0.5 - 1024 MHz) was used to radiate unmodulated CW signal to EUT at 302.0 MHz. Please refer to radiated emission data no: 990713C1 for six highest readings.

10. EQUIPMENT MODIFICATIONS

To achieve compliance to FCC section 15.109, the following change(s) were made during compliance testing:

NOT APPLICABLE

11. TEST CONFIGURATION PHOTOS (Radiated Emission Test)