



Valued Quality. Delivered.

TEST REPORT

Report No.: 14060481HKG-001

HeathCo LLC

Application
For
Certification
(Original Grant)
(FCC ID: BJ4-WLTX201)

Transmitter

Prepared and Checked by:

Approved by:

Signed On File
Yeung Yung Fai, James
Engineer

Wong Kwok Yeung, Kenneth
Lead Engineer
Date: July 9, 2014

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.

Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-ettsemko.com

INTERTEK TESTING SERVICES

GENERAL INFORMATION

| | |
|---------------------------|--|
| Grantee: | HeathCo LLC |
| Grantee Address: | 2445 Nashville Road, Bowling Green, Kentucky 42101, United States. |
| Contact Person: | Jeff Bessinger |
| Tel: | 270-846-8271 |
| Fax: | 270-846-8501 |
| e-mail: | jbessinger@heathcollc.com |
| Manufacturer: | ZheJiang Bernal Electric Co., Ltd. |
| Manufacturer Address: | Weishiqi Road (east end), Yueqing Economic Development Zone, Zhejiang Province, China. |
| Brand Name: | HeathCo LLC |
| Model: | WLTX-201 |
| Type of EUT: | Transmitter |
| Description of EUT: | Wireless Door Chime Transmitter |
| Serial Number: | N/A |
| FCC ID: | BJ4-WLTX201 |
| Date of Sample Submitted: | June 10, 2014 |
| Date of Test: | June 10, 2014 to June 12, 2014 |
| Report No.: | 14060481HKG-001 |
| Report Date: | July 9, 2014 |
| Environmental Conditions: | Temperature: +10 to 40°C Humidity: 10 to 90% |

INTERTEK TESTING SERVICES

SUMMARY OF TEST RESULT

| TEST SPECIFICATION | REFERENCE | RESULTS |
|---|-----------|---------|
| Transmitter Field Strength, Bandwidth and Timing Requirement | 15.231(a) | Pass |

The equipment under test is found to be complying with the following standards:
FCC Part 15, October 1, 2012 Edition

- Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

INTERTEK TESTING SERVICES

Table of Contents

| | | |
|------|--|----|
| 1.0 | <u>General Description</u> | 1 |
| 1.1 | Product Description | 1 |
| 1.2 | Related Submittal(s) Grants..... | 1 |
| 1.3 | Test Methodology | 1 |
| 1.4 | Test Facility | 1 |
| 2.0 | <u>System Test Configuration</u> | 2 |
| 2.1 | Justification..... | 2 |
| 2.2 | EUT Exercising Software..... | 2 |
| 2.3 | Special Accessories | 2 |
| 2.4 | Measurement Uncertainty..... | 2 |
| 2.5 | Support Equipment List and Description..... | 2 |
| 3.0 | <u>Emission Results</u> | 3 |
| 3.1 | Field Strength Calculation..... | 3 |
| 3.2 | Radiated Emission Configuration Photograph | 4 |
| 3.3 | Radiated Emission Data | 4 |
| 4.0 | <u>Equipment Photographs</u> | 7 |
| 5.0 | <u>Product Labelling</u> | 7 |
| 6.0 | <u>Technical Specifications</u> | 7 |
| 7.0 | <u>Instruction Manual</u> | 7 |
| 8.0 | <u>Miscellaneous Information</u> | 8 |
| 8.1 | Measured Bandwidth..... | 8 |
| 8.2 | Discussion of Pulse Desensitization | 9 |
| 8.3 | Calculation of Average Factor..... | 9 |
| 8.4 | Emissions Test Procedures | 12 |
| 9.0 | <u>Confidentiality Request</u> | 13 |
| 10.0 | <u>Equipment List</u> | 14 |

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is a transmitter for Remote door bell operating at 315MHz which is operated by a crystal. The EUT is powered by 1 x 3.0V CR2032 button cell. The EUT has one control key, press the control key on the EUT in order to control the desired door bell receiver. This manually transmitter will automatically deactivate the transmitter within not more than 5 seconds of being released.

The timing plot is saved with file name: timing.pdf

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is a single application for certification of a transmitter.

The receiver for this transmitter (with FCC ID: BJ4-WLTX201) has been authorized by Declaration of the Conformity procedure.

1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

INTERTEK TESTING SERVICES

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The device was powered by 1 x 3.0V CR2032 button cell.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.5 Support Equipment List and Description

N/A.

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where FS = Field Strength in dB μ V/m
 RA = Receiver Amplitude (including preamplifier) in dB μ V
 CF = Cable Attenuation Factor in dB
 AF = Antenna Factor in dB
 AG = Amplifier Gain in dB
 AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where FS = Field Strength in dB μ V/m
 RR = RA - AG - AV in dB μ V
 LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$\begin{aligned} RA &= 52.0 \text{ dB}\mu\text{V/m} \\ AF &= 7.4 \text{ dB} & RR &= 18.0 \text{ dB}\mu\text{V} \\ CF &= 1.6 \text{ dB} & LF &= 9.0 \text{ dB} \\ AG &= 29.0 \text{ dB} \\ AV &= 5.0 \text{ dB} \\ FS &= RR + LF \\ FS &= 18 + 9 = 27 \text{ dB}\mu\text{V/m} \end{aligned}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 1575.000 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 8.8 dB

INTERTEK TESTING SERVICES

Applicant: HeathCo LLC

Date of Test: June 12, 2014

Model: WLTX-201

Worst-Case Operating Mode: Transmission

Table 1

Radiated Emissions Pursuant to FCC Part 15 Section 15.231(a) Requirement

| Polarization | Frequency (MHz) | Reading (dB μ V) | Pre-Amp (dB) | Antenna factor (dB) | Average Factor (dB) | Net at 3m (dB μ V/m) | Average Limit at 3m (dB μ V/m) | Margin (dB) |
|--------------|-----------------|----------------------|--------------|---------------------|---------------------|--------------------------|------------------------------------|--------------|
| H | 315.000 | 70.3 | 16 | 23.0 | 10.8 | 66.5 | 75.6 | -9.1 |
| H | 630.000 | 27.7 | 16 | 29.0 | 10.8 | 29.9 | 55.6 | -25.7 |
| H | 945.000 | 25.6 | 16 | 33.0 | 10.8 | 31.8 | 55.6 | -23.8 |
| V | 1260.000 | 56.7 | 34 | 26.1 | 10.8 | 38.0 | 55.6 | -17.6 |
| V | 1575.000 | 62.8 | 34 | 27.2 | 10.8 | 45.2 | 54.0 | -8.8 |
| H | 1890.000 | 64.3 | 34 | 27.2 | 10.8 | 46.7 | 55.6 | -8.9 |
| V | 2205.000 | 57.4 | 34 | 29.4 | 10.8 | 42.0 | 54.0 | -12.0 |
| H | 2520.000 | 51.4 | 34 | 30.4 | 10.8 | 37.0 | 55.6 | -18.6 |
| H | 2835.000 | 46.9 | 34 | 30.4 | 10.8 | 32.5 | 54.0 | -21.5 |
| H | 3150.000 | 45.1 | 34 | 31.9 | 10.8 | 32.2 | 55.6 | -23.4 |

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by bold italic) within the restricted band meets the requirement of FCC Part15 Section 15.205/RSS-210 Section 2.2.

INTERTEK TESTING SERVICES

Applicant: HeathCo LLC

Date of Test: June 12, 2014

Model: WLTX-201

Worst-Case Operating Mode: Transmission

Table 2

Radiated Emissions Pursuant to FCC Part 15 Section 15.231(a) Requirement

| Polarization | Frequency (MHz) | Reading (dB μ V) | Pre-Amp (dB) | Antenna factor (dB) | Net at 3m (dB μ V/m) | Peak Limit at 3m (dB μ V/m) | Margin (dB) |
|--------------|-----------------|----------------------|--------------|---------------------|--------------------------|---------------------------------|--------------|
| H | 315.000 | 70.3 | 16 | 23.0 | 77.3 | 95.6 | -18.3 |
| H | 630.000 | 27.7 | 16 | 29.0 | 40.7 | 75.6 | -34.9 |
| H | 945.000 | 25.6 | 16 | 33.0 | 42.6 | 75.6 | -33.0 |
| V | 1260.000 | 56.7 | 34 | 26.1 | 48.8 | 75.6 | -26.8 |
| V | 1575.000 | 62.8 | 34 | 27.2 | 56.0 | 74.0 | -18.0 |
| H | 1890.000 | 64.3 | 34 | 27.2 | 57.5 | 75.6 | -18.1 |
| V | 2205.000 | 57.4 | 34 | 29.4 | 52.8 | 74.0 | -21.2 |
| H | 2520.000 | 51.4 | 34 | 30.4 | 47.8 | 75.6 | -27.8 |
| H | 2835.000 | 47.4 | 34 | 30.4 | 43.8 | 74.0 | -30.2 |
| H | 3150.000 | 45.1 | 34 | 31.9 | 43.0 | 75.6 | -32.6 |

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by bold italic) within the restricted band meets the requirement of FCC Part15 Section 15.205/RSS-210 Section 2.2.

INTERTEK TESTING SERVICES

4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

6.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.


INTERTEK TESTING SERVICES

8.0 Miscellaneous Information

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

8.1 Measured Bandwidth

For below plot, which shows the fundamental emission when modulated is saved with filename: bw.pdf. From the plot, the 20dB bandwidth is 430kHz and less than the limit of 787.5kHz. It fulfils the requirement of 15.231(C).



INTERTEK TESTING SERVICES

8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately 0.32ms for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

8.3 Calculation of Average Factor

The duty cycle is simply the on-time divided by the period:



The duration of one cycle = $0.32\text{ms} \times 5 + 0.72\text{ms} \times 8 = 7.36\text{ms}$

Effective period of the cycle = 25.48ms


DC = $(7.36\text{ms}) / 25.48\text{ms} = 0.2889$

Therefore, the averaging factor is found by $20\log(0.2889) = -10.8\text{dB}$.

INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

INTERTEK TESTING SERVICES

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 (2009).

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

9.0 **Confidentiality Request**

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

INTERTEK TESTING SERVICES

10.0 Equipment List

1) Radiated Emissions Test

| Equipment | EMI Test Receiver | Biconical Antenna | Log Periodic Antenna |
|----------------------|-------------------|-------------------|----------------------|
| Registration No. | EW-2666 | EW-0571 | EW-0572 |
| Manufacturer | R&S | EMCO | EMCO |
| Model No. | ESCI7 | 3104C | 3146 |
| Calibration Date | Jun. 20, 2013 | Nov. 01, 2013 | Jun. 26, 2013 |
| Calibration Due Date | Jun. 20, 2014 | May 01, 2015 | Dec. 26, 2014 |

| Equipment | Spectrum Analyzer | Double Ridged Guide Antenna |
|----------------------|-------------------|-----------------------------|
| Registration No. | EW-2466 | EW-1015 |
| Manufacturer | R&S | EMCO |
| Model No. | FSP30 | 3115 |
| Calibration Date | Aug. 04, 2013 | Mar. 05, 2013 |
| Calibration Due Date | Aug. 04, 2014 | Sep. 05, 2014 |

2) Bandedge Measurement

| Equipment | Spectrum Analyzer |
|----------------------|-------------------|
| Registration No. | EW-2249 |
| Manufacturer | R&S |
| Model No. | FSP30 |
| Calibration Date | Oct. 28, 2013 |
| Calibration Due Date | Oct. 28, 2014 |

END OF TEST REPORT