

RF Exposure Evaluation declaration

Product Name : Digital Entertainment Center
Model No. : KHA-01651B
FCC ID : BJM-KHA01651B

Applicant : TATUNG CO.

Address : 22, Chungshan N. Rd., 3rd Sec. Taipei, Taiwan, 104, R.O.C.

Date of Receipt : May 10, 2007

Date of Declaration : July 09, 2007

Report No. : 076011R-RFUSP05V01

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product : Digital Entertainment Center
 Test Item : RF Exposure Evaluation
 Test Site : No.3 OATS

Use PIFA Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.5 dBi in logarithm scale.

802.11b (PIFA)

Output Power Into Antenna & RF Exposure Evaluation Distance (1.5 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412.00	39.9945	0.0112
6	2437.00	56.3638	0.0158
11	2462.00	72.6106	0.0204

802.11g (PIFA)

Output Power Into Antenna & RF Exposure Evaluation Distance (1.5 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412.00	73.6207	0.0207
6	2437.00	95.7194	0.0269
11	2462.00	129.7179	0.0365

The distance r (4th column) calculated from the Friis transmission formula is far shorter than 20 cm separation requirement.

Use Dipole Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2 dBi in logarithm scale.

802.11b (Dipole)

Output Power Into Antenna & RF Exposure Evaluation Distance (2 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412.00	39.9945	0.0126
6	2437.00	56.3638	0.0178
11	2462.00	72.6106	0.0229

802.11g (Dipole)

Output Power Into Antenna & RF Exposure Evaluation Distance (2 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412.00	73.6207	0.0232
6	2437.00	95.7194	0.0302
11	2462.00	129.7179	0.0409

The distance r (4th column) calculated from the Friis transmission formula is far shorter than 20 cm separation requirement.