

## 1.2. Operational Description

The EUT is a ROS Video DMA with a built-in 2.4GHz and 5GHz WLAN card. This device provided four kinds of transmitting speed 1, 2, 5.5 and 11Mbps and the device of RF carrier is DBPSK, DQPSK and CCK (IEEE 802.11b). The device provided of eight kinds of transmitting speed 6, 9, 12, 18, 24, 36, 48 and 54Mbps the device of RF carrier is BPSK, QPSK, 16QAM and 64QAM (IEEE 802.11a/g).

The device provided of eight kinds of transmitting speed 13,26,39,52,78,104,117 and 130Mbps in 802.11n(20BW) mode and 27,54,81,108,162,216,243 and 270Mbps(40BW) the device of RF carrier is BPSK, QPSK, 16QAM and 64QAM (IEEE 802.11n), the IEEE 802.11n is Multiple In, Multiple Out" (MIMO) technology.

The device adapts direct sequence spread spectrum modulation. The antenna provides diversity function to improve the receiving function and the antennas to support 2 (Transmit) × 3 (Receive) MIMO technology.

This ROS Video DMA, compliant with IEEE 802.11b and IEEE 802.11a/g/n, is a high-efficiency Wireless LAN adapter. It allows your computer to connect to a wireless network and to share resources, such as files or printers without being bound to the network wires. Operation in 2.4GHz Direct Sequence Spread Spectrum (DSSS) radio transmission, the ROS Video DMA Wired Equivalent Protection (WEP) algorithm is used. In addition, its standard compliance ensures that it can communicate with any IEEE 802.11b and IEEE 802.11a/g/n network.

No ad-hoc operation in the DFS band, Another information please refer to users manual.