



Exhibit 4

The RFI / EMI Test Report issued by the Tatung EMC Lab

**ELECTROMAGNETIC EMISSIONS
TEST REPORT
FCC CLASS B COMPLIANCE**

ON

**TATUNG CO.
COLOR MONITOR
MODEL C7B**

REPORT PREPARED BY
TATUNG CO.
22 CHUNGSHAN NORTH RD., 3RD SEC.,
TAIPEI, TAIWAN, R. O. C.
TEL: (02)2592-5252

REPORT NUMBER : TTEMC - 99001
DATE OF TEST : Dec. 31, 1998
DATE OF REPORT : Jan. 6, 1998

TEST REPORT CERTIFICATION

APPLICANT : TATUNG CO.

MANUFACTURER : TATUNG CO.

EUT DESCRIPTION : Color Monitor

(A) MODEL NO. : C7B

(B) SERIAL NO. : - - -

(C) POWER SUPPLY : 120 V AC 60 Hz

MEASUREMENT PROCEDURE USED :

FCC RULES AND REGULATIONS PART 15 SUBPART B CLASS

B JUNE 1989 AND ANSI C63.4 / 1992

The device described above was tested by TATUNG CO. to determine the maximum emission levels emanating from the device.

The maximum emission levels were compared to the FCC PART 15B Class B limits both radiated and conducted emissions.

The measurement results are contained in this test report and TATUNG CO. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliant with the FCC official limits.

Date of test : Dec. 31 , 1998

Prepared by : (Wu Wan Ling) Wu Wan Ling

Test engineer : (Chen Yow Chang) Chen Yow-Chang

Approved & Authorized Signer : (Chia-Fu Lee) Chia Fu Lee

1. GENERAL INFORMATION

1.1 Description of EUT

Description	Color Monitor
Model Number	C7B
Manufacturer	Tatung Co. 22 Chungshan N. Rd., 3rd, Sec., Taipei, Taiwan 10451, R.O.C.
Applicant	Tatung Co.
FCC ID	BJMC7B
Date of Test	Dec.31 ,1998
Signal Cable	Shielded,undetachable
Power Cord	Shielded,detachable

Note : The EUT was tested under the following resolution & horizontal synchronization speed mode :

1280 × 1024 mode (64KHz, 1280 × 1024 Noninterlaced)

1024 × 768 mode (69KHz)

800 × 600 mode (48KHz)

640 × 480 mode (31.5KHz)

1.2 Description of Configuration

1.2.1 Host Personal Computer

Model Number	TCS-5950
Serial Number	95003459
Manufacturer	BJM5950
Power Supply Type	Switching
Power Cord	Shielded,detachable

1.2.2 MOUSE

Model Number	DMS-400+
Serial Number	N/A
FCC ID	F4Z4K3FDM-201
Manufacturer	DFI
Data Cable	Shielded, undetachable

1.2.3 KEYBOARD

Model Number	FDA-102D
Serial Number	K101020
FCC ID	F4Z4K3FDA-102D
Manufacturer	FORWARD ELECTRONICS CO.,LTD.
Data Cable	Shielded, undetachable

1.2.4 PRINTER

Model Number	EN3211
Serial Number	508A0086962
FCC ID	BDB9F2EN3211
Manufacturer	OK IDATA
Power Supply	Within Mother Board
Power Cord	Unshielded, undetachable
Data Cable	Shielded, detachable

1.2.5 MODEM

Model Number	1200AT
Serial Number	AT122290
FCC ID	EF56A5 1200AT
Manufacturer	TEAM TECHNOLOGY, INC.
Power Supply Type	Linear
Data Cable	Shielded, detachable
Power Cord	Unshielded

1.2.6 VGA DISPLAY CARD

Model Number	DSV3365E
Serial Number	E601404314
Power Supply Type	DC
FCC ID	LUT-DSV3365

1.3 Description of Test Site

Site description	May 8, 1990 On file with Federal Communication Commission FCC Engineering Laboratory 7435 Oakland Mills Road Columbia, MD 21046
Name of Firm	TATUNG CO.
Site Location	393, SEC. 1, Chung Cheng Rd., San-Hsia County, Taipei, Taiwan R.O.C.


2. POWER LINE CONDUCTED TEST

2.1 Test Equipments

The following test equipments are used during the power line conducted tests :

Equipments Type & Manufacturer	Model No.	Date of Calibration
Spectrum Analyzer (HP)	8568B	September,1997
Quasi-Peak Adapter (HP)	85650A	September,1997
L.I.S.N. (EMCO)	3825/2	September,1997
Printer (HP)	2227B	N/A
Plotter (HP)	7440A	September,1997
Rohde & Schwarz Test Receiver	ESH3	September,1997
Shielded Room (7.2 m × 5.4 m × 2.45 m)	---	N/A

2.2 Block Diagram of Test Setup



2.3 CLASS B Conducted Powerline Emission Limit

Frequency	Maximum RF Line Voltage	
	μV	dB μV
0.45 – 30	250	48

REMARKS : RF LINE VOLTAGE (db μV) = 20 log RF LINE VOLTAGE (μV)

2.4 EUT Configuration on Measurement

The equipments in Item 1.2 are installed on RF LINE VOLTAGE measurement to meet the Commission requirement and operating in a manner which tends to maximize its emission characteristics in a normal application.

2.5 Operating Condition of EUT

2.5.1 Setup the EUT and peripheral devices as shown on 2.2.

2.5.2 Turn on the power of all equipments.

2.5.3 Set the VGA display card on 1280×1024 mode (69KHz).

2.5.4 PC reads test program from hard disk and run it.

2.5.5 PC sends "H" character to monitor and the screen will display and fill with "H" pattern.

2.5.6 PC sends "H" character to printer, the printer will print "H" pattern on paper.

2.5.7 PC sends "H" character to modem.

2.5.8 Repeat the above procedures from 2.5.4 to 2.5.7.

2.5.9 Change the mode of VGA display card to 800×600 mode (48KHz) and repeat steps 2.5.4 to 2.5.8.

2.5.10 Change the mode of VGA display card on Standard VGA mode (31.5KHz) and repeat steps 2.5.4 to 2.5.8.

2.6 Test Procedure

The test is performed in a shielded room. The EUT is placed on a wooden table which is 80cm height at a distance of 40cm in front of an earthed metal wall of the shielded room.

The EUT is connected to the power mains through a line impedance stabilization network(L.I.S.N.). This provides a 50 ohm coupling impedance for the measuring equipment. Both sides of A. C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables must be changed according to ANSI C 63.4 / 1992 on conducted measurement.

The bandwidth of the Quasi-Peak Adapter (HP 85650A) is set at 10 kHz.

The frequency range from 450 kHz to 30 MHz is checked.

2.7.1 Line Conducted RF Voltage Measurement Results

The frequency spectrum from 0.45 MHz to 30 MHz is investigated.
All emissions not reported below are too low against the FCC Class B limit.

Date of Test : Dec. 31, 1998

Temperature : 20 °C

EUT : Color Monitor : C7B

Humidity : 70 %

Working Frequency : 31.5KHz

Display Pattern: 640×480


Frequency (MHz)	Reading (dB μ V)		Limits (dB μ V)
	One End & GRD	The Other End & GRD	
	(dB μ V)	(dB μ V)	
0.47	30.8	31.6	48
1.25	25.8	23.4	48
3.75	32.1	30.1	48
8.71	31.1	28.9	48
20.05	32.5	32.3	48
25.84	31.6	31.6	48

REMARKS : 1.All readings are Quasi-peak values.

TATUNG EMC LAB.
FCC CLASS B

EUT: C7B
Manuf: TATUNG
Op Cond: L1
Operator: Y C. CHEN
Test Spec: 640x480 31.5KHz
Date: 08. Jan 99 11:56


FCC ID:BJMC7B



TATUNG EMC LAB.
FCC CLASS B

EUT: C7B
Manuf: TATUNG
Op Cond: L2
Operator: Y C. CHEN
Test Spec: 640x480 31.5KHz
Date: 08. Jan 99 12:07

FCC ID:BJMC7B



2.7.2 Line Conducted RF Voltage Measurement Results

The frequency spectrum from 0.45 MHz to 30 MHz is investigated.
All emissions not reported below are too low against the FCC Class B limit.

Date of Test : Dec. 31, 1998

Temperature : 20 °C

EUT : Color Monitor : C7B

Humidity : 70 %

Working Frequency : 48KHz

Display Pattern : 800×600


Frequency (MHz)	Reading (dB μ V)		Limits (dB μ V)
	One End & GRD	The Other End & GRD	
	(dB μ V)	(dB μ V)	
0.65	27.8	30.1	48
3.70	32.9	35.3	48
5.67	29.5	31.8	48
9.66	26.6	38.8	48
15.85	34.4	37.3	48
26.31	30.0	30.6	48

REMARKS : 1.All readings are Quasi-peak values.

TATUNG EMC LAB.
FCC CLASS B

EUT: C7B
Manuf: TATUNG
Op Cond: L1
Operator: Y C. CHEN
Test Spec: 800x600 48KHz
Date: 08. Jan 99 11:46


FCC ID:BJMC7B



TATUNG EMC LAB.
FCC CLASS B

EUT: C7B
Manuf: TATUNG
Op Cond: L2
Operator: Y C. CHEN
Test Spec: 800x600 48KHz
Date: 08. Jan 99 11:36

FCC ID:BJMC7B



2.7.3 Line Conducted RF Voltage Measurement Results

The frequency spectrum from 0.45 MHz to 30 MHz is investigated.
All emissions not reported below are too low against the FCC Class B limit.

Date of Test : Dec. 31, 1998

Temperature : 20 °C

EUT : Color Monitor : C7B

Humidity : 70 %

Working Frequency : 69KHz

Display Pattern : 1024×768
(Noninterlaced)

Frequency (MHz)	Reading (dB μ V)		Limits (dB μ V)
	One End & GRD	The Other End & GRD	
	(dB μ V)	(dB μ V)	
0.48	41.2	39.1	48
1.57	27.7		48
3.50		41.5	48
3.98	38.3	7.97	48
7.55	37.7	10.09	48
9.54	38.5	15.87	48
18.89	38.0	18.89	48


REMARKS: 1.ALL readings are Quasi-peak values.

TATUNG EMC LAB.

FCC CLASS B

EUT: C7B
Manuf: TATUNG
Op Cond: L1
Operator: Y C. CHEN
Test Spec: 1024x768 69KHz
Date: 08. Jan 99 10:56


FCC ID:BJMC7B



TATUNG EMC LAB.
FCC CLASS B

EUT: C7B
Manuf: TATUNG
Op Cond: L2
Operator: Y C. CHEN
Test Spec: 1024x768 69KHz
Date: 08. Jan 99 11:14

FCC ID:BJMC7B



2.7.4 Line Conducted RF Voltage Measurement Results

The frequency spectrum from 0.45 MHz to 30 MHz is investigated.
All emissions not reported below are too low against the FCC Class B limit.

Date of Test : Dec. 31, 1998

Temperature : 20 °C

EUT : Color Monitor : C7B

Humidity : 70 %

Working Frequency : 64KHz

Display Pattern : 1280×1024
(Noninterlaced)


Frequency (MHz)	Reading (dB μ V)		Limits (dB μ V)
	One End & GRD	The Other End & GRD	
	(dB μ V)	(dB μ V)	
0.57	37.3	37.4	48
1.54	31.8	29.9	48
3.72	38.9	36.9	48
7.82	39.3	37.0	48
21.68	38.5	38.3	48
25.86	37.5	36.9	48

REMARKS: 1.ALL readings are Quasi-peak values.

TATUNG EMC LAB.
FCC CLASS B

EUT: C7B
Manuf: TATUNG
Op Cond: L1
Operator: Y C. CHEN
Test Spec: 1280x1024 64KHz
Date: 08. Jan 99 12:29


FCC ID:BJMC7B



TATUNG EMC LAB.
FCC CLASS B

EUT: C7B
Manuf: TATUNG
Op Cond: L2
Operator: Y C. CHEN
Test Spec: 1280x1024 64KHz
Date: 08. Jan 99 12:18

FCC ID:BJMC7B



3. RADIATED EMISSION TEST


3.1 Test Equipment

The following test equipments are used during the radiated emission tests :


Equipments Type & Manufacturer	Model No.	Date of Calibration
Spectrum Analyzer (HP)	8568B	September,1997
RF Preselector (HP)	85685A	September,1997
Quasi-Peak Adapter (HP)	85650A	September,1997
Preamplifier (HP)	8447F OPT. H64	September,1997
Printer (HP)	2227B	
Plotter (HP)	7440A	
Dipole Antenna (EMCO)	3121C	September,1997

3.2 Test Setup

3.2.1 Block Diagram of Connections between EUT and Peripheral Devices



3.2.2 Open Field Test Site Setup Diagram



3.3 Class B Radiated Limit

Frequency (MHz)	Distance (m)	Field Strength Limits	
		$\mu V/m$	$dB \mu V/m$
30 – 88	3	100	40.0
88 – 216	3	150	43.5
216 – 960	3	200	46.0
960 – 1000	3	500	54.0

- REMARKS :
1. Emission level ($dB \mu V/m$)
= $20 \log$ Emission level ($\mu V/m$)
 2. The tighter limit shall apply at the edge between two frequency bands.
 3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3.4 EUT Configuration

The configuration of EUT and its peripheral devices are the same as those used in conducted test. Please refer to 2.4.

3.5 Operating condition of EUT

Same as conducted test which is listed in 2.5.

3.6 Test Procedure

The EUT and its peripheral devices are placed on a turn table which is 1 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3 meters away from the receiving antenna which is mounted on an antenna tower. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Biconical, log and dipole antennas are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, the relative positions of equipments and all of the interface cable must be changed according to ANSI C63.4/1992 on radiated measurement.

The bandwidth setting on the field strength meter (HP Spectrum Analyzer 85650A) is 120 kHz.

3.7.1 Radiated Emission Noise Measurement Results

The frequency spectrum from 30 MHz to 1000 MHz is investigated. All the emissions not reported below are too low against the FCC CLASS B limit.

Date of Test : Dec. 31, 1998

Temperature : 20 °C

EUT : Color Monitor : C7B

Humidity : 70 %

Working Frequency : 31.5KHz

Display Pattern : 640 × 480

Frequency (MHz)	Antenna Factor (dB)	Cable Loss +Amp. (dB)	Meter Reading Horizontal (dB μ V/m)	Emission Level Horizontal (dB μ V/m)	Limits (dB μ V/m)
33.340	12.95	25.13	37.70	25.52	40.00
48.180	10.41	25.42	42.80	27.79	40.00
57.600	10.08	25.38	44.70	29.44	40.00
69.750	7.92	25.22	39.90	22.60	40.00
73.950	7.15	24.95	44.10	26.30	40.00
82.740	7.36	24.91	40.40	22.85	40.00
130.360	12.87	24.61	29.60	17.86	43.50
150.380	13.92	24.45	29.60	19.07	43.50
157.900	14.21	24.41	29.80	19.61	43.50
162.930	14.47	24.57	30.30	20.20	43.50
170.450	15.53	24.55	27.60	18.58	43.50
195.530	17.05	24.02	29.50	22.52	43.50
205.560	12.30	23.96	26.30	14.64	43.50
208.050	12.26	23.90	29.50	17.87	43.50
213.060	12.19	23.77	30.20	18.62	43.50
220.600	12.07	23.76	30.40	18.71	46.00
225.600	12.07	23.82	31.10	19.35	46.00
238.127	12.54	23.62	32.00	20.92	46.00
245.620	12.83	23.52	31.00	20.32	46.00
250.640	13.02	23.53	30.50	19.99	46.00
258.210	13.31	23.52	29.00	18.79	46.00

REMARKS : 1. All readings are Quasi-peak values

Date of Test : Dec. 31, 1998

Temperature : 20 °C

EUT : Color Monitor : C7B

Humidity : 70 %

Working Frequency : 31.5KHz

Display Pattern : 640×480

Frequency (MHz)	Antenna Factor (dB)	Cable Loss +Amp. (dB)	Meter Reading Vertical (dB μ V/m)	Emission Level Vertical (dB μ V/m)	Limits (dB μ V/m)
32.600	13.15	25.19	40.20	28.15	40.00
42.610	10.93	25.55	38.60	23.98	40.00
45.130	10.62	25.51	39.80	24.91	40.00
57.640	10.08	25.38	40.70	25.41	40.00
73.720	7.16	24.96	48.50	30.70	40.00
82.740	7.36	24.91	43.10	25.55	40.00
130.360	12.87	24.61	31.60	19.86	43.50
150.380	13.92	24.45	31.30	20.77	43.50
157.920	14.22	24.41	28.40	18.21	43.50
162.950	14.47	24.57	31.10	21.00	43.50
170.000	15.45	24.55	30.50	21.40	43.50
220.590	12.07	23.76	27.60	15.91	46.00

REMARKS : 1. All readings are Quasi-peak values

3.7.2 Radiated Emission Noise Measurement Results

The frequency spectrum from 30 MHz to 1000 MHz is investigated. All the emissions not reported below are too low against the FCC CLASS B limit.

Date of Test : Dec. 31, 1998

Temperature : 20 °C

EUT : Color Monitor : C7B

Humidity : 70 %

Working Frequency : 48KHz

Display Pattern : 800 × 600

Frequency (MHz)	Antenna Factor (dB)	Cable Loss +Amp. (dB)	Meter Reading Horizontal (dB μ V/m)	Emission Level Horizontal (dB μ V/m)	Limits (dB μ V/m)
39.600	11.39	25.58	37.30	23.11	40.00
59.440	9.95	25.40	41.50	26.05	40.00
66.090	8.62	25.36	44.60	27.86	40.00
84.210	7.63	24.91	46.30	29.02	40.00
108.980	13.49	24.77	37.10	25.82	43.503
113.930	14.12	24.64	35.40	24.87	43.50
138.710	12.65	24.63	36.50	24.52	43.50
158.520	14.24	24.45	33.80	23.59	43.50
163.460	14.51	24.56	34.00	23.94	43.50
173.690	15.85	24.38	32.90	24.37	43.50
232.790	12.32	23.68	34.80	23.44	46.00
237.770	12.53	23.63	38.30	27.20	46.00
242.710	12.72	23.53	30.50	19.69	46.00
247.700	12.91	23.51	35.20	24.60	46.00
252.640	13.10	23.56	32.90	22.45	46.00
257.580	13.29	23.53	34.90	24.65	46.00
262.530	13.46	23.41	37.50	27.55	46.00
272.450	13.81	23.17	35.20	25.84	46.00
287.330	14.71	23.02	34.40	26.09	46.00
297.220	15.31	22.95	34.20	26.57	46.00

REMARKS : 1. All readings are Quasi-peak values.

Date of Test : Dec. 31, 1998

Temperature : 20 °C

EUT : Color Monitor : C7B

Humidity : 70 %

Working Frequency : 48KHz

Display Pattern : 800×600

Frequency (MHz)	Antenna Factor (dB)	Cable Loss +Amp. (dB)	Meter Reading Vertical (dB μ V/m)	Emission Level Vertical (dB μ V/m)	Limits (dB μ V/m)
39.600	11.39	25.58	42.70	28.51	40.00
59.450	9.95	25.40	41.70	26.25	40.00
66.700	8.50	25.34	44.00	27.16	40.00
84.190	7.63	24.91	44.90	27.62	40.00
108.980	13.49	24.77	36.70	25.42	43.50
148.600	13.56	24.47	31.50	20.59	43.50
232.790	12.32	23.68	30.00	18.64	46.00
237.760	12.53	23.63	31.90	20.80	46.00
247.680	12.91	23.51	29.80	19.20	46.00
257.580	13.29	23.53	32.40	22.15	46.00
262.530	13.46	23.41	35.00	25.05	46.00
272.440	13.81	23.17	34.70	25.34	46.00
287.310	14.71	23.02	31.70	23.39	46.00

REMARKS : 1. All readings are Quasi-peak values.

3.7.3 Radiated Emission Noise Measurement Results

The frequency spectrum from 30 MHz to 1000 MHz is investigated. All the emissions not reported below are too low against the FCC CLASS B limit.

Date of Test : Dec. 31, 1998

Temperature : 20 °C

EUT : Color Monitor : C7B

Humidity : 70 %

Working Frequency : 69KHz

Display Pattern : 1024 × 768

(Noninterlaced)

Frequency (MHz)	Antenna Factor (dB)	Cable Loss +Amp. (dB)	Meter Reading Horizontal (dB μ V/m)	Emission Level Horizontal (dB μ V/m)	Limits (dB μ V/m)
37.810	11.81	25.37	38.60	25.04	40.00
75.610	7.08	24.87	46.50	28.72	40.00
122.870	13.43	24.49	35.00	23.94	43.50
141.790	12.65	24.59	39.10	27.16	43.50
151.240	14.10	24.44	35.70	25.36	43.50
160.710	14.33	24.58	42.30	32.05	43.50
170.180	15.48	24.55	39.20	30.13	43.50
207.980	12.26	23.90	40.10	28.46	43.50
217.440	12.12	23.73	39.30	27.68	46.00
226.800	12.10	23.81	36.50	24.80	46.00
236.350	12.47	23.64	37.20	26.03	46.00
245.810	12.84	23.52	35.20	24.52	46.00
255.230	13.20	23.55	43.00	32.65	46.00
264.700	13.54	23.35	33.70	23.88	46.00
274.180	13.90	23.13	35.10	25.87	46.00

REMARKS : 1. All readings are Quasi-peak values.

Date of Test : Dec. 31, 1998

Temperature : 20 °C

EUT : Color Monitor : C7B

Humidity : 70 %

Working Frequency : 69KHz

Display Pattern : 1024×768

(Noninterlaced)

Frequency (MHz)	Antenna Factor (dB)	Cable Loss +Amp. (dB)	Meter Reading Vertical (dB μ V/m)	Emission Level Vertical (dB μ V/m)	Limits (dB μ V/m)
37.810	11.81	25.37	41.00	27.44	40.00
75.590	7.08	24.87	48.40	30.62	40.00
113.450	14.10	24.65	35.90	25.35	43.50
151.260	14.10	24.44	31.30	20.96	43.50
160.710	14.33	24.58	41.50	31.25	43.50
170.150	15.48	24.55	33.90	24.83	43.50
179.580	16.13	23.97	33.00	25.16	43.50
207.990	12.26	23.90	32.40	20.77	43.50
217.420	12.12	23.73	34.00	22.38	46.00
226.890	12.10	23.80	32.80	21.10	46.00
236.360	12.47	23.64	32.90	21.73	46.00
255.260	13.20	23.55	37.20	26.85	46.00
264.690	13.54	23.35	33.20	23.38	46.00
274.170	13.90	23.13	34.20	24.97	46.00
302.510	15.42	22.82	30.70	23.31	46.00
330.900	14.89	22.14	31.00	23.75	46.00

REMARKS : 1. All readings are Quasi-peak values

3.7.4 Radiated Emission Noise Measurement Results

The frequency spectrum from 30 MHz to 1000 MHz is investigated. All the emissions not reported below are too low against the FCC CLASS B limit.

Date of Test : Dec. 31, 1998

Temperature : 20 °C

EUT : Color Monitor : C7B

Humidity : 70 %

Working Frequency : 69KHz

Display Pattern : 1280 × 1024

(Noninterlaced)

Frequency (MHz)	Antenna Factor (dB)	Cable Loss +Amp. (dB)	Meter Reading Horizontal (dB μ V/m)	Emission Level Horizontal (dB μ V/m)	Limits (dB μ V/m)
54.160	10.21	25.32	51.00	35.89	40.00
65.000	8.83	25.40	41.00	24.44	40.00
129.980	12.88	24.60	36.80	25.08	43.50
140.800	12.63	24.61	42.70	30.73	43.50
151.650	14.10	24.43	40.30	29.98	43.50
162.480	14.44	24.57	49.70	39.57	43.50
173.300	15.81	24.40	39.20	30.61	43.50
184.150	16.68	23.92	47.00	39.76	43.50
194.980	17.01	24.03	46.20	39.19	43.50
205.790	12.30	23.96	41.30	29.64	43.50
216.640	12.13	23.74	48.40	36.80	46.00
227.450	12.12	23.80	44.00	32.32	46.00
238.290	12.55	23.62	53.70	42.63	46.00
249.110	12.96	23.52	49.10	38.55	46.00
259.960	13.37	23.48	52.00	41.90	46.00
270.780	13.75	23.21	49.20	39.74	46.00
292.510	15.04	22.96	48.40	40.48	46.00

REMARKS : 1. All readings are Quasi-peak values.

Date of Test : Dec. 31, 1998

Temperature : 20 °C

EUT : Color Monitor : C7B

Humidity : 70 %

Working Frequency : 64KHz

Display Pattern : 1280×1024

(Noninterlaced)

Frequency (MHz)	Antenna Factor (dB)	Cable Loss +Amp. (dB)	Meter Reading Vertical (dB μ V/m)	Emission Level Vertical (dB μ V/m)	Limits (dB μ V/m)
32.490	13.18	25.20	45.70	33.68	40.00
54.160	10.21	25.32	48.20	33.09	40.00
75.830	7.07	24.85	51.30	33.52	40.00
86.630	8.24	24.85	50.00	33.39	40.00
108.320	13.38	24.79	45.30	33.89	43.50
129.990	12.88	24.60	37.10	25.38	43.50
151.650	14.10	24.43	39.10	28.78	43.50
162.440	14.44	24.57	37.50	27.36	43.50
194.960	17.01	24.03	38.20	31.18	43.50
238.310	12.55	23.62	45.10	34.03	46.00
227.460	12.12	23.80	37.60	25.92	46.00
238.290	12.55	23.62	44.20	33.13	46.00
249.110	12.96	23.52	40.90	30.35	46.00
259.950	13.37	23.48	45.70	35.59	46.00
270.810	13.75	23.21	45.10	35.64	46.00
292.470	15.04	22.96	39.60	31.68	46.00
357.460	15.41	22.02	37.50	30.89	46.00
411.610	17.09	22.06	35.70	30.73	46.00

REMARKS : 1. All readings are Quasi-peak values