
APPENDIX 2: SAR Measurement data

Appendix 2-1: Evaluation procedure

The SAR evaluation was performed with the following procedure:

- Step 1:** Measurement of the E-field at a fixed location above the central position of flat phantom was used as a reference value for assessing the power drop.
- Step 2:** The SAR distribution at the exposed side of head or body position was measured at a distance of each device from the inner surface of the shell. The area covered the entire dimension of the antenna of EUT and suitable horizontal grid spacing of EUT. Based on these data, the area of the maximum absorption was determined by splines interpolation.
- Step 3:** Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure.
A volume of 30 mm (X) × 30 mm (Y) × 30 mm (Z) (or more) was assessed by measuring 7×7×7 points (or more) under 3GHz
A volume of 28 mm (X) × 28 mm (Y) × 24 mm (Z) (or more) was assessed by measuring 8×8×7 (“Ratio step” method (*1)) points (or more) for 3~6 GHz frequency band.
When the SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are proceeded for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.
- Step 4:** Re-measurement of the E-field at the same location as in Step 1 for the assessment of the power drift.
- Step 5:** Repeat Step 1-Step 4 with other condition or/and setup of EUT.

*. The all SAR tests were conservatively performed with test separation distance 0mm. The distance between the SAR probe tip to the surface of test device which is touched the bottom surface of the phantom is approx. 3 mm for 2.4GHz band and 2.4 mm for 5GHz band. The phantom bottom thickness is approx. 2mm in the SAR test area.

*1. “Ratio step” method parameters used; the first measurement point: “1.4mm” from the phantom surface, the initial grid separation: “1.4mm”, subsequent graded grid ratio: “1.4”. These parameters comply with the requirement of KDB 865664 D01 and recommended by Schmid & Partner Engineering AG (DASY5 manual).

Appendix 2-2: SAR measurement data

SAR plot of worst reported SAR (2.4GHz band)

Plot 1-1: (Body-touch) Antenna 0, Bottom & touch, 11b(1Mbps), 2412MHz ->Highest reported SAR(1g), 2.4GHz band

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi_2.4GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2412 MHz; Crest Factor: 1.0**

Medium: M2450(1901); Medium parameters used: f = 2412 MHz; $\sigma = 1.969$ S/m; $\epsilon_r = 50.94$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2412 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0, 161.0

touch/24b3;ant0,2412,btm&d0,11b(1m)

Area:48x72,12 (5x7x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.758 W/kg


Area:48x72,12 (41x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 0.765 W/kg

Z:160,5 (1x1x33): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 0.886 W/kg

Zoom:30x30x30,5 (7x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 20.61 V/m; Power Drift = -0.06 dB; Maximum value of SAR (measured) = 0.889 W/kg; Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.482 W/kg; SAR(10 g) = 0.186 W/kg



Remarks: * . Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place:No.7 shielded room,
 * . liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45) %RH,
 * . liquid temperature: 21.7(start)/21.8(end)/21.9(in check) deg.C.; * . White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 1-2: (Hand-held) Antenna 0, Back & touch, 11b(1Mbps), 2412MHz ->Highest reported SAR(10g), 2.4GHz band

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi_2.4GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2412 MHz; Crest Factor: 1.0**

Medium: M2450(1901); Medium parameters used: f = 2412 MHz; $\sigma = 1.969$ S/m; $\epsilon_r = 50.94$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2412 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0, 161.0

touch,add/24b42(re33);ant0,2412,back&d0,11b(1m)

Area:72x72,12 (7x7x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.60 W/kg


Area:72x72,12 (61x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.72 W/kg

Z:160,5 (1x1x33): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 1.53 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 27.80 V/m; Power Drift = -0.18 dB; Maximum value of SAR (measured) = 1.60 W/kg; Peak SAR (extrapolated) = 2.47 W/kg

SAR(1 g) = 1.04 W/kg; SAR(10 g) = 0.480 W/kg



Remarks: * . Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place:No.7 shielded room,
 * . liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45) %RH,
 * . liquid temperature: 21.8(start)/21.8(end)/21.9(in check) deg.C.; * . White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data (cont'd)

SAR plot of worst reported SAR (5GHz band)

Plot 4-1: (Body-touch) Antenna 0, Bottom & touch, ac20(SISO, MCS0), 5825MHz >Higher reported SAR(1g), U-NII-3 & 5GHz band

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5825 MHz; Crest Factor: 1.0

Medium: MSL5800(1901); Medium parameters used: f = 5825 MHz; $\sigma = 6.22$ S/m; $\epsilon_r = 47.49$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5825 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0

btm,touch/5b34.58.0.7;ant0,5825,btm&d0,ac20(m0)

Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.49 W/kg


Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.68 W/kg

Z;155,5 (1x1x32): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 4.27 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 24.02 V/m; Power Drift = 0.10 dB; Maximum value of SAR (measured) = 4.31 W/kg; Peak SAR (extrapolated) = 8.66 W/kg

SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.225 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 3-2: (Hand-held) Antenna 1, Front & touch, n40(MCS0), 5670MHz >Higher reported SAR(10g), U-NII-2C & 5GHz band

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5670 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: f = 5670 MHz; $\sigma = 6.026$ S/m; $\epsilon_r = 47.62$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5670 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0

top,touch,56,58/5b73.56.1.11;ant1,5670,top&d0,n40(m0)

Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.47 W/kg


Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 3.92 W/kg

Z;155,5 (1x1x32): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 5.11 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 32.68 V/m; Power Drift = 0.19 dB; Maximum value of SAR (measured) = 5.07 W/kg; Peak SAR (extrapolated) = 10.9 W/kg

SAR(1 g) = 1.75 W/kg; SAR(10 g) = 0.355 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data (cont'd)

SAR plots of other SAR conditions

Plot 1-3: (2.4GHz band, Body-touch) Antenna 0, Bottom & touch, 11b(1Mbps), 2437MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi 2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 2437 MHz; Crest Factor: 1.0

Medium: M2450(1901); Medium parameters used: $f = 2437$ MHz; $\sigma = 2.003$ S/m; $\epsilon_r = 50.85$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2437 MHz; Calibrated: 2018/05/15
-Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

touch/24b2;ant0,2437,btm&d0,11b(1m)


Area:48x228,12 (5x20x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.672 W/kg

Area:48x228,12 (41x191x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 0.711 W/kg

Zoom:30x30x30,5 (7x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 19.90 V/m; Power Drift = -0.00 dB; Maximum value of SAR (measured) = 0.844 W/kg; Peak SAR (extrapolated) = 1.29 W/kg

SAR(1 g) = 0.442 W/kg; SAR(10 g) = 0.170 W/kg



Remarks: * Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
* liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45) %RH,
* liquid temperature: 21.7(start)/21.7(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g) /small=SAR(1g)

Plot 1-4: (2.4GHz band, Body-touch) Antenna 0, Bottom & touch, 11b(1Mbps), 2462MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi 2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 2462 MHz; Crest Factor: 1.0

Medium: M2450(1901); Medium parameters used: $f = 2462$ MHz; $\sigma = 2.038$ S/m; $\epsilon_r = 50.74$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2462 MHz; Calibrated: 2018/05/15
-Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

touch/24b4;ant0,2462,btm&d0,b(1m)


Area:48x72,12 (5x7x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.673 W/kg

Area:48x72,12 (41x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 0.676 W/kg

Zoom:30x30x30,5 (7x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 18.95 V/m; Power Drift = -0.06 dB; Maximum value of SAR (measured) = 0.753 W/kg; Peak SAR (extrapolated) = 1.19 W/kg

SAR(1 g) = 0.408 W/kg; SAR(10 g) = 0.155 W/kg



Remarks: * Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
* liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45) %RH,
* liquid temperature: 21.8(start)/21.9(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g) /small=SAR(1g)

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 1-5: (2.4GHz band, Hand-held) Antenna 0, Front & touch, 11b(1Mbps), 2412MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi_2.4GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 2412 MHz; Crest Factor: 1.0

Medium: M2450(1901); Medium parameters used: f = 2412 MHz; $\sigma = 1.969$ S/m; $\epsilon_r = 50.94$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2412 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0, 161.0

frt,rear/24b21;ant0,2412,front&d0,b(1m)

Area:72x72,12 (7x7x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.901 W/kg


Area:72x72,12 (61x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.07 W/kg

Z:160,5 (1x1x33): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 1.09 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 23.11 V/m; Power Drift = -0.10 dB; Maximum value of SAR (measured) = 1.09 W/kg; Peak SAR (extrapolated) = 1.70 W/kg

SAR(1 g) = 0.702 W/kg; SAR(10 g) = 0.307 W/kg



Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45) %RH,
 * liquid temperature: 21.8(start)/21.9(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 1-6: (2.4GHz band, Hand-held) Antenna 0, Front & touch, 11b(1Mbps), 2437MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi_2.4GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 2437 MHz; Crest Factor: 1.0

Medium: M2450(1901); Medium parameters used: f = 2437 MHz; $\sigma = 2.003$ S/m; $\epsilon_r = 50.85$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2437 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

frt,rear/24b20;ant0,2437,front&d0,b(1m)


Area:132x228,12 (12x20x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.876 W/kg

Area:132x228,12 (111x191x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.01 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 22.69 V/m; Power Drift = -0.12 dB; Maximum value of SAR (measured) = 1.04 W/kg; Peak SAR (extrapolated) = 1.62 W/kg

SAR(1 g) = 0.662 W/kg; SAR(10 g) = 0.285 W/kg



Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45) %RH,
 * liquid temperature: 21.8(start)/21.8(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 1-7: (2.4GHz band, Hand-held) Antenna 0, Front & touch, 11b(1Mbps), 2462MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi_2.4GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2462 MHz; Crest Factor: 1.0**

Medium: M2450(1901); Medium parameters used: f = 2462 MHz; $\sigma = 2.038$ S/m; $\epsilon_r = 50.74$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2462 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

frt,rear/24b22;ant0,2462,front&d0,b(1m)/


Area:72x72,12 (7x7x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.829 W/kg

Area:72x72,12 (61x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 0.987 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 22.02 V/m; Power Drift = -0.10 dB; Maximum value of SAR (measured) = 1.02 W/kg; Peak SAR (extrapolated) = 1.60 W/kg

SAR(1 g) = 0.654 W/kg; SAR(10 g) = 0.280 W/kg



Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 21.9(start)/21.8(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 1-8: (2.4GHz band, Hand-held) Antenna 0, Back & touch, 11b(1Mbps), 2437MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi_2.4GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2437 MHz; Crest Factor: 1.0**

Medium: M2450(1901); Medium parameters used: f = 2437 MHz; $\sigma = 2.003$ S/m; $\epsilon_r = 50.85$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2437 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

frt,rear/24b32;ant0,2437,back&d0,11b(1m)/


Area:132x228,12 (12x20x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.61 W/kg

Area:132x228,12 (111x191x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.82 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 29.05 V/m; Power Drift = -0.01 dB; Maximum value of SAR (measured) = 1.62 W/kg; Peak SAR (extrapolated) = 2.41 W/kg

SAR(1 g) = 0.980 W/kg; SAR(10 g) = 0.446 W/kg



Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 21.9(start)/21.8(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 1-9: (2.4GHz band, Hand-held) Antenna 0, Back & touch, 11b(1Mbps), 2462MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi_2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 2462 MHz; Crest Factor: 1.0

Medium: M2450(1901); Medium parameters used: f = 2462 MHz; $\sigma = 2.038$ S/m; $\epsilon_r = 50.74$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2462 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

frt,rear/24b35;ant0,2462,back&d0,11b(1m)/


Area:72x72,12 (7x7x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.16 W/kg

Area:72x72,12 (61x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.52 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 26.77 V/m; Power Drift = -0.03 dB; Maximum value of SAR (measured) = 1.40 W/kg; Peak SAR (extrapolated) = 2.11 W/kg

SAR(1 g) = 0.867 W/kg; SAR(10 g) = 0.392 W/kg



Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 21.7(start)/21.8(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 1-10: (2.4GHz band, Hand-held) Antenna 1, Top & touch, 11b(1Mbps), 2412MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi_2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 2412 MHz; Crest Factor: 1.0

Medium: M2450(1901); Medium parameters used: f = 2412 MHz; $\sigma = 1.969$ S/m; $\epsilon_r = 50.94$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2412 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

touch/24b6;ant1,2412,top&d0,b(1m)/


Area:48x84,12 (5x8x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.17 W/kg

Area:48x84,12 (41x71x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.18 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 25.06 V/m; Power Drift = -0.06 dB; Maximum value of SAR (measured) = 1.21 W/kg; Peak SAR (extrapolated) = 1.92 W/kg

SAR(1 g) = 0.682 W/kg; SAR(10 g) = 0.242 W/kg



Remarks: * Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 21.9(start)/22.0(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)**Plot 1-11: (2.4GHz band, Hand-held) Antenna 1, Top & touch, 11b(1Mbps), 2437MHz****Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi_2.4GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 2437 MHz; Crest Factor: 1.0****Medium: M2450(1901); Medium parameters used: $f = 2437$ MHz; $\sigma = 2.003$ S/m; $\epsilon_r = 50.85$; $\rho = 1000$ kg/m³**


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2437 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$ **touch/24b1;ant1,2437,top&d0,b(1m)****Area:48x228,12 (5x20x1):** Measurement grid: $dx=12$ mm, $dy=12$ mm; Maximum value of SAR (measured) = 1.18 W/kg**Area:48x228,12 (41x191x1):** Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm; Maximum value of SAR (interpolated) = 1.25 W/kg**Zoom:30x30x30,5 (7x7x7)/Cube 0:** Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm;

Reference Value = 27.27 V/m; Power Drift = -0.12 dB; Maximum value of SAR (measured) = 1.44 W/kg; Peak SAR (extrapolated) = 2.26 W/kg

SAR(1 g) = 0.793 W/kg; SAR(10 g) = 0.275 W/kg

Remarks: * Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23-24) deg.C. / (35-45) %RH,
 * liquid temperature: 21.7(start)/21.7(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 1-12: (2.4GHz band, Hand-held) Antenna 1, Top & touch, 11b(1Mbps), 2462MHz**Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi_2.4GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 2462 MHz; Crest Factor: 1.0****Medium: M2450(1901); Medium parameters used: $f = 2462$ MHz; $\sigma = 2.038$ S/m; $\epsilon_r = 50.74$; $\rho = 1000$ kg/m³**


Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2462 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0, 161.0$ **touch/24b7;ant1,2462,top&d0,b(1m)****Area:48x84,12 (5x8x1):** Measurement grid: $dx=12$ mm, $dy=12$ mm; Maximum value of SAR (measured) = 1.46 W/kg**Area:48x84,12 (41x71x1):** Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm; Maximum value of SAR (interpolated) = 1.48 W/kg**Z;160,5 (1x1x33):** Measurement grid: $dx=20$ mm, $dy=20$ mm, $dz=5$ mm; Maximum value of SAR (measured) = 1.55 W/kg**Zoom:30x30x30,5 (7x7x7)/Cube 0:** Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm;

Reference Value = 28.11 V/m; Power Drift = -0.06 dB; Maximum value of SAR (measured) = 1.57 W/kg; Peak SAR (extrapolated) = 2.49 W/kg

SAR(1 g) = 0.873 W/kg; SAR(10 g) = 0.301 W/kg

Remarks: * Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23-24) deg.C. / (35-45) %RH,
 * liquid temperature: 22.0(start)/22.0(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

Report Cover Page - 13-EM-F0429 Issue # 14.0

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 1-13:(2.4GHz band, Hand-held) Antenna 1, Front & touch, 11b(1Mbps), 2412MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi_2.4GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2412 MHz; Crest Factor: 1.0**

Medium: M2450(1901); Medium parameters used: f = 2412 MHz; $\sigma = 1.969$ S/m; $\epsilon_r = 50.94$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2412 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

frt,rear/24b28;ant1,2412,front&d0,b(1m)


Area:72x72,12 (7x7x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.982 W/kg

Area:72x72,12 (61x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.06 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 23.51 V/m; Power Drift = -0.06 dB; Maximum value of SAR (measured) = 1.06 W/kg; Peak SAR (extrapolated) = 1.58 W/kg

SAR(1 g) = 0.582 W/kg; SAR(10 g) = 0.229 W/kg



Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
* liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45) %RH,
* liquid temperature: 21.8(start)/21.8(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 1-14:(2.4GHz band, Hand-held) Antenna 1, Front & touch, 11b(1Mbps), 2437MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11b(1Mbps, DBPSK/DSSS) (UID: 0; Wi-fi_2.4GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2437 MHz; Crest Factor: 1.0**

Medium: M2450(1901); Medium parameters used: f = 2437 MHz; $\sigma = 2.003$ S/m; $\epsilon_r = 50.85$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2437 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

frt,rear/24b26;ant1,2437,front&d0,b(1m)


Area:132x228,12 (12x20x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.10 W/kg

Area:132x228,12 (111x191x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.22 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 24.60 V/m; Power Drift = -0.17 dB; Maximum value of SAR (measured) = 1.16 W/kg; Peak SAR (extrapolated) = 1.75 W/kg

SAR(1 g) = 0.632 W/kg; SAR(10 g) = 0.246 W/kg



Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
* liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45) %RH,
* liquid temperature: 21.8(start)/21.8(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)**Plot 1-15: (2.4GHz band, Hand-held) Antenna 1, Front & touch, 11b(1Mbps), 2462MHz****Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: 11b(1Mbps, DBPSK/DSSS)** (UID: 0; Wi-fi_2.4GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2462 MHz; Crest Factor: 1.0****Medium: M2450(1901); Medium parameters used: $f = 2462$ MHz; $\sigma = 2.038$ S/m; $\epsilon_r = 50.74$; $\rho = 1000$ kg/m³**

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)


DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2462 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

frt,rear/24b27;ant1,2462,front&d0,b(1m)**Area: 72x72,12 (7x7x1):** Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.12 W/kg**Area: 72x72,12 (61x61x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.20 W/kg**Zoom: 30x30x30,5 (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 24.81 V/m; Power Drift = 0.15 dB; Maximum value of SAR (measured) = 1.24 W/kg; Peak SAR (extrapolated) = 1.90 W/kg

SAR(1 g) = 0.679 W/kg; SAR(10 g) = 0.261 W/kg

Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 21.8(start)/21.8(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 1-16: (2.4GHz band, Hand-held) Antenna 1, Back & touch, 11b(1Mbps), 2437MHz**Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: 11b(1Mbps, DBPSK/DSSS)** (UID: 0; Wi-fi_2.4GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2437 MHz; Crest Factor: 1.0****Medium: M2450(1901); Medium parameters used: $f = 2437$ MHz; $\sigma = 2.003$ S/m; $\epsilon_r = 50.85$; $\rho = 1000$ kg/m³**

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)


DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2437 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

frt,rear/24b34;ant1,2437,bck&d0,11b(1m)**Area: 132x228,12 (12x20x1):** Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.150 W/kg**Area: 132x228,12 (111x191x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 0.160 W/kg**Zoom: 30x30x30,5 (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 9.265 V/m; Power Drift = 0.07 dB; Maximum value of SAR (measured) = 0.167 W/kg; Peak SAR (extrapolated) = 0.228 W/kg

SAR(1 g) = 0.116 W/kg; SAR(10 g) = 0.062 W/kg

Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 21.8(start)/21.7(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

Report Cover Page - 13-EM-F0429 Issue # 14.0

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 1-17: (2.4GHz band, Hand-held) OFDM, Antenna 0, Bottom & touch, 11b(1Mbps), 2412MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11g(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2412 MHz; Crest Factor: 1.0**

Medium: M2450(1901); Medium parameters used: f = 2412 MHz; $\sigma = 1.969$ S/m; $\epsilon_r = 50.94$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2412 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

touch/24b5;ant0,2412,btm&d0,g(6m)/


Area:48x72,12 (5x7x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.652 W/kg

Area:48x72,12 (41x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 0.659 W/kg

Zoom:30x30x30,5 (7x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 19.07 V/m; Power Drift = -0.06 dB; Maximum value of SAR (measured) = 0.758 W/kg; Peak SAR (extrapolated) = 1.18 W/kg

SAR(1 g) = 0.405 W/kg; SAR(10 g) = 0.157 W/kg



Remarks: * Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 21.9(start)/21.9(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 1-18: (2.4GHz band, Hand-held) OFDM, Antenna 0, Bottom & touch, 11b(1Mbps), 2437MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11g(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2437 MHz; Crest Factor: 1.0**

Medium: M2450(1901); Medium parameters used: f = 2437 MHz; $\sigma = 2.003$ S/m; $\epsilon_r = 50.85$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2437 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

touch,add/24b40;ant0,2437,btm&d0,g(6m)/


Area:48x72,12 (5x7x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.603 W/kg

Area:48x72,12 (41x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 0.637 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 18.57 V/m; Power Drift = -0.20 dB; Maximum value of SAR (measured) = 0.657 W/kg; Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.349 W/kg; SAR(10 g) = 0.134 W/kg



Remarks: * Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 22.0(start)/22.0(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)**Plot 1-19: (2.4GHz band, Hand-held) OFDM, Antenna 0, Bottom & touch, 11b(1Mbps), 2462MHz****Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: 11g(6Mbps, BPSK/OFDM)** (UID: 0; Wi-fi_2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2462 MHz; Crest Factor: 1.0****Medium: M2450(1901); Medium parameters used: $f = 2462$ MHz; $\sigma = 2.038$ S/m; $\epsilon_r = 50.74$; $\rho = 1000$ kg/m³**

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)


DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2462 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

touch.add/24b41;ant0,2462,btm&d0,g(6m)**Area:48x72,12 (5x7x1):** Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.600 W/kg**Area:48x72,12 (41x61x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 0.631 W/kg**Zoom:30x30x30,5 (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 18.04 V/m; Power Drift = -0.09 dB; Maximum value of SAR (measured) = 0.644 W/kg; Peak SAR (extrapolated) = 0.992 W/kg

SAR(1 g) = 0.339 W/kg; SAR(10 g) = 0.130 W/kg

Remarks: * Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 22.0(start)/22.0(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 1-20: (2.4GHz band, Hand-held) OFDM, Antenna 0, Back & touch, 11b(1Mbps), 2412MHz**Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: 11g(6Mbps, BPSK/OFDM)** (UID: 0; Wi-fi_2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2412 MHz; Crest Factor: 1.0****Medium: M2450(1901); Medium parameters used: $f = 2412$ MHz; $\sigma = 1.969$ S/m; $\epsilon_r = 50.94$; $\rho = 1000$ kg/m³**

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)


DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2412 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

touch.add/24b43;ant0,2412,back&d0,11g(6m)**Area:72x72,12 (7x7x1):** Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.37 W/kg**Area:72x72,12 (61x61x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.47 W/kg**Zoom:30x30x30,5 (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 25.50 V/m; Power Drift = -0.10 dB; Maximum value of SAR (measured) = 1.35 W/kg; Peak SAR (extrapolated) = 2.04 W/kg

SAR(1 g) = 0.863 W/kg; SAR(10 g) = 0.401 W/kg

Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 21.9(start)/21.9(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

Report Cover Page - 13-EM-F0429 Issue # 14.0

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 1-21: (2.4GHz band, Hand-held) OFDM, Antenna 0, Back & touch, 11b(1Mbps), 2437MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11g(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2437 MHz; Crest Factor: 1.0**

Medium: M2450(1901); Medium parameters used: f = 2437 MHz; $\sigma = 2.003$ S/m; $\epsilon_r = 50.85$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2437 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

touch.add/24b44;antf0,2437,back&d0,11g(6m)


Area:72x72,12 (7x7x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.19 W/kg

Area:72x72,12 (61x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.27 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 23.90 V/m; Power Drift = 0.01 dB; Maximum value of SAR (measured) = 1.19 W/kg; Peak SAR (extrapolated) = 1.85 W/kg

SAR(1 g) = 0.774 W/kg; SAR(10 g) = 0.359 W/kg



Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45) %RH,
 * liquid temperature: 21.9(start)/21.9(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 1-22: (2.4GHz band, Hand-held) OFDM, Antenna 0, Back & touch, 11b(1Mbps), 2462MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11g(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2462 MHz; Crest Factor: 1.0**

Medium: M2450(1901); Medium parameters used: f = 2462 MHz; $\sigma = 2.038$ S/m; $\epsilon_r = 50.74$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2462 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

touch.add/24b45;antf0,2462,back&d0,11g(6m)


Area:72x72,12 (7x7x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.04 W/kg

Area:72x72,12 (61x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.11 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 22.39 V/m; Power Drift = -0.04 dB; Maximum value of SAR (measured) = 1.03 W/kg; Peak SAR (extrapolated) = 1.60 W/kg

SAR(1 g) = 0.672 W/kg; SAR(10 g) = 0.310 W/kg



Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45) %RH,
 * liquid temperature: 21.9(start)/21.9(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 1-23: (2.4GHz band, Hand-held) OFDM, Antenna 1, Top & touch, 11b(1Mbps), 2412MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11g(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2412 MHz; Crest Factor: 1.0**

Medium: M2450(1901); Medium parameters used: $f = 2412$ MHz; $\sigma = 1.969$ S/m; $\epsilon_r = 50.94$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2412 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

touch/24b11;ant1,2412,top&d0.g(6m)


Area:48x84,12 (5x8x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 0.912 W/kg

Area:48x84,12 (41x71x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 0.921 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 22.67 V/m; Power Drift = -0.01 dB; Maximum value of SAR (measured) = 0.988 W/kg; Peak SAR (extrapolated) = 1.55 W/kg

SAR(1 g) = 0.550 W/kg; SAR(10 g) = 0.196 W/kg



Remarks: * Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 21.9(start)/21.9(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 1-24: (2.4GHz band, Hand-held) OFDM, Antenna 1, Top & touch, 11b(1Mbps), 2437MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11g(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2437 MHz; Crest Factor: 1.0**

Medium: M2450(1901); Medium parameters used: $f = 2437$ MHz; $\sigma = 2.003$ S/m; $\epsilon_r = 50.85$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2437 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

touch/24b10;ant1,2437,top&d0.g(6m)


Area:48x84,12 (5x8x1): Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.05 W/kg

Area:48x84,12 (41x71x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.07 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 24.20 V/m; Power Drift = 0.00 dB; Maximum value of SAR (measured) = 1.15 W/kg; Peak SAR (extrapolated) = 1.82 W/kg

SAR(1 g) = 0.642 W/kg; SAR(10 g) = 0.225 W/kg



Remarks: * Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 21.9(start)/21.9(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)**Plot 1-25:(2.4GHz band, Hand-held) OFDM, Antenna 1, Top & touch, 11b(1Mbps), 2462MHz****Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: 11g(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_2.4GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 2462 MHz; Crest Factor: 1.0****Medium: M2450(1901); Medium parameters used: $f = 2462$ MHz; $\sigma = 2.038$ S/m; $\epsilon_r = 50.74$; $\rho = 1000$ kg/m³**

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)


DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2462 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

touch/24b9;ant1,2462,top&d0,g(6m)**Area:48x84,12 (5x8x1):** Measurement grid: dx=12mm, dy=12mm; Maximum value of SAR (measured) = 1.16 W/kg**Area:48x84,12 (41x71x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm; Maximum value of SAR (interpolated) = 1.17 W/kg**Zoom:30x30x30,5 (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm;

Reference Value = 24.92 V/m; Power Drift = 0.01 dB; Maximum value of SAR (measured) = 1.24 W/kg; Peak SAR (extrapolated) = 1.99 W/kg

SAR(1 g) = 0.689 W/kg; SAR(10 g) = 0.238 W/kg


Remarks: * Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23~24) deg.C. / (35~45)%RH,
 * liquid temperature: 22.0(start)/21.9(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)**Plot 2-1: (Body-touch) Antenna 0, Bottom & touch, ac40(SISO, MCS0), 5310MHz->Higher reported SAR(1g), U-NII-1&2A band
Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: ac40(MCS0, BPSK/OFDM)** (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5310 MHz; Crest Factor: 1.0****Medium: MSL5800(1902); Medium parameters used: $f = 5310$ MHz; $\sigma = 5.533$ S/m; $\epsilon_r = 48.20$; $\rho = 1000$ kg/m³**

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5310 MHz; Calibrated: 2018/05/15
-Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0**btm,touch,53/5b58.53.0.14;ant0,5310,btm&d0,ac40(m0)****Area:50x80,10 (6x9x1):** Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.15 W/kg**Area:50x80,10 (51x81x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.59 W/kg**Z;155,5 (1x1x32):** Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 2.69 W/kg**Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 25.08 V/m; Power Drift = -0.14 dB; Maximum value of SAR (measured) = 2.70 W/kg; Peak SAR (extrapolated) = 5.30 W/kg

SAR(1 g) = 0.882 W/kg; SAR(10 g) = 0.226 W/kg


Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
* liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
* liquid temperature: 23.0(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

**Plot 2-2: (Hand-held) Antenna 0, Front & touch, n40(MCS0), 5310MHz->Higher reported SAR(10g), U-NII-1&2A band
Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: n40(MCS0, BPSK/OFDM)** (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5310 MHz; Crest Factor: 1.0****Medium: MSL5800(1901); Medium parameters used: $f = 5310$ MHz; $\sigma = 5.501$ S/m; $\epsilon_r = 48.28$; $\rho = 1000$ kg/m³**

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5310 MHz; Calibrated: 2018/05/15
-Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0**frt,rear/5b9.53.0.1;ant0,5310,front&d0,n40(m0)****Area:120x220,10 (13x23x1):** Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.973 W/kg**Area:120x220,10 (121x221x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 2.412 W/kg**Z;155,5 (1x1x32):** Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 2.00 W/kg**Zoom:28x28x24,4,4,1.4(ratio) (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 23.89 V/m; Power Drift = -0.07 dB; Maximum value of SAR (measured) = 2.03 W/kg; Peak SAR (extrapolated) = 4.04 W/kg

SAR(1 g) = 0.809 W/kg; SAR(10 g) = 0.222 W/kg

Remarks: * Date tested: 2019/01/30; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
* liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
* liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

Report Cover Page - 13-EM-F0429 Issue # 14.0

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)**Plot 2-3: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, n40(MCS0), 5270MHz****Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: n40(MCS0, BPSK/OFDM)** (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5270 MHz; Crest Factor: 1.0****Medium: MSL5800(1902); Medium parameters used: $f = 5270$ MHz; $\sigma = 5.484$ S/m; $\epsilon_r = 48.25$; $\rho = 1000$ kg/m³**

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)


DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5270 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58,56,53/5b46.53.0.7;ant0,5270,btm&d0,n40(m0)**Area:50x80,10 (6x9x1):** Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.12 W/kg**Area:50x80,10 (51x81x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.40 W/kg**Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.38 V/m; Power Drift = -0.17 dB; Maximum value of SAR (measured) = 2.61 W/kg; Peak SAR (extrapolated) = 4.67 W/kg

SAR(1 g) = 0.790 W/kg; SAR(10 g) = 0.208 W/kg

Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g) / small-SAR(1g)

Plot 2-4: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, n40(MCS0), 5310MHz**Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: n40(MCS0, BPSK/OFDM)** (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5310 MHz; Crest Factor: 1.0****Medium: MSL5800(1901); Medium parameters used: $f = 5310$ MHz; $\sigma = 5.501$ S/m; $\epsilon_r = 48.28$; $\rho = 1000$ kg/m³**

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)


DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5310 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,btm/5b12.53.0.3;ant0,5310,btm&d0,n40(m0)**Area:50x220,10 (6x23x1):** Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.05 W/kg**Area:50x220,10 (51x221x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 2.20 W/kg**Zoom:28x28x24,4,4,1.4(ratio) (9x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 23.15 V/m; Power Drift = 0.19 dB; Maximum value of SAR (measured) = 2.87 W/kg; Peak SAR (extrapolated) = 5.04 W/kg

SAR(1 g) = 0.839 W/kg; SAR(10 g) = 0.214 W/kg

Remarks: * Date tested: 2019/01/30; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g) / small-SAR(1g)

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

Report Cover Page - 13-EM-F0429 Issue # 14.0

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 2-5: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, n40(MCS0), 5230MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5230 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5230 MHz; $\sigma = 5.434$ S/m; $\epsilon_r = 48.34$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5230 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58,56,53/5b47.53.0.8;ant0,5230,btm&d0,n40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.916 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.20 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.17 V/m; Power Drift = 0.00 dB; Maximum value of SAR (measured) = 1.99 W/kg; Peak SAR (extrapolated) = 3.78 W/kg

SAR(1 g) = 0.655 W/kg; SAR(10 g) = 0.178 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 2-6: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, ac40(MCS0), 5270MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5270 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5270 MHz; $\sigma = 5.484$ S/m; $\epsilon_r = 48.25$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5270 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,53/5b59.53.0.15;ant0,5270,btm&d0,ac40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.15 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.33 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.01 V/m; Power Drift = -0.19 dB; Maximum value of SAR (measured) = 2.47 W/kg; Peak SAR (extrapolated) = 4.40 W/kg

SAR(1 g) = 0.730 W/kg; SAR(10 g) = 0.195 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 2-7: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, ac40(MCS0), 5230MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5230 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: $f = 5230$ MHz; $\sigma = 5.434$ S/m; $\epsilon_r = 48.34$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5230 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,53/5b60.53.0.16;ant0,5230,btm&d0,ac40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.12 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.21 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.41 V/m; Power Drift = -0.16 dB; Maximum value of SAR (measured) = 1.79 W/kg; Peak SAR (extrapolated) = 3.51 W/kg

SAR(1 g) = 0.626 W/kg; SAR(10 g) = 0.165 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Plot 2-8: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, 11a(6Mbps), 5300MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5300 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: $f = 5300$ MHz; $\sigma = 5.531$ S/m; $\epsilon_r = 48.23$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5300 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58,56,53/5b49.53.0.10;ant0,5300,btm&d0,a(6m)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.10 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.42 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 23.31 V/m; Power Drift = 0.01 dB; Maximum value of SAR (measured) = 2.62 W/kg; Peak SAR (extrapolated) = 4.74 W/kg

SAR(1 g) = 0.782 W/kg; SAR(10 g) = 0.200 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)**Plot 2-9: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, 11a(6Mbps), 5320MHz****Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: 11a(6Mbps, BPSK/OFDM)** (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5320 MHz; Crest Factor: 1.0****Medium: MSL5800(1902); Medium parameters used: $f = 5320$ MHz; $\sigma = 5.54$ S/m; $\epsilon_r = 48.21$; $\rho = 1000$ kg/m³**

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)


DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5320 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58,56,53/5b48.53.0.9;ant0,5320,btm&d0,a(6m)**Area:50x80,10 (6x9x1):** Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.17 W/kg**Area:50x80,10 (51x81x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.54 W/kg**Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 23.88 V/m; Power Drift = -0.06 dB; Maximum value of SAR (measured) = 2.87 W/kg; Peak SAR (extrapolated) = 5.15 W/kg

SAR(1 g) = 0.838 W/kg; SAR(10 g) = 0.211 W/kg

Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Plot 2-10: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, 11a(6Mbps), 5180MHz**Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163****Mode: 11a(6Mbps, BPSK/OFDM)** (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5180 MHz; Crest Factor: 1.0****Medium: MSL5800(1901); Medium parameters used: $f = 5180$ MHz; $\sigma = 5.334$ S/m; $\epsilon_r = 48.51$; $\rho = 1000$ kg/m³**

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)


DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5180 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,btm/5b25.53.0.4;ant0,5180,btm&d0,a(6m)**Area:50x80,10 (6x9x1):** Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.762 W/kg**Area:50x80,10 (51x81x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 0.861 W/kg**Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.80 V/m; Power Drift = -0.04 dB; Maximum value of SAR (measured) = 1.50 W/kg; Peak SAR (extrapolated) = 2.64 W/kg

SAR(1 g) = 0.538 W/kg; SAR(10 g) = 0.139 W/kg

Remarks: * Date tested: 2019/01/30; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

Report Cover Page - 13-EM-F0429 Issue # 14.0

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 2-11: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, 11a(6Mbps), 5240MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5240 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5240$ MHz; $\sigma = 5.446$ S/m; $\epsilon_r = 48.32$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5240 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58,56,53/5b51.53.0.12;ant0,5240,btm&d0,a(6m)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.878 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.14 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.08 V/m; Power Drift = -0.11 dB; Maximum value of SAR (measured) = 1.94 W/kg; Peak SAR (extrapolated) = 3.77 W/kg

SAR(1 g) = 0.648 W/kg; SAR(10 g) = 0.174 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Plot 2-12: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, n20(MCS0), 5260MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5260 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5260$ MHz; $\sigma = 5.48$ S/m; $\epsilon_r = 48.27$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5260 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,53/5b63.53.0.19;ant0,5260,btm&d0,n20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.961 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.11 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 17.39 V/m; Power Drift = -0.12 dB; Maximum value of SAR (measured) = 2.25 W/kg; Peak SAR (extrapolated) = 3.93 W/kg

SAR(1 g) = 0.662 W/kg; SAR(10 g) = 0.177 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 2-13: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, n20(MCS0), 5300MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5300 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5300 MHz; $\sigma = 5.531$ S/m; $\epsilon_r = 48.23$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5300 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,53/5b62.53.0.18;ant0,5300,btm&d0,n20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.997 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.26 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.71 V/m; Power Drift = -0.18 dB; Maximum value of SAR (measured) = 2.60 W/kg; Peak SAR (extrapolated) = 4.55 W/kg

SAR(1 g) = 0.755 W/kg; SAR(10 g) = 0.195 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Plot 2-14: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, n20(MCS0), 5320MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5320 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5320 MHz; $\sigma = 5.54$ S/m; $\epsilon_r = 48.21$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5320 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,53/5b61.53.0.17;ant0,5320,btm&d0,n20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.957 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.25 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 20.52 V/m; Power Drift = -0.11 dB; Maximum value of SAR (measured) = 2.30 W/kg; Peak SAR (extrapolated) = 4.72 W/kg

SAR(1 g) = 0.780 W/kg; SAR(10 g) = 0.198 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 2-15: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, n20(MCS0), 5220MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5220 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5220 MHz; $\sigma = 5.417$ S/m; $\epsilon_r = 48.37$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5220 MHz; Calibrated: 2018/05/15
-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,53/5b65.53.0.21;ant0,5220,btm&d0,n20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.02 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.10 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 17.90 V/m; Power Drift = -0.01 dB; Maximum value of SAR (measured) = 1.61 W/kg; Peak SAR (extrapolated) = 3.10 W/kg

SAR(1 g) = 0.565 W/kg; SAR(10 g) = 0.150 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
* liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
* liquid temperature: 22.8(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g) /small=SAR(1g)

Plot 2-16: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, n20(MCS0), 5240MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5240 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5240 MHz; $\sigma = 5.446$ S/m; $\epsilon_r = 48.32$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5240 MHz; Calibrated: 2018/05/15
-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,53/5b64.53.0.20;ant0,5240,btm&d0,n20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.891 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 0.993 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 16.23 V/m; Power Drift = -0.09 dB; Maximum value of SAR (measured) = 2.01 W/kg; Peak SAR (extrapolated) = 3.49 W/kg

SAR(1 g) = 0.610 W/kg; SAR(10 g) = 0.164 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
* liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
* liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g) /small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 2-17: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, ac20(SISO,MCS0), 5260MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5260 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: f = 5260 MHz; $\sigma = 5.48$ S/m; $\epsilon_r = 48.27$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5260 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,53/5b68.53.0.24;ant0,5260,btm&d0,ac20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.906 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.07 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 17.34 V/m; Power Drift = -0.20 dB; Maximum value of SAR (measured) = 2.24 W/kg; Peak SAR (extrapolated) = 3.89 W/kg

SAR(1 g) = 0.659 W/kg; SAR(10 g) = 0.177 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g) / small-SAR(1g)

Plot 2-18: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, ac20(SISO,MCS0), 5300MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5300 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: f = 5300 MHz; $\sigma = 5.531$ S/m; $\epsilon_r = 48.23$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5300 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,53/5b67.53.0.23;ant0,5300,btm&d0,ac20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.912 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.23 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 20.76 V/m; Power Drift = -0.14 dB; Maximum value of SAR (measured) = 2.17 W/kg; Peak SAR (extrapolated) = 4.39 W/kg

SAR(1 g) = 0.744 W/kg; SAR(10 g) = 0.193 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g) / small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 2-19: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, ac20(SISO,MCS0), 5320MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5320 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: $f = 5320$ MHz; $\sigma = 5.54$ S/m; $\epsilon_r = 48.21$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5320 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,53/5b66.53.0.22;ant0,5320,btm&d0,ac20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.00 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.31 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 20.77 V/m; Power Drift = -0.14 dB; Maximum value of SAR (measured) = 2.56 W/kg; Peak SAR (extrapolated) = 4.91 W/kg

SAR(1 g) = 0.811 W/kg; SAR(10 g) = 0.206 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Plot 2-20: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, ac20(SISO,MCS0), 5220MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5220 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: $f = 5220$ MHz; $\sigma = 5.417$ S/m; $\epsilon_r = 48.37$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5220 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,53/5b70.53.0.26;ant0,5220,btm&d0,ac20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.898 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 0.976 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 17.93 V/m; Power Drift = -0.13 dB; Maximum value of SAR (measured) = 1.59 W/kg; Peak SAR (extrapolated) = 3.10 W/kg

SAR(1 g) = 0.558 W/kg; SAR(10 g) = 0.148 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 2-21: (U-NII-1&2A band, Body-touch) Antenna 0, Bottom & touch, ac20(SISO,MCS0), 5240MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5240 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5240$ MHz; $\sigma = 5.446$ S/m; $\epsilon_r = 48.32$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5240 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,53/5b69.53.0.25;ant0,5240,btm&d0,ac20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.839 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 0.932 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 17.46 V/m; Power Drift = -0.09 dB; Maximum value of SAR (measured) = 1.65 W/kg; Peak SAR (extrapolated) = 3.39 W/kg

SAR(1 g) = 0.595 W/kg; SAR(10 g) = 0.153 W/kg



Remarks: * . Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place:No.7 shielded room,
 * . liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * . liquid temperature: 23.0(start)/23.0(end)/23.0(in check) deg.C.; * . White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Plot 2-22: (U-NII-1&2A band, Hand-held) Antenna 0, Front & touch, n40(MCS0), 5270MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5270 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5270$ MHz; $\sigma = 5.484$ S/m; $\epsilon_r = 48.25$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5270 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt,add2,ant0/5b102.53.0.32;ant0,5270,front&d0,n40(m0)


Area:60x70,10 (7x8x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.89 W/kg

Area:60x70,10 (61x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 2.09 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 19.97 V/m; Power Drift = -0.10 dB; Maximum value of SAR (measured) = 1.97 W/kg; Peak SAR (extrapolated) = 3.48 W/kg

SAR(1 g) = 0.712 W/kg; SAR(10 g) = 0.203 W/kg



Remarks: * . Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place:No.7 shielded room,
 * . liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * . liquid temperature: 22.8(start)/22.9(end)/23.0(in check) deg.C.; * . White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 2-23: (U-NII-1&2A band, Hand-held) Antenna 0, Front & touch, 11a(6Mbps), 5180MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5180 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5180$ MHz; $\sigma = 5.364$ S/m; $\epsilon_r = 48.42$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5180 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt,add2,ant0/5b100.53.0.30;ant0,5180,front&d0,a(6m)


Area:60x70,10 (7x8x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.26 W/kg

Area:60x70,10 (61x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.36 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 16.00 V/m; Power Drift = -0.18 dB; Maximum value of SAR (measured) = 1.24 W/kg; Peak SAR (extrapolated) = 2.21 W/kg

SAR(1 g) = 0.456 W/kg; SAR(10 g) = 0.129 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 2-24: (U-NII-1&2A band, Hand-held) Antenna 0, Front & touch, 11a(6Mbps), 5260MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5260 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5260$ MHz; $\sigma = 5.48$ S/m; $\epsilon_r = 48.27$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5260 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt,add2,ant0/5b99.53.0.29;ant0,5260,front&d0,a(6m)


Area:60x70,10 (7x8x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.75 W/kg

Area:60x70,10 (61x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.94 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 19.04 V/m; Power Drift = -0.10 dB; Maximum value of SAR (measured) = 1.80 W/kg; Peak SAR (extrapolated) = 3.17 W/kg

SAR(1 g) = 0.653 W/kg; SAR(10 g) = 0.188 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 2-25: (U-NII-1&2A band, Hand-held) Antenna 0, Front & touch, 11a(6Mbps), 5320MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5320 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5320$ MHz; $\sigma = 5.54$ S/m; $\epsilon_r = 48.21$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5320 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt,add1,ant0/5b97.53.0.27;ant0,5320,front&d0,a(6m)/


Area:60x70,10 (7x8x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.06 W/kg

Area:60x70,10 (61x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 2.36 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 21.83 V/m; Power Drift = -0.17 dB; Maximum value of SAR (measured) = 2.10 W/kg; Peak SAR (extrapolated) = 3.76 W/kg

SAR(1 g) = 0.740 W/kg; SAR(10 g) = 0.207 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 2-26: (U-NII-1&2A band, Hand-held) Antenna 0, Back & touch, n40(MCS0), 5310MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5310 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5310$ MHz; $\sigma = 5.501$ S/m; $\epsilon_r = 48.28$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5310 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt,rear/5b1.53.0.1;ant0,5310,back&d0,n40(m0)/


Area:130x220,10 (14x23x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.644 W/kg

Area:130x220,10 (131x221x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 0.716 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 13.01 V/m; Power Drift = -0.08 dB; Maximum value of SAR (measured) = 0.904 W/kg; Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 0.336 W/kg; SAR(10 g) = 0.111 W/kg



Remarks: * Date tested: 2019/01/30; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.6(start)/22.6(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 2-27: (U-NII-1&2A band, Hand-held) Antenna 1, Top & touch, n40(MCS0), 5310MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5310 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5310$ MHz; $\sigma = 5.501$ S/m; $\epsilon_r = 48.28$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5310 MHz; Calibrated: 2018/05/15
-Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,btm/5b21.53.1.3;ant1,5310,top&d0,n40(m0)/


Area:50x220,10 (6x23x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.02 W/kg

Area:50x220,10 (51x221x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.46 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 21.57 V/m; Power Drift = 0.01 dB; Maximum value of SAR (measured) = 2.02 W/kg; Peak SAR (extrapolated) = 3.70 W/kg

SAR(1 g) = 0.697 W/kg; SAR(10 g) = 0.160 W/kg



Remarks: * Date tested: 2019/01/30; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
* liquid depth: : 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50)%RH,
* liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Plot 2-28: (U-NII-1&2A band, Hand-held) Antenna 1, Front & touch, n40(MCS0), 5310MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5310 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5310$ MHz; $\sigma = 5.501$ S/m; $\epsilon_r = 48.28$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5310 MHz; Calibrated: 2018/05/15
-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt1/5b27.53.1.4;ant1,5310,front&d0,n40(m0)/


Area:60x70,10 (7x8x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.688 W/kg

Area:60x70,10 (61x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 0.979 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (2 (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 15.70 V/m; Power Drift = 0.08 dB; Maximum value of SAR (measured) = 1.26 W/kg; Peak SAR (extrapolated) = 2.24 W/kg

SAR(1 g) = 0.462 W/kg; SAR(10 g) = 0.130 W/kg



Remarks: * Date tested: 2019/01/30; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
* liquid depth: : 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50)%RH,
* liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 2-29: (U-NII-1&2A band, Hand-held) Antenna 1, Back & touch, n40(MCS0), 5310MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5310 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: f = 5310 MHz; $\sigma = 5.501$ S/m; $\epsilon_r = 48.28$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5310 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt,rear/5b8.53.1.1;ant1,5310,back&d0,n40(m0)/


Area:60x70,10 (7x8x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.169 W/kg

Area:60x70,10 (61x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 0.171 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (9x11x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 6.156 V/m; Power Drift = -0.01 dB; Maximum value of SAR (measured) = 0.174 W/kg; Peak SAR (extrapolated) = 0.431 W/kg

SAR(1 g) = 0.075 W/kg; SAR(10 g) = 0.027 W/kg



Remarks: * Date tested: 2019/01/30; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g) /small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 3-1: (Body-touch) Antenna 0, Bottom & touch, ac20(SISO, MCS0), 5500MHz ->Higher reported SAR(1g), U-NII-2C band

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5500 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5500 MHz; $\sigma = 5.793$ S/m; $\epsilon_r = 47.93$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5500 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)); Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0

btm,touch,56/5b86.56.0.16;ant0,5500,btm&d0,ac20(m0)

Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.45 W/kg


Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.56 W/kg

Z;155,5 (1x1x32): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 2.59 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 20.59 V/m; Power Drift = 0.04 dB; Maximum value of SAR (measured) = 2.61 W/kg; Peak SAR (extrapolated) = 4.93 W/kg

SAR(1 g) = 0.726 W/kg; SAR(10 g) = 0.164 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 3-3: (U-NII-2C band, Body-touch) Antenna 0, Bottom & touch, n40(MCS0), 5510MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5510 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: f = 5510 MHz; $\sigma = 5.775$ S/m; $\epsilon_r = 47.97$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5510 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,btm/5b13.56.0.4;ant0,5510,btm&d0,n40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.52 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.64 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 22.05 V/m; Power Drift = -0.02 dB; Maximum value of SAR (measured) = 2.32 W/kg; Peak SAR (extrapolated) = 4.55 W/kg

SAR(1 g) = 0.690 W/kg; SAR(10 g) = 0.158 W/kg



Remarks: * Date tested: 2019/01/31; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.7(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 3-4: (U-NII-2C band, Body-touch) Antenna 0, Bottom & touch, n40(MCS0), 5550MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5550 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5550 MHz; $\sigma = 5.866$ S/m; $\epsilon_r = 47.82$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5550 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58,56,53/5b44.56.0.10;ant0,5550,btm&d0,n40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.775 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.00 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 20.79 V/m; Power Drift = -0.09 dB; Maximum value of SAR (measured) = 1.81 W/kg; Peak SAR (extrapolated) = 4.07 W/kg

SAR(1 g) = 0.590 W/kg; SAR(10 g) = 0.135 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Plot 3-5: (U-NII-2C band, Body-touch) Antenna 0, Bottom & touch, n40(MCS0), 5670MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5670 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5670 MHz; $\sigma = 6.026$ S/m; $\epsilon_r = 47.62$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5670 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58,56,53/5b45.56.0.11;ant0,5670,btm&d0,n40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.947 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.05 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 15.39 V/m; Power Drift = -0.09 dB; Maximum value of SAR (measured) = 1.53 W/kg; Peak SAR (extrapolated) = 3.76 W/kg

SAR(1 g) = 0.503 W/kg; SAR(10 g) = 0.127 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 3-6: (U-NII-2C band, Body-touch) Antenna 0, Bottom & touch, ac40(SISO,MCS0), 5510MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5510 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: f = 5510 MHz; $\sigma = 5.793$ S/m; $\epsilon_r = 47.90$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5510 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,56/5b82.56.0.12;ant0,5510,btm&d0,ac40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.57 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.65 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 20.21 V/m; Power Drift = 0.09 dB; Maximum value of SAR (measured) = 2.31 W/kg; Peak SAR (extrapolated) = 4.41 W/kg

SAR(1 g) = 0.663 W/kg; SAR(10 g) = 0.152 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Plot 3-7: (U-NII-2C band, Body-touch) Antenna 0, Bottom & touch, ac40(SISO,MCS0), 5550MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5550 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: f = 5550 MHz; $\sigma = 5.866$ S/m; $\epsilon_r = 47.82$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5550 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,56/5b83.56.0.13;ant0,5550,btm&d0,ac40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.31 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.39 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.60 V/m; Power Drift = 0.09 dB; Maximum value of SAR (measured) = 2.10 W/kg; Peak SAR (extrapolated) = 4.03 W/kg

SAR(1 g) = 0.592 W/kg; SAR(10 g) = 0.137 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 3-8: (U-NII-2C band, Body-touch) Antenna 0, Bottom & touch, 11a(6Mbps), 5500MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5500 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5500$ MHz; $\sigma = 5.793$ S/m; $\epsilon_r = 47.93$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5500 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58,56,53/5b43.56.0.9;ant0,5500,btm&d0,a(6m)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.11 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.38 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 22.31 V/m; Power Drift = -0.02 dB; Maximum value of SAR (measured) = 2.50 W/kg; Peak SAR (extrapolated) = 4.91 W/kg

SAR(1 g) = 0.731 W/kg; SAR(10 g) = 0.166 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 3-9: (U-NII-2C band, Body-touch) Antenna 0, Bottom & touch, 11a(6Mbps), 5580MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5580 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5580$ MHz; $\sigma = 5.874$ S/m; $\epsilon_r = 47.87$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5580 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,btm/5b24.56.0.6;ant0,5580,btm&d0,a(6m)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.875 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.01 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.47 V/m; Power Drift = 0.13 dB; Maximum value of SAR (measured) = 2.18 W/kg; Peak SAR (extrapolated) = 4.25 W/kg

SAR(1 g) = 0.623 W/kg; SAR(10 g) = 0.145 W/kg



Remarks: * Date tested: 2019/01/31; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 3-10: (U-NII-2C band, Body-touch) Antenna 0, Bottom & touch, 11a(6Mbps), 5700MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5700 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5700$ MHz; $\sigma = 6.043$ S/m; $\epsilon_r = 47.67$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5700 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,btm/5b23.56.0.5;ant0,5700,btm&d0,a(6m)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.869 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 0.970 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 15.94 V/m; Power Drift = -0.15 dB; Maximum value of SAR (measured) = 1.56 W/kg; Peak SAR (extrapolated) = 3.96 W/kg

SAR(1 g) = 0.542 W/kg; SAR(10 g) = 0.136 W/kg



Remarks: * Date tested: 2019/01/31; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 3-11: (U-NII-2C band, Body-touch) Antenna 0, Bottom & touch, n20(MCS0), 5500MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5500 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5500$ MHz; $\sigma = 5.793$ S/m; $\epsilon_r = 47.93$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5500 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,56/5b84.56.0.14;ant0,5500,btm&d0,n20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.58 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.69 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 20.50 V/m; Power Drift = 0.10 dB; Maximum value of SAR (measured) = 2.54 W/kg; Peak SAR (extrapolated) = 4.80 W/kg

SAR(1 g) = 0.710 W/kg; SAR(10 g) = 0.163 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 3-12: (U-NII-2C band, Body-touch) Antenna 0, Bottom & touch, n20(MCS0), 5700MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5700 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5700$ MHz; $\sigma = 6.072$ S/m; $\epsilon_r = 47.58$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5700 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,56/5b85.56.0.15;ant0,5700,btm&d0,n20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.22 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.31 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.31 V/m; Power Drift = -0.03 dB; Maximum value of SAR (measured) = 2.11 W/kg; Peak SAR (extrapolated) = 4.04 W/kg

SAR(1 g) = 0.547 W/kg; SAR(10 g) = 0.130 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Plot 3-13: (U-NII-2C band, Body-touch) Antenna 0, Bottom & touch, ac20(SISO,MCS0), 5580MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5580 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5580$ MHz; $\sigma = 5.898$ S/m; $\epsilon_r = 47.79$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5580 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,56/5b87.56.0.17;ant0,5580,btm&d0,ac20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.12 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.24 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 19.48 V/m; Power Drift = 0.03 dB; Maximum value of SAR (measured) = 2.00 W/kg; Peak SAR (extrapolated) = 3.95 W/kg

SAR(1 g) = 0.595 W/kg; SAR(10 g) = 0.138 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 3-14: (U-NII-2C band, Body-touch) Antenna 0, Bottom & touch, ac20(SISO,MCS0), 5700MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5700 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5700$ MHz; $\sigma = 6.072$ S/m; $\epsilon_r = 47.58$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5700 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,56/5b88.56.0.18;ant0,5700,btm&d0,ac20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.13 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.21 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.00 V/m; Power Drift = -0.04 dB; Maximum value of SAR (measured) = 2.11 W/kg; Peak SAR (extrapolated) = 4.03 W/kg

SAR(1 g) = 0.553 W/kg; SAR(10 g) = 0.131 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 3-15: (U-NII-2C band, Hand-held) Antenna 0, Front & touch, n40(MCS0), 5510MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5510 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5510$ MHz; $\sigma = 5.775$ S/m; $\epsilon_r = 47.97$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5510 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt,rear/5b10.56.0.3;ant0,5510,front&d0,n40(m0)


Area:60x70,10 (7x8x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.31 W/kg

Area:60x70,10 (61x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 2.84 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 24.23 V/m; Power Drift = -0.05 dB; Maximum value of SAR (measured) = 2.27 W/kg; Peak SAR (extrapolated) = 4.93 W/kg

SAR(1 g) = 0.844 W/kg; SAR(10 g) = 0.218 W/kg



Remarks: * Date tested: 2019/01/31; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 3-16: (U-NII-2C band, Hand-held) Antenna 0, Back & touch, n40(MCS0), 5510MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5510 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5510$ MHz; $\sigma = 5.775$ S/m; $\epsilon_r = 47.97$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5510 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt,rear/5b2.56.0.1;ant0,5510,back&d0,n40(m0)/


Area:60x60,10 (7x7x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.698 W/kg

Area:60x60,10 (61x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 0.777 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (9x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 13.64 V/m; Power Drift = 0.14 dB; Maximum value of SAR (measured) = 0.875 W/kg; Peak SAR (extrapolated) = 1.58 W/kg

SAR(1 g) = 0.320 W/kg; SAR(10 g) = 0.097 W/kg



Remarks: * Date tested: 2019/01/31; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.6(start)/22.7(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 3-17: (U-NII-2C band, Hand-held) Antenna 1, Top & touch, n40(MCS0), 5510MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5510 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5510$ MHz; $\sigma = 5.793$ S/m; $\epsilon_r = 47.90$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5510 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,touch,56,58/5b71.56.1.9;ant1,5510,top&d0,n40(m0)/


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.03 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 3.09 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 30.73 V/m; Power Drift = -0.20 dB; Maximum value of SAR (measured) = 4.04 W/kg; Peak SAR (extrapolated) = 8.49 W/kg

SAR(1 g) = 1.44 W/kg; SAR(10 g) = 0.303 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 3-18: (U-NII-2C band, Hand-held) Antenna 1, Top & touch, n40(MCS0), 5550MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5550 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5550$ MHz; $\sigma = 5.866$ S/m; $\epsilon_r = 47.82$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5550 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,touch,56,58/5b72.56.1.10;ant1,5550,top&d0,n40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.23 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 3.59 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 32.16 V/m; Power Drift = -0.09 dB; Maximum value of SAR (measured) = 4.55 W/kg; Peak SAR (extrapolated) = 9.57 W/kg

SAR(1 g) = 1.62 W/kg; SAR(10 g) = 0.338 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 3-19: (U-NII-2C band, Hand-held) Antenna 1, Top & touch, 11a(6Mbps), 5500MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5500 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5500$ MHz; $\sigma = 5.793$ S/m; $\epsilon_r = 47.93$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5500 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,touch,56,58/5b74.56.1.12;ant1,5500,top&d0,a(6m)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.16 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 3.31 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 31.61 V/m; Power Drift = -0.03 dB; Maximum value of SAR (measured) = 4.34 W/kg; Peak SAR (extrapolated) = 9.17 W/kg

SAR(1 g) = 1.54 W/kg; SAR(10 g) = 0.323 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 3-20: (U-NII-2C band, Hand-held) Antenna 1, Top & touch, 11a(6Mbps), 5580MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5580 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5580$ MHz; $\sigma = 5.898$ S/m; $\epsilon_r = 47.79$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5580 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,touch,56,58/5b76.56.1.14;ant1,5580,top&d0,a(6m)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.72 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 4.24 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 34.88 V/m; Power Drift = -0.02 dB; Maximum value of SAR (measured) = 5.55 W/kg; Peak SAR (extrapolated) = 11.6 W/kg

SAR(1 g) = 1.93 W/kg; SAR(10 g) = 0.400 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Plot 3-21: (U-NII-2C band, Hand-held) Antenna 1, Top & touch, 11a(6Mbps), 5700MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5700 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5700$ MHz; $\sigma = 6.072$ S/m; $\epsilon_r = 47.58$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5700 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,touch,56,58/5b75.56.1.13;ant1,5700,top&d0,a(6m)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.44 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 3.85 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 32.61 V/m; Power Drift = -0.04 dB; Maximum value of SAR (measured) = 4.84 W/kg; Peak SAR (extrapolated) = 9.99 W/kg

SAR(1 g) = 1.66 W/kg; SAR(10 g) = 0.338 W/kg



Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 3-22: (U-NII-2C band, Hand-held) Antenna 1, Front & touch, n40(MCS0), 5510MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5510 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5510$ MHz; $\sigma = 5.775$ S/m; $\epsilon_r = 47.97$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5510 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt1/5b26.56.1.6;ant1,5510,front&d0,n40(m0)/


Area:60x70,10 (7x8x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.34 W/kg

Area:60x70,10 (61x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.95 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 22.37 V/m; Power Drift = -0.06 dB; Maximum value of SAR (measured) = 2.38 W/kg; Peak SAR (extrapolated) = 4.88 W/kg

SAR(1 g) = 0.871 W/kg; SAR(10 g) = 0.207 W/kg



Remarks: * Date tested: 2019/01/31; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 3-23: (U-NII-2C band, Hand-held) Antenna 1, Back & touch, n40(MCS0), 5510MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5510 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5510$ MHz; $\sigma = 5.775$ S/m; $\epsilon_r = 47.97$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5510 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt,rear/5b7.56.1.2;ant1,5510,back&d0,n40(m0)/


Area:60x70,10 (7x8x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.287 W/kg

Area:60x70,10 (61x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 0.307 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 8.059 V/m; Power Drift = -0.07 dB; Maximum value of SAR (measured) = 0.303 W/kg; Peak SAR (extrapolated) = 0.527 W/kg

SAR(1 g) = 0.135 W/kg; SAR(10 g) = 0.051 W/kg



Remarks: * Date tested: 2019/01/31; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 4-2: (Hand-held) Antenna 1, Top & touch, 11a(1Mbps), 5745MHz->Higher reported SAR(10g), U-NII-3 band

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5745 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5745 MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 47.508$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5745 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,touch,56,58/5b81.58.1.9;ant1,5745,top&d0,a(6m)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.10 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 3.38 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 30.15 V/m; Power Drift = -0.06 dB; Maximum value of SAR (measured) = 4.14 W/kg; Peak SAR (extrapolated) = 8.61 W/kg

SAR(1 g) = 1.44 W/kg; SAR(10 g) = 0.295 W/kg



Remarks: * Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g) / small=SAR(1g)

Plot 4-3: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, ac80(SISO, MCS0), 5775MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac80(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5775 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: f = 5775 MHz; $\sigma = 6.155$ S/m; $\epsilon_r = 47.56$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5775 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,btm/5b14.58.0.3;ant0,5775,btm&d0,ac80(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.59 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.70 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 21.17 V/m; Power Drift = 0.15 dB; Maximum value of SAR (measured) = 2.60 W/kg; Peak SAR (extrapolated) = 5.22 W/kg

SAR(1 g) = 0.666 W/kg; SAR(10 g) = 0.144 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.7(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g) / small=SAR(1g)

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

Report Cover Page - 13-EM-F0429 Issue # 14.0

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 4-4: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, n40(MCS0), 5755MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5755 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: f = 5755 MHz; $\sigma = 6.134$ S/m; $\epsilon_r = 47.58$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5755 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch/5b39.58.0.12;ant0,5755,btm&d0,n40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.00 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.09 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (9x10x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 19.68 V/m; Power Drift = 0.15 dB; Maximum value of SAR (measured) = 2.66 W/kg; Peak SAR (extrapolated) = 5.18 W/kg

SAR(1 g) = 0.670 W/kg; SAR(10 g) = 0.156 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.7(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 4-5: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, n40(MCS0), 5795MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5795 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: f = 5795 MHz; $\sigma = 6.182$ S/m; $\epsilon_r = 47.52$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5795 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch/5b38.58.0.11;ant0,5795,btm&d0,n40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.14 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.27 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 17.12 V/m; Power Drift = -0.02 dB; Maximum value of SAR (measured) = 2.69 W/kg; Peak SAR (extrapolated) = 7.07 W/kg

SAR(1 g) = 0.866 W/kg; SAR(10 g) = 0.189 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.7(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 4-6: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, ac40(SISO, MCS0), 5755MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5755 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: $f = 5755$ MHz; $\sigma = 6.148$ S/m; $\epsilon_r = 47.48$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5755 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)); Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58,56,53/5b57.58.0.19;ant0,5755,btm&d0,ac40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.943 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.17 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 22.62 V/m; Power Drift = 0.06 dB; Maximum value of SAR (measured) = 2.61 W/kg; Peak SAR (extrapolated) = 5.51 W/kg

SAR(1 g) = 0.703 W/kg; SAR(10 g) = 0.155 W/kg



Remarks: * . Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * . liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50)%RH,
 * . liquid temperature: 23.1(start)/23.0(end)/23.0(in check) deg.C.; * . White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 4-7: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, ac40(SISO, MCS0), 5795MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5795 MHz; Crest Factor: 1.0

Medium: MSL5800(1901); Medium parameters used: $f = 5795$ MHz; $\sigma = 6.182$ S/m; $\epsilon_r = 47.52$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5795 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)); Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,w58/5b40.58.0.13;ant0,5795,btm&d0,ac40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.44 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.55 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 20.23 V/m; Power Drift = -0.05 dB; Maximum value of SAR (measured) = 3.39 W/kg; Peak SAR (extrapolated) = 6.72 W/kg

SAR(1 g) = 0.860 W/kg; SAR(10 g) = 0.181 W/kg



Remarks: * . Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * . liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50)%RH,
 * . liquid temperature: 22.8(start)/22.9(end)/23.0(in check) deg.C.; * . White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 4-8: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, 11a(6Mbps), 5745MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5745 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5745$ MHz; $\sigma = 6.108$ S/m; $\epsilon_r = 47.60$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5745 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch/5b37.58.0.10;ant0,5745,btm&d0,a(6m)/


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.07 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.19 W/kg

Zoom(1st):28x28x24,4,4,1,4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 17.21 V/m; Power Drift = -0.15 dB; Maximum value of SAR (measured) = 2.27 W/kg; Peak SAR (extrapolated) = 5.83 W/kg

SAR(1 g) = 0.734 W/kg; SAR(10 g) = 0.170 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g) / small-SAR(1g)

Plot 4-9: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, 11a(6Mbps), 5785MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5785 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5785$ MHz; $\sigma = 6.172$ S/m; $\epsilon_r = 47.51$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5785 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch/5b36.58.0.9;ant0,5785,btm&d0,a(6m)/


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.27 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.43 W/kg

Zoom:28x28x24,4,4,1,4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 22.70 V/m; Power Drift = 0.13 dB; Maximum value of SAR (measured) = 3.80 W/kg; Peak SAR (extrapolated) = 7.51 W/kg

SAR(1 g) = 0.958 W/kg; SAR(10 g) = 0.203 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g) / small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 4-10: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, 11a(6Mbps), 5825MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5825 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5825$ MHz; $\sigma = 6.22$ S/m; $\epsilon_r = 47.49$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5825 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,btm/5b22.58.0.4;ant0,5825,btm&d0,a(6m)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 2.23 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 2.41 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 23.70 V/m; Power Drift = 0.19 dB; Maximum value of SAR (measured) = 4.24 W/kg; Peak SAR (extrapolated) = 8.26 W/kg

SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.216 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 4-11: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, n20(MCS0), 5745MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5745 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5745$ MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 47.50$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5745 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58,56,53/5b56,58,0.18;ant0,5745,btm&d0,n20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.10 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.18 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 16.26 V/m; Power Drift = 0.06 dB; Maximum value of SAR (measured) = 2.31 W/kg; Peak SAR (extrapolated) = 5.35 W/kg

SAR(1 g) = 0.700 W/kg; SAR(10 g) = 0.164 W/kg



Remarks: * Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.1(start)/23.1(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 4-12: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, n20(MCS0), 5785MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5785 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5785 MHz; $\sigma = 6.183$ S/m; $\epsilon_r = 47.46$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5785 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58.56,53/5b53.58.0.15;ant0,5785,btm&d0,n20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.30 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.60 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 25.52 V/m; Power Drift = 0.19 dB; Maximum value of SAR (measured) = 3.45 W/kg; Peak SAR (extrapolated) = 7.24 W/kg

SAR(1 g) = 0.912 W/kg; SAR(10 g) = 0.193 W/kg



Remarks: * Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 4-13: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, n20(MCS0), 5825MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5825 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: f = 5825 MHz; $\sigma = 6.22$ S/m; $\epsilon_r = 47.49$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5825 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch/5b32.58.0.5;ant0,5825,btm&d0,n20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.45 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.63 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.38 V/m; Power Drift = -0.08 dB; Maximum value of SAR (measured) = 3.44 W/kg; Peak SAR (extrapolated) = 8.64 W/kg

SAR(1 g) = 1.07 W/kg; SAR(10 g) = 0.229 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 4-14: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, ac20(SISO, MCS0), 5745MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5745 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: f = 5745 MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 47.50$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5745 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58,56,53/5b55.58.0.17;ant0,5745,btm&d0,ac20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.06 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.27 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 20.69 V/m; Power Drift = 0.05 dB; Maximum value of SAR (measured) = 2.63 W/kg; Peak SAR (extrapolated) = 5.23 W/kg

SAR(1 g) = 0.693 W/kg; SAR(10 g) = 0.156 W/kg



Remarks: * Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.1(start)/23.1(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 4-15: (U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, ac20(SISO, MCS0), 5785MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5785 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: f = 5785 MHz; $\sigma = 6.183$ S/m; $\epsilon_r = 47.46$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5785 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

btm,touch,58,56,53/5b54.58.0.16;ant0,5785,btm&d0,ac20(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.33 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.42 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 17.25 V/m; Power Drift = -0.20 dB; Maximum value of SAR (measured) = 2.60 W/kg; Peak SAR (extrapolated) = 7.21 W/kg

SAR(1 g) = 0.887 W/kg; SAR(10 g) = 0.196 W/kg



Remarks: * Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 23.0(start)/23.1(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 4-16: (U-NII-3 band, Body-touch) Antenna 0, Front & touch, ac80(SISO, MCS0), 5775MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac80(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5775 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: f = 5775 MHz; $\sigma = 6.155$ S/m; $\epsilon_r = 47.56$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5775 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt,rear/5b11.58,0.2;ant0,5775,front&d0,ac80(m0)

Area:60x70,10 (7x8x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.55 W/kg


Area:60x70,10 (61x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.81 W/kg

Z;155,5 (1x1x32): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 1.42 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.79 V/m; Power Drift = -0.17 dB; Maximum value of SAR (measured) = 1.44 W/kg; Peak SAR (extrapolated) = 3.18 W/kg

SAR(1 g) = 0.485 W/kg; SAR(10 g) = 0.117 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Plot 4-17: (U-NII-3 band, Body-touch) Antenna 0, Back & touch, ac80(SISO, MCS0), 5775MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac80(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5775 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: f = 5775 MHz; $\sigma = 6.155$ S/m; $\epsilon_r = 47.56$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5775 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt,rear/5b3.58,0.1;ant0,5775,back&d0,ac80(m0)


Area:60x60,10 (7x7x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.425 W/kg

Area:60x60,10 (61x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 0.523 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 11.89 V/m; Power Drift = 0.01 dB; Maximum value of SAR (measured) = 0.642 W/kg; Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.221 W/kg; SAR(10 g) = 0.066 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.7(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 4-18: (U-NII-3 band, Hand-held) Antenna 1, Top & touch, ac80(SISO, MCS0), 5775MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac80(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5775 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: f = 5775 MHz; $\sigma = 6.155$ S/m; $\epsilon_r = 47.56$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5775 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,btm/5b15.58.1.2;ant1,5775,top&d0,ac80(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.32 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 3.27 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 26.09 V/m; Power Drift = -0.08 dB; Maximum value of SAR (measured) = 3.10 W/kg; Peak SAR (extrapolated) = 6.68 W/kg

SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.217 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g) / small-SAR(1g)

Plot 4-19: (U-NII-3 band, Hand-held) Antenna 1, Top & touch, n40(MCS0), 5755MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5755 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5755 MHz; $\sigma = 6.148$ S/m; $\epsilon_r = 47.48$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5755 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,touch,56,58/5b77.58.1.5;ant1,5755,top&d0,n40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.88 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 3.07 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 28.56 V/m; Power Drift = -0.06 dB; Maximum value of SAR (measured) = 3.68 W/kg; Peak SAR (extrapolated) = 7.65 W/kg

SAR(1 g) = 1.27 W/kg; SAR(10 g) = 0.258 W/kg



Remarks: * Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g) / small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 4-20: (U-NII-3 band, Hand-held) Antenna 1, Top & touch, n40(MCS0), 5795MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: n40(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5795 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5795 MHz; $\sigma = 6.196$ S/m; $\epsilon_r = 47.43$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5795 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,touch,56,58/5b78.58.1.6;ant1,5795,top&d0,n40(m0)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.71 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 2.72 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 26.47 V/m; Power Drift = -0.06 dB; Maximum value of SAR (measured) = 3.30 W/kg; Peak SAR (extrapolated) = 6.97 W/kg

SAR(1 g) = 1.13 W/kg; SAR(10 g) = 0.231 W/kg



Remarks: * Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g) / small-SAR(1g)

Plot 4-21: (U-NII-3 band, Hand-held) Antenna 1, Top & touch, 11a(6Mbps), 5785MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5785 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: f = 5785 MHz; $\sigma = 6.183$ S/m; $\epsilon_r = 47.46$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5785 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,touch,56,58/5b79.58.1.7;ant1,5785,top&d0,a(6m)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.88 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 3.06 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 28.38 V/m; Power Drift = -0.05 dB; Maximum value of SAR (measured) = 3.71 W/kg; Peak SAR (extrapolated) = 7.60 W/kg

SAR(1 g) = 1.27 W/kg; SAR(10 g) = 0.259 W/kg



Remarks: * Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g) / small-SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 4-22: (U-NII-3 band, Hand-held) Antenna 1, Top & touch, 11a(6Mbps), 5825MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: 11a(6Mbps, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5825 MHz; Crest Factor: 1.0**

Medium: MSL5800(1902); Medium parameters used: $f = 5825$ MHz; $\sigma = 6.25$ S/m; $\epsilon_r = 47.38$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5825 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

top,touch,56,58/5b80.58.1.8;ant1,5825,top&d0,a(6m)


Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.81 W/kg

Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 2.90 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 27.01 V/m; Power Drift = -0.03 dB; Maximum value of SAR (measured) = 3.47 W/kg; Peak SAR (extrapolated) = 7.06 W/kg

SAR(1 g) = 1.17 W/kg; SAR(10 g) = 0.239 W/kg



Remarks: * Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Plot 4-23: (U-NII-3 band, Hand-held) Antenna 1, Front & touch, ac80(SISO, MCS0), 5775MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac80(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5775 MHz; Crest Factor: 1.0**

Medium: MSL5800(1901); Medium parameters used: $f = 5775$ MHz; $\sigma = 6.155$ S/m; $\epsilon_r = 47.56$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5775 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt1/5b28.58.1.4;ant1,5775,front&d0,ac80(m0)


Area:60x70,10 (7x8x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.877 W/kg

Area:60x70,10 (61x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.20 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 18.72 V/m; Power Drift = -0.16 dB; Maximum value of SAR (measured) = 1.79 W/kg; Peak SAR (extrapolated) = 3.49 W/kg

SAR(1 g) = 0.578 W/kg; SAR(10 g) = 0.123 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 4-24: (U-NII-3 band, Hand-held) Antenna 1, Back & touch, ac80(SISO, MCS0), 5775MHz

Antenna#1; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac80(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5775 MHz; Crest Factor: 1.0

Medium: MSL5800(1901); Medium parameters used: $f = 5775$ MHz; $\sigma = 6.155$ S/m; $\epsilon_r = 47.56$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5775 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0

frt,rear/5b6.58.1.1;ant1,5775,back&d0,ac80(m0)


Area:60x70,10 (7x8x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 0.142 W/kg

Area:60x70,10 (61x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 0.149 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 5.487 V/m; Power Drift = 0.04 dB; Maximum value of SAR (measured) = 0.147 W/kg; Peak SAR (extrapolated) = 0.239 W/kg

SAR(1 g) = 0.061 W/kg; SAR(10 g) = 0.023 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.8(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 2-2: SAR measurement data / SAR plots of other SAR conditions (cont'd)

Plot 5-1: SAR Measurement Variability

(U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, ac20(SISO, MCS0), 5825MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5825 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: f = 5825 MHz; $\sigma = 6.25$ S/m; $\epsilon_r = 47.38$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5825 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0

repeat,btm/5b95.58,0.20;ant0,5825,btm&d0,ac20(m0)/

Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.66 W/kg


Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 2.00 W/kg

Z;155,5 (1x1x32): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 4.34 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 25.97 V/m; Power Drift = 0.08 dB; Maximum value of SAR (measured) = 4.30 W/kg; Peak SAR (extrapolated) = 8.33 W/kg

SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.227 W/kg



Remarks: * Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g) /small=SAR(1g)

Plot 5-2: Device holder perturbation verification:

(U-NII-3 band, Body-touch) Antenna 0, Bottom & touch, ac20(SISO, MCS0), 5825MHz

Antenna#0; EUT: Game Console; Type: HDH-001; Serial: XJW01000021163

Mode: ac20(MCS0, BPSK/OFDM) (UID: 0; Wi-fi_5GHz (0); Frame Length in ms: 0; PAR: 0; PMF: 1); Frequency: 5825 MHz; Crest Factor: 1.0

Medium: MSL5800(1902); Medium parameters used: f = 5825 MHz; $\sigma = 6.25$ S/m; $\epsilon_r = 47.38$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section

-DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5825 MHz; Calibrated: 2018/05/15

-Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0

repeat,btm/no-DH,re,5b96.58,0.21;ant0,5825,btm&d0,ac20(m0)/

Area:50x80,10 (6x9x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 1.39 W/kg


Area:50x80,10 (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 1.85 W/kg

Z;155,5 (1x1x32): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 4.21 W/kg

Zoom:28x28x24,1,4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;

Reference Value = 27.95 V/m; Power Drift = 0.19 dB; Maximum value of SAR (measured) = 3.94 W/kg; Peak SAR (extrapolated) = 8.42 W/kg

SAR(1 g) = 1.1 W/kg; SAR(10 g) = 0.232 W/kg



Remarks: * Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of EUT to phantom: 0 mm (2 mm to liquid); ambient: (23.5~25) deg.C. / (35~50) %RH,
 * liquid temperature: 22.9(start)/22.9(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g) /small=SAR(1g)

APPENDIX 3: Test instruments**Appendix 3-1: Equipment used**

Local ID	Test Name	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Calibration Due Date	Calibration Interval (Month)
KATI0-S3	AT	144893	Attenuator	AGILENT	8490D 010	50924	2018/12/12	2019/12/31	12
KPM-08	AT	145105	Power meter	ANRITSU	ML2495A	6K00003356	2018/9/28	2019/9/30	12
KPSS-04	AT	144991	Power sensor	ANRITSU	MA2411B	12088	2018/9/28	2019/9/30	12
KTM-G1	AT	145935	Terminator	Hirose Electric	HRM-TMP-05(40)	-	-	-	-
SPM-07	AT	146247	Power Meter	AGILENT	E990B	MY5100272	2018/7/13	2019/7/31	12
SPSS-04	AT	146310	Power sensor	AGILENT	N1923A	MY5326009	2018/7/13	2019/7/31	12
COTS-SSAR-02	SAR	144885	DASY52 software	Schmid&Partner Engineering AG	DASY5 PRO	Ver.52.10.2.1495	-	-	-
COTS-SSEP-02	SAR	144886	Dielectric assessment software	Schmid&Partner Engineering AG	DAK	Ver.DAK1.10.317.11	-	-	-
KATI0-P1	SAR	144882	Attenuator	Weinschel - API Technologies Corp	24-10-34	BY5927	2018/12/12	2019/12/31	12
KCPL-07	SAR	146100	Directional Coupler	Pulsar Microwave Corp	CCS30-B26	621	-	-	-
KDAE-01	SAR	144944	Data Acquisition Electronics	Schmid&Partner Engineering AG	DAE4	626	2018/10/15	2019/10/31	12
KIU-08	SAR	145059	Power sensor	Rohde & Schwarz	NRV-Z4	100372	2018/9/28	2019/9/30	12
KIU-09	SAR	145099	Power sensor	Rohde & Schwarz	NRV-Z4	100371	2018/9/28	2019/9/30	12
KOS-13	SAR	144985	Digital thermometer	HANNA	Checktemp-2	KOS-13	2018/12/5	2019/12/31	12
KOS-14	SAR	144986	Thermo-Hygrometer data logger	SATO KEIRYOKI	SK-L200THIIa/SK-LTHIIa-2	015246/08169	2018/12/5	2019/12/31	12
KPA-12	SAR	145359	RF Power Amplifier	Milmega	AS2560-50	1018582	-	-	-
KPFL-01	SAR	145560	Flat Phantom	Schmid&Partner Engineering AG	Oval flat phantom ELI 4.0	1059	2018/8/27	2019/8/31	12
KPM-05	SAR	144988	Power meter	AGILENT	E4417A	GB41290718	2018/4/12	2019/4/30	12
KPM-06	SAR	144989	Power Meter	Rohde & Schwarz	NRVD	101599	2018/9/28	2019/9/30	12
KPSS-01	SAR	144990	Power sensor	AGILENT	E9327A	US40440544	2018/4/12	2019/4/30	12
KRU-04	SAR	145086	Ruler(300mm)	SHINWA	13134	-	2018/5/23	2019/5/31	12
KRU-05	SAR	145087	Ruler(100x50mm,L)	SHINWA	12101	-	2018/5/23	2019/5/31	12
KSDA-02	SAR	145091	Dipole Antenna	Schmid&Partner Engineering AG	D5GHzV2	1070	2018/3/1	2019/3/31	12
KSDH-01	SAR	145596	Device holder	Schmid&Partner Engineering AG	Mounting device for transmitter	-	2018/9/27	2019/9/30	12
KSG-08	SAR	145109	Signal Generator	Rohde & Schwarz	SMT06	100763	2018/9/27	2019/9/30	12
KSLM245-01	SAR	145365	Tissue simulation liquid (2450MHz,body)	Schmid&Partner Engineering AG	MSL2450V2	SL AAM 245 BA	-	-	-
KSLM580-02	SAR	145366	Tissue simulation liquid (5800MHz,body)	Schmid&Partner Engineering AG	MBBL3500-5800V5	SL AAM 501 AB(110520-3)	-	-	-
SALC-01	SAR	146112	Primepure Ethanol	Kanto Chemical Co., Inc.	14032-79	-	-	-	-
SAT20-SAR1	SAR	145149	Attenuator	TME	SFA-01AXPJ-20	-	2018/12/12	2019/12/31	12
SAT6-SAR1	SAR	145160	Attenuator	Huber+Suhner	6806.17.A	766429-1	2018/12/12	2019/12/31	12
SCC-SAR2	SAR	145405	Coaxial Cable	Huber+Suhner	SF104A/11PC3542/11N451/4M	MY699/4A	-	-	-
SEPP-02	SAR	145500	Dielectric probe	Schmid&Partner Engineering AG	DAK3.5	1129	2018/8/17	2019/8/31	12
SOS-11	SAR	146296	Humidity Indicator	A&D	AD-5681	4063424	2019/1/11	2020/1/31	12
SOS-12	SAR	146320	Digital thermometer	HANNA	Checktemp-4	SOS-12	2019/1/11	2020/1/31	12
SOS-SAR1	SAR	146323	Digital thermometer	LKMelectronic	DTM3000	3171	2018/10/25	2019/10/31	12
SPB-02	SAR	146235	Dosimetric E-Field Probe	Schmid&Partner Engineering AG	EX3DV4	3907	2018/5/15	2019/5/31	12
SSA-04	SAR	146176	Spectrum Analyzer	ADVANTEST	R3272	101100994	-	-	-
SSAR-02	SAR	146177	SAR measurement system	Schmid&Partner Engineering AG	DASY5	1324	-	-	-
SSDA-R01	SAR	145558	Dipole Antenna	Schmid&Partner Engineering AG	D2450V2	765	2018/5/16	2019/5/31	12
SSNA-01	SAR	146258	Network Analyzer	AGILENT	8753ES	US39171777	2018/12/17	2019/12/31	12
SSRBT-02	SAR	145621	SAR robot	Schmid&Partner Engineering AG	TX60 Lspeag	F12/5L2QA1/A/01	2018/9/27	2019/9/30	12
SWTR-03	SAR	146185	DI water	MonotaRo	34557433	-	-	-	-

*. AT (antenna terminal conducted power measurement) was measured January 8-11, 2019. (Refer to Section 6 in this report.)

The expiration date of calibration is the end of the expired month.


As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

[Test Item] SAR: Specific Absorption Rate; AT: Antenna terminal conducted power

Appendix 3-2: Configuration and peripherals

These measurements were performed with the automated near-field scanning system DASY5 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot, which positions the probes with a positional repeatability of better than ± 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetry probes EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.



The DASY5 system for performing compliance tests consist of the following items:

1	A standard high precision 6-axis robot (Stäubli TX/RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
2	An isotropic field probe optimized and calibrated for the targeted measurement.
3	A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4	The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
5	The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
6	The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
7	A computer running Win7 professional operating system and the DASY5 software.
8	R Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
9	The phantom.
10	The device holder for EUT. (low-loss dielectric palette) (*. when it was used.)
11	Tissue simulating liquid mixed according to the given recipes.
12	Validation dipole kits allowing to validate the proper functioning of the system.

Appendix 3-3: Test system specification

TX60 Lsepag robot/CS8Csepag-TX60 robot controller

- Number of Axes : 6
- Repeatability : ±0.02 mm
- Manufacture : Stäubli Unimation Corp.

DASY5 Measurement server

- Features : The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz intel ULV Celeron, 128MB chip-disk and 128MB RAM. The necessary circuits for communication with the DAE4 electronics box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.

- Calibration : No calibration required.
- Manufacture : Schmid & Partner Engineering AG

Data Acquisition Electronic (DAE)

- Features : Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY5 embedded system (fully remote controlled). 2 step probe touch detector for mechanical surface detection and emergency robot stop (not in -R version)

- Measurement Range : 1 µV to > 200 mV (16bit resolution and 2 range settings: 4 mV, 400 mV)
- Input Offset voltage : < 1 µV (with auto zero)
- Input Resistance : 200 MΩ
- Battery Power : > 10 hrs. of operation (with two 9 V battery)
- Manufacture : Schmid & Partner Engineering AG

Electro-Optical Converter (EOC61)

- Manufacture : Schmid & Partner Engineering AG

Light Beam Switch (LB5/80)

- Manufacture : Schmid & Partner Engineering AG

SAR measurement software

- Item : Dosimetric Assessment System DASY5
- Software version : Refer to Appendix 3-1 (Equipment used)
- Manufacture : Schmid & Partner Engineering AG

E-Field Probe


- Model : EX3DV4 (serial number: 3907)
- Construction : Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).
- Frequency : 10MHz to 6GHz, Linearity: ±0.2 dB (30MHz to 6GHz)
- Conversion Factors : 2.45, 5.2, 5.25, 5.5, 5.6, 5.75, 5.8 GHz (Head)
: 2.45, 5.25, 5.6, 5.75 GHz (Body)
- Directivity : ±0.3 dB in HSL (rotation around probe axis)
: ±0.5 dB in tissue material (rotation normal to probe axis)
- Dynamic Range : 10µW/g to > 100 mW/g; Linearity: ±0.2 dB (noise: typically < 1 µW/g)
- Dimension : Overall length: 330 mm (Tip: 20 mm)
Tip diameter: 2.5 mm (Body: 12 mm)
Typical distance from probe tip to dipole centers: 1mm
- Application : High precision dosimetric measurement in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6GHz with precision of better 30%.
- Manufacture : Schmid & Partner Engineering AG

Phantom

- Type : **ELI 4.0 oval flat phantom**
- Shell Material : Fiberglass
- Shell Thickness : Bottom plate: 2 ±0.2 mm
- Dimensions : Bottom elliptical: 600×400 mm, Depth: 190 mm (Volume: Approx. 30 liters)
- Manufacture : Schmid & Partner Engineering AG

Device Holder

- Urethane foam
- KSDH-01: In combination with the ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Transmitter devices can be easily and accurately positioned. The low-loss dielectric urethane foam was used for the mounting section of device holder.
 - Material : Polyoxymethylene (POM)
 - Manufacture : Schmid & Partner Engineering AG
- SSDH-02: A simple but effective and easy-to-use extension for the Mounting Device; facilitates testing of larger devices (e.g., laptops, cameras, etc.) according to IEC 62209-2.
 - Material : Polyoxymethylene (POM), PET-G, Foam
 - Manufacture : Schmid & Partner Engineering AG



Appendix 3-4: Simulated tissue composition and parameter confirmation

Liquid type	Body	Body
Control No.	KSLM245-01	KSLM580-02
Model No. / Product No.	MSL2450V2 / SL AAM 245 BA	MBBL3500-5800V5 / SL AAM 501 AB
Ingredient: Mixture(%)	Water: 52-75%, DGBE: 25-48%, NaCl: <1.0%	Water: 60-80%, Ester/Emulsifiers/Inhibitors: 20-40%, Sodium salt: 0-1.5%
Manufacture	Schmid & Partner Engineering AG	

*. The dielectric parameters were checked prior to assessment using the DAK3.5 dielectric probe kit.

Measured date	Freq. [MHz]	Liquid type	Ambient [deg.C.] [%RH]	Liquid temp. [deg.C.]	Liquid Depth [mm]	Liquid parameters (*a)						ASAR			
						Permittivity (εr) [-]			Conductivity [S/m]			(1g) [%] (*b)	(10g) [%] (*b)		
						Target	Measured	Limit	Target	Measured	Limit				
January 28-29, 2019 (*1)	2450	Body	23/32	21.9	(151)	52.7	50.79	-3.6	±5%	1.95	2.020	+3.6	±5%	+2.53	+1.50
January 30, 2019	5250	Body	23/32	23.0	(151)	48.95	48.39	-1.1	±5%	5.358	5.428	+1.3	±5%	+0.19	+0.22
January 31, 2019	5600	Body	23/32	23.0	(151)	48.47	47.82	-1.3	±5%	5.766	5.895	+2.2	±5%	+0.17	+0.25
February 1, 2019	5750	Body	23/32	23.0	(151)	49.04	47.58	-1.4	±5%	5.942	6.122	+3.0	±5%	+0.19	+0.27
February 4, 2019	5250	Body	24/34	23.0	(151)	48.95	48.34	-1.2	±5%	5.358	5.454	+1.8	±5%	+0.19	+0.23
February 5, 2019	5600	Body	24/34	23.0	(151)	48.47	47.75	-1.5	±5%	5.766	5.928	+2.8	±5%	+0.17	+0.26
February 6, 2019	5750	Body	24/34	23.0	(151)	49.04	47.51	-1.6	±5%	5.942	6.143	+3.4	±5%	+0.16	+0.29

*1. On January 29, it was within 24 hours from measurement on January 28 and same liquid temperature, so parameters of January 28 were used continuously.

*a. The target values of (2000, 2450, 3000 and 5800) MHz are parameters defined in Appendix A of KDB 865664 D01. For other frequencies, the target nominal dielectric values shall be obtained by linear interpolation between the higher and lower tabulated figures.

Standard						Interpolated & Extrapolated								
f (MHz)	Head Tissue		Body Tissue		f (MHz)	Head Tissue		Body Tissue		f (MHz)	Head Tissue		Body Tissue	
	εr	σ [S/m]	εr	σ [S/m]		εr	σ [S/m]	εr	σ [S/m]		εr	σ [S/m]	εr	σ [S/m]
(1800-2000)	40.0	1.40	53.3	1.52	3000	38.5	2.40	52.0	2.73	5250	35.93	4.706	48.95	5.358
2450	39.2	1.80	52.7	1.95	5800	35.3	5.27	48.2	6.00	5600	35.53	5.065	48.47	5.766

*b. The coefficients are parameters defined in IEEE Std. 1528-2013.

$$ASAR(1g) = C_{\epsilon r} \times \Delta \epsilon_r + C_{\sigma} \times \Delta \sigma, C_{\epsilon r} = 7.854E-4 \times f^3 + 9.402E-3 \times f^2 - 2.742E-2 \times f + 0.2026 / C_{\sigma} = 9.804E-3 \times f^3 - 8.661E-2 \times f^2 + 2.981E-2 \times f + 0.7829$$

$$ASAR(10g) = C_{\epsilon r} \times \Delta \epsilon_r + C_{\sigma} \times \Delta \sigma, C_{\epsilon r} = 3.456 \times 10^{-3} \times f^3 - 3.531 \times 10^{-2} \times f^2 + 7.675 \times 10^{-2} \times f + 0.1860 / C_{\sigma} = 4.479 \times 10^{-3} \times f^3 - 1.586 \times 10^{-2} \times f^2 - 0.1972 \times f + 0.7717$$

Appendix 3-5: Daily check results

*. Prior to the SAR assessment of EUT, the Daily check was performed to test whether the SAR system was operating within its target of ±10%. The Daily check results are in the table below.

Daily check results																				
Date	Freq. [MHz]	Liquid Type	Daily check target & measured																	
			SAR (1g) [W/kg] (*d)							SAR (10g) [W/kg] (*d)										
			Meas. (%)	ASAR-correct	1W scaled	Target Cal. (%)	STD (%)	Deviation Cal. [%]	STD [%]	Limit [%]	Pass ?	Meas. (%)	ASAR-correct	1W scaled	Target Cal. (%)	STD (%)	Deviation Cal. [%]	STD [%]	Limit [%]	Pass ?
January 28, 2019	2450	Body	12.7	12.38	49.52	49.8	n/a	-0.6	n/a	±10	Pass	5.92	5.83	23.32	23.2	n/a	+0.5	n/a	±10	Pass
January 29, 2019	2450	Body	12.8	12.48	49.92	49.8	n/a	+0.2	n/a	±10	Pass	5.97	5.7	22.8	23.2	n/a	+1.4	n/a	±10	Pass
January 30, 2019	5250	Body	7.56	7.55	75.5	75.4	n/a	+0.1	n/a	±10	Pass	2.13	2.13	21.3	21.0	n/a	+1.4	n/a	±10	Pass
January 31, 2019	5600	Body	7.96	7.94	79.4	78.6	n/a	+1.0	n/a	±10	Pass	2.21	2.21	22.1	21.9	n/a	+0.9	n/a	±10	Pass
February 1, 2019	5750	Body	7.5	7.49	74.9	74.6	n/a	+0.4	n/a	±10	Pass	2.09	2.08	20.8	20.6	n/a	+1.0	n/a	±10	Pass
February 4, 2019	5250	Body	7.37	7.36	73.6	73.6	n/a	-2.4	n/a	±10	Pass	2.09	2.08	20.8	21.0	n/a	-1.0	n/a	±10	Pass
February 5, 2019	5600	Body	8.09	8.07	80.7	78.6	n/a	+2.7	n/a	±10	Pass	2.25	2.24	22.4	21.9	n/a	+2.3	n/a	±10	Pass
February 6, 2019	5750	Body	7.56	7.55	75.5	74.6	n/a	+1.2	n/a	±10	Pass	2.11	2.10	21.0	20.6	n/a	+1.9	n/a	±10	Pass


*. Calculating formula: ASAR corrected SAR (1g,10g) (W/kg) = (Observed SAR(1g,10g) (W/kg)) × (100 - (ASAR(%)) / 100

*c. The "Meas. (Measured)" SAR value is obtained at 250 mW for 2450MHz, and at 100 mW for 5GHz band.

*d. The measured SAR value of Daily check was compensated for tissue dielectric deviations (ASAR) and scaled to 1W of output power in order to compare with the manufacturer's calibration target value which was normalized.


*e. The target value is a parameter defined in the calibration data sheet of D2450V2 (sn:765) and D5GHZV2 (sn:1070) dipole calibrated by Schmid & Partner Engineering AG (Certification No. D2450V2-765_May18 / D5GHZV2-1070_Mar18, the data sheet was filed in this report).

*f. The target value (normalized to 1W) is defined in IEEE Std.1528.



Test setup for the system performance check

Appendix 3-6: Daily check measurement data




(January 28, 2019) EUT: Dipole(2.45GHz); Type: D2450V2; Serial: 765; Forward conducted power: 250mW
Communication System: CW (* UID:0; CW; Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2450 MHz; Crest Factor: 1.0**
Medium: M2450(1901); Medium parameters used: f = 2450 MHz; $\sigma = 2.02$ S/m; $\epsilon_r = 50.79$; $\rho = 1000$ kg/m³
 Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2450 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0, 161.0

Area:60x60,15 (5x5x1): Measurement grid: dx=15mm, dy=15mm; Maximum value of SAR (measured) = 18.7 W/kg
Area:60x60,15 (41x41x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm; Maximum value of SAR (interpolated) = 19.0 W/kg
Z;160,5 (1x1x33): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 19.3 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;
 Reference Value = 97.92 V/m; Power Drift = 0.02 dB; Maximum value of SAR (measured) = 19.2 W/kg; Peak SAR (extrapolated) = 25.9 W/kg
SAR(1 g) = 12.7 W/kg; SAR(10 g) = 5.92 W/kg




Remarks: * Date tested: 2019/01/28; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of dipole to phantom: 8mm (10mm to liquid); ambient: 23 deg.C. / 39 %RH,
 * liquid temperature: 21.8(start)/21.7(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

(January 29, 2019) EUT: Dipole(2.45GHz); Type: D2450V2; Serial: 765; Forward conducted power: 250mW
Communication System: CW (* UID:0; CW; Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 2450 MHz; Crest Factor: 1.0**
Medium: M2450(1901); Medium parameters used: f = 2450 MHz; $\sigma = 2.02$ S/m; $\epsilon_r = 50.79$; $\rho = 1000$ kg/m³
 Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(7.32, 7.32, 7.32) @ 2450 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0, 161.0

Area:60x60,15 (5x5x1): Measurement grid: dx=15mm, dy=15mm; Maximum value of SAR (measured) = 18.9 W/kg
Area:60x60,15 (41x41x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm; Maximum value of SAR (interpolated) = 19.4 W/kg
Z;160,5 (1x1x33): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 19.6 W/kg

Zoom:30x30x30,5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm;
 Reference Value = 97.94 V/m; Power Drift = -0.02 dB; Maximum value of SAR (measured) = 19.5 W/kg; Peak SAR (extrapolated) = 26.1 W/kg
SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.97 W/kg



Remarks: * Date tested: 2019/01/29; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of dipole to phantom: 8mm (10mm to liquid); ambient: 23 deg.C. / 43 %RH,
 * liquid temperature: 21.9(start)/21.9(end)/21.9(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)


UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401


Appendix 3-6: Daily check measurement data (cont'd)



(January 30, 2019) EUT: Dipole(5GHz); Type: D5GHzV2; Serial: 1070; Forward conducted power: 100mW
Communication System: CW (* UID:0; CW(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5250 MHz; Crest Factor: 1.0**
Medium: MSL5800(1901); Medium parameters used: f = 5250 MHz; $\sigma = 5.428$ S/m; $\epsilon_r = 48.39$; $\rho = 1000$ kg/m³
 Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5250 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0

Area:60x60,10 (7x7x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 16.8 W/kg
Area:60x60,10 (61x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 18.0 W/kg
Z:155,5 (1x1x32): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 17.1 W/kg
Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;
 Reference Value = 63.05 V/m; Power Drift = -0.01 dB; Maximum value of SAR (measured) = 17.3 W/kg; Peak SAR (extrapolated) = 29.9 W/kg
SAR(1 g) = 7.56 W/kg; SAR(10 g) = 2.13 W/kg




Remarks: * Date tested: 2019/01/30; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of dipole to phantom: 8mm (10mm to liquid); ambient: 24 deg.C. / 42 %RH,
 * liquid temperature: 22.8(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

(January 31, 2019) EUT: Dipole(5GHz); Type: D5GHzV2; Serial: 1070; Forward conducted power: 100mW
Communication System: CW (* UID:0; CW(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5600 MHz; Crest Factor: 1.0**
Medium: MSL5800(1901); Medium parameters used: f = 5600 MHz; $\sigma = 5.895$ S/m; $\epsilon_r = 47.82$; $\rho = 1000$ kg/m³
 Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)


DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5600 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0

Area:60x60,10 (7x7x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 20.3 W/kg
Area:60x60,10 (61x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 20.6 W/kg
Z:155,5 (1x1x32): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 19.0 W/kg
Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;
 Reference Value = 65.47 V/m; Power Drift = -0.08 dB; Maximum value of SAR (measured) = 19.1 W/kg; Peak SAR (extrapolated) = 35.8 W/kg
SAR(1 g) = 7.96 W/kg; SAR(10 g) = 2.21 W/kg



Remarks: * Date tested: 2019/01/31; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of dipole to phantom: 8mm (10mm to liquid); ambient: 24 deg.C. / 36 %RH,
 * liquid temperature: 22.9(start)/22.8(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)

Appendix 3-6: Daily check measurement data (cont'd)




(February 1, 2019) EUT: Dipole(5GHz); Type: D5GHzV2; Serial: 1070; Forward conducted power: 100mW
Communication System: CW (* UID:0; CW(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5750 MHz; Crest Factor: 1.0**
Medium: MSL5800(1901); Medium parameters used: f = 5750 MHz; $\sigma = 6.122$ S/m; $\epsilon_r = 47.58$; $\rho = 1000$ kg/m³
 Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5750 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0

Area:60x60,10 (7x7x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 17.6 W/kg
Area:60x60,10 (61x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 19.1 W/kg
Z;155,5 (1x1x32): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 18.0 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;
 Reference Value = 60.60 V/m; Power Drift = -0.06 dB; Maximum value of SAR (measured) = 18.3 W/kg; Peak SAR (extrapolated) = 34.6 W/kg

SAR(1 g) = 7.5 W/kg; SAR(10 g) = 2.09 W/kg



Remarks: * Date tested: 2019/02/01; Tested by: Hiroshi Naka; Tested place:No.7 shielded room,
 * liquid depth: 151 mm; Position: distance of dipole to phantom: 8mm (10mm to liquid); ambient: 24 deg.C. / 46 %RH,
 * liquid temperature: 22.8(start)/22.7(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)


(February 4, 2019) EUT: Dipole(5GHz); Type: D5GHzV2; Serial: 1070; Forward conducted power: 100mW
Communication System: CW (* UID:0; CW(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5250 MHz; Crest Factor: 1.0**
Medium: MSL5800(1902); Medium parameters used: f = 5250 MHz; $\sigma = 5.454$ S/m; $\epsilon_r = 48.34$; $\rho = 1000$ kg/m³
 Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4.49, 4.49, 4.49) @ 5250 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0

Area:60x60,10 (7x7x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 17.9 W/kg
Area:60x60,10 (61x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 18.3 W/kg
Z;155,5 (1x1x32): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 17.5 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;
 Reference Value = 65.41 V/m; Power Drift = -0.00 dB; Maximum value of SAR (measured) = 17.5 W/kg; Peak SAR (extrapolated) = 29.3 W/kg

SAR(1 g) = 7.37 W/kg; SAR(10 g) = 2.09 W/kg



Remarks: * Date tested: 2019/02/04; Tested by: Hiroshi Naka; Tested place:No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of dipole to phantom: 8mm (10mm to liquid); ambient: 24 deg.C. / (45-50) %RH,
 * liquid temperature: 23.0(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big-SAR(10g)/small-SAR(1g)


UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

Appendix 3-6: Daily check measurement data (cont'd)




(February 5, 2019) EUT: Dipole(5GHz); Type: D5GHzV2; Serial: 1070; Forward conducted power: 100mW
Communication System: CW (*: UID:0; CW(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5600 MHz; Crest Factor: 1.0**
Medium: MSL5800(1902); Medium parameters used: f = 5600 MHz; $\sigma = 5.928$ S/m; $\epsilon_r = 47.75$; $\rho = 1000$ kg/m³
 Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(3.92, 3.92, 3.92) @ 5600 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0

Area:60x60,10 (7x7x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 20.4 W/kg
Area:60x60,10 (61x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 20.9 W/kg
Z;155,5 (1x1x32): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 19.7 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;
 Reference Value = 65.68 V/m; Power Drift = -0.08 dB; Maximum value of SAR (measured) = 19.7 W/kg; Peak SAR (extrapolated) = 36.8 W/kg
SAR(1 g) = 8.09 W/kg; SAR(10 g) = 2.25 W/kg




Remarks: * Date tested: 2019/02/05; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of dipole to phantom: 8mm (10mm to liquid); ambient: 24 deg.C. / (45~50) %RH,
 * liquid temperature: 22.9(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

(February 6, 2019) EUT: Dipole(5GHz); Type: D5GHzV2; Serial: 1070; Forward conducted power: 100mW
Communication System: CW (*: UID:0; CW(0); Frame Length in ms: 0; PAR: 0; PMF: 1); **Frequency: 5750 MHz; Crest Factor: 1.0**
Medium: MSL5800(1902); Medium parameters used: f = 5750 MHz; $\sigma = 6.143$ S/m; $\epsilon_r = 47.51$; $\rho = 1000$ kg/m³
 Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration: -Electronics: DAE4 Sn626; Calibrated: 2018/10/15 ; -Phantom: ELI v4.0; Type: QDOVA001BA; Serial: 1059; Phantom section: Flat Section
 -DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450); -Probe: EX3DV4 - SN3907; ConvF(4, 4, 4) @ 5750 MHz; Calibrated: 2018/05/15
 -Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 25.0, 156.0

Area:60x60,10 (7x7x1): Measurement grid: dx=10mm, dy=10mm; Maximum value of SAR (measured) = 19.2 W/kg
Area:60x60,10 (61x61x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm; Maximum value of SAR (interpolated) = 19.5 W/kg
Z;155,5 (1x1x32): Measurement grid: dx=20mm, dy=20mm, dz=5mm; Maximum value of SAR (measured) = 18.5 W/kg

Zoom:28x28x24,4,4,1.4(ratio) (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm;
 Reference Value = 63.92 V/m; Power Drift = 0.00 dB; Maximum value of SAR (measured) = 18.6 W/kg; Peak SAR (extrapolated) = 34.5 W/kg
SAR(1 g) = 7.56 W/kg; SAR(10 g) = 2.11 W/kg



Remarks: * Date tested: 2019/02/06; Tested by: Hiroshi Naka; Tested place: No.7 shielded room,
 * liquid depth: 152 mm; Position: distance of dipole to phantom: 8mm (10mm to liquid); ambient: 24 deg.C. / (45~50) %RH,
 * liquid temperature: 23.0(start)/23.0(end)/23.0(in check) deg.C.; * White cubic: zoom scan area, Red cubic: big=SAR(10g)/small=SAR(1g)

Appendix 3-7: Daily check uncertainty

Although this standard determines only the limit value of uncertainty, there is no applicable rule of uncertainty in this. Therefore, the following results are derived depending on whether or not laboratory uncertainty is applied.

Uncertainty of daily check (2.4~6GHz) (*,ε&σ tolerance: ≤±5%, DAK3.5, CW) (v08)							1g SAR	10g SAR	
Combined measurement uncertainty of the measurement system (k=1)							±11.0 %	±10.9 %	
Expanded uncertainty (k=2)							±22.1 %	±21.8 %	
	Error Description (v08)	Uncertainty Value	Probability distribution	Divisor	ci (1g)	ci (10g)	ui (1g) (std. uncertainty)	ui (10g) (std. uncertainty)	Vi, veff
A	Measurement System (DASY5)								
1	Probe Calibration Error	±6.55 %	Normal	1	1	1	±6.55 %	±6.55 %	∞
2	Axial isotropy error	±4.7 %	Rectangular	√3	√0.5	√0.5	±1.9 %	±1.9 %	∞
3	Hemispherical isotropy error	±9.6 %	Rectangular	√3	0	0	0 %	0 %	∞
4	Probe linearity	±4.7 %	Rectangular	√3	1	1	±2.7 %	±2.7 %	∞
5	Probe modulation response (CW)	±0.0 %	Rectangular	√3	1	1	0 %	0 %	∞
6	System detection limit	±1.0 %	Rectangular	√3	1	1	±0.6 %	±0.6 %	∞
7	Boundary effects	±4.8 %	Rectangular	√3	1	1	±2.8 %	±2.8 %	∞
8	System readout electronics (DAE)	±0.3 %	Normal	1	1	1	±0.3 %	±0.3 %	∞
9	Response Time Error (<5ms/100ms wait)	±0.0 %	Rectangular	√3	1	1	0 %	0 %	∞
10	Integration Time Error (CW)	±0.0 %	Rectangular	√3	1	1	0 %	0 %	∞
11	RF ambient conditions-noise	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
12	RF ambient conditions-reflections	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
13	Probe positioner mechanical tolerance	±3.3 %	Rectangular	√3	1	1	±1.9 %	±1.9 %	∞
14	Probe positioning with respect to phantom shell	±6.7 %	Rectangular	√3	1	1	±3.9 %	±3.9 %	∞
15	Max. SAR evaluation (Post-processing)	±4.0 %	Rectangular	√3	1	1	±2.3 %	±2.3 %	∞
B	Test Sample Related								
16	Deviation of the experimental source	±3.5 %	Normal	1	1	1	±3.5 %	±3.5 %	∞
17	Dipole to liquid distance (10mm±0.2mm, <2deg.)	±2.0 %	Rectangular	√3	1	1	±1.2 %	±1.2 %	∞
18	Drift of output power (measured, <0.2dB)	±2.3 %	Rectangular	√3	1	1	±1.3 %	±1.3 %	∞
C	Phantom and Setup								
19	Phantom uncertainty	±2.0 %	Rectangular	√3	1	1	±1.2 %	±1.2 %	∞
20	Algorithm for correcting SAR (ε,σ: ≤5%)	±1.2 %	Normal	1	1	0.84	±1.2 %	±0.97 %	∞
21	Liquid conductivity (meas.) (DAK3.5)	±3.0 %	Normal	1	0.78	0.71	±2.3 %	±2.1 %	∞
22	Liquid permittivity (meas.) (DAK3.5)	±3.1 %	Normal	1	0.23	0.26	±0.7 %	±0.8 %	∞
23	Liquid Conductivity-temp.uncertainty (≤2deg.C.)	±5.3 %	Rectangular	√3	0.78	0.71	±2.4 %	±2.2 %	∞
24	Liquid Permittivity-temp.uncertainty (≤2deg.C.)	±0.9 %	Rectangular	√3	0.23	0.26	±0.1 %	±0.1 %	∞
	Combined Standard Uncertainty						±11.0 %	±10.9 %	
	Expanded Uncertainty (k=2)						±22.1 %	±21.8 %	

*. This measurement uncertainty budget is suggested by IEEE Std. 1528(2013) and determined by Schmid & Partner Engineering AG (DASY5 Uncertainty Budget).

Appendix 3-8: Calibration certificate: E-Field Probe (EX3DV4)

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **UL Japan (Vitec)**

Certificate No: **EX3-3907_May18**

CALIBRATION CERTIFICATE

Object: **EX3DV4 - SN:3907**

Calibration procedure(s): **QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6
Calibration procedure for dosimetric E-field probes**

Calibration date: **May 15, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-18 (No. 217-02682)	Apr-19
Reference Probe ES3DV2	SN: 3013	30-Dec-17 (No. ES3-3013_Dec17)	Dec-18
DAE4	SN: 660	21-Dec-17 (No. DAE4-660_Dec17)	Dec-18
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
RF generator HP B648C	SN: US3642U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

Calibrated by: **Claudio Leubler** (Name), **Laboratory Technician** (Function), *[Signature]* (Signature)

Approved by: **Katja Pokovic** (Name), **Technical Manager** (Function), *[Signature]* (Signature)

Issued: May 15, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Appendix 3-8: Calibration certificate: E-Field Probe (EX3DV4) (cont'd)

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Appendix 3-8: Calibration certificate: E-Field Probe (EX3DV4) (cont'd)

EX3DV4 – SN:3907

May 15, 2018

Probe EX3DV4

SN:3907

Manufactured: September 4, 2012

Calibrated: May 15, 2018

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)

Appendix 3-8: Calibration certificate: E-Field Probe (EX3DV4) (cont'd)

EX3DV4- SN:3907

May 15, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3907**Basic Calibration Parameters**

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.45	0.58	0.54	$\pm 10.1 \%$
DCP (mV) ^B	104.8	98.0	99.2	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	132.5	$\pm 3.8 \%$
		Y	0.0	0.0	1.0		131.4	
		Z	0.0	0.0	1.0		144.8	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Appendix 3-8: Calibration certificate: E-Field Probe (EX3DV4) (cont'd)

EX3DV4- SN:3907

May 15, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3907**Calibration Parameter Determined in Head Tissue Simulating Media**

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
2450	39.2	1.80	7.31	7.31	7.31	0.36	0.80	± 12.0 %
5200	36.0	4.66	5.31	5.31	5.31	0.35	1.80	± 13.1 %
5250	35.9	4.71	5.16	5.16	5.16	0.35	1.80	± 13.1 %
5500	35.6	4.96	4.73	4.73	4.73	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.49	4.49	4.49	0.40	1.80	± 13.1 %
5750	35.4	5.22	4.70	4.70	4.70	0.40	1.80	± 13.1 %
5800	35.3	5.27	4.69	4.69	4.69	0.40	1.80	± 13.1 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Appendix 3-8: Calibration certificate: E-Field Probe (EX3DV4) (cont'd)

EX3DV4- SN:3907

May 15, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3907**Calibration Parameter Determined in Body Tissue Simulating Media**

f (MHz) ^c	Relative Permittivity ^f	Conductivity (S/m) ^f	ConvF X	ConvF Y	ConvF Z	Alpha ^g	Depth ^g (mm)	Unc (k=2)
2450	52.7	1.95	7.32	7.32	7.32	0.34	0.84	± 12.0 %
5250	48.9	5.36	4.49	4.49	4.49	0.45	1.90	± 13.1 %
5600	48.5	5.77	3.92	3.92	3.92	0.40	1.90	± 13.1 %
5750	48.3	5.94	4.00	4.00	4.00	0.45	1.90	± 13.1 %

^c Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 126, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^f At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.


^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Appendix 3-8: Calibration certificate: E-Field Probe (EX3DV4) (cont'd)

EX3DV4- SN:3907

May 15, 2018

Frequency Response of E-Field
(TEM-Cell: ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)


Appendix 3-8: Calibration certificate: E-Field Probe (EX3DV4) (cont'd)

EX3DV4- SN:3907



May 15, 2018

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM



f=1800 MHz,R22





Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)

Appendix 3-8: Calibration certificate: E-Field Probe (EX3DV4) (cont'd)

EX3DV4- SN:3907

May 15, 2018

Dynamic Range f(SAR_{head}) (TEM cell, f_{eval}= 1900 MHz)




Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Appendix 3-8: Calibration certificate: E-Field Probe (EX3DV4) (cont'd)

EX3DV4- SN:3907


May 15, 2018

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), f = 900 MHz



Appendix 3-8: Calibration certificate: E-Field Probe (EX3DV4) (cont'd)

EX3DV4- SN:3907

May 15, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3907**Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	39.9
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

Appendix 3-9: Calibration certificate: Dipole (D2450V2)

**Calibration Laboratory of
 Schmid & Partner
 Engineering AG**
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **VGEL**

Certificate No: **D2450V2-765_May18**

CALIBRATION CERTIFICATE			
Object	D2450V2 - SN:765		
Calibration procedure(s)	QA CAL-05.v10 Calibration procedure for dipole validation kits above 700 MHz		
Calibration date:	May 16, 2018		
<p>This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.</p> <p>All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.</p> <p>Calibration Equipment used (M&TE critical for calibration)</p>			
Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-18 (No. 217-02682)	Apr-19
Type-N mismatch combination	SN: 5047.2 / 06327	04-Apr-18 (No. 217-02683)	Apr-19
Reference Probe EX3DV4	SN: 7349	30-Dec-17 (No. EX3-7349_Dec17)	Dec-18
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18
Calibrated by:	Name Menu Seitz	Function Laboratory Technician	Signature
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature
			Issued: May 17, 2018
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			

Appendix 3-9: Calibration certificate: Dipole (D2450V2) (cont'd)

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Appendix 3-9: Calibration certificate: Dipole (D2450V2) (cont'd)**Measurement Conditions**

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.1
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	38.2 ± 6 %	1.85 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.1 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	51.4 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.04 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.9 W/kg ± 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	52.3 ± 6 %	1.99 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.6 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	49.8 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.84 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.2 W/kg ± 16.5 % (k=2)

Appendix 3-9: Calibration certificate: Dipole (D2450V2) (cont'd)**Appendix (Additional assessments outside the scope of SCS 0108)****Antenna Parameters with Head TSL**

Impedance, transformed to feed point	54.8 Ω + 6.0 j Ω
Return Loss	- 22.7 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	50.3 Ω + 6.9 j Ω
Return Loss	- 23.2 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.156 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	August 10, 2004

Appendix 3-9: Calibration certificate: Dipole (D2450V2) (cont'd)

DASY5 Validation Report for Head TSL

Date: 16.05.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:765

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.85$ S/m; $\epsilon_r = 38.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.88, 7.88, 7.88) @ 2450 MHz; Calibrated: 30.12.2017
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.1(1476); SEMCAD X 14.6.11(7439)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 115.3 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 26.1 W/kg

SAR(1 g) = 13.1 W/kg; SAR(10 g) = 6.04 W/kg


Maximum value of SAR (measured) = 21.6 W/kg



0 dB = 21.6 W/kg = 13.34 dBW/kg

Appendix 3-9: Calibration certificate: Dipole (D2450V2) (cont'd)

Impedance Measurement Plot for Head TSL



Appendix 3-9: Calibration certificate: Dipole (D2450V2) (cont'd)**DASY5 Validation Report for Body TSL**

Date: 16.05.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:765

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.99$ S/m; $\epsilon_r = 52.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.01, 8.01, 8.01) @ 2450 MHz; Calibrated: 30.12.2017
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.1(1476); SEMCAD X 14.6.11(7439)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 107.3 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 25.2 W/kg

SAR(1 g) = 12.6 W/kg; SAR(10 g) = 5.84 W/kg


Maximum value of SAR (measured) = 20.6 W/kg



0 dB = 20.6 W/kg = 13.14 dBW/kg

Appendix 3-9: Calibration certificate: Dipole (D2450V2) (cont'd)

Impedance Measurement Plot for Body TSL



Appendix 3-10: Calibration certificate: Dipole (D5GHzV2)

**Calibration Laboratory of
 Schmid & Partner
 Engineering AG**
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **UL Japan Shonan (Vitec)**

Certificate No: **D5GHzV2-1070_Mar18**

CALIBRATION CERTIFICATE																																																											
Object	D5GHzV2 - SN:1070																																																										
Calibration procedure(s)	QA CAL-22.v2 Calibration procedure for dipole validation kits between 3-6 GHz																																																										
Calibration date:	March 01, 2018																																																										
<p>This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.</p> <p>All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.</p> <p>Calibration Equipment used (M&TE critical for calibration)</p> <table border="1"> <thead> <tr> <th>Primary Standards</th> <th>ID #</th> <th>Cal Date (Certificate No.)</th> <th>Scheduled Calibration</th> </tr> </thead> <tbody> <tr> <td>Power meter NRP</td> <td>SN: 104778</td> <td>04-Apr-17 (No. 217-02521/02522)</td> <td>Apr-18</td> </tr> <tr> <td>Power sensor NRP-Z91</td> <td>SN: 103244</td> <td>04-Apr-17 (No. 217-02521)</td> <td>Apr-18</td> </tr> <tr> <td>Power sensor NRP-Z91</td> <td>SN: 103245</td> <td>04-Apr-17 (No. 217-02522)</td> <td>Apr-18</td> </tr> <tr> <td>Reference 20 dB Attenuator</td> <td>SN: 5058 (20k)</td> <td>07-Apr-17 (No. 217-02528)</td> <td>Apr-18</td> </tr> <tr> <td>Type-N mismatch combination</td> <td>SN: 5047.2 / 06327</td> <td>07-Apr-17 (No. 217-02529)</td> <td>Apr-18</td> </tr> <tr> <td>Reference Probe EX3DV4</td> <td>SN: 3503</td> <td>30-Dec-17 (No. EX3-3503_Dec17)</td> <td>Dec-18</td> </tr> <tr> <td>DAE4</td> <td>SN: 601</td> <td>26-Oct-17 (No. DAE4-601_Oct17)</td> <td>Oct-18</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Secondary Standards</th> <th>ID #</th> <th>Check Date (in house)</th> <th>Scheduled Check</th> </tr> </thead> <tbody> <tr> <td>Power meter EPM-442A</td> <td>SN: GB37480704</td> <td>07-Oct-15 (in house check Oct-16)</td> <td>In house check: Oct-18</td> </tr> <tr> <td>Power sensor HP 8481A</td> <td>SN: US37292783</td> <td>07-Oct-15 (in house check Oct-16)</td> <td>In house check: Oct-18</td> </tr> <tr> <td>Power sensor HP 8481A</td> <td>SN: MY41092317</td> <td>07-Oct-15 (in house check Oct-16)</td> <td>In house check: Oct-18</td> </tr> <tr> <td>RF generator R&S SMT-06</td> <td>SN: 100972</td> <td>15-Jun-15 (in house check Oct-16)</td> <td>In house check: Oct-18</td> </tr> <tr> <td>Network Analyzer HP 8753E</td> <td>SN: US37390585</td> <td>18-Oct-01 (in house check Oct-17)</td> <td>In house check: Oct-18</td> </tr> </tbody> </table>				Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration	Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18	Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18	Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18	Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18	Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18	Reference Probe EX3DV4	SN: 3503	30-Dec-17 (No. EX3-3503_Dec17)	Dec-18	DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18	Secondary Standards	ID #	Check Date (in house)	Scheduled Check	Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18	Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18	Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18	RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18	Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18
Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration																																																								
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18																																																								
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18																																																								
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18																																																								
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18																																																								
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18																																																								
Reference Probe EX3DV4	SN: 3503	30-Dec-17 (No. EX3-3503_Dec17)	Dec-18																																																								
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18																																																								
Secondary Standards	ID #	Check Date (in house)	Scheduled Check																																																								
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18																																																								
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18																																																								
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18																																																								
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18																																																								
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18																																																								
Calibrated by:	Name Jeton Kastrati	Function Laboratory Technician	Signature 																																																								
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature 																																																								
			Issued: March 5, 2018																																																								
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.																																																											

Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)

Calibration Laboratory of
Schmid & Partner
Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL tissue simulating liquid
 ConvF sensitivity in TSL / NORM x,y,z
 N/A not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)**Measurement Conditions**

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with UL Spacer
Zoom Scan Resolution	dx, dy = 4.0 mm, dz = 1.4 mm	Graded Ratio = 1.4 (Z direction)
Frequency	5200 MHz ± 1 MHz 5250 MHz ± 1 MHz 5500 MHz ± 1 MHz 5600 MHz ± 1 MHz 5750 MHz ± 1 MHz 5800 MHz ± 1 MHz	

Head TSL parameters at 5200 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	36.0	4.66 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	36.4 ± 6 %	4.53 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5200 MHz

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	7.89 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	79.0 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.26 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	22.6 W/kg ± 19.5 % (k=2)

Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)**Head TSL parameters at 5250 MHz**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.9	4.71 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	36.3 ± 6 %	4.59 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5250 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.07 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	80.8 W / kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.32 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.2 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5500 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.6	4.96 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	36.0 ± 6 %	4.84 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5500 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.36 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	83.7 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.37 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.7 W/kg ± 19.5 % (k=2)

Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)**Head TSL parameters at 5600 MHz**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.5	5.07 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.8 ± 6 %	4.95 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.43 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	84.3 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.41 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.1 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5750 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.4	5.22 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.6 ± 6 %	5.10 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5750 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.07 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	80.7 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.29 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	22.9 W/kg ± 19.5 % (k=2)

Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)**Head TSL parameters at 5800 MHz**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.3	5.27 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.5 ± 6 %	5.16 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5800 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.13 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	81.3 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.31 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.1 W/kg ± 19.5 % (k=2)

Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)**Body TSL parameters at 5250 MHz**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.9	5.36 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	47.4 ± 6 %	5.48 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5250 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.58 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	75.4 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.11 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.0 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.5	5.77 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.8 ± 6 %	5.95 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.91 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	78.6 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.21 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.9 W/kg ± 19.5 % (k=2)

Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)**Body TSL parameters at 5750 MHz**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.3	5.94 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.5 ± 6 %	6.15 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5750 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.51 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	74.6 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.08 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.6 W/kg ± 19.5 % (k=2)

Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)**Appendix (Additional assessments outside the scope of SCS 0108)****Antenna Parameters with Head TSL at 5200 MHz**

Impedance, transformed to feed point	50.2 Ω - 13.3 j Ω
Return Loss	- 17.6 dB

Antenna Parameters with Head TSL at 5250 MHz

Impedance, transformed to feed point	51.5 Ω - 8.5 j Ω
Return Loss	- 21.5 dB

Antenna Parameters with Head TSL at 5500 MHz

Impedance, transformed to feed point	47.8 Ω - 8.0 j Ω
Return Loss	- 21.5 dB

Antenna Parameters with Head TSL at 5600 MHz

Impedance, transformed to feed point	56.9 Ω - 8.1 j Ω
Return Loss	- 20.1 dB

Antenna Parameters with Head TSL at 5750 MHz

Impedance, transformed to feed point	55.6 Ω - 1.8 j Ω
Return Loss	- 25.1 dB

Antenna Parameters with Head TSL at 5800 MHz

Impedance, transformed to feed point	53.8 Ω - 2.9 j Ω
Return Loss	- 26.8 dB

Antenna Parameters with Body TSL at 5250 MHz

Impedance, transformed to feed point	51.9 Ω - 7.1 j Ω
Return Loss	- 22.9 dB

Antenna Parameters with Body TSL at 5600 MHz

Impedance, transformed to feed point	58.2 Ω - 6.3 j Ω
Return Loss	- 20.4 dB

Antenna Parameters with Body TSL at 5750 MHz

Impedance, transformed to feed point	56.8 Ω - 1.2 j Ω
Return Loss	- 23.8 dB

Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)**General Antenna Parameters and Design**

Electrical Delay (one direction)	1.202 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	September 26, 2008

Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)**DASY5 Validation Report for Head TSL**

Date: 01.03.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1070

Communication System: UID 0 - CW; Frequency: 5200 MHz, Frequency: 5250 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz, Frequency: 5800 MHz

Medium parameters used: $f = 5200$ MHz; $\sigma = 4.53$ S/m; $\epsilon_r = 36.4$; $\rho = 1000$ kg/m³,Medium parameters used: $f = 5250$ MHz; $\sigma = 4.59$ S/m; $\epsilon_r = 36.3$; $\rho = 1000$ kg/m³,Medium parameters used: $f = 5500$ MHz; $\sigma = 4.84$ S/m; $\epsilon_r = 36$; $\rho = 1000$ kg/m³,Medium parameters used: $f = 5600$ MHz; $\sigma = 4.95$ S/m; $\epsilon_r = 35.8$; $\rho = 1000$ kg/m³,Medium parameters used: $f = 5750$ MHz; $\sigma = 5.1$ S/m; $\epsilon_r = 35.6$; $\rho = 1000$ kg/m³,Medium parameters used: $f = 5800$ MHz; $\sigma = 5.16$ S/m; $\epsilon_r = 35.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.75, 5.75, 5.75); Calibrated: 30.12.2017, ConvF(5.51, 5.51, 5.51); Calibrated: 30.12.2017, ConvF(5.2, 5.2, 5.2); Calibrated: 30.12.2017, ConvF(5.05, 5.05, 5.05); Calibrated: 30.12.2017, ConvF(4.98, 4.98, 4.98); Calibrated: 30.12.2017, ConvF(4.96, 4.96, 4.96); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 69.64 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 28.6 W/kg

SAR(1 g) = 7.89 W/kg; SAR(10 g) = 2.26 W/kg

Maximum value of SAR (measured) = 18.1 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 71.02 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 28.5 W/kg

SAR(1 g) = 8.07 W/kg; SAR(10 g) = 2.32 W/kg

Maximum value of SAR (measured) = 18.4 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 70.02 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 33.1 W/kg

SAR(1 g) = 8.36 W/kg; SAR(10 g) = 2.37 W/kg

Maximum value of SAR (measured) = 20.0 W/kg

Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 70.30 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 32.6 W/kg

SAR(1 g) = 8.43 W/kg; SAR(10 g) = 2.41 W/kg

Maximum value of SAR (measured) = 19.8 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 68.89 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 31.9 W/kg

SAR(1 g) = 8.07 W/kg; SAR(10 g) = 2.29 W/kg

Maximum value of SAR (measured) = 19.4 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:


Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 69.04 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 32.5 W/kg

SAR(1 g) = 8.13 W/kg; SAR(10 g) = 2.31 W/kg


Maximum value of SAR (measured) = 19.6 W/kg



0 dB = 19.6 W/kg = 12.92 dBW/kg


Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)

Impedance Measurement Plot for Head TSL (5200, 5600, 5800)



Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)

Impedance Measurement Plot for Head TSL (5250, 5500, 5750)



Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)**DASY5 Validation Report for Body TSL**

Date: 01.03.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1070

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz

Medium parameters used: $f = 5250$ MHz; $\sigma = 5.48$ S/m; $\epsilon_r = 47.4$; $\rho = 1000$ kg/m³,Medium parameters used: $f = 5600$ MHz; $\sigma = 5.95$ S/m; $\epsilon_r = 46.8$; $\rho = 1000$ kg/m³,Medium parameters used: $f = 5750$ MHz; $\sigma = 6.15$ S/m; $\epsilon_r = 46.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.26, 5.26, 5.26); Calibrated: 30.12.2017, ConvF(4.65, 4.65, 4.65); Calibrated: 30.12.2017, ConvF(4.57, 4.57, 4.57); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan,**dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.71 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 29.4 W/kg

SAR(1 g) = 7.58 W/kg; SAR(10 g) = 2.11 W/kg

Maximum value of SAR (measured) = 17.4 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan,**dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.78 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 33.5 W/kg

SAR(1 g) = 7.91 W/kg; SAR(10 g) = 2.21 W/kg

Maximum value of SAR (measured) = 18.9 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan,**dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm


Reference Value = 63.92 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 32.6 W/kg

SAR(1 g) = 7.51 W/kg; SAR(10 g) = 2.08 W/kg

Maximum value of SAR (measured) = 18.1 W/kg

Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)



Appendix 3-10: Calibration certificate: Dipole (D5GHzV2) (cont'd)

Impedance Measurement Plot for Body TSL

