



September 18, 2014

UL Japan, Inc.  
1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

FCC ID: BKEKTR001

To whom it may concern,

We, UL Japan, Inc., hereby declare that Portable Game Machine with Wireless LAN, model : KTR-001 (FCC ID: BKEKTR001) of NINTENDO CO., LTD. is exempt from RF exposure SAR evaluation as its output power meets the exclusion limits stated in FCC Part 2 §2.1093.

KDB 447498D01(v05r02) has the following exclusion for portable devices:

The 1g and 10g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\frac{[(\text{maximum average output power with tolerance (mW)})/(\text{Minimum separation distance(mm)})] \cdot \sqrt{f \text{ (GHz)}}}{\leq 3.0 \text{ for 1g SAR and } \leq 7.5 \text{ for 10g extremity SAR where}}$$

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

This device  $f = 2.48$  GHz, distance = 5mm (minimum separation distance: 5 mm was used in the calculation) and the maximum average output power with tolerance was 5 mW

So for this device:

$5 \text{ mW} [\text{maximum average output power with tolerance}] / 5 \text{ mm} [\text{minimum separation distance}] * (\sqrt{2.48}) = 1.6$

\*This is less than 3.0, so no SAR is required.

Thank you for your attention to this matter.

---

Toyokazu Imamura  
Leader  
Consumer Technology Division  
UL Japan, Inc.

---

**UL Japan, Inc.**  
**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN  
Telephone: +81 463 50 6400  
Facsimile: +81 463 50 6401