



# RF Exposure Evaluation Report

**Equipment** : WirelessHD Transmitter  
**Brand Name** : EPSON  
**Model No.** : WiT4-G0  
**FCC ID** : BKMAE-WIT4G0  
**Standard** : 47 CFR Part 2.1091  
**Applicant** : SEIKO EPSON CORPORATION  
3-3-5 Owa Suwa-shi Nagano-Ken 392-8502, Japan  
**Manufacturer** : SEIKO EPSON CORPORATION Toyoshina office  
6925 Tazawa, Toyoshina Azumino-shi, Nagano  
399-8285 Japan

The product sample received on Dec. 04, 2015 and completely tested on Jan. 13, 2016. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

  
Sam Chen  
SPORTON INTERNATIONAL INC.





## TABLE OF CONTENTS

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>4</b>
1.1	EUT General Information .....	4
1.2	Testing Location .....	4
<b>2</b>	<b>MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>5</b>
2.1	Limit of Maximum Permissible Exposure .....	5
2.2	MPE Calculation Method .....	5
2.3	Calculated Result and Limit.....	6





# 1 General Description

## 1.1 EUT General Information

The Channel Plan(s)	
Low-rate PHY (LRP) Band	Channel 2 LRP: 60.16275-60.79725 GHz Channel 3 LRP: 62.32275-62.95725 GHz
High-rate PHY (HRP) Band	Channel 2 HRP: 60.48 GHz Channel 3 HRP: 62.64 GHz

## 1.2 Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



### 2.3 Calculated Result and Limit

<b>Exposure Environment</b>	General Population / Uncontrolled Exposure					
<b>Temp</b>	20.5°C		<b>Humidity</b>	32%		
<b>Test Engineer</b>	Owen Hsu		<b>Test Date</b>	Dec. 21, 2015		
<b>Test results</b>						
<b>Maximum EIPR Power of Test Frequency (GHz)</b>	<b>Average EIRP Power (dBm)</b>	<b>Average EIRP Power (mW)</b>	<b>Power Density (S) (mW/cm<sup>2</sup>)</b>	<b>Separation Distance (cm)</b>	<b>Limit of Power Density (S) (mW/cm<sup>2</sup>)</b>	
<b>LRP 60.7925 GHz</b>	22.41	174.35	0.035	20	1.00	
<b>HRP 60.48 GHz</b>	30.60	1148.34	0.229	20	1.00	