

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen,
Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594

Email: sgs_internet_operations@sgs.com

Report No.: SZEM110600158902

Page: 1 of 3

RF Exposure Evaluation declaration

Application No.: SZEM1106001589RF
Applicant: Philips Consumer Lifestyle
Address of Applicant: 3029 East Governor John Sevier Hwy. Knoxville, Tennessee37914, United States
Manufacturer: Philips Electronics Hong Kong Ltd.
Address of Manufacturer: 5/F., Philips Electronics Building 5 Science Park East Avenue, Hong Kong Science Park, Shatin, New Territories, Hong Kong
Factory:
1.ACTION ASIA(SHENZHEN)CO LTD
2.Philips Ltd. Assembly Centre Hungary
3.Dixon Technologies(India) Pvt.Ltd.
4.PHILIPS DO BRASIL LTDA CNPJ: 61.086.336/0018-51
5.Fabrica Austral de Productos Electricos Sociedad Anonima (FAPESA)
6.Action Industries (M) Sdn Bhd (Company No : 166780-H)
Address of Factory:
1.Dede Industrial Park Jianan Rd, FuyongHI- tech Park, Fuyong Town, Bao'an District, Shenzhen, China
2.Szekesfehervar, Holland fasor 6, H-8000 Hungary
3.Khasra No.1050, Central Hope Town, Industrial Area, Selaqui-248197, Dehradun(Uttarakhand) India
4. AV. TORQUATO TAPAJÓS, 2236, BAIRRO: FLORES, CEP: 69058-830, MANAUS – AM – BRAZIL
5. Islas Malvinas 1180 , Río Grande 9420, Provincia de Tierra del Fuego, Argentina
6.2480 Tingkat Perusahaan Enam, Prai Free Trade Zone, 13600 Perai, Penang, Malaysia
FCC ID: BOUBDP3406
Fundamental Carrier Frequency: 2412MHz~2462MHz
Equipment Under Test (EUT):
Name: 2.4 Wifi DVD PLAYER
Model: BDP3406
Date of Receipt: 2011-06-27
Date of Test: 2011-06-28 to 2011-08-09
Date of Issue: 2011-08-15

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 RF Exposure Evaluation

2.1 Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	300

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

2.3 Test Result of RF Exposure Evaluation

Product : Bluetooth hands-free system

Test Item : RF Exposure Evaluation

Test Site : No.3 OATS

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
Lowest	2412	22.95	197.2423	0.03924

The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.