

#### \* RF Exposure

#### 1. Regulation

According to \$15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See \$1.1307(b)(1) of this Chapter.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm <sup>2</sup> ]	Averaging Time [minute]			
Limits for General Population / Uncontrolled Exposure							
0.3 ~ 1.34	614	1.63	*(100)	30			
1.34 ~ 30	824/f	2.19/f	*(180/f <sup>2</sup> )	30			
30 ~ 300	27.5	0.073	0.2	30			
300 ~ 1 500	/	/	f/1 500	30			
1 500 ~ 15 000	/	/	1.0	30			

Limits for Maximum Permissive Exposure: RF exposure is calculated.

*f=frequency in Mb*; \*= *plane-wave equivalent power density* 

#### MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01  $S = PG/4\pi R^2 \quad \left(\Rightarrow R = \sqrt{PG/4\pi S}\right)$ 

S = PO/(4)aR ( $\implies R = \sqrt{2}$ S = power density [mW/cm<sup>2</sup>]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]



### 2. RF Exposure Compliance Issue

The information should be included in the user's manual: This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

## 3. Calculation Result of RF Exposure

Mode	Target power [dBm]	Tune up tolerance [dB]	Max tune up power [dBm]	Max tune up power [nW]	Ant Gain [dBi]	Ant Gain	Power Density at 20 cm [mW/cm <sup>*</sup> ]	Limit [mW/cm²]
Bluetooth_GFSK	3.5	±2.0	5.5	3.55	1.99	1.58	0.001 12	1.000 00
Total							0.001 12	1.000 00

# 4. Target power and tolerance, Max tuneup power

Mode	Target power [dBm]	Tolerance [dB]	Max tuneup power [dBm]	Average Power [dBm]
Bluetooth_GFSK Lowest	3.5	±2.0	5.5	3.87
Bluetooth_GFSK Middle	3.5	±2.0	5.5	4.29
Bluetooth_GFSK Highest	3.5	±2.0	5.5	4.76
Bluetooth_8DPSK Lowest	0.0	±2.0	2.0	0.08
Bluetooth_8DPSK Middle	0.0	±2.0	2.0	0.41
Bluetooth_8DPSK Highest	0.0	±2.0	2.0	0.87