FCC ID: BPO-DAGE-DA988

WLAN(Portable device)

According to § 15.247(e)(i)and § 1.1307(b)(1),systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. According to KDB 447498(2)(a)(i)

| Frequency Range | | Center | 60/f SAR |
|--------------------|---------------------|--------------------|----------------|
| Low Frequency(MHz) | High Frequency(MHz) | frequency (MHz) | Limitation(mw) |
| 2412 | 2462 | 2442 | 25 |

Maximum measured transmitter power:802.11b

| Conducted Power(dBm) | Max Antenna Gain (dBi) | EIRP(mw) |
|----------------------|------------------------|----------|
| 9.97 | 2.0 | 15.74 |

Maximum measured transmitter power:802.11g

| Conducted Power(dBm) | Max Antenna Gain (dBi) | EIRP(mw) |
|----------------------|------------------------|----------|
| 8.78 | 2.0 | 11.97 |

Maximum measured transmitter power:802.11n HT20

| Conducted Power(dBm) | Max Antenna Gain (dBi) | EIRP(mw) |
|----------------------|------------------------|----------|
| 7.84 | 2.0 | 9.64 |

Maximum measured transmitter power:802.11n HT40

| Conducted Power(dBm) | Max Antenna Gain (dBi) | EIRP(mw) |
|----------------------|------------------------|----------|
| 6.786 | 2.0 | 7.56 |

Threshold at which no SAR required is 25 mw.

Maximum Tx power is 15.74mw EIRP.

Conclusion: No SAR is required.