



6. ATTACHMENT I-TECHNICAL DESCRIPTION OF EUT

SPECIFICATIONS:

* Picture Tube	17" (16" diagonal viewable image) flat square tube (FST) with enhanced contrast, dark-tinted CRT, invar shadow mask, advanced anti-reflection, anti-glare, and anti-static coating with low electromagnetic field.
* Dot Pitch	0.28mm
* Rec. Resolution	1280 x 1024@ 60 Hz, 1024 x 768@ 85Hz
* Deflection Frequency	
Horizontal:	30 to 69 KHz
Vertical:	50 to 160 Hz
* Max. Video Input Bandwidth	108 MHz
* Display Area	
Factory Setting:	approx. 300 mm x 225 mm
Active Area:	approx. 320 mm x 240 mm
* Input Signals	
Video:	Analog 0.7 V
Sync:	Digital 3.3 V
* Input Connector	15-pin D-sub Type
* Display Colors	Analog input, unlimited colors
* Power Source	90 - 264 Vac (Universal)
* Power Consumption	125 watts (max.)
* Power Management	EPA/ Energy Star VESA DPMS signaling method
* PnP Compatibility	VESA DDC 1 & 2B standards compliant
* USB hub (Option)	Locally powered hub with 4 downstream ports and 1 upstream port. (+5V, 2Amps. max.; 0.5 Amps. each port) Monitor control class
* Multimedia	Speakers 3W x 2; response: 70Hz - 20KHz Built-in microphone; response: 300Hz - 4 KHz
* Front Panel Controls	Contrast, Brightness, Function key, ∨ (Decrease), ∧ (Increase), Speaker Mute, Surround, Volume, Tone, POWER
* EasyScreen™	H-Size, H-Position, V-Size, V-Position, Pincushion, Tilt, Trapezoid, Moire, Color Adjustment, Management (Power Saver, Display Mode), Language, Degauss and Factory Reset, Pin-balance, Parallelogram, Corner, V-Linearity, H-linearity
* Monitor Dimension	415 mm (W) x 415 mm (H) x 452 mm (D)
* Net Weight	16 kg
* Ambient Temperature	
Operating:	0°C ~ 40°C
Storage:	-20°C ~ -65°C
* Humidity	
Operating	20% ~ 95%
Storage	10% ~ 95%