

TEST REPORT

Reference No...... : WTF22D04074006W001
FCC ID : BRWSPMR20500
Applicant..... : Horizon Hobby, LLC.
Address..... : 2904 Research Rd., Champaign, IL, 61822 United States
Manufacturer : Horizon Hobby, LLC.
Address..... : 2904 Research Rd., Champaign, IL, 61822 United States
Product..... : NX20 20 Channel Transmitter
Model(s). : SPMR20500, SPMR205001(alternate stickconfig),
SPMR20500EU (EU only version), SPMR20500 Regular US,
SPMR20500EU EU Version
Standards..... : FCC CFR47 Part 15.247
Date of Receipt sample : 2022-04-20
Date of Test : 2022-04-20 to 2022-07-18
Date of Issue..... : 2022-08-30
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:
Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China
Tel: +86-769-2267 6998
Fax: +86-769-2267 6828

Compiled by:

James Cheng

James Cheng / Project Engineer

Approved by:

Deval Qin

Deval Qin / Designated Reviewer

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS.....	2
3 REVISION HISTORY.....	4
4 GENERAL INFORMATION.....	5
4.1 GENERAL DESCRIPTION OF E.U.T.....	5
4.2 DETAILS OF E.U.T.....	5
4.3 CHANNEL LIST.....	5
4.4 TEST MODE.....	5
4.5 TEST FACILITY.....	7
5 TEST SUMMARY.....	8
6 EQUIPMENT USED DURING TEST.....	9
6.1 EQUIPMENTS LIST.....	9
6.2 DESCRIPTION OF SUPPORT UNITS.....	10
6.3 MEASUREMENT UNCERTAINTY.....	10
6.4 TEST EQUIPMENT CALIBRATION.....	10
7 CONDUCTED EMISSION.....	11
7.1 E.U.T. OPERATION.....	11
7.2 EUT SETUP.....	11
7.3 MEASUREMENT DESCRIPTION.....	12
7.4 CONDUCTED EMISSION TEST RESULT.....	12
8 RADIATED EMISSIONS.....	14
8.1 EUT OPERATION.....	14
8.2 TEST SETUP.....	15
8.3 SPECTRUM ANALYZER SETUP.....	16
8.4 TEST PROCEDURE.....	17
8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	17
8.6 SUMMARY OF TEST RESULTS.....	18
9 CONDUCTED SPURIOUS EMISSIONS.....	28
9.1 TEST PROCEDURE.....	28
9.2 TEST RESULT.....	29
10 BAND EDGE MEASUREMENT.....	38
10.1 TEST PROCEDURE.....	38
10.2 TEST RESULT.....	39
11 6 DB BANDWIDTH AND 99% BANDWIDTH MEASUREMENT.....	42
11.1 TEST PROCEDURE:.....	42
11.2 TEST RESULT:.....	42
12 MAXIMUM PEAK OUTPUT POWER.....	52
12.1 TEST PROCEDURE:.....	52
12.2 TEST RESULT:.....	53
13 POWER SPECTRAL DENSITY.....	59
13.1 TEST PROCEDURE:.....	59
13.2 TEST RESULT:.....	59
14 ANTENNA REQUIREMENT.....	65

15	RF EXPOSURE	66
16	PHOTOGRAPHS OF TEST SETUP AND EUT	66

3 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTF22D04074006W001	2022-04-20	2022-04-20 to 2022-07-18	2022-08-30	Original	-	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	NX20 20 Channel Transmitter
Model(s):	SPMR20500, SPMR205001(alternate stickconfig), SPMR20500EU (EU only version), SPMR20500 Regular US, SPMR20500EU EU Version
Model Description:	Only the model names are different for different market requirement. The test sample's model name is SPMR20500.
Wi-Fi Specification:	2.4G-802.11b/g/n HT20
Hardware Version:	Rev K
Software Version:	1.0

4.2 Details of E.U.T.

Operation Frequency:	WiFi: 802.11b/g/n HT20: 2412~2462MHz
Max. RF output power:	WiFi(2.4G): 15.63dBm
Type of Modulation:	WiFi: CCK, OFDM
Antenna installation:	WiFi: PCB printed antenna
Antenna Gain:	WiFi(2.4G): 0dBi
Ratings:	Cylindrical Li-Ion Battery 3.7V 1S 3P 10500mAh 38.85Wh

4.3 Channel List

WIFI

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

4.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
Power Spectral Density	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
6dB Bandwidth	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
Band Edge	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
Transmitter Spurious Emissions	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product .

4.5 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

5 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.247(d) 15.205(a) 15.209(a)	PASS
Conducted Spurious Emissions	15.247(d)	PASS
Conducted Emissions	15.207(a)	N/A
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3),(4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

6 Equipment Used during Test

6.1 Equipments List

3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP30	100091	2021-04-26 2022-04-28	2022-04-25 2023-04-27
2	Amplifier	Agilent	8447D	2944A10178	2021-04-26 2022-04-28	2022-04-25 2023-04-27
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2021-08-23	2022-08-22
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2021-04-26 2022-04-28	2022-04-25 2023-04-27
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2021-04-30 2022-04-29	2022-04-29 2023-04-28
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2021-07-30	2022-07-29
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2021-07-26	2022-07-25
8	Coaxial Cable (above 1GHz)	ZT26-NJ-NJ-8M/FA	1GHz-18GHz	NA	2021-04-26 2022-04-28	2022-04-25 2023-04-27
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2021-04-26 2022-04-28	2022-04-25 2023-04-27
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2021-04-26 2022-04-28	2022-04-25 2023-04-27
3	Active Loop Antenna	Com-Power Corp.	AL-130R	10160007	2022-05-05	2023-05-04
4	Amplifier	ANRITSU	MH648A	M43381	2021-04-26 2022-04-28	2022-04-25 2023-04-27
5	Cable	HUBER+SUHNER	CBL2	525178	2021-04-26 2022-04-28	2022-04-25 2023-04-27
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	2021-04-26 2022-04-28	2022-04-25 2023-04-27
2.	Spectrum Analyzer	R&S	FSP30	100091	2021-04-26 2022-04-28	2022-04-25 2023-04-27
3.	EXA Signal Analyzer	Malaysia Keysight	N9010A	MY50520207	2021-04-26 2022-04-28	2022-04-25 2023-04-27

6.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

6.3 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Conducted Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)
Conducted Spurious Emissions test	± 3.12 dB (9kHz~30MHz)
	± 4.21 dB (30M~1000MHz)
	± 5.14 dB (1000M~26500MHz)

6.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

7 Conducted Emission

Test Requirement: 47CFR FCC Part15 Subpart C §15.207

Test Method: ANSI C63.10:2013

Test Result: PASS

Frequency Range: 150kHz to 30MHz

Limit:

Frequency (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5.0	56	46
5.0 to 30	60	50

*Decreases with the logarithm of the frequency.

7.1 E.U.T. Operation

Operating Environment:

Temperature: 21.4 °C

Humidity: 50.7 % RH


Atmospheric Pressure: 101.6kPa

Test Voltage: AC 120V, 60Hz

EUT Operation: The test was performed in WIFI link, the worst data were shown in the report.

7.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.




7.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

7.4 Conducted Emission Test Result


Remark: only the worst data (TX 11b mode High channel mode) were reported

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1620	27.91	12.02	39.93	65.36	-25.43	QP	
2	0.1620	8.78	12.02	20.80	55.36	-34.56	AVG	
3	0.3140	20.07	11.74	31.81	59.86	-28.05	QP	
4	0.3140	6.33	11.74	18.07	49.86	-31.79	AVG	
5	0.5299	25.22	11.76	36.98	56.00	-19.02	QP	
6	0.5299	10.70	11.76	22.46	46.00	-23.54	AVG	
7	1.7060	20.49	11.90	32.39	56.00	-23.61	QP	
8	1.7060	8.18	11.90	20.08	46.00	-25.92	AVG	
9	2.8100	18.86	12.06	30.92	56.00	-25.08	QP	
10	2.8100	4.99	12.06	17.05	46.00	-28.95	AVG	
11	16.0820	19.11	11.70	30.81	60.00	-29.19	QP	
12	16.0820	8.80	11.70	20.50	50.00	-29.50	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1620	29.13	11.49	40.62	65.36	-24.74	QP	
2	0.1620	12.67	11.49	24.16	55.36	-31.20	AVG	
3	0.3060	22.69	11.24	33.93	60.08	-26.15	QP	
4	0.3060	11.72	11.24	22.96	50.08	-27.12	AVG	
5	0.4180	23.87	11.18	35.05	57.49	-22.44	QP	
6	0.4180	13.95	11.18	25.13	47.49	-22.36	AVG	
7	0.5299	30.82	11.16	41.98	56.00	-14.02	QP	
8	0.5299	21.12	11.16	32.28	46.00	-13.72	AVG	
9	0.8660	21.21	11.30	32.51	56.00	-23.49	QP	
10	0.8660	11.27	11.30	22.57	46.00	-23.43	AVG	
11	14.6300	19.89	11.51	31.40	60.00	-28.60	QP	
12	14.6300	9.41	11.51	20.92	50.00	-29.08	AVG	

8 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

8.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in WIFI link mode, the test data were shown in the report.


8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



8.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
 IF Bandwidth..... 10kHz
 Video Bandwidth..... 10kHz
 Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 100kHz
 Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 3MHz
 Detector Ave.
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 10Hz

8.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

8.6 Summary of Test Results

Wifi:

Test Frequency: 9KHz~30MHz

Remark: only the worst data (802.11b/g/n Low channel mode) were recorded.

Frequency	Measurement results dB μ V @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dB μ V/m @30m	Limits dB μ V/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
802.11b							
6.022	25.46	QP	21.84	40.00	7.30	29.54	-22.24
15.730	24.35	QP	21.35	40.00	5.70	29.54	-23.84
25.680	24.74	QP	20.67	40.00	5.41	29.54	-24.13
802.11g							
6.022	25.16	QP	21.84	40.00	7.00	29.54	-22.54
15.730	25.63	QP	21.35	40.00	6.98	29.54	-22.56
25.680	24.36	QP	20.67	40.00	5.03	29.54	-24.51
802.11n(HT20)							
6.022	25.96	QP	21.84	40.00	7.80	29.54	-21.74
15.730	25.60	QP	21.35	40.00	6.95	29.54	-22.59
25.680	24.09	QP	20.67	40.00	4.76	29.54	-24.78

Test Frequency : 30MHz ~ 8GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: Low Channel 2412MHz									
223.45	39.02	QP	137	2.0	H	-11.62	27.40	46.00	-18.60
223.45	32.22	QP	261	1.5	V	-11.62	20.60	46.00	-25.40
4824.00	46.91	PK	103	1.2	V	-1.06	45.85	74.00	-28.15
4824.00	37.77	Ave	103	1.2	V	-1.06	36.71	54.00	-17.29
7236.00	43.38	PK	240	1.9	H	1.33	44.71	74.00	-29.29
7236.00	39.03	Ave	240	1.9	H	1.33	40.36	54.00	-13.64
2327.08	46.72	PK	39	1.5	V	-13.19	33.53	74.00	-40.47
2327.08	37.01	Ave	39	1.5	V	-13.19	23.82	54.00	-30.18
2375.22	44.83	PK	57	1.9	H	-13.14	31.69	74.00	-42.31
2375.22	36.39	Ave	57	1.9	H	-13.14	23.25	54.00	-30.75
2499.76	43.34	PK	274	1.7	V	-13.08	30.26	74.00	-43.74
2499.76	36.59	Ave	274	1.7	V	-13.08	23.51	54.00	-30.49

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: Middle Channel 2437MHz									
223.45	37.75	QP	276	1.8	H	-11.62	26.13	46.00	-19.87
223.45	30.91	QP	24	1.4	V	-11.62	19.29	46.00	-26.71
4874.00	47.01	PK	321	1.1	V	-0.62	46.39	74.00	-27.61
4874.00	37.81	Ave	321	1.1	V	-0.62	37.19	54.00	-16.81
7311.00	44.73	PK	87	1.0	H	2.21	46.94	74.00	-27.06
7311.00	40.24	Ave	87	1.0	H	2.21	42.45	54.00	-11.55
2348.69	45.64	PK	9	1.0	V	-13.19	32.45	74.00	-41.55
2348.69	39.39	Ave	9	1.0	V	-13.19	26.20	54.00	-27.80
2372.55	44.51	PK	153	1.8	H	-13.14	31.37	74.00	-42.63
2372.55	37.34	Ave	153	1.8	H	-13.14	24.20	54.00	-29.80
2490.76	43.88	PK	76	1.9	V	-13.08	30.80	74.00	-43.20
2490.76	38.40	Ave	76	1.9	V	-13.08	25.32	54.00	-28.68

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: High Channel 2462MHz									
223.45	36.90	QP	264	1.0	H	-11.62	25.28	46.00	-20.72
223.45	30.81	QP	306	1.5	V	-11.62	19.19	46.00	-26.81
4924.00	46.33	PK	109	1.1	V	-0.24	46.09	74.00	-27.91
4924.00	36.75	Ave	109	1.1	V	-0.24	36.51	54.00	-17.49
7386.00	43.44	PK	111	1.9	H	2.84	46.28	74.00	-27.72
7386.00	39.34	Ave	111	1.9	H	2.84	42.18	54.00	-11.82
2328.16	45.75	PK	67	1.7	V	-13.19	32.56	74.00	-41.44
2328.16	38.46	Ave	67	1.7	V	-13.19	25.27	54.00	-28.73
2359.62	43.84	PK	185	1.4	H	-13.14	30.70	74.00	-43.30
2359.62	37.78	Ave	185	1.4	H	-13.14	24.64	54.00	-29.36
2484.80	44.14	PK	28	1.2	V	-13.08	31.06	74.00	-42.94
2484.80	36.97	Ave	28	1.2	V	-13.08	23.89	54.00	-30.11

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11g: Low Channel 2412MHz									
223.45	36.87	QP	278	1.5	H	-11.62	25.25	46.00	-20.75
223.45	31.52	QP	57	1.2	V	-11.62	19.90	46.00	-26.10
4824.00	46.57	PK	37	1.2	V	-1.06	45.51	74.00	-28.49
4824.00	37.05	Ave	37	1.2	V	-1.06	35.99	54.00	-18.01
7236.00	43.69	PK	157	1.3	H	1.33	45.02	74.00	-28.98
7236.00	38.97	Ave	157	1.3	H	1.33	40.30	54.00	-13.70
2334.67	46.56	PK	328	1.8	V	-13.19	33.37	74.00	-40.63
2334.67	39.67	Ave	328	1.8	V	-13.19	26.48	54.00	-27.52
2381.75	44.06	PK	78	1.9	H	-13.14	30.92	74.00	-43.08
2381.75	38.89	Ave	78	1.9	H	-13.14	25.75	54.00	-28.25
2498.21	44.20	PK	203	1.8	V	-13.08	31.12	74.00	-42.88
2498.21	36.78	Ave	203	1.8	V	-13.08	23.70	54.00	-30.30

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11g: Middle Channel 2437MHz									
223.45	38.23	QP	47	1.9	H	-11.62	26.61	46.00	-19.39
223.45	31.90	QP	209	1.2	V	-11.62	20.28	46.00	-25.72
4874.00	47.29	PK	253	1.5	V	-0.62	46.67	74.00	-27.33
4874.00	37.17	Ave	253	1.5	V	-0.62	36.55	54.00	-17.45
7311.00	44.00	PK	358	1.5	H	2.21	46.21	74.00	-27.79
7311.00	39.62	Ave	358	1.5	H	2.21	41.83	54.00	-12.17
2335.23	46.14	PK	90	1.1	V	-13.19	32.95	74.00	-41.05
2335.23	39.36	Ave	90	1.1	V	-13.19	26.17	54.00	-27.83
2354.25	44.87	PK	37	1.3	H	-13.14	31.73	74.00	-42.27
2354.25	36.79	Ave	37	1.3	H	-13.14	23.65	54.00	-30.35
2495.25	42.03	PK	250	1.6	V	-13.08	28.95	74.00	-45.05
2495.25	37.53	Ave	250	1.6	V	-13.08	24.45	54.00	-29.55

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11g: High Channel 2462MHz									
223.45	37.20	QP	2	1.3	H	-11.62	25.58	46.00	-20.42
223.45	32.64	QP	227	1.9	V	-11.62	21.02	46.00	-24.98
4924.00	45.92	PK	297	1.6	V	-0.24	45.68	74.00	-28.32
4924.00	36.14	Ave	297	1.6	V	-0.24	35.90	54.00	-18.10
7386.00	43.14	PK	14	1.7	H	2.84	45.98	74.00	-28.02
7386.00	41.11	Ave	14	1.7	H	2.84	43.95	54.00	-10.05
2320.21	45.43	PK	127	1.7	V	-13.19	32.24	74.00	-41.76
2320.21	38.39	Ave	127	1.7	V	-13.19	25.20	54.00	-28.80
2365.33	42.96	PK	346	1.7	H	-13.14	29.82	74.00	-44.18
2365.33	38.91	Ave	346	1.7	H	-13.14	25.77	54.00	-28.23
2487.05	42.07	PK	149	1.2	V	-13.08	28.99	74.00	-45.01
2487.05	37.37	Ave	149	1.2	V	-13.08	24.29	54.00	-29.71

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n20: Low Channel 2412MHz									
223.45	37.42	QP	122	1.1	H	-11.62	25.80	46.00	-20.20
223.45	31.63	QP	94	1.4	V	-11.62	20.01	46.00	-25.99
4824.00	46.49	PK	94	1.0	V	-1.06	45.43	74.00	-28.57
4824.00	37.25	Ave	94	1.0	V	-1.06	36.19	54.00	-17.81
7236.00	43.91	PK	146	1.0	H	1.33	45.24	74.00	-28.76
7236.00	42.22	Ave	146	1.0	H	1.33	43.55	54.00	-10.45
2310.91	47.00	PK	332	1.4	V	-13.19	33.81	74.00	-40.19
2310.91	39.40	Ave	332	1.4	V	-13.19	26.21	54.00	-27.79
2353.20	42.49	PK	40	1.8	H	-13.14	29.35	74.00	-44.65
2353.20	38.13	Ave	40	1.8	H	-13.14	24.99	54.00	-29.01
2496.31	44.87	PK	3	1.1	V	-13.08	31.79	74.00	-42.21
2496.31	36.17	Ave	3	1.1	V	-13.08	23.09	54.00	-30.91

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n20: Middle Channel 2437MHz									
223.45	38.39	QP	165	1.6	H	-11.62	26.77	46.00	-19.23
223.45	32.63	QP	84	1.6	V	-11.62	21.01	46.00	-24.99
4874.00	47.48	PK	136	1.6	V	-0.62	46.86	74.00	-27.14
4874.00	37.65	Ave	136	1.6	V	-0.62	37.03	54.00	-16.97
7311.00	43.21	PK	5	1.3	H	2.21	45.42	74.00	-28.58
7311.00	42.52	Ave	5	1.3	H	2.21	44.73	54.00	-9.27
2344.29	45.53	PK	152	1.2	V	-13.19	32.34	74.00	-41.66
2344.29	38.67	Ave	152	1.2	V	-13.19	25.48	54.00	-28.52
2377.81	43.97	PK	283	1.3	H	-13.14	30.83	74.00	-43.17
2377.81	36.36	Ave	283	1.3	H	-13.14	23.22	54.00	-30.78
2483.67	43.54	PK	176	2.0	V	-13.08	30.46	74.00	-43.54
2483.67	37.57	Ave	176	2.0	V	-13.08	24.49	54.00	-29.51

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n20: High Channel 2462MHz									
223.45	37.19	QP	145	1.6	H	-11.62	25.57	46.00	-20.43
223.45	37.67	QP	33	1.6	V	-11.62	26.05	46.00	-19.95
4924.00	41.91	PK	149	1.8	V	-0.24	41.67	74.00	-32.33
4924.00	40.02	Ave	149	1.8	V	-0.24	39.78	54.00	-14.22
7386.00	40.68	PK	244	1.2	H	2.84	43.52	74.00	-30.48
7386.00	34.86	Ave	244	1.2	H	2.84	37.70	54.00	-16.30
2334.47	46.27	PK	2	1.4	V	-13.19	33.08	74.00	-40.92
2334.47	38.76	Ave	2	1.4	V	-13.19	25.57	54.00	-28.43
2379.10	44.46	PK	33	1.0	H	-13.14	31.32	74.00	-42.68
2379.10	38.30	Ave	33	1.0	H	-13.14	25.16	54.00	-28.84
2495.47	44.46	PK	236	1.8	V	-13.08	31.38	74.00	-42.62
2495.47	36.92	Ave	236	1.8	V	-13.08	23.84	54.00	-30.16

Test Frequency: 8GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

9 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

Test Result: PASS

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

9.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
 - a) Set instrument center frequency to DTS channel center frequency.
 - b) Set the span to ≈ 1.5 times the DTS bandwidth.
 - c) Set the RBW = 100 kHz.
 - d) Set the VBW $\approx [3 \times \text{RBW}]$.
 - e) Detector = peak.
 - f) Sweep time = auto couple.
 - g) Trace mode = max hold.
 - h) Allow trace to fully stabilize.
 - i) Use the peak marker function to determine the maximum PSD level.


Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

9.2 Test Result


9KHz – 30MHz

802.11b


Low Channel



Middle Channel






High Channel



802.11g


Low Channel







802.11n HT20

Low Channel



Middle Channel






Above 30MHz


802.11b

Low Channel




Middle Channel

Fundamental



High Channel


Fundamental



802.11g


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11n HT20


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel

Fundamental



10 Band Edge Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

Test Limit: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



Test Mode: Transmitting

10.1 Test Produce


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

10.2 Test Result


Test result plots shown as follows:




TX 11g: Band edge-left side




TX 11g: Band edge-right side



TX 11n HT20: Band edge-left side



TX 11n HT20: Band edge-right side



11 6 dB Bandwidth and 99% Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

11.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz


11.2 Test Result:

Operation mode	Test Channel	6dB Bandwidth (MHz)	99% Bandwidth (MHz)
TX 11b	Channel 1	10.144	13.120
	Channel 6	10.144	13.120
	Channel 11	17.712	13.120
TX 11g	Channel 1	16.500	16.800
	Channel 6	16.500	16.800
	Channel 11	16.500	16.800
TX 11n HT20	Channel 1	17.684	17.766
	Channel 6	17.712	17.820
	Channel 11	17.712	17.820


Test result plot:

6dB Bandwidth


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode: TX 11g channel 1




Mode: TX 11g channel 6




Mode: TX 11g channel 11




Mode: TX 11n HT20 channel 1



Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




99% Bandwidth


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode: TX 11g channel 1




Mode: TX 11g channel 6




Mode: TX 11g channel 11




Mode: TX 11n HT20 channel 1



Mode: TX 11n HT20 channel 6



Mode: TX 11n HT20 channel 11



12 Maximum Peak Output Power

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

12.1 Test Procedure:

KDB 558074 D01 15.247 Meas Guidance v05 August 24, 2018

section 8.3.1.1 (For BLE)

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW \geq DTS bandwidth.
- b) Set VBW ≥ 3 RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

section 8.3.1.2 (For WIFI)

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.


- a) Set the RBW = 1% to 5% of the OBW, not to exceed 1 MHz..
- b) Set the VBW $\geq 3 \times$ RBW
- c) Set the span $\geq 1.5 \times$ OBW.
- d) Detector = RMS.
- e) Sweep time = auto couple.
- f) trigger = free run..
- g) Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\geq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- h) Trace average at least 100 traces in power averaging (rms) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum..

12.2 Test Result:


Operation mode	Channel Frequency (MHz)	Maximum Peak Output Power (dBm)	Limit
TX 11b	Low-2412	12.88	1W/30dBm
	Middle-2437	12.97	1W/30dBm
	High-2462	12.72	1W/30dBm
TX 11g	Low-2412	10.44	1W/30dBm
	Middle-2437	15.47	1W/30dBm
	High-2462	11.04	1W/30dBm
TX 11n HT20	Low-2412	11.26	1W/30dBm
	Middle-2437	15.63	1W/30dBm
	High-2462	11.16	1W/30dBm

Test Plot


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode :TX 11g channel 1




Mode :TX 11g channel 6




Mode :TX 11g channel 11




Mode: TX 11n HT20 channel 1



Mode: TX 11n HT20 channel 6





13 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

13.1 Test Procedure:


KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017 section 10.2

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section
Submit this plot.


13.2 Test Result:

Operation mode	Channel Frequency (MHz)	Power Spectral (dBm per 3kHz)	Limit
TX 11b	Low-2412	-17.79	8dBm per 3kHz
	Middle-2437	-16.84	8dBm per 3kHz
	High-2462	-18.45	8dBm per 3kHz
TX 11g	Low-2412	-24.60	8dBm per 3kHz
	Middle-2437	-19.15	8dBm per 3kHz
	High-2462	-23.51	8dBm per 3kHz
TX 11n HT20	Low-2412	-24.19	8dBm per 3kHz
	Middle-2437	-19.71	8dBm per 3kHz
	High-2462	-23.60	8dBm per 3kHz


Test Plot Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode :TX 11g channel 1




Mode :TX 11g channel 6




Mode :TX 11g channel 11




Mode: TX 11n HT20 channel 1



Mode: TX 11n HT20 channel 6





14 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfill the requirement of this section.

15 RF Exposure

Remark: refer to SAR test report: WTF22X04076577W

16 Photographs of test setup and EUT.

Note: Please refer to appendix: Appendix-SPMR20500-Photos.

=====**End of Report**=====