



## RADIO FREQUENCY EXPOSURE

### LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

### EUT Specification

<b>EUT</b>	X1TXP1UC Module
<b>Model</b>	X1TXP
<b>Frequency Band (Operating)</b>	2404.0 MHz ~2476.0 MHz
<b>Device Category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
<b>Exposure Classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna Diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. Mix Output Power</b>	20.44dBm
<b>Antenna Gain (Max)</b>	2.0dBi (Numeric gain:1.58)
<b>Evaluation Applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation
<b>Note:</b>	
1. The maximum mix output power is 20.44dBm (110.66mW) with 1.58 numeric antenna gain. 2. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.	

### TEST RESULT

No non-compliance noted.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

#### CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

## Calculation

Given 
$$S = \frac{P \times G}{4\pi d^2}$$
 (Equation 1)

Where d = distance in cm  
P = Power in mW  
G = Numeric antenna gain  
S = Power Density in mW / cm<sup>2</sup>

## Maximum Permissible Exposure

EUT Output Power=110.66mW

Numeric antenna gain=1.58dBi

Substituting the MPE safe distance using d=20 cm into **Equation 1** :

Yields

The power density  $S = 110.66 \times 1.58 / (4\pi \times 400) \text{ cm}^2 = 0.0348 \text{ mW/cm}^2$

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW / cm<sup>2</sup> even if the calculation indicates that the power density would be larger.)