

## RF Exposure evaluation

Product Description: Bluetooth Headphone

Model Number: AH-GC30

FCC ID: BV2-AH-GC30

IC: 10369A-AHGC30

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:  $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

According to the follow transmitter output power (  $P_t$  ) formula :

$$P_t = ( E \times d )^2 / ( 30 \times g_t )$$

$P_t$ =transmitter output power in watts

$g_t$ =numeric gain of the transmitting antenna (unitless)

$E$ =electric field strength in V/m

$d$ =measurement distance in meters (m)

According to the above test data,

$$P_t = 6.750 \text{ dBm} = 4.73 \text{ mW}$$

The result is rounded to one decimal place for comparison

Worse case is as below: [2480MHz -4.73mW output power]

$$(4.73 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.480(\text{GHz})}] = 1.49 < 3.0 \text{ for 1-g SAR}$$

Then SAR evaluation is not required

**NOTE:** For the maximum power, you can refer FCC test report.

According to Clause 2.5.1 of RSS-102 Issue 5 SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance<sup>4,5</sup>

Frequency(MHz)	At separation distance of $\leq 20$ mm
2450	30mW

According to the follow transmitter output power (Pt) formula:

$$P_{MAX}=6.750\text{dBm}$$

$$\text{Antenna gain}=2.5\text{dBi}$$

$$P_{EIRP}=6.750+2.5=9.25\text{dBm}=8.41\text{mW} < 30\text{mW}$$

Then SAR evaluation is not required

**NOTE:** For the maximum power, you can refer IC test report.