

## FCC 47 CFR MPE REPORT

D&M Holdings Inc.

HOME THEATER SYSTEM

Model Number: SC-DHT-S517-BAR

FCC ID: BV2-DHT-S517BAR

Prepared for:	D&M Holdings Inc.
	2-1 Nisshin-cho, Kawasaki-ku, Kawasaki, Japan
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2108204
Date of Test:	Jul. 05~Aug. 20, 2021
Date of Report:	Aug. 23, 2021

## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

##### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance,  $d=0.2\text{m}$ , as well as the gain of the used antenna, the RF power density can be obtained

## 2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)
Bluetooth GFSK	2402	2.34	1.7140	2±1
	2441	2.45	1.7579	2±1
	2480	2.38	1.7298	2±1
Bluetooth 8-DPSK	2402	3.19	2.0845	3±1
	2441	3.33	2.1528	3±1
	2480	3.23	2.1038	3±1
2.4G Wireless	2404	6.64	4.6132	6±1
	2438	6.57	4.5394	6±1
	2476	6.54	4.5082	6±1

### 3. Calculated Result and Limit

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm <sup>2</sup> )	Limited of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
		(dBi)	(Linear)			
2.4G Band						
Bluetooth GFSK	3	3.80	2.399	0.00095	1	Complies
Bluetooth 8-DPSK	4	3.80	2.399	0.00120	1	Complies
2.4G Wireless	7	2.74	1.879	0.00187	1	Complies

MAX Power Density (S) (mW/cm <sup>2</sup> ) Bluetooth (Soundbar)	MAX Power Density (S) (mW/cm <sup>2</sup> ) 2.4G Wireless (Soundbar)	Power Density (S) (mW/cm <sup>2</sup> ) Total	Limited of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
0.00120	0.00187	0.00307	1	Complies

**End of Test Report**