

FASSON MC PRIMECOAT / S451 / BG40 brown

imprint / AA0973

Facestock

A white, one side machine coated, calendered woodfree printing paper with semi gloss appearance.

Basis weight	80 g/m ²	ISO 536
Caliper	0,069 mm	ISO 534

Adhesive

A general purpose permanent, rubber based adhesive.

Liner

BG40 brown, a supercalendered glassine paper.

Basis weight	60 g/m ²	ISO 536
Caliper	0,055 mm	ISO 534
Transparency	45%	DIN 53147

Laminate

Caliper 0,139 mm +/- 10%

PERFORMANCE DATA

Peel Adhesion 90°	480 N/m	FTM2, st.st
Quick Stick	880 N/m	FTM9, glass
Min. applic. temp.	- 5°C	
Service temperature	- 40°C / + 80°C	

N.B.

All data to be considered as typical values.

Adhesive performance

The adhesive is suitable for general application on a wide range of substrates at temperatures down to - 5°C.

The adhesive provides excellent tack and adhesion to most surfaces including apolar materials such as polyethylene. Even on slightly damp surfaces the adhesive often performs well.

Application and use

Wide range of promotional labels and stickers of brilliant multicolour quality. The facestock's flexible nature provides excellent performance on most curved substrates.

Typical application areas: Supermarkets catchweigh, industrial labeling, food packaging.

Printing / Conversion

This glossy, coated quality is specially suited to obtain top printing quality in all the usual processes, be it single or multicolour, line or process colour printing.

Excellent conversion in rotary and flat bed. Temperatures up to 80°C can be used for ink drying provided the web temperature is below 50°C when it reaches the waste stripping unit.

Shelf life

Two years, stored at 22°C / 50% RH.

