

Straubing, November 24, 1998

TEST - REPORT

No. 51940-80919

for

ZB 001

Hand Held Verifier

Applicant: Sensormatic GmbH

Purpose of testing: To show compliance with
I-ETS 300 330 (December 1994)
Product Class 1

Radio Equipment and Systems (RES);
Short Range Devices (SRDs);
Technical characteristics and test methods
for radio equipment in the frequency range
9 kHz to 25 MHz and inductive loop systems
in the frequency range 9 kHz to 30 MHz

Note:

The test data of this report relate only to the individual item which have been tested.
This report shall not be reproduced except in full extent without the written approval of
the testing laboratory.

Table of Contents

1. Identification of the Test Laboratory.....	3
2. Administrative Data.....	4
3. Deviations from the Test Specifications.....	6
4. Summary of Test Results.....	7
5. Additional References.....	8
6. Test Results.....	9
7. Test Equipment and Ancillaries used for Tests.....	14
8. Measurement Uncertainty Values.....	18
9. Photographs of the Equipment Under Test.....	21
10. Additional Information supplementary to the Test Report.....	33

1. Identification of the Test Laboratory

DETAILS OF THE TEST LABORATORY

COMPANY NAME:	Senton GmbH EMI/EMC Test Center
ADDRESS:	Aeussere Fruehlingstrasse 45 D-94315 Straubing Germany
LABORATORY ACCREDITATION:	DAR-Registration No. TTI-P-G 062/94-30 DAR-Registration No. TTI-P-G 109/95-20
NAME FOR CONTACT PURPOSES:	Mr. Johann Roidt
TELEPHONE: (+49) 09421 55 22-0	FAX: (+49) 09421 55 22 99

PERSONNEL INVOLVED IN THIS TEST REPORT

TECHNICAL DIRECTOR: Mr. Johann Roidt
RESPONSIBLE FOR TESTING: Mr. Thomas Eberl
RESPONSIBLE FOR TEST REPORT:	Mr. Thomas Eberl

2. Administrative Data

IDENTIFICATION OF EUT	
TYPE DESIGNATION OF EUT (i.e. system if EUT consists of more than one part):	ZB 001
PARTS OF THE SYSTEM (including appropriate type designations)	1
SERIAL NUMBER(S):	--
FREQUENCY RANGE:	1 kHz - 135 kHz (according to BAPT 222 ZV 122)
OPERATING FREQUENCY:	57.6 kHz
CHANNEL SPACING:	--
ITU DESIGNATION:	1H00 NON
NUMBER OF RF-CHANNELS:	
NUMBER OF CONTROL FUNCTIONS:	
POWER SUPPLY:	Accu 12 V
TYPE OF ANTENNA:	Printed antenna
SIZE / LENGTH OF ANTENNA:	0.0176 m ²
INTERFACE(S):	--

ADMINISTRATIVE DATA

APPLICANT (full address):	Sensormatic GmbH Am Schimmersfeld 7 40880 Ratingen (Germany)
CONTACT PERSON:	Mr. Zinke
TELEPHONE NO.:	02102/431326
FAX NO.:	02102/431250
RECEIPT OF EUT:	Oct. 98
DATE(S) OF TEST:	Nov. 98
VERSION OF EUT:	series version
NOTE:	

3. Deviations from the Test Specifications

All tests were performed without deviations from the test specifications.

4. Summary of Test Results

REFERENCE FOR PERFORMED TESTS	
Reference:	I-ETS 300 330 (December 1994)
Title:	Radio Equipment and Systems (RES); Short Range Devices (SRDs); Technical characteristics and test methods for radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz
Result:	The tested sample fully complies with the requirements set forth in I-ETS 300 330 (December 1994) for equipment belonging to product class 1

LIST OF MEASUREMENTS			
Sub- clause	Parameter to be measured	Test	Page
Transmitter parameters			
7.2.1	H-field (Class 1)	Passed	
7.2.2	RF carrier current (Classes 2 and 3)	Not applicable	
7.2.3	Radiated E-field (Class 4)	Not applicable	
7.3.2	Frequency error	Not applicable	
7.3.3	Modulation bandwidth	Passed	
7.4.2.1 7.4.2.2	Spurious emissions conducted - transmitter operating	Not applicable	
7.4.2.1 7.4.2.2	Spurious emissions conducted - transmitter on standby	Not applicable	
7.4.3 7.4.4	Spurious emissions radiated - transmitter operating	Passed	
7.4.3 7.4.4	Spurious emissions radiated - transmitter on standby	Not applicable	

5. Additional References

ADDITIONAL REFERENCES
<ul style="list-style-type: none"><input checked="" type="checkbox"/> The EUT meets the requirements of BAPT 222 ZV 122<input type="checkbox"/> The EUT complies with performance specification MPT 1337 published by Radiocommunications Agency<input type="checkbox"/> The EUT complies with performance specification MPT 1339 published by Radiocommunications Agency

6. Test Results

Ambiente temperature: +20.0 °C

Relative humidity: 50 %

**H-FIELD FIELD STRENGTH
(CLASS 1)**

SUBCLAUSE 7.2.1

Rated field strength (maximum) 28.4 dBµA/m at 10 metres

Antenna size 0.0176 m²

Test conditions		Transmitter field strength (dBµA/m)		
		CH 1	CH 2	CH 3
T_{nom} +20.0 °C	V_{nom} 12.0 V	28.4	--	--
Maximum deviation from rated output under normal test conditions (dB)		1.5		
Measurement uncertainty (dBµA/m)		± 3		

LIMIT:

SUBCLAUSE 7.2.1.3

Frequency range (MHz)	H-field field strength limit (H_f) dBµA/m at 10 m
For loop coil antennas with area ≥ 0.16 m²	
$0.009 \leq f < 0.03$	72
$0.03 \leq f < 0.135$	72 at 0.03 MHz descending 3.5 dB/oct
$0.135 \leq f < 4.78$	38 at 0.135 MHz descending 3.5 dB/oct
$4.78 \leq f < 30$	20
$6.765 \leq f \leq 6.795$ (ISM)	42
$13.553 \leq f \leq 13.567$ (ISM)	
$26.957 \leq f \leq 27.283$ (ISM)	
For loop coil antennas < 0.05 m²	
$0.009 \leq f < 0.03$	62
$0.03 \leq f < 0.135$	62 at 0.03 MHz descending 3.5 dB/oct
For loop coil antennas with area between 0.05 m² and 0.16 m²	
$0.009 \leq f < 0.135$	H_f table values for loop coils ≥ 0.16 m² + $10 * \log(\text{area} / 0.16 \text{ m}^2)$

Reference number(s) of test equipment used (for reference see test equipment listing):
001, 012, 103, 123, 140

Ambiente temperature: +20.0 °C

Relative humidity: 50 %

PERMITTED RANGE OF OPERATING FREQUENCIES FOR WIDEBAND EQUIPMENT (>25 KHZ)

SUBCLAUSE 7.3

Applicants declared operating frequency band:
Lowest frequency: kHz

Highest frequency: kHz

Test conditions		Limit
		Frequency (kHz)
T _{nom} +20.0 °C	V _{nom} 12.0 V	F _L = 53.089
		F _H = 63.422
T _{min} -20.0 °C	V _{min} 10.8 V	F _L = 53.200
		F _H = 62.844
	V _{max} 13.2 V	F _L = 52.467
		F _H = 64.111
T _{max} +55.0 °C	V _{min} 10.8 V	F _L = 53.756
		F _H = 62.178
	V _{max} 13.2 V	F _L = 52.956
		F _H = 63.600
Measurement uncertainty (Hz)		

Where F_L Lowest frequency at the appropriate spurious emission level
F_H Highest frequency at the appropriate spurious emission level

Band edge limits
F_{LM} Lowest F_L (measured): 53.089 kHz
F_{HM} Highest F_H (measured): 63.600 kHz

Reference number(s) of test equipment used (for reference see test equipment listing):
007, 008, 020, 022, 102

Ambiente temperature: +20.0 °C

Relative humidity: 50 %

**TRANSMITTER SPURIOUS EMISSIONS
RADIATED (<30 MHz)**

SUBCLAUSE 7.4.3

Rated carrier output 28.4 dBμA/m
Transmitter operating/standby*

Modulated/Unmodulated*
(Delete whichever is inappropriate)

Spurious Emissions Level (dBμA/m)								
CH 1			CH 2			CH 3		
f (MHz)	Bandwidth** (kHz)	Level (dBμA/m)	f (MHz)	Bandwidth** (kHz)	Level (dBμA/m)	f (MHz)	Bandwidth** (kHz)	Level (dBμA/m)
*								
Measurement uncertainty (dBμA/m)						± 3		

**Bandwidth = the measuring receiver bandwidth

*Note .: No values above noise level of the appropriate test receiver

LIMIT:

SUBCLAUSE 7.4.3.2

State	Frequency 9 kHz ≤ f < 4.78 MHz	Frequency 4.78 MHz ≤ f < 30 MHz
Operating	24.5 dBμA/m descending 3 dB/oct	-2.8 dBμA/m
Standby	3.5 dBμA/m descending 3 dB/oct	-23.7 dBμA/m

Reference number(s) of test equipment used (for reference see test equipment listing):
001, 003, 012, 014, 103, 104, 140

Ambiente temperature: +20.0 °C

Relative humidity: 50 %

**TRANSMITTER SPURIOUS EMISSIONS
RADIATED (>30 MHz)**

SUBCLAUSE 7.4.4

Rated carrier output 28.4 dBμA/m

Transmitter operating/~~standby~~*

Modulated/~~Unmodulated~~*
*(Delete whichever is inappropriate)

Spurious Emissions Level (nW)								
CH 1			CH 2			CH 3		
f (MHz)	Bandwidth** (kHz)	Level (nW)	f (MHz)	Bandwidth** (kHz)	Level (nW)	f (MHz)	Bandwidth** (kHz)	Level (nW)
*								
Measurement uncertainty (dB)						± 3		

**Bandwidth = the measuring receiver bandwidth

*Note .: No values above noise level of the appropriate test receiver

LIMIT:

SUBCLAUSE 7.4.4.2

State	47 MHz to 74 MHz 87.5 MHz to 118 MHz 174 MHz to 230 MHz 470 MHz to 862 MHz	Other frequencies between 30 MHz to 1000 MHz
Operating	4 nW	250 nW
Standby	2 nW	2 nW

Reference number(s) of test equipment used (for reference see test equipment listing):
001, 004, 012, 015, 101, 106, 141, 142, 143, 144

7. Test Equipment and Ancillaries used for Tests

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the test laboratory (version 11/20/1995).

General Test Equipment and Ancillaries

No.	Instrument/Ancillary	Type	Serial Number	Manufacturer
001	Open area test site	EG 1		Senton
002	Shielded room	No. 1	1451	Senton
003	Shielded room	No. 2	1452	Senton
004	Semi-anechoic room	No. 3	1453	Siemens
005	Shielded room	No. 4	3FD 100 544	Euroshield
006	Shielded room	No. 5	5468	Ray Proof Division
007	Temperature test chamber	HT4010	07065550	Heraeus
008	Cable	RG214	1309	Senton
009	Cable	200CM_001	1357	Rosenberger
010	Cable	150CM_001	1479	Rosenberger
011	Cable	150CM_002	1480	Rosenberger
012	Cable set EG1	RG214	1189 - 1191	Senton
013	Cable set cabin no. 1	RG214		Senton
014	Cable set cabin no. 2	RG214		Senton
015	Cable set cabin no. 3	RG214		Senton
016	Cable set cabin no. 4	RG214		Senton
017	DC power supply	NGSM 32/10	203	Rohde & Schwarz
018	DC power supply	NGB	2455	Rohde & Schwarz
019	DC power supply	NGA	386	Rohde & Schwarz
020	Isolating transformer	RT 5A	10387	Grundig
021	Isolating transformer	RT 5A	10416	Grundig
022	Digital multimeter	199	463386	Keithley
023	Multimeter	HP E2373A	2927J03345	Hewlett Packard

Test Equipment and Ancillaries used for Emission Tests

No.	Instrument/Ancillary	Type	Serial Number	Manufacturer
101	EMI test receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
102	Spectrum analyzer	R 3271	05050023	Advantest
103	Test receiver	ESH 3	880112/032	Rohde & Schwarz
104	Test receiver	ESHS 10	860043/016	Rohde & Schwarz
105	Test receiver	ESV	881414/009	Rohde & Schwarz
106	Test receiver	ESVP	881120/024	Rohde & Schwarz
107	Audio analyzer	UPA	862954	Rohde & Schwarz
108	Radio communication service monitor	CMS 54	838384/030	Rohde & Schwarz
109	Power meter	NRVS	836856/015	Rohde & Schwarz
110	Power sensor	NRV-Z52	837901/030	Rohde & Schwarz
111	Power sensor	NRV-Z4	863828/015	Rohde & Schwarz
112	Preamplifier	ESV-Z3	860907/004	Rohde & Schwarz
113	Preamplifier	R14601		Advantest
114	Preamplifier	ACX/080-3030	32640	CTT
115	Preamplifier	ACO/180-3530	32641	CTT
116	Signal generator	SMS	872166/039	Rohde & Schwarz
117	Signal generator	HP 8673 D	2930A00966	Hewlett Packard
118	Waveform generator	HP 33120 A	US34005375	Hewlett Packard
119	UHF attenuator set	DPU	300771/075	Rohde & Schwarz
120	UHF attenuator set	DPU	300788/006	Rohde & Schwarz
121	Attenuator	4776-10	9412	Narda
122	Attenuator	4776-20	9503	Narda
123	Pulse limiter	ESH 3-Z2	1144	Rohde & Schwarz
124	Pulse limiter	11947 A	3107A00566	Hewlett Packard
125	V-network	ESH 3-Z5	862770/018	Rohde & Schwarz
126	V-network	ESH 3-Z5	894785/005	Rohde & Schwarz
127	V-network	ESH 3-Z5	830952/025	Rohde & Schwarz
128	V-network	ESH 3-Z6	830722/010	Rohde & Schwarz
129	V-network	NSLK 8127	8127152	Schwarzbeck
130	Artificial mains network	ESH 2-Z5	842966/004	Rohde & Schwarz
131	T-network	ESH 3-Z4	890602/011	Rohde & Schwarz
132	T-network	ESH 3-Z4	890602/012	Rohde & Schwarz
133	Diode detector negative	8473D	01492	Hewlett Packard

Test Equipment and Ancillaries used for Emission Tests (continued)

No.	Instrument/Ancillary	Type	Serial Number	Manufacturer
134	High impedance probe	TK 9416	01	Schwarzbeck
135	High impedance probe	TK 9416	02	Schwarzbeck
136	Current probe	ESH 2-Z1	863366/18	Rohde & Schwarz
137	Current probe	ESV-Z1	862553/3	Rohde & Schwarz
138	Absorbing clamp	MDS 21	80911	Lüthi
139	Absorbing clamp	MDS 21	79690	Lüthi
140	Loop antenna	HFH2-Z2	882964/1	Rohde & Schwarz
141	Biconical antenna	HK 116	836239/02	Rohde & Schwarz
142	Biconical antenna	HK 116	842204/001	Rohde & Schwarz
143	Log. periodic antenna	HL 223	834408/12	Rohde & Schwarz
144	Log. periodic antenna	HL 223	841516/023	Rohde & Schwarz
145	Horn antenna	3115	9508-4553	Emco
146	Horn antenna	3160-03	9112-1003	Emco
147	Horn antenna	3160-04	9112-1001	Emco
148	Horn antenna	3160-05	9112-1001	Emco
149	Horn antenna	3160-06	9112-1001	Emco
150	Horn antenna	3160-07	9112-1008	Emco
151	Horn antenna	3160-08	9112-1002	Emco
152	Horn antenna	3160-09	9403-1025	Emco
153	Stub tuner	904N	04	Narda
154	Mains analyzer	DPA 503	496 - 02	EM Test
155	Controller	HIS 500	X71010	EM Test
156	AC Amplifier	ACS 500	HK51736	EM Test
157	Mains impedance	AIF 500	X71062	EM Test

Test Equipment and Ancillaries used for Immunity Tests

No.	Type	Model	Serial Number	Manufacturer
201	ESD simulator	NSG 435	000290	Schaffner
202	EFT generator	NSG 1025	3020	Schaffner
203	Ultra compact simulator	UCS	1195-30	EM Test
204	Coupling clamp	CDN 8014	131	Schaffner
205	Coupling clamp	SL 400-071D	007	Schaffner
206	Coupling filter	FP 16	080554-14-84	Haefely
207	Oscilloscope	2225	203550	Tektronix
208	Signal generator	SMT 03	838129/029 837533/032	Rohde & Schwarz
209	Power amplifier	150 L	8835	Amplifier Research
210	Power amplifier	200 W 1000	12904	Amplifier Research
211	Power meter	NRVS	838624/016	Rohde & Schwarz
212	E-field generator	3107 B	2302	Emco
213	Biconical antenna	VHBA 9123	1018	Schwarzbeck
214	Log. periodic antenna	AT 1080	12834	Amplifier Research
215	Isotropic field probe	FP 2000	12847	Amplifier Research
216	Isotropic field monitor	FM 2004	12632	Amplifier Research
217	Ultra compact simulator	UCS	1195-30	EM Test
218	Surge generator	NSG 650	1679204	Schaffner
219	Coupling network	CDN 110	1649135	Schaffner
220	Coupling network	CDN 115	132	Schaffner
221	Dropping resistor	INA 110-40	121	Schaffner
222	Oscilloscope	HM 408	9005 F 3144	Hameg
223	Signal generator	SMX	883184/018	Rohde & Schwarz
224	Power amplifier	411 LA	299	ENI
225	Power amplifier	HVV 250	836956/004	Rohde & Schwarz
226	Power meter	NRV	863825/018	Rohde & Schwarz
227	Coupling network	FCC - 801- M3-25	117	FCC
228	Coupling network	FCC - 801- M4-25	17	FCC
229	Coupling network	FCC - 801- M5-25	16	FCC
230	Coupling network	FCC - 801- AF4	47	FCC
231	Coupling network	FCC - 801- AF4	48	FCC
232	Coupling network	FCC - 801-T4	68	FCC
233	Coupling network	FCC - 801- C1	64	FCC
234	Coupling network	CDN 801-M3	--	Senton
235	Coupling network	CDN 801-S37	--	Senton
236	Current clamp	FCC-120-9B	15	FCC
237	EM injection clamp	EM 101	35354	Lüthi
238	Ultra compact simulator	UCS 500	1195-30	EM Test
239	Transformer			Senton
240	Oscilloscope	54602B	US35060304	Hewlett Packard

8. Measurement Uncertainty Values

8.1. Radio Interference Emission Testing

8.1.1. Conducted Emission 9 kHz - 30 MHz

Used measuring instrument	Maximum value
Test receiver ESHS 10 (CISPR-detector, S/N \geq 16 dB)	< \pm 1.5 dB
Test receiver ESH 3 (CISPR-detector, S/N \geq 16 dB)	< \pm 1.5 dB
Pulse Limiter ESH 3-Z2	\leq \pm 0.3 dB
Network ESH 3-Z4, ESH 3-Z5 or ESH 3-Z6	\leq \pm 1.0 dB
High impedance probe TK 9416	\leq \pm 1.0 dB
Cable attenuation (determined with power meter NRV)	< \pm 0.2 dB

8.1.2. Radiated Emission 9 kHz - 30 MHz

Used measuring instrument	Maximum value
Test receiver ESHS 10 (CISPR-detector, S/N \geq 16 dB)	< \pm 1.5 dB
Test receiver ESH 3 (CISPR-detector, S/N \geq 16 dB)	< \pm 1.5 dB
Loop Antenna HFH 2-Z2	< \pm 1.0 dB
Cable attenuation (determined with power meter NRV)	< \pm 0.2 dB

8.1.3. Radiated Emission / Equivalent Radiated Power 30 MHz - 1000 MHz

Used measuring instrument	Maximum value
Spectrum analyzer R3261A	\leq \pm 1.5 dB
Spectrum analyzer R3271	\leq \pm 1.5 dB
Test receiver ESVP (CISPR-detector, S/N > 15 dB)	< \pm 1.5 dB
Test receiver ESV (CISPR-detector, S/N \geq 10 dB)	< \pm 1.5 dB
Preamplifier ESV-Z3	max. +2.0 / -1.0 dB
Biconical antenna EMCO 3110	\leq \pm 1.5 dB
Biconical antenna HK 116	\leq \pm 1.0 dB
Log.-per. antenna EMCO 3147	\leq \pm 1.5 dB
Log.-per. antenna HL 223	\leq \pm 1.0 dB
Open area test site (related to theoretical site attenuation)	< \pm 3.0 dB
Cable attenuation (determined with power meter NRV)	< \pm 0.2 dB

8.1.4. Interference Power 30 MHz - 1000 MHz

Used measuring instrument	Maximum value
Spectrum analyzer R3261A	$\leq \pm 1.5$ dB
Spectrum analyzer R3271	$\leq \pm 1.5$ dB
Test receiver ESVP (CISPR-detector, S/N > 15 dB)	$< \pm 1.5$ dB
Test receiver ESV (CISPR-detector, S/N \geq 10 dB)	$< \pm 1.5$ dB
Preamplifier ESV-Z3	max. +2.0 / -1.0 dB
Absorbing clamp MDS 21	$\leq \pm 1.0$ dB
Cable attenuation (determined with power meter NRV)	$< \pm 0.2$ dB

8.2. Immunity Testing

8.2.1. Electrostatic Discharge

Used measuring instrument

Maximum value

ESD simulator NSG 435

$\leq \pm 5\%$ of selected discharge voltage

ESD simulator PSD 25

max. $+20\%$ / $- 0\%$ of selected discharge voltage

8.2.2. Electromagnetic Fields (RF-Fields)

Used measuring instrument

Maximum value

Field probe FP 2000 / field monitor FM 2004

Selected range up to 10 V/m

$\leq \pm 0.7$ V/m

Selected range up to 30 V/m

$\leq \pm 1.9$ V/m

Selected range up to 100 V/m

$\leq \pm 6.1$ V/m

Selected range up to 300 V/m

$\leq \pm 18.1$ V/m

8.2.3. Electrical Fast Transients (Burst)

Used measuring instrument

Maximum value

EFT generator NSG 1025

$\leq \pm 10\%$ of selected pulse amplitude

8.2.4. Surge Immunity

Used measuring instrument

Maximum value

Surge generator NSG 650

$\leq \pm 10\%$ of selected pulse amplitude

9. Photographs of the Equipment Under Test

Photo No. 1

Antenna

Photo No. 2

Front of unit

Photo No. 3

Rear of unit

Photo No. 4

Label or identifying mark

Photo No. 5

Top view - Antenna - PCB

Photo No. 6

Bottom view - Antenna - PCB

Photo No. 7

Unit disassembled

Photo No. 8

Top view - printed board

Photo No. 9

Bottom view - printed board

Photo No. 10

Top view - Accu - pack

Photo No. 11

Bottom view - Accu - pack

10. Additional Information supplementary to the Test Report

Item	Description	No. of Pages
1	Technical documents including data sheet, circuit diagrams, positioning of components and layout	12
2	Application form for testing to I-ETS 300 330	18