

UPCS (DECT based) – Implementation Conformance Statement

Description : US-DECT Portable Part						
	Model : DT590					
	Use :					
		FP	РР	Repeater		
	System		\boxtimes			
L	Туре					
DUT	HW version		PCB V7.0 RC			
	SW version		SW version 3.0			
	RFPI / PIN		000000010			
	Decl. emission BW		1,4 MHz			
	Decl. lower threshold					
	Decl.upper threshold ¹⁾		-62.4 dBm			
	Standard:	⊠ FCC part 15D	□ other:			
ion	Frequency band:	⊠ 1920 – 1930 MHz	\Box other:			
Product information	Number of RF channels: 5					
; info	Number of logical chann	els: 60 (tir	ne and spectrum windows	s)		
oduct	Used slot type:	\boxtimes single \square double				
Pro	Used slot(s):	even odd				
	Operating mode:	\Box simplex \boxtimes duplex	□ other:			

¹⁾ if applicable

rev. 1.2 Maxima - UPCS DECTbased ICS v2.doc

page 1 (6)



	Antennas:								
	FP:	FP: Antenna Type		ype	Gain [dBi]	internal	external		
		1							
		2							
		3							
		Do Tx and Rx use the same antenna(s)?: \Box Yes \Box No							
	PP:	Antenna	Туре		Gain [dBi]	internal	external		
		1	P	CB	0	\boxtimes			
ion		2	РСВ		0				
Product information		3							
duct in		Do Tx and Rx use the same antenna(s)?: \square Yes \square No					l No		
Proe	Antenna diversit	Antenna diversity: 1)							
		Ar	ıtenna	Diversity supported					
				Tx		Rx			
	FP	1 2 3							
	PP	PP 1		\boxtimes		\boxtimes			
			2						
			3						

rev. 1.2 Maxima - UPCS DECTbased ICS v2.doc

page 2 (6)



	Supply and supported temperature ranges (Manufacturer declaration):					
		FP	PP		Repeater	
	U _{normal} [V]		3.7V DC (Li-Ion)			
	U _{min} [V]		3.2V DC			
	U _{max} [V]		4.2V DC			
	T _{min} [°C]		10 (Class E1)			
	T _{max} [°C]		40			
ion	Power Source	Туре		Manufacturer		
Product information	FP or WRS					
luct inf	PP (charger)	DT590 Charger				
Prod	Data connection: PSTN other					
	Used radio module ¹⁾ :					
	Туре :	Manufacturer :				
	Ancillary equipment ¹⁾ :					
	Description	:				
	Туре	:				
	Manufacturer	:				
	Host device ¹):					
	Description	:				
	Туре	:				
	Manufacturer	:				

rev. 1.2 Maxima - UPCS DECTbased ICS v2.doc

page 3 (6)



Control s	oftware ¹⁾
-----------	-----------------------

:

:

Name

Version

Manufacturer :

Product information **Additional remarks:**

¹⁾ if applicable

rev. 1.2 Maxima - UPCS DECTbased ICS v2.doc

page 4 (6)



	FCC 15.323 (c) (5): This device or group of co-operating devices located within 1 meter of each other shall during any frame period occupy more than 6 MHz of aggregate bandwidth, or alternatively more than one third of the time and spectrum windows defined by the system.					
	Manu	nufacturer agrees: \boxtimes Yes \square No				
	FCC 15.323 (c) (12): This device shall not use the provisions of (c) (10) or (c) (11) to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices. Manufacturer agrees: ⊠ Yes □ No					
	FCC 15.307 (b): The applicant is a participating member of UTAM, Inc. and will provide a related affidavit from UTAM, Inc. in course of certification.					
suc	Confirmation by applicant: \boxtimes Yes \square No					
Manufacturer declarations	This device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. Automatic break off the transmissions means break off of connection and break of transmissions which are not control and signalling information or repetitive codes of complete frame or burst intervals. In case of devices using basics of DECT technology at least fixed parts and repeaters are using control and signalling information without direct connection without direct connection to their remote station. <i>Please fill in the table below with the reaction of the EUT (FP and/or PP) using A, B or C.</i>					
				Reaction of EUT		TT 1
	1	Situation		FP	PP	Verdict
	$\frac{1}{2}$	Switch-off counter part Hook-off by counter part	t			
	3	Switch-off by EUT	L			
	4	Hook-off on EUT side				
	5	Remote power from EUT	Г			
	6	Remote power from counterpart				
	 A – Connection break down, cease of transmit B – Connection break down, EUT transmits signalling information C – Connection break down, counter part transmits signalling information 					

rev. 1.2 Maxima - UPCS DECTbased ICS v2.doc



Supplement	Additional rema	rks:	
	Declared by:		
	Date:	Name (print):	Signature:

rev. 1.2 Maxima - UPCS DECTbased ICS v2.doc

page 6 (6)