

UPCS (DECT based) – Implementation Conformance Statement

DUT	Description : US-DECT Portable Part			
	Model : DT292			
	Use :			
		FP	PP	Repeater
	System	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Type			
	HW version		PCB V5.0 RB	
	SW version		V30	
	RFPI / PIN		0000000010	
	Decl. emission BW		1,4 MHz	
Decl. lower threshold				
Decl.upper threshold ¹⁾		-62.4 dBm		
Product information	Standard: <input checked="" type="checkbox"/> FCC part 15D <input type="checkbox"/> other:			
	Frequency band: <input checked="" type="checkbox"/> 1920 – 1930 MHz <input checked="" type="checkbox"/> other: 1921.536 KHz - 1928.448 KHz			
	Number of RF channels: 5			
	Number of logical channels: 60 (time and spectrum windows)			
	Used slot type: <input checked="" type="checkbox"/> single <input type="checkbox"/> double			
	Used slot(s): <input type="checkbox"/> even <input type="checkbox"/> odd			
Operating mode: <input type="checkbox"/> simplex <input checked="" type="checkbox"/> duplex <input type="checkbox"/> other:				

¹⁾ if applicable

Product information	Antennas:					
	FP:	Antenna	Type	Gain [dBi]	internal	external
		1			<input type="checkbox"/>	<input type="checkbox"/>
		2			<input type="checkbox"/>	<input type="checkbox"/>
		3			<input type="checkbox"/>	<input type="checkbox"/>
		Do Tx and Rx use the same antenna(s)?: <input type="checkbox"/> Yes <input type="checkbox"/> No				
	PP:	Antenna	Type	Gain [dBi]	internal	external
		1	PCB	0	<input checked="" type="checkbox"/>	<input type="checkbox"/>
		2	PCB	0	<input checked="" type="checkbox"/>	<input type="checkbox"/>
		3			<input type="checkbox"/>	<input type="checkbox"/>
		Do Tx and Rx use the same antenna(s)?: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No				
	Antenna diversity: ¹⁾					
		Antenna	Diversity supported			
			Tx	Rx		
	FP	1	<input type="checkbox"/>	<input type="checkbox"/>		
2		<input type="checkbox"/>	<input type="checkbox"/>			
3		<input type="checkbox"/>	<input type="checkbox"/>			
PP	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>			
	2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>			
	3	<input type="checkbox"/>	<input type="checkbox"/>			

¹⁾ if applicable



Product information	Supply and supported temperature ranges (Manufacturer declaration):			
		FP	PP	Repeater
	U _{normal} [V]		3.6V DC (NiMH)	
	U _{min} [V]		3.35V DC	
	U _{max} [V]		4.3V DC	
	T _{min} [°C]		10 (Class E1)	
	T _{max} [°C]		40	
	Power Source	Type		Manufacturer
	FP or WRS			
	PP (charger)	DT292 Charger		
	Data connection: <input type="checkbox"/> PSTN <input type="checkbox"/> other			

	Used radio module ¹⁾:			
	Type :		Manufacturer :	

Ancillary equipment ¹⁾:				
Description :				
Type :				
Manufacturer :				

Host device ¹⁾:				
Description :				
Type :				
Manufacturer :				

¹⁾ if applicable



Product information	Control software ¹⁾: Name : Version : Manufacturer :
	----- Additional remarks:

¹⁾ if applicable



Manufacturer declarations

FCC 15.323 (c) (5):

This device or group of co-operating devices located within 1 meter of each other shall during any frame period occupy more than 6 MHz of aggregate bandwidth, or alternatively more than one third of the time and spectrum windows defined by the system.

Manufacturer agrees: Yes No

FCC 15.323 (c) (12):

This device shall not use the provisions of (c) (10) or (c) (11) to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.

Manufacturer agrees: Yes No

FCC 15.307 (b):

The applicant is a participating member of UTAM, Inc. and will provide a related affidavit from UTAM, Inc. in course of certification.

Confirmation by applicant: Yes No

FCC 15.319 (f) Automatic discontinuation of transmission:

This device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. Automatic break off the transmissions means break off of connection and break of transmissions which are not control and signalling information or repetitive codes of complete frame or burst intervals. In case of devices using basics of DECT technology at least fixed parts and repeaters are using control and signalling information without direct connection without direct connection to their remote station.

Please fill in the table below with the reaction of the EUT (FP and/or PP) using A, B or C.

	Situation	Reaction of EUT		Verdict
		FP	PP	
1	Switch-off counter part			
2	Hook-off by counter part			
3	Switch-off by EUT			
4	Hook-off on EUT side			
5	Remote power from EUT			
6	Remote power from counterpart			

- A – Connection break down, cease of transmit
- B – Connection break down, EUT transmits signalling information
- C – Connection break down, counter part transmits signalling information

¹⁾ if applicable



Supplement	<p>Additional remarks:</p>
	<p>Declared by:</p> <p>Date: Name (print): Signature:</p>

¹⁾ if applicable