

849 NW STATE ROAD 45 NEWBERRY, FL 32669 USA PH: 888.472.2424 OR 352.472.5500 FAX: 352.472.2030 EMAIL: <u>INFO@TIMCOENGR.COM</u> HTTP://WWW.TIMCOENGR.COM

FCC PART 15.235 TEST REPORT

LOW POWER UNLICENSED TRANSMITTER

Applicant	SCIENTIFIC TOYS, LTD.
Address	RM.1108, 11/F., BLOCK B, NEW MANDARIN
	PLAZA 14 SCIENCE MUSEUM ROAD TST EAST
	KOWLOON HONG KONG
FCC ID	BY31775-49SP
Product Description	49 MHz REMOTE CONTROL TRANSMITTER
Date Sample Received	11/9/2009
Date Tested	11/11/2009
Tested By	Richard Block
Approved By	Mario de Aranzeta
Timco Report No.	2702HT9TestReport.doc
Test Results	\square Pass \square Fail

THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.



TABLE OF CONTENTS

GENERAL REMARKS	3
REPORT SUMMARY	4
TEST ENVIRONMENT	4
TEST SETUP	4
DUT SPECIFICATION	5
TEST EQUIPMENT LIST	6
TEST PROCEDURES	7
RADIATION INTERFERENCE	8
OCCUPIED BANDWIDTH	9

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

Summary

The device under test does:

fulfill the general approval requirements as identified in this test report

not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.



Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc. 849 NW State Road 45 Newberry, Fl 32669



Authorized Signatory Name:

Mario de Aranzeta C.E.T. Compliance Engineer/ Lab. Supervisor

Date: 11/10/2009

APPLICANT:SCIENTIFIC TOYS LTD.FCC ID:BY31775-49SPREPORT:Y:\S\SCIENTIF\2702HT9\2702HT9TestReport.doc

Page 3 of 11 mdea 09.20.2007

REPORT SUMMARY

Disclaimer	The test results only relate to the item tested.
Applicable Rule(s)	FCC Pt 15.235, ANSI C63.4: 2003

TEST ENVIRONMENT

Test Facility	The test sites are located at 849 NW State Road 45 Newberry, FL 32669 USA.
Test Condition:	Temperature: 26°C
	Relative humidity: 50%

TEST SETUP

Test Exercise (e.g software description, test signal, etc.):	The DUT was placed in continuous transmit mode of operation.
Deviation from the standard(s)	No deviation from the standard(s)
Modification to the DUT:	No modification was made to the DUT.
Supporting Peripheral Equipment	Not applicable. The device is a stand-alone remote control.

DUT SPECIFICATION

Applicant	SCIENTIFIC TOYS, LTD.					
Description	49 MHz REMOTI	49 MHz REMOTE CONTROL TRANSMITTER				
FCC ID	BY31775-49SP	BY31775-49SP				
Frequency Range	49.86 MHz					
DUT Power Source	110–120Vac/50– 60Hz					
	DC Power					
	Battery Operated Exclusively					
Test Item	Prototype Pre-Production Production					
Type of Equipment	☐ Fixed					

TEST EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3/10-Meter OATS	TEI	N/A	N/A	Listed 1/10/08	1/10/10
3-Meter OATS	TEI	N/A	N/A	Listed 2/5/09	2/5/12
3-Meter Semi- Anechoic Chamber	Panashield	N/A	N/A	Listed 5/11/07	5/10/10
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CAL 11/30/07	11/30/09
Analyzer Tan Tower Quasi- Peak Adapter	HP	85650A	3303A01690	CAL 11/30/07	11/30/09
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 11/30/07	11/30/09
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 11/30/07	11/30/09
Antenna: Biconnical	Eaton	94455-1	1057	CAL 1/15/08	1/15/10
Antenna: Log-Periodic	Eaton	96005	1243	CAL 12/13/07	12/13/09

TEST PROCEDURES

Spurious Emissions: The test procedure used was ANSI C63.4-2003 using a spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was always greater than the RBW. The spectrum was searched to at least the 10th harmonic.

Occupied Bandwidth: A small sample of the transmitter output was fed into the spectrum analyzer and the following plot was generated. The vertical scale is set to 10 dB per division.

Formula Of Conversion Factors: The field strength at 3m was established by adding the meter reading of the spectrum analyzer to the antenna correction factor supplied by the antenna manufacturer plus the coax loss. The antenna correction factors are stated in terms of dB/m. The gain of the preselector was accounted for in the spectrum analyzer reading.

Example:				
Freq	Meter Reading	ACF	Cable Loss	Field Strength
MHz	dBuV	dB/m	dB	dBuV/m @ 3 m
33	20	+10.36	+1.2	= 31.56

ANSI C63.4-2003 Measurement: The DUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The DUT was placed in the center of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the 10th harmonic of the fundamental.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

RADIATION INTERFERENCE

Rules Part No.: 15.235

Requirements:

Frequency MHz	Limits
Fundamental Frequency	80.0 dBµV/m measured @ 3 meters
30 - 88	40.0 dBµV/m measured @ 3 meters
80 - 216	43.5 dBµV/m measured @ 3 meters
216 - 960	46.0 dBµV/m measured @ 3 meters
Above 960	54.0 dBµV/m measured @ 3 meters

Test Data:

Tuned	Emission	Meter	Ant.	Coax	Correction	Field	Margin
Frequency	Frequency	Reading	Polarity	Loss	Factor dB	Strength	dB
MHz	MHz	dBuV		dB		dBuV/m	
49.9	49.86	37.5	Н	0.50	11.64	49.64	30.36
49.9	49.86	61.6	V	0.50	10.83	72.93	7.07
49.9	99.70	16.9	Н	0.65	10.69	28.24	15.26
49.9	99.70	24.1	V	0.65	11.50	36.25	7.25
49.9	149.50	3.7	Н	0.70	16.06	20.46	23.04
49.9	149.50	5.3	V	0.70	17.18	23.18	20.32
49.9	199.40	4.8	V	0.90	17.22	22.92	20.58
49.9	199.40	5.7	Н	0.90	16.63	23.23	20.27
49.9	249.30	9.6	V	1.00	12.46	23.06	22.94
49.9	249.30	12.7	Н	1.00	12.47	26.17	19.83
49.9	299.10	3.1	V	1.10	14.36	18.56	27.44
49.9	299.10	5.1	Н	1.10	14.36	20.56	25.44
49.9	349.00	6.4	V	1.15	14.60	22.15	23.85
49.9	349.00	6.7	Н	1.15	14.98	22.83	23.17
49.9	398.80	3.3	Н	1.20	16.06	20.56	25.44
49.9	398.80	6.1	V	1.20	15.69	22.99	23.01
49.9	448.70	6.1	Н	1.25	16.89	24.24	21.76
49.9	448.70	10.1	V	1.25	16.56	27.91	18.09
49.9	498.60	2.3	Н	1.30	17.84	21.44	24.56
49.9	498.60	3.4	V	1.30	17.87	22.57	23.43


APPLICANT:SCIENTIFIC TOYS LTD.FCC ID:BY31775-49SPREPORT:Y:\S\SCIENTIF\2702HT9\2702HT9TestReport.doc

OCCUPIED BANDWIDTH

Rules Part No.: 15.235


Requirements: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the un-modulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

Test Data: Please refer to the following plot.



APPLICANT:SCIENTIFIC TOYS LTD.FCC ID:BY31775-49SPREPORT:Y:\S\SCIENTIF\2702HT9\2702HT9TestReport.doc

RADIATED EMISSIONS TEST SETUP PHOTO



APPLICANT:SCIENTIFIC TOYS LTD.FCC ID:BY31775-49SPREPORT:Y:\S\SCIENTIF\2702HT9\2702HT9TestReport.doc

Page 10 of 11 mdea 09.20.2007