



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR 352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

FCC PART 15.235 TEST REPORT

LOW POWER UNLICENSED TRANSMITTER

| | |
|-----------------------------|---|
| Applicant | SCIENTIFIC TOYS, LTD. |
| Address | RM.1108, 11/F., BLOCK B, NEW MANDARIN PLAZA 14 SCIENCE MUSEUM ROAD TST EAST KOWLOON HONG KONG |
| FCC ID | BY34204-49PP |
| Product Description | 49 MHZ REMOTE CONTROL TRANSMITTER |
| Date Sample Received | 5/19/2011 |
| Date Tested | May 19, 2011 |
| Tested By | Mario de Aranzeta |
| Approved By | Mario de Aranzeta |
| Timco Report No. | 1082UT11TestReport.doc |
| Test Results | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail |

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



Certificate # 0955-01



TABLE OF CONTENTS

GENERAL REMARKS..... 3
REPORT SUMMARY 4
TEST ENVIRONMENT..... 4
TEST SETUP..... 4
DUT SPECIFICATION 5
TEST EQUIPMENT LIST 6
TEST PROCEDURES 7
RADIATION INTERFERENCE..... 8
OCCUPIED BANDWIDTH..... 9

APPLICANT: SCIENTIFIC TOYS, LTD.
FCC ID: BY34204-49PP
REPORT: S\SCIENTIF\1082UT11\1082UT11TestReport.doc

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report
 not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.



Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, Fl 32669

Authorized Signatory Name:



Mario de Aranzeta C.E.T.
Compliance Engineer/ Lab. Supervisor

Date: May 19, 2011

APPLICANT: SCIENTIFIC TOYS, LTD.
FCC ID: BY34204-49PP
REPORT: S\SCIENTIF\1082UT11\1082UT11TestReport.doc

REPORT SUMMARY

| | |
|--------------------|--|
| Disclaimer | The test results only relate to the item tested. |
| Applicable Rule(s) | FCC Pt 15.235, ANSI C63.4: 2003 |

TEST ENVIRONMENT

| | |
|-----------------|--|
| Test Facility | The test sites are located at 849 NW State Road 45 Newberry, FL 32669 USA. |
| Test Condition: | Temperature: 26°C Relative humidity: 50% |

TEST SETUP

| | |
|--|--|
| Test Exercise (e.g software description, test signal, etc.): | The DUT was placed in continuous transmit mode of operation. |
| Deviation from the standard(s) | No deviation from the standard(s) |
| Modification to the DUT: | No modification was made to the DUT. |
| Supporting Peripheral Equipment | Not applicable. The device is a stand-alone remote control. |

DUT SPECIFICATION

| | | | |
|-------------------|--|--|--|
| Applicant | SCIENTIFIC TOYS, LTD. | | |
| Description | 49 MHZ REMOTE CONTROL TRANSMITTER | | |
| FCC ID | BY34204-49PP | | |
| Frequency Range | 49.86 MHz | | |
| DUT Power Source | <input type="checkbox"/> 110-120Vac/50- 60Hz | | |
| | <input type="checkbox"/> DC Power | | |
| | <input checked="" type="checkbox"/> Battery Operated Exclusively | | |
| Test Item | <input type="checkbox"/> Prototype | <input checked="" type="checkbox"/> Pre-Production | <input type="checkbox"/> Production |
| Type of Equipment | <input type="checkbox"/> Fixed | <input type="checkbox"/> Mobile | <input checked="" type="checkbox"/> Portable |

APPLICANT: SCIENTIFIC TOYS, LTD.
 FCC ID: BY34204-49PP
 REPORT: S\SCIENTIF\1082UT11\1082UT11TestReport.doc

TEST EQUIPMENT LIST

| Device | Manufacturer | Model | Serial Number | Cal/Char Date | Due Date |
|---------------------------------------|--------------------|---------------|--------------------------|-------------------|----------|
| 3-Meter Semi-Anechoic Chamber | Panashield | N/A | N/A | Listed 3/10/10 | 3/10/12 |
| Antenna: Dipole Kit | Electro-Metrics | TDA-30/1-4 | 153 | CHAR 6/10/09 | 6/10/11 |
| Antenna: Passive Loop | EMC Test Systems | EMCO 6512 | 9706-1211 | CAL. 6/1/09 | 6/2/11 |
| Frequency Counter | HP | 5385A | 2730A03025 | CAL 8/4/09 | 8/4/11 |
| Hygro-Thermometer | Extech | 445703 | 0602 | CAL 1/30/10 | 1/30/12 |
| Modulation Analyzer | HP | 8901A | 3435A06868 | CAL 5/26/09 | 5/26/11 |
| Digital Multimeter | Fluke | FLUKE-77-3 | 79510405 | CAL 5/18/09 | 5/18/11 |
| Analyzer Tan Tower Preamplifier | HP | 8449B-H02 | 3008A00372 | CAL 11/21/09 | 11/21/11 |
| Analyzer Tan Tower Quasi-Peak Adapter | HP | 85650A | 3303A01690 | CAL 11/22/09 | 11/22/11 |
| Analyzer Tan Tower RF Preselector | HP | 85685A | 3221A01400 | CAL 11/21/09 | 11/21/11 |
| Analyzer Tan Tower Spectrum Analyzer | HP | 8566B Opt 462 | 3138A07786 3144A20661 | CAL 11/24/09 | 11/24/11 |
| Temperature Chamber | Tenney Engineering | TTRC | 11717-7 | CHAR 4/25/10 | 4/25/12 |

APPLICANT: SCIENTIFIC TOYS, LTD.
 FCC ID: BY34204-49PP
 REPORT: S\SCIENTIF\1082UT11\1082UT11TestReport.doc

TEST PROCEDURES

Spurious Emissions: The test procedure used was ANSI C63.4-2003 using a spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was always greater than the RBW. The spectrum was searched to at least the 10th harmonic.

Occupied Bandwidth: A small sample of the transmitter output was fed into the spectrum analyzer and the following plot was generated. The vertical scale is set to 10 dB per division.

Formula Of Conversion Factors: The field strength at 3m was established by adding the meter reading of the spectrum analyzer to the antenna correction factor supplied by the antenna manufacturer plus the coax loss. The antenna correction factors are stated in terms of dB/m. The gain of the preselector was accounted for in the spectrum analyzer reading.

Example:

| Freq MHz | Meter Reading dB μ V | ACF dB/m | Cable Loss dB | Field Strength dB μ V/m @ 3 m |
|-------------|-----------------------------|-------------|------------------|--------------------------------------|
| 33 | 20 | +10.36 | +1.2 | = 31.56 |

ANSI C63.4-2003 Measurement: The DUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The DUT was placed in the center of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the 10th harmonic of the fundamental.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

RADIATION INTERFERENCE

Rules Part No.: 15.235

Requirements:

| Frequency MHz | Limits |
|-----------------------|---------------------------------------|
| Fundamental Frequency | 80.0 dB μ V/m measured @ 3 meters |
| 30 – 88 | 40.0 dB μ V/m measured @ 3 meters |
| 80 – 216 | 43.5 dB μ V/m measured @ 3 meters |
| 216 – 960 | 46.0 dB μ V/m measured @ 3 meters |
| Above 960 | 54.0 dB μ V/m measured @ 3 meters |

Test Data:

| Tuned Frequency MHz | Emission Frequency MHz | Meter Reading dB μ V | Ant. Polarity | Coax Loss dB | Correction Factor dB/m | Field Strength dB μ V/m | Margin dB |
|---------------------|------------------------|--------------------------|---------------|--------------|------------------------|-----------------------------|-----------|
| 49.9 | 49.80 | 49.5 | H | 0.50 | 10.90 | 60.90 | 19.10 |
| 49.9 | 49.80 | 58.5 | V | 0.50 | 10.78 | 69.78 | 10.22 |
| 49.9 | 99.70 | 22.2 | H | 0.65 | 11.19 | 34.04 | 9.46 |
| 49.9 | 99.70 | 26.8 | V | 0.65 | 11.63 | 39.08 | 4.42 |
| 49.9 | 149.60 | 16.1 | V | 0.70 | 14.24 | 31.04 | 12.46 |
| 49.9 | 149.60 | 16.5 | H | 0.70 | 13.87 | 31.07 | 12.43 |
| 49.9 | 199.40 | 14.1 | H | 0.90 | 17.02 | 32.02 | 11.48 |
| 49.9 | 199.40 | 16.3 | V | 0.90 | 17.05 | 34.25 | 9.25 |
| 49.9 | 249.30 | 17.5 | H | 1.00 | 12.85 | 31.35 | 14.65 |
| 49.9 | 249.30 | 26.4 | V | 1.00 | 12.85 | 40.25 | 5.75 |
| 49.9 | 299.10 | 8.0 | V | 1.10 | 14.56 | 23.66 | 22.34 |
| 49.9 | 349.00 | 9.2 | H | 1.15 | 15.00 | 25.35 | 20.65 |
| 49.9 | 349.00 | 14.2 | V | 1.15 | 15.00 | 30.35 | 15.65 |
| 49.9 | 398.90 | 12.4 | V | 1.20 | 16.28 | 29.88 | 16.12 |
| 49.9 | 448.70 | 9.8 | H | 1.25 | 17.51 | 28.56 | 17.44 |
| 49.9 | 448.70 | 13.8 | V | 1.25 | 17.51 | 32.56 | 13.44 |
| 49.9 | 498.60 | 9.3 | H | 1.30 | 18.27 | 28.87 | 17.13 |
| 49.9 | 498.60 | 14.9 | V | 1.30 | 18.27 | 34.47 | 11.53 |

APPLICANT: SCIENTIFIC TOYS, LTD.
 FCC ID: BY34204-49PP
 REPORT: S\SCIENTIF\1082UT11\1082UT11TestReport.doc


OCCUPIED BANDWIDTH

Rules Part No.: 15.235

Requirements: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the un-modulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

Test Data: Please refer to the following plot.

NOTES:



APPLICANT: SCIENTIFIC TOYS, LTD.
 FCC ID: BY34204-49PP
 REPORT: S\SCIENTIF\1082UT11\1082UT11TestReport.doc