

## INTERTEK TESTING SERVICES

---

### RF Exposure

The Equipment under Test (EUT) is a Car unit for R/C VEHICLE model: BY35102-24GR operating at 2.4GHz band. It is powered by 1 x DC 9.6V rechargeable battery. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -14.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -14.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 81.0dB $\mu$ V/m at 3m in the frequency 2480MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -14.23dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 78.4dB $\mu$ V/m at 3m in the frequency 2440MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -16.83dBm

which is within the production variation.

The maximum conducted output power specified is -11.0dBm = 0.08mW

The source- based time-averaging conducted output power

= 0.08\* Duty cycle mW <0.1 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 \* 5 / sqrt (2.480) mW

= 9.5 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 14.9565ms

Effective period of the cycle = 2.5217ms

DC = 2.5217ms / 14.9565ms = 0.1686 or 16.86%