

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an Toys Controller (TX) operating at 2.4G Band. The EUT can be powered by DC 3.0V (2 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -16.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -16.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 78.7dB μ V/m at 3m in the frequency 2402MHz

The EIRP = [(FS*D) ^2 / 30] mW = -16.53dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 78.6dB μ V/m at 3m in the frequency 2480MHz

The EIRP = [(FS*D) ^2 / 30] mW = -16.63dBm

which is within the production variation.

The maximum conducted output power specified is -13.0dBm= 0.050mW

The source- based time-averaging conducted output power

=0.050* Duty cycle mW <0.050 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.480) mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 8.4638ms

Effective period of the cycle = 1362.3 μ s x1 = 1.3623ms

DC =1.3623ms / 8.4638ms =0.1610 or 16.10%

FCC ID: BY35284-24GT