

TABLE OF CONTENTS LIST

APPLICANT: Scientific Toys Ltd.

FCC ID: BY3E892

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST AND TEST PROCEDURE
PAGE 2.....TEST PROCEDURE CONTD. & CIRCUIT DESCRIPTION
PAGE 3.....RADIATION INTERFERENCE TEST DATA
PAGE 4.....OCCUPIED BANDWIDTH TEST DATA

EXHIBITS CONTAINING:

EXHIBIT 1.....POWER OF ATTORNEY LETTER
EXHIBIT 2.....BLOCK DIAGRAM
EXHIBIT 3.....SCHEMATIC
EXHIBIT 4A-4B.....INSTRUCTION MANUAL
EXHIBIT 5.....SAMPLE OF FCC ID LABEL AND LOCATION
EXHIBIT 6.....EXTERNAL PHOTO - FRONT SIDE
EXHIBIT 7.....EXTERNAL PHOTO - BACK SIDE
EXHIBIT 8.....INTERNAL PHOTO - COMPONENT SIDE
EXHIBIT 9.....INTERNAL PHOTO - COPPER SIDE
EXHIBIT 10.....INTERNAL PHOTO - COPPER SIDE CHASSIS VIEW
EXHIBIT 11.....OCCUPIED BANDWIDTH PLOT - CW

APPLICANT: Scientific Toys Ltd.

FCC ID: BY3E892

REPORT #: T:\CUS\S\SCIENTIF\SCI83H0\SCI83H0.RPT

PAGE: TABLE OF CONTENTS LIST

APPLICANT: Scientific Toys Ltd.
FCC ID: BY3E892

TEST EQUIPMENT LIST

1. X Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/
preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter
HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02,
S/N 3008A00372 Cal. 10/17/99
2. X Signal Generator: HP 8640B, S/N 2308A21464 Cal. 9/23/99
3. Signal Generator: HP 8614A, S/N 2015A07428 Cal. 5/29/99
4. Passive Loop Antenna: EMCO Model 6512, 9KHz to 30MHz, S/N
9706-1211 Cal. 6/23/97
5. X Biconnical Antenna: Eaton Model 94455-1, S/N 1057
6. X Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632
7. Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153
Cal. 11/24/99
8. Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180,
1-18 GHz, S/N 2319 Cal. 4/27/99
9. Horn 40-60GHz: ATM Part #19-443-6R
10. Line Impedance Stabilization Network: Electro-Metrics Model
ANS-25/2, S/N 2604 Cal. 2/9/00
11. Line Impedance Stabilization Network: Electro-Metrics Model
EM-7820, S/N 2682 Cal. 12/1/99
12. Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7
13. AC Voltmeter: HP Model 400FL, S/N 2213A14499 Cal. 9/21/99
14. Digital Multimeter: Fluke Model 8012A, S/N 4810047 Cal 9/21/99
15. Digital Multimeter: Fluke Model 77, S/N 43850817 Cal 9/21/99
16. Oscilloscope: Tektronix Model 2230, S/N 300572 Cal 9/23/99
17. Frequency Counter: HP Model 5385A, S/N 3242A07460 Cal 10/6/99

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without
the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD
C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a prese-
lector. The bandwidth of the spectrum analyzer was 100 kHz with an
appropriate sweep speed. The analyzer was calibrated in dB above a
microvolt at the output of the antenna. The resolution bandwidth was
100KHz and the video bandwidth was 300KHz. The ambient temperature of
the UUT was 80oF with a humidity of 76%.

APPLICANT: Scientific Toys Ltd.
FCC ID: BY3E892
REPORT #: T:\CUS\S\SCIENTIF\SCI83H0\SCI83H0.RPT
PAGE: 1

APPLICANT: Scientific Toys Ltd.
FCC ID: BY3E892

TEST PROCEDURES CONTINUED

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

CIRCUIT DESCRIPTION:

The circuit is activated by the action of the paddle switches which make ground contact for the battery. This allows the proper current to be supplied to Q1 the crystal oscillator and Q2 the modulator/buffer. Zener diode ZD1 reduces the voltage from the battery to supply the proper voltage level to U1. The modulation to base of Q2 is supplied by U1. The different modulation patterns are generated by U1 using the different actions of the paddle switches. Pin 8 of U1 is the modulation output. C8, C9, C10 and L3 provide the output impedance match to the antenna and harmonics suppression.

ANTENNA AND GROUND CIRCUITRY

This unit makes use of a external 5" antenna. The antenna is inductively coupled. This unit is powered from a 9.0V battery.

No ground connection is provided. The unit relies on the ground tract of the printed circuit board.

REPORT #: T:\CUS\S\SCIENTIF\SCI83H0\SCI83H0.RPT
PAGE #: 2

APPLICANT: Scientific Toys Ltd.

FCC ID: BY3E892

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.235

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 80 dBuV/m AT 3M.
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz	40.0 dBuV/M	MEASURED AT 3 METERS
88 - 216 MHz	43.5 dBuV/M	
216 - 960 MHz	46.0 dBuV/M	
ABOVE 960 MHz	54.0 dBuV/M	

TEST DATA:

EMISSION FREQUENCY MHz	METER READING AT 3 METERS dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR dB	PEAK FIELD STRENGTH dBuV/m@3m	MARGIN dB	ANT. POL.
49.90	61.80	0.25	11.00	73.05	6.95	V
99.80	24.70	0.80	8.34	33.84	9.66	H
149.70	11.80	0.80	16.90	29.50	14.00	V
249.50	15.20	1.20	13.36	29.76	16.24	H
299.40	11.50	1.40	15.66	28.56	17.44	H
399.20	20.00	1.40	16.98	38.38	7.62	H
449.10	9.20	1.60	18.13	28.93	17.07	V
499.00	8.40	1.60	19.28	29.28	16.72	V

SAMPLE CALCULATION: $FSdBuV/m = MR(dBuV) + ACFdB.$

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: S. S. SANDERS

DATE: March 20, 2000

APPLICANT: Scientific Toys Ltd.

FCC ID: BY3E892

REPORT #: T:\CUS\S\SCIENTIF\SCI83H0\SCI83H0.RPT

PAGE #: 3

APPLICANT: Scientific Toys Ltd.
FCC ID: BY3E892
NAME OF TEST: Occupied Bandwidth
RULES PART NO.: 15.235
REQUIREMENTS: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

THE GRAPH IN EXHIBIT 11 REPRESENT THE EMISSIONS TAKEN FOR THE DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was taken. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: S. S. SANDERS

DATE: March 20, 2000

APPLICANT: Scientific Toys Ltd.
FCC ID: BY3E892
REPORT #: T:\CUS\S\SCIENTIF\SCI83H0\SCI83H0.RPT
PAGE #: 4