

TABLE OF CONTENTS

APPLICANT: SCIENTIFIC TOYS, LTD.

FCC ID: BY3E893

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST AND TEST PROCEDURE
PAGE 2.....TEST PROCEDURE CONTD.
PAGE 3.....RADIATION INTERFERENCE TEST DATA
PAGE 4.....OCCUPIED BANDWIDTH TEST DATA
PAGE 5.....OCCUPIED BANDWIDTH PLOT

EXHIBITS CONTAINING:

EXHIBIT 1.....BLOCK DIAGRAM
EXHIBIT 2.....SCHEMATIC
EXHIBIT 3A-B.....INSTRUCTION MANUAL
EXHIBIT 4.....SAMPLE OF FCC ID LABEL
EXHIBIT 5.....LOCATION OF FCC ID LABEL
EXHIBIT 6.....EXTERNAL PHOTO - FRONT SIDE
EXHIBIT 7.....EXTERNAL PHOTO - BACK SIDE
EXHIBIT 8.....INTERNAL PHOTO - COMPONENT SIDE
EXHIBIT 9.....INTERNAL PHOTO - COPPER SIDE
EXHIBIT 10.....CIRCUIT DESCRIPTION
EXHIBIT 11.....TEST SET UP PHOTO

APPLICANT: SCIENTIFIC TOYS, LTD.

FCC ID: BY3E893

REPORT #: S\SCIENTIF\542H1\542H1RPT.doc

PAGE: TABLE OF CONTENTS LIST

APPLICANT: SCIENTIFIC TOYS, LTD.
FCC ID: BY3E893

TEST EQUIPMENT LIST

1. Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/
preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter
HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02,
S/N 3008A00372 Cal. 10/17/99
2. Biconnical Antenna: Eaton Model 94455-1, S/N 1057
3. Biconnical Antenna: Electro-Metrics Model BIA-25, S/N 1171
4. Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632
5. Log-Periodic Antenna: Electro-Metrics Model LPA-30, S/N 409
6. Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180,
1-18 GHz, S/N 2319
7. 18-26.3GHz Systron Donner Standard Gain Horn #DBE-520-20
8. Horn 40-60GHz: ATM Part #19-443-6R
9. Line Impedance Stabilization Network: Electro-Metrics Model
ANS-25/2, S/N 2604 Cal. 2/9/00
10. Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7
11. Frequency Counter: HP Model 5385A, S/N 3242A07460 Cal 10/6/99
12. Peak Power Meter: HP Model 8900C, S/N 2131A00545
13. Open Area Test Site #1-3meters Cal. 12/22/99
14. Signal Generator: HP 8640B, S/N 2308A21464 Cal. 9/23/99
15. Signal Generator: HP 8614A, S/N 2015A07428
16. Passive Loop Antenna: EMCO Model 6512, 9KHz to 30MHz, S/N
9706-1211 Cal. 6/10/00
17. Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153
Cal. 11/24/99
18. AC Voltmeter: HP Model 400FL, S/N 2213A14499 Cal. 9/21/99
19. Digital Multimeter: Fluke Model 8012A, S/N 4810047 Cal 9/21/99
20. Digital Multimeter: Fluke Model 77, S/N 43850817 Cal 9/21/99
21. Oscilloscope: Tektronix Model 2230, S/N 300572 Cal 9/23/99

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was 94° with a humidity of 20%.

APPLICANT: SCIENTIFIC TOYS, LTD.
FCC ID: BY3E893
REPORT #: S\SCIENTIF\542H1\542H1RPT.doc
PAGE #: 1

APPLICANT: SCIENTIFIC TOYS, LTD.
FCC ID: BY3E893

TEST PROCEDURES CONTINUED

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

| | |
|------------|--|
| Freq (MHz) | METER READING + ACF = FS |
| 33 | 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m |

ANTENNA AND GROUND CIRCUITRY

This unit makes use of a short, antenna. The antenna is inductively coupled. The antenna is self contained, no provision is made for an external antenna. This unit is powered from a 9.0V battery.

No ground connection is provided. The unit relies on the ground tract of the printed circuit board.

APPLICANT: SCIENTIFIC TOYS, LTD.
FCC ID: BY3E893
REPORT #: S\SCIENTIF\542H1\542H1RPT.doc
PAGE #: 2

APPLICANT: SCIENTIFIC TOYS, LTD.

FCC ID: BY3E893

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.227

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 80 dBuV/m AT 3M.
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

| | |
|---------------|----------------------------------|
| 30 - 88 MHz | 40.0 dBuV/M MEASURED AT 3 METERS |
| 88 - 216 MHz | 43.5 dBuV/M |
| 216 - 960 MHz | 46.0 dBuV/M |
| ABOVE 960 MHz | 54.0 dBuV/M |

TEST DATA:

| Emission Frequency MHz | Meter Reading dBuV | Ant. Polarity | Coax Loss dB | Correction Factor dB | Field Strength dBuV/m | Margin dB |
|------------------------|--------------------|---------------|--------------|----------------------|-----------------------|-----------|
| 27.20 | 64.5 | V | 0.60 | 10.25 | 75.35 | 4.65 |
| 54.40 | 27.9 | V | 0.90 | 7.75 | 36.55 | 3.45 |
| 81.60 | 16.9 | H | 1.10 | 12.90 | 30.90 | 9.10 |
| 108.80 | 13.5 | V | 1.30 | 11.35 | 26.15 | 17.35 |
| 136.10 | 3.0 | H | 1.40 | 16.90 | 21.30 | 22.20 |
| 163.30 | 3.0 | H | 1.60 | 16.67 | 21.27 | 22.23 |
| 190.50 | 3.0 | H | 1.80 | 12.60 | 17.40 | 26.10 |
| 217.70 | 3.0 | H | 2.00 | 12.40 | 17.40 | 28.60 |
| 244.90 | 3.0 | H | 2.00 | 14.40 | 19.40 | 26.60 |
| 272.20 | 3.0 | H | 2.20 | 15.30 | 20.50 | 25.50 |

SAMPLE CALCULATION: $FSdBuV/m = MR(dBuV) + ACFdB$.

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: JOSEPH SCOGLIO

DATE: MAY 18, 2001

APPLICANT: SCIENTIFIC TOYS, LTD.

FCC ID: BY3E893

REPORT #: S\SCIENTIF\542H1\542H1RPT.doc

PAGE #: 3

APPLICANT: SCIENTIFIC TOYS, LTD.
FCC ID: BY3E893
NAME OF TEST: Occupied Bandwidth
RULES PART NO.: 15.227
REQUIREMENTS: The field strength of any emissions appearing outside the 26.96-27.28 MHz band shall not exceed the general radiated emission limits in (15.209).

THE GRAPH ON THE FOLLOWING PAGE REPRESENTS THE WORSE CASE OCCUPIED BANDWIDTH EMISSIONS FOR THIS DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was taken. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: JOSEPH SCOGLIO

DATE : MAY 18, 2001

APPLICANT: SCIENTIFIC TOYS, LTD.
FCC ID: BY3E893
REPORT #: S\SCIENTIF\542H1\542H1RPT.doc
PAGE #: 4


MKR 27.14495 MHz
55.00 dB μ V

hp REF 56.0 dB μ V ATTEN 10 dB +0 dB

10 dB/

OFFSET
-20.0
dB

SCIENTIFIC TOYS, LTD.
JOB #: 542H1
FCC ID : BY3E893
PAGE : 5



CENTER 27.14495 MHz RES BW 300 Hz VBW 100 kHz SWP 1.0 sec SPAN 50.00 kHz