

RF EXPOSURE REPORT

CERTIFICATE OF CONFORMITY

FCC Rule Part: FCC Part 2 (Section 2.1091)

Report No.: MFBEOA-WTW-P23080341

FCC ID: BYG-HDR19

Product: HD RADIO/FM-RDS/AM/BLUETOOTH/AUX PREMIUM WOODEN CABINET RADIO

Brand: SANGEAN

Model No.: HDR-19

Received Date: 2023/8/16

Test Date: 2023/8/31 **Issued Date**: 2023/9/20

Applicant: Sangean Electronics Inc.

Address: No. 18, Lane 7, Li-De Street, Chung Ho District, New Taipei City, 235, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan **Test Location:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

FCC Registration / 198487 / TW2021

Designation Number:

Jeremy Lin / Project Engineer

This test report consists of 9 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.





Prepared by: Jessica Cheng / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at https://www.bureauveritas.com/home/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Report No.: MFBEOA-WTW-P23080341 Page No. 1 / 9 Report Format Version: 7.1.0 Reference No.: BEOA-WTW-P23080341



Table of Contents

Relea	se Control Record	3
1	Certificate	4
	Applicable RF Exposure Limit	
	Test Results	
4	Conclusion	8
5	Information of the Testing Laboratories	6



Release Control Record

Issue No.	Description	Date Issued
MFBEOA-WTW-P23080341	Original release.	2023/9/20

Report No.: MFBEOA-WTW-P23080341 Page No. 3 / 9 Report Format Version: 7.1.0 Reference No.: BEOA-WTW-P23080341



Report Format Version: 7.1.0

Certificate

HD RADIO/FM-RDS/AM/BLUETOOTH/AUX PREMIUM WOODEN CABINET RADIO Product:

Brand: **SANGEAN**

Test Model: HDR-19

Sample Status: Engineering sample

> Applicant: Sangean Electronics Inc.

Test Date: 2023/8/31

FCC Rule Part: FCC Part 2 (Section 2.1091)

KDB 447498 D04 Interim General RF Exposure Guidance v01 Standard:

The above equipment has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Report No.: MFBEOA-WTW-P23080341 Page No. 4 / 9

Reference No.: BEOA-WTW-P23080341



2 Applicable RF Exposure Limit

- § 1.1310 Radiofrequency radiation exposure limits.
- (a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).
- (b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatialaverage SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.
- (c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

(e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)					
Limits For General Population / Uncontrolled Exposure									
0.3-1.34	614	1.63	(100)*	30					
1.34-30	824/f	2.19/f	(180/f ²)*	30					
30-300	27.5	0.073	0.2	30					
300-1500			f/1500	30					
1500-100,000			1.0	30					

f = frequency in MHz. * = Plane-wave equivalent power density.

Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
0.3-3.0	614	1.63	*(100)	≤6				
3.0-30	1842/f	4.89/f	*(900/f²)	<6				
30-300	61.4	0.163	1.0	<6				
300-1,500			f/300	<6				
1,500-100,000			5	<6				

f = frequency in MHz. * = Plane-wave equivalent power density.

Report No.: MFBEOA-WTW-P23080341 Page No. 5 / 9 Report Format Version: 7.1.0 Reference No.: BEOA-WTW-P23080341



Report Format Version: 7.1.0

MPE-based Exemption - §1.1307(b)(3)(i)(C)

The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.

Table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance

criteria for each of the five frequency ranges used for the MPE limits.

DE Course fraguesey (MHz)	Minimum	Distance	Throphold CDD (wette)		
RF Source frequency (MHz)	λ∟/ 2π	λн/ 2π	Threshold ERP (watts)		
0.3-1.34	159 m–35.6 m 35.6 m–1.6 m 1.6 m–159 mm		1,920 R².		
1.34-30			3,450 R ² /f ² .		
30-300			3.83 R ² .		
300-1,500	159 mm-	0.0128 R ² f.			
1,500-100,000	31.8 mm	–0.5 mm	19.2 R ^{2.}		
R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.					

Report No.: MFBEOA-WTW-P23080341 Page No. 6 / 9



3 Test Results

Environmental 25°C, 76% RH	Tested By:	Waydi Tuan
----------------------------	------------	------------

MPE-based Exemption §1.1307(b)(3)(i)(C)							
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result
Bluetooth	2402-2480	1.361	-0.25	0.783	20	768	Pass

Report No.: MFBEOA-WTW-P23080341 Page No. 7 / 9 Report Format Version: 7.1.0 Reference No.: BEOA-WTW-P23080341



4 Conclusion

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

Report No.: MFBEOA-WTW-P23080341 Page No. 8 / 9 Report Format Version: 7.1.0 Reference No.: BEOA-WTW-P23080341



5 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180 Fax: 886-2-26051924

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@bureauveritas.com Web Site: http://ee.bureauveritas.com.tw

The address and road map of all our labs can be found in our web site also.

--- END ---

Report No.: MFBEOA-WTW-P23080341 Reference No.: BEOA-WTW-P23080341

Page No. 9 / 9