

# RF EXPOSURE REPORT

Applicant	Sagean Electronics Inc
Address	No 18, Lane 7, Li-De Street, Chung Ho District, New Taipei City, Taiwan


Manufacturer or Supplier	SANGEAN ELECTRONICS (DONGGUAN) LIMITED
Address	No.1 Riverside street, Shishuikou section, Lianhu Road, Qiaotou town, Dongguan city, Guangdong province P.R.C
Product	INTERNET RADIO/INTERNET DAB/AUX/ BLUETOOTH/SPOTIFY CONNECT/CLOUD MUSIC/AIRMUSIC APP DIGITAL WOODEN RADIO
Brand Name	SANGEAN
Model	WFR-32
Additional Model & Model Difference	N/A
Date of tests	Sep. 29, 2020 ~ Feb. 04, 2021

- FCC Part 2 (Section 2.1091)
- KDB 447498 D01
- IEEE C95.1

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Tested by Tom Chen  
Project Engineer / EMC Department

Approved by Glyn He  
Assistant Manager / EMC Department




Date: Jul. 22, 2021

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <https://www.cps.bureauveritas.com/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



## TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT .....	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION .....	5
5. ANTENNA GAIN .....	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



**BUREAU  
VERITAS**

Test Report No.: FM2009WDG0226

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM2009WDG0226	Original release	Jul. 22, 2021

Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie  
Town, Dongguan City, Guangdong Province.  
523942. People's Republic of China.

Tel: +86 769 8998 2098  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@bureauveritas.com](mailto:customerservice.dg@bureauveritas.com)



## 1. CERTIFICATION

<b>FCC ID:</b>	BYG-WFR32
<b>PRODUCT:</b>	INTERNET RADIO/INTERNET DAB/AUX/ BLUETOOTH/SPOTIFY CONNECT/CLOUD MUSIC/AIRMUSIC APP DIGITAL WOODEN RADIO
<b>BRAND NAME:</b>	N/A
<b>MODEL NO.:</b>	WFR-32
<b>ADDITIONAL NO.:</b>	N/A
<b>TEST SAMPLE:</b>	Engineering Sample
<b>APPLICANT:</b>	SANGEAN ELECTRONICS (DONGGUAN) LIMITED
<b>STANDARDS:</b>	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1



## 2. RF EXPOSURE LIMIT

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm <sup>2</sup> )	AVERAGE TIME (minutes)
<b>LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE</b>				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

## 3. MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

## 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



## 5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Mode	Peak Gain (dBi)	Antenna Type
BT	0	PCB
WIFI	2.55	Integral

## 6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
BT (GFSK)	2402-2480MHz	2	+1	1	3
BT (8DPSK)	2402-2480MHz	2	+1	1	3
802.11b	2412-2462MHz	15	+1	14	16
802.11g	2412-2462MHz	11	+1	10	12
802.11n HT20	2412-2462MHz	11	+1	10	12
802.11n HT40	2422-2452MHz	11	+1	10	12

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
BT (GFSK)	2402	2.58
BT (8DPSK)	2402	2.45
802.11b	2412	15.11
802.11g	2437	11.10
802.11n HT20	2437	11.06
802.11n HT40	2422	10.98



FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
BT 2402-2480	3	0	20	0.0004	1.0
WiFi 2412-2462	16	2.55	20	0.01425	1.0

**CONCLUSION:**

The BT and WLAN can transmit simultaneously, the formula of calculated the MPE is:

**CPD1 / LPD1 + CPD2 / LPD2 + .....etc. < 1**

**CPD = Calculation power density**

**LPD = Limit of power density**

$(0.0004/1)+(0.01425/1) = 0.01465 < 1$ , which is less than the “1” limit.

--- END ---