

FCC Part 15 EMI TEST REPORT

of

E.U.T. : FM RDS/INTERNET
CLOCK RADIO

FCC ID. : BYG013

MODEL : RCR-7WF; RCR-8WF

for

APPLICANT : SANGEAN ELECTRONICS INC.

ADDRESS : NO.18, LANE7, LI-DE STREET, CHUNG
HO CITY, TAIPEI HSIEN, 235, TAIWAN,
R.O.C.

Test Performed by

ELECTRONICS TESTING CENTER, TAIWAN

NO.34, LIN 5, DINGFU TSUEN, LINKOU SHIANG

TAIPEI COUNTY, TAIWAN, 24442, R.O.C.

Tel : (02)26023052 Fax : (02)26010910

<http://www.etc.org.tw> ; e-mail: emc@etc.org.tw

Report Number : 09-02-RBF-033-04

TEST REPORT CERTIFICATION

Applicant : SANGEAN ELECTRONICS INC.
NO.18, LANE7, LI-DE STREET, CHUNG HO CITY, TAIPEI HSIEN,
235, TAIWAN, R.O.C.

Manufacturer : SANGEAN ELECTRONICS INC.
NO.18, LANE7, LI-DE STREET, CHUNG HO CITY, TAIPEI HSIEN,
235, TAIWAN, R.O.C.

Description of EUT

- a) Type of EUT : FM RDS/INTERNET CLOCK RADIO
- b) Trade Name : SANGEAN
- c) Model No. : RCR-7WF; RCR-8WF
- d) Power Supply : AC 100-240 volts 50-60Hz

Regulation Applied : FCC Rules and Regulations Part 15 Subpart C (2008)

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.4, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.


- Note: 1. The result of the testing report relate only to the item tested.
2. The testing report shall not be reproduced expect in full, without the written approval of ETC.

Date Test Item Received : Feb. 17, 2009

Date Test Campaign Completed : Mar. 02, 2009


Date of Issue : Mar. 16, 2009

Test Engineer :



(Vincent Chang)

Approve & Authorized Signer :



Will Yauo, Manager
EMC Dept. II of ELECTRONICS
TESTING CENTER, TAIWAN

Table of Contents	Page
1 GENERAL INFORMATION	1
1.1 Product Description.....	1
1.2 Characteristics of Device	1
1.3 Test Methodology	1
1.4 Test Facility.....	1
2 PROVISIONS APPLICABLE	2
2.1 Definition	2
2.2 Requirement for Compliance	3
2.3 Restricted Bands of Operation	5
2.4 Labeling Requirement.....	5
2.5 User Information	6
3. SYSTEM TEST CONFIGURATION	7
3.1 Justification	7
3.2 Devices for Tested System.....	7
4 RADIATED EMISSION MEASUREMENT.....	8
4.1 Applicable Standard.....	8
4.2 Measurement Procedure.....	8
4.3 Measuring Instrument	10
4.4 Radiated Emission Data	11
4.5 Field Strength Calculation	23
4.6 Photos of Radiation Measuring Setup.....	24
5 CONDUCTED EMISSION MEASUREMENT	25
5.1 Standard Applicable.....	25
5.2 Measurement Procedure.....	25
5.3 Conducted Emission Data	26
5.4 Result Data Calculation	40
5.5 Conducted Measurement Equipment.....	40
5.6 Photos of Conduction Measuring Setup.....	41
6 ANTENNA REQUIREMENT	42
6.1 Standard Applicable.....	42
6.2 Antenna Construction and Directional Gain.....	42
7 EMISSION BANDWIDTH MEASUREMENT	43
7.1 Standard Applicable.....	43
7.2 Measurement Procedure.....	43

7.3 Measurement Equipment	43
7.4 Measurement Data	44
8 OUTPUT POWER MEASUREMENT	51
8.1 Standard Applicable	51
8.2 Measurement Procedure	51
8.3 Measurement Equipment	51
8.4 Measurement Data	52
9 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT	59
9.1 Standard Applicable	59
9.2 Measurement Procedure	59
9.3 Measurement Equipment	59
9.4 Measurement Data	60
10 POWER DENSITY MEASUREMENT	65
10.1 Standard Applicable	65
10.2 Measurement Procedure	65
10.3 Measurement Equipment	65
10.4 Measurement Data	66
11. OUT-OF-BAND CONDUCTED EMISSION MEASUREMENT	73
11.1 Standard Applicable	73
11.2 Measurement Procedure	73
11.3 Measurement Equipment	73
11.4 Measurement Data	74

1 GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : FM RDS/INTERNET CLOCK RADIO
- b) Trade Name : SANGEAN
- c) Model No. : RCR-7WF; RCR-8WF
- d) Power Supply : AC 100-240 volts 50-60Hz
- e) Model difference : RCR-7WF supports USB, SD card reader and RJ-45 Ethernet
declared by the manufacturer while RCR-8WF has no such interfaces.

1.2 Characteristics of Device

Power: AC 100-240 volts, 50-60Hz.

Connectivity: Wired Ethernet Wi-Fi 10/100M bits/sec via RJ-45.

802.11b and 802.11g supported.

WEP and WPA encryption supported.

1.3 Test Methodology

Both conducted and radiated emissions were performed according to the procedures illustrated in ANSI C63.4 (2003). Other required measurements were illustrated in separate sections of this test report for details.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at NO.34, LIN 5, DINGFU TSUEN, LINKOU SHIANG TAIPEI COUNTY, TAIWAN, 24442, R.O.C.

This site has been fully described in a report submitted to your office, and accepted in a letter dated Aug. 05, 2008

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device:

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business of industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

* Decreases with the logarithm of the frequency

(2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

(4) Bandwidth Requirement

For direct sequence system, according to 15.247(a)(2), the minimum 6dB bandwidth shall be at least 500 kHz.

(5) Output Power Requirement

For direct sequence system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(6) 100 kHz Bandwidth of Frequency Band Edges Requirement

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

(7) Power Density Requirement

According to 15.247(d), for direct sequence systems, the transmitted power density averaged over any 1 second interval shall not be greater than 8 dBm in any 3 kHz bandwidth within these bands.

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.15
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3360-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions : (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.

- Increase the separation between the equipment and receiver.

- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

- Consult the dealer or an experienced radio / TV technician for help.

3. SYSTEM TEST CONFIGURATION

3.1 Justification

For both radiated and conducted emissions below 1 GHz, the system was configured for testing in a typical fashion as a customer would normally use it. The peripherals other than EUT were connected in normally standing by situation. Measurement was performed under the condition that a computer program was exercised to simulate data communication of EUT, and the transmission rate was set to maximum allowed by EUT. Three highest emissions were verified with varying placement of the transmitting antenna connected to EUT to maximize the emission from EUT.

For conducted emissions, only measured on TX and RX operation, for the digital circuits portion also function normally whenever TX or RX is operated. For radiated emissions, whichever RF channel is operated, the digital circuits function identically. As the reason, measurement of radiated emissions from digital circuits is only performed with channel 7 by transmitting mode.

During the preliminary test, the worse case is the antenna with a cable, and data presented in this test report just shows the worse case.

3.2 Devices for Tested System

Device	Manufacture	Model / FCC ID.	Cable Description
FM	SANGEAN	RCR-7WF; RCR-8WF	1.5m Unshielded AC Adaptor
RDS/INTERNET	ELECTRONICS	/ BYG013	Power Cord
CLOCK RADIO	INC.		0.8m Unshielded RJ-45 Cable
*			
Speaker	ACER	N/A	0.8m Unshielded AC Power Line
			0.8m Unshielded Audio Cable
Walkman	AIWA	HS-TS193	0.8m Unshielded Audio Cable
Earphone	PHILIPS	N/A	0.8m Unshielded Earphone Line
iPod	Apple	A1051	1.0m Unshielded Line
USB 256MB	My Flash	256MB	----
Card			
SD Card	Canon	16MB	----

Remark “*” means equipment under test.

4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with §15.109(a).

For intentional radiators, according to §15.247 (a), operation under this provision is limited to frequency hopping and direct sequence spread spectrum, and the out band emission shall be comply with §15.247 (c)

4.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the placement of cables associated with EUT to obtain the worse case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement:

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Test Receiver	Rohde & Schwarz	ESCI	2009/02/04	2010/02/04
EMI Test Receiver	Rohde & Schwarz	ESCS 30	2008/09/03	2009/09/02
Log-periodic Antenna	EMCO	3146	2008/10/08	2009/10/08
Biconical Antenna	EMCO	3110B	2008/09/16	2009/09/16
Double Ridged Antenna	EMCO	3115	2008/05/14	2009/05/14
Amplifier	HP	8449B	2008/12/05	2009/12/05
Amplifier	HP	83051A	2008/05/23	2009/05/23
Amplifier	HP	8447D	2008/05/16	2009/05/16
Spectrum	Rohde & Schwarz	FSP40	2008/09/11	2009/09/11

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

4.4 Radiated Emission Data

4.4.1 RF Portion

A. Channel Low(802.11b)

Operation Mode : Transmitting

Fundamental Frequency : 2412.000 MHz

Test Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m)		Limit @3m (dBUV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
4824.000	42.1	***	43.8	***	2.6	46.4	***	74.0	54.0	-7.6	182	1.0
7236.000	---	---	---	---	5.8	---	---	74.0	54.0	---	---	---
9648.000	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
12060.000	---	---	---	---	9.2	---	---	74.0	54.0	---	---	---
14472.000	---	---	---	---	11.6	---	---	74.0	54.0	---	---	---
16884.000	---	---	---	---	12.1	---	---	74.0	54.0	---	---	---
19296.000	---	---	---	---	8.8	---	---	74.0	54.0	---	---	---
21708.000	---	---	---	---	9.8	---	---	74.0	54.0	---	---	---
24120.000	---	---	---	---	10.4	---	---	74.0	54.0	---	---	---

Operation Mode : Receiving

Fundamental Frequency : Local Frequency : 2412.000 MHz

Test Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m)		Limit @3m (dBUV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
* 2412.000	---	---	---	---	-3.0	---	---	74.0	54.0	---	---	---
* 4824.000	---	---	---	---	2.6	---	---	74.0	54.0	---	---	---
* 7236.000	---	---	---	---	5.8	---	---	74.0	54.0	---	---	---
* 9648.000	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
* 12060.000	---	---	---	---	9.2	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "****" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

B. Channel Middle(802.11b)Operation Mode : TransmittingFundamental Frequency : 2437.000 MHzTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4874.000	42.3	***	43.8	***	2.7	46.5	***	74.0	54.0	-7.5	175	1.0
7311.000	---	---	---	---	5.9	---	---	74.0	54.0	---	---	---
9748.000	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
12185.000	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---
14622.000	---	---	---	---	11.6	---	---	74.0	54.0	---	---	---
17059.000	---	---	---	---	13.1	---	---	74.0	54.0	---	---	---
19496.000	---	---	---	---	8.5	---	---	74.0	54.0	---	---	---
21933.000	---	---	---	---	9.9	---	---	74.0	54.0	---	---	---
24370.000	---	---	---	---	10.7	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2437.000 MHzTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2437.000	---	---	---	---	-2.9	---	---	74.0	54.0	---	---	---
* 4874.000	---	---	---	---	2.7	---	---	74.0	54.0	---	---	---
* 7311.000	---	---	---	---	5.9	---	---	74.0	54.0	---	---	---
* 9748.000	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
* 12185.000	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "****" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

C. Channel High(802.11b)Operation Mode : TransmittingFundamental Frequency : 2462.000 MHzTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
4924.000	42.4	***	43.9	***	2.8	46.7	***	74.0	54.0	-7.3	178	1.0
7386.000	---	---	---	---	6.0	---	---	74.0	54.0	---	---	---
9848.000	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
12310.000	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---
14772.000	---	---	---	---	11.5	---	---	74.0	54.0	---	---	---
17234.000	---	---	---	---	14.3	---	---	74.0	54.0	---	---	---
19696.000	---	---	---	---	8.5	---	---	74.0	54.0	---	---	---
22158.000	---	---	---	---	10.0	---	---	74.0	54.0	---	---	---
24620.000	---	---	---	---	10.9	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2462.000 MHzTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 60 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
* 2462.000	---	---	---	---	-2.8	---	---	74.0	54.0	---	---	---
* 4924.000	---	---	---	---	2.8	---	---	74.0	54.0	---	---	---
* 7386.000	---	---	---	---	6.0	---	---	74.0	54.0	---	---	---
* 9848.000	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
* 12310.000	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "****" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

D. Channel Low(802.11g)Operation Mode : TransmittingFundamental Frequency : 2412.000 MHzTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4824.000	42.3	***	43.1	***	2.6	45.7	***	74.0	54.0	-8.3	175	1.0
7236.000	---	---	---	---	5.8	---	---	74.0	54.0	---	---	---
9648.000	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
12060.000	---	---	---	---	9.2	---	---	74.0	54.0	---	---	---
14472.000	---	---	---	---	11.6	---	---	74.0	54.0	---	---	---
16884.000	---	---	---	---	12.1	---	---	74.0	54.0	---	---	---
19296.000	---	---	---	---	8.8	---	---	74.0	54.0	---	---	---
21708.000	---	---	---	---	9.8	---	---	74.0	54.0	---	---	---
24120.000	---	---	---	---	10.4	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2412.000 MHzTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2412.000	---	---	---	---	-3.0	---	---	74.0	54.0	---	---	---
* 4824.000	---	---	---	---	2.6	---	---	74.0	54.0	---	---	---
* 7236.000	---	---	---	---	5.8	---	---	74.0	54.0	---	---	---
* 9648.000	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
* 12060.000	---	---	---	---	9.2	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark “***” means that Peak result is meet average limit.
3. Remark “---” means that the emissions level is too low to be measured.
4. Remark “*” means the local oscillator frequency and its harmonics.
5. Item “Margin” referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

E. Channel Middle(802.11g)Operation Mode : TransmittingFundamental Frequency : 2437.000 MHzTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4874.000	42.4	***	43.8	***	2.7	46.5	***	74.0	54.0	-7.5	192	1.0
7311.000	---	---	---	---	5.9	---	---	74.0	54.0	---	---	---
9748.000	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
12185.000	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---
14622.000	---	---	---	---	11.6	---	---	74.0	54.0	---	---	---
17059.000	---	---	---	---	13.1	---	---	74.0	54.0	---	---	---
19496.000	---	---	---	---	8.5	---	---	74.0	54.0	---	---	---
21933.000	---	---	---	---	9.9	---	---	74.0	54.0	---	---	---
24370.000	---	---	---	---	10.7	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2437.000 MHzTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2437.000	---	---	---	---	-2.9	---	---	74.0	54.0	---	---	---
* 4874.000	---	---	---	---	2.7	---	---	74.0	54.0	---	---	---
* 7311.000	---	---	---	---	5.9	---	---	74.0	54.0	---	---	---
* 9748.000	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
* 12185.000	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "****" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

F. Channel High(802.11g)Operation Mode : TransmittingFundamental Frequency : 2462.000 MHzTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4924.000	42.9	***	43.9	***	2.8	46.7	***	74.0	54.0	-7.3	177	1.0
7386.000	---	---	---	---	6.0	---	---	74.0	54.0	---	---	---
9848.000	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
12310.000	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---
14772.000	---	---	---	---	11.5	---	---	74.0	54.0	---	---	---
17234.000	---	---	---	---	14.3	---	---	74.0	54.0	---	---	---
19696.000	---	---	---	---	8.5	---	---	74.0	54.0	---	---	---
22158.000	---	---	---	---	10.0	---	---	74.0	54.0	---	---	---
24620.000	---	---	---	---	10.9	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2462.000 MHzTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2462.000	---	---	---	---	-2.8	---	---	74.0	54.0	---	---	---
* 4924.000	---	---	---	---	2.8	---	---	74.0	54.0	---	---	---
* 7386.000	---	---	---	---	6.0	---	---	74.0	54.0	---	---	---
* 9848.000	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
* 12310.000	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark “***” means that Peak result is meet average limit.
3. Remark “---” means that the emissions level is too low to be measured.
4. Remark “*” means the local oscillator frequency and its harmonics.
5. Item “Margin” referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

4.4.2 Radiated Emission of Restricted bands**A. 802.11b**Test Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %**Operation Mode : CH 01****Restricted Frequency band: 2310MHz – 2390MHz**

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.			
2318.520	41.1	***	43.0	***	-3.4	39.6	***	74.0	54.0	-14.4	178	1.5
2375.920	41.8	***	43.5	***	-3.2	40.3	***	74.0	54.0	-13.7	182	1.5

Operation Mode : CH 11**Restricted Frequency band: 2483.5MHz – 2500MHz**

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.			
2488.920	41.5	***	43.4	***	-2.7	40.7	***	74.0	54.0	-13.3	178	1.5
2491.150	42.3	***	44.7	***	-2.7	42.0	***	74.0	54.0	-12.0	175	1.5

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark “***” means that Peak result is meet average limit.
3. Remark “---” means that the emissions level is too low to be measured.
4. Item “Margin” referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.

B. 802.11gTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %**Operation Mode : CH 01 Restricted Frequency band: 2310MHz – 2390MHz**

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.			
2341.920	42.1	---	43.4	---	-3.3	40.1	---	74.0	54.0	-13.9	175	1.0
2359.190	41.8	---	42.9	---	-3.2	39.7	---	74.0	54.0	-14.3	188	1.0

Operation Mode : CH 11 Restricted Frequency band: 2483.5MHz – 2500MHz

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.			
2485.910	42.2	---	43.4	---	-2.8	40.6	---	74.0	54.0	-13.4	192	1.0
2492.190	42.4	---	43.9	---	-2.7	41.2	---	74.0	54.0	-12.8	174	1.0

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark “***” means that Peak result is meet average limit.
3. Remark “---” means that the emissions level is too low to be measured.
4. Item “Margin” referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.

4.4.3 Other Emission

a) Emission frequencies below 1 GHz

Operation Mode : 802.11B

Test Date : Feb. 12, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
171.460	H	32.8	-9.0	23.8	43.5	-19.7	62	1.5
174.990	H	35.1	-9.0	26.1	43.5	-17.4	72	1.5
180.130	H	35.4	-9.1	26.3	43.5	-17.2	92	1.5
287.720	H	31.3	-2.2	29.1	46.0	-16.9	78	1.5
349.000	H	43.1	-10.3	32.8	46.0	-13.2	62	1.5
478.500	H	34.4	-4.5	29.9	46.0	-16.1	74	1.5

Operation Mode : 802.11G

Test Date : Feb. 12, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
171.460	V	32.5	-9.0	23.5	43.5	-20.0	175	1.0
174.990	H	35.4	-9.0	26.4	43.5	-17.1	92	1.5
180.130	H	35.6	-9.1	26.5	43.5	-17.0	78	1.5
287.720	H	31.4	-2.2	29.2	46.0	-16.8	92	1.5
349.000	H	44.5	-10.3	34.2	46.0	-11.8	78	1.5
399.400	V	37.8	-6.4	31.4	46.0	-14.6	182	1.0

Note :

1. Remark “---” means that the emissions level is too low to be measured.
2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

b) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 25 GHz were too low to be measured with a pre-amplifier of 35 dB.

c) Emission frequencies below 1 GHz

Operation Mode : USB ModeTest Date : Feb. 12, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
37.320	V	40.0	-11.3	28.7	40.0	-11.3	178	1.0
131.350	V	39.3	-11.4	27.9	43.5	-15.6	192	1.0
180.130	H	35.4	-9.1	26.3	43.5	-17.2	83	1.5
199.920	H	35.1	-7.1	28.0	43.5	-15.5	92	1.5
349.000	H	43.1	-10.3	32.8	46.0	-13.2	75	1.5
719.300	V	31.1	-0.8	30.3	46.0	-15.7	175	1.0

Operation Mode : SD ModeTest Date : Feb. 12, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
34.070	V	39.3	-10.6	28.7	40.0	-11.3	175	1.0
42.470	V	40.9	-12.4	28.5	40.0	-11.5	182	1.0
137.050	V	38.3	-11.0	27.3	43.5	-16.2	192	1.0
199.920	H	35.5	-7.1	28.4	43.5	-15.1	75	1.5
349.000	H	44.3	-10.3	34.0	46.0	-12.0	76	1.5
399.400	H	37.4	-6.4	31.0	46.0	-15.0	78	1.5

Note :

1. Remark "---" means that the emissions level is too low to be measured.
2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

d) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 25 GHz were too low to be measured with a pre-amplifier of 35 dB.

e) Emission frequencies below 1 GHz

Operation Mode : Internet ModeTest Date : Feb. 12, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
95.850	V	42.4	-13.9	28.5	43.5	-15.0	178	1.0
119.700	V	33.4	-10.8	22.6	43.5	-20.9	192	1.0
144.360	V	33.3	-10.5	22.8	43.5	-20.7	178	1.0
168.210	V	33.1	-9.1	24.0	43.5	-19.5	192	1.0
199.920	V	33.3	-7.1	26.2	43.5	-17.3	188	1.0
346.900	V	33.4	-10.0	23.4	46.0	-22.6	175	1.0

Operation Mode : AUX ModeTest Date : Feb. 12, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
95.850	V	42.3	-13.9	28.4	43.5	-15.1	174	1.0
119.700	V	33.2	-10.8	22.4	43.5	-21.1	182	1.0
168.210	V	33.9	-9.1	24.8	43.5	-18.7	192	1.0
199.920	V	33.5	-7.1	26.4	43.5	-17.1	174	1.0
346.900	V	33.1	-10.0	23.1	46.0	-22.9	182	1.0
699.700	V	28.8	-1.0	27.8	46.0	-18.2	192	1.0

Note :

1. Remark "---" means that the emissions level is too low to be measured.
2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

f) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 25 GHz were too low to be measured with a pre-amplifier of 35 dB.

g) Emission frequencies below 1 GHz

Operation Mode : Internet ModeTest Date : Feb. 12, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
35.960	V	34.7	-11.0	23.7	40.0	-16.3	177	1.0
140.030	V	31.1	-10.8	20.3	43.5	-23.2	182	1.0
280.130	V	29.1	-2.7	26.4	46.0	-19.6	192	1.0
349.000	H	38.2	-10.3	27.9	46.0	-18.1	92	1.5
419.000	H	29.3	-5.7	23.6	46.0	-22.4	74	1.5
489.700	H	28.6	-4.4	24.2	46.0	-21.8	75	1.5

Note :

1. Remark “---” means that the emissions level is too low to be measured.
2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

h) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 25 GHz were too low to be measured with a pre-amplifier of 35 dB.

4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\mathbf{Result = Reading + Corrected Factor}$$

where

$$\text{Corrected Factor} = \text{Antenna FACTOR} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

4.6 Photos of Radiation Measuring Setup



5 CONDUCTED EMISSION MEASUREMENT


5.1 Standard Applicable

For unintentional and intentional device, Line Conducted Emission Limits are in accordance to § 15.107(a) and § 15.207(a) respectively. Both Limits are identical specification.

5.2 Measurement Procedure

1. Setup the configuration per figure 3.
2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
3. Record the 6 or 8 highest emissions relative to the limit.
4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then record the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
5. Confirm the highest three emissions with variation of the EUT cable configuration and record the final data.
6. Repeat all above procedures on measuring each operation mode of EUT.

Figure 3 : Conducted emissions measurement configuration



5.3 Conducted Emission Data

Operation Mode : 802.11B

Test Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Mode: 802.11B

N1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.782	42.9	31.2	0.3	43.2	31.5	56.0	46.0	-12.8	-14.5
1.169	42.5	30.8	0.3	42.8	31.1	56.0	46.0	-13.2	-14.9
1.411	41.3	30.4	0.4	41.7	30.8	56.0	46.0	-14.3	-15.2
3.247	40.1	30.4	0.6	40.7	31.0	56.0	46.0	-15.3	-15.0
3.267	41.7	30.7	0.6	42.3	31.3	56.0	46.0	-13.7	-14.7
3.427	40.7	31.4	0.6	41.3	32.0	56.0	46.0	-14.7	-14.0
3.525	40.8	31.4	0.6	41.4	32.0	56.0	46.0	-14.6	-14.0
3.630	40.9	31.6	0.6	41.5	32.2	56.0	46.0	-14.5	-13.8

Mode: 802.11B


L1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
1.126	45.1	31.8	0.3	45.4	32.1	56.0	46.0	-10.6	-13.9
1.810	44.2	31.0	0.5	44.7	31.5	56.0	46.0	-11.3	-14.5
2.017	42.6	31.4	0.5	43.1	31.9	56.0	46.0	-12.9	-14.1
3.267	43.8	31.4	0.6	44.4	32.0	56.0	46.0	-11.6	-14.0
3.314	42.7	31.8	0.6	43.3	32.4	56.0	46.0	-12.7	-13.6
3.368	44.5	30.4	0.6	45.1	31.0	56.0	46.0	-10.9	-15.0
3.392	44.3	30.9	0.6	44.9	31.5	56.0	46.0	-11.1	-14.5
3.528	44.6	30.9	0.6	45.2	31.5	56.0	46.0	-10.8	-14.5
3.618	45.0	31.2	0.6	45.6	31.8	56.0	46.0	-10.4	-14.2

Note : The expanded uncertainty of the conducted emission tests is 2.45 dB


Mode: 802.11B

N1



Mode: 802.11B

L1



Operation Mode : 802.11G

Test Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Mode: 802.11G

N1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
	0.775	42.7		30.4	0.3	43.0	30.7	56.0	46.0
1.017	40.9	30.4	0.3	41.2	30.7	56.0	46.0	-14.8	-15.3
1.403	41.1	30.8	0.4	41.5	31.2	56.0	46.0	-14.5	-14.8
1.790	39.8	31.1	0.5	40.3	31.6	56.0	46.0	-15.7	-14.4
3.216	39.1	30.2	0.6	39.7	30.8	56.0	46.0	-16.3	-15.2
3.321	38.9	30.1	0.6	39.5	30.7	56.0	46.0	-16.5	-15.3

Mode: 802.11G


L1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
	0.763	44.4		31.3	0.3	44.7	31.6	56.0	46.0
1.165	45.3	31.2	0.3	45.6	31.5	56.0	46.0	-10.4	-14.5
1.415	44.1	31.0	0.4	44.5	31.4	56.0	46.0	-11.5	-14.6
1.806	44.0	30.8	0.5	44.5	31.3	56.0	46.0	-11.5	-14.7
3.427	43.9	31.4	0.6	44.5	32.0	56.0	46.0	-11.5	-14.0
3.450	43.9	31.8	0.6	44.5	32.4	56.0	46.0	-11.5	-13.6
3.525	44.8	30.9	0.6	45.4	31.5	56.0	46.0	-10.6	-14.5
3.614	45.0	30.1	0.6	45.6	30.7	56.0	46.0	-10.4	-15.3
3.630	44.9	31.4	0.6	45.5	32.0	56.0	46.0	-10.5	-14.0

Note : The expanded uncertainty of the conducted emission tests is 2.45 dB


Mode: 802.11G

N1



Mode: 802.11G

L1



Operation Mode : USB ModeTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Mode: USB Mode

N1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.505	42.5	31.1	0.3	42.8	31.4	56.0	46.0	-13.2	-14.6
0.763	42.3	30.2	0.3	42.6	30.5	56.0	46.0	-13.4	-15.5
0.778	42.7	31.5	0.3	43.0	31.8	56.0	46.0	-13.0	-14.2
1.028	40.9	31.4	0.3	41.2	31.7	56.0	46.0	-14.8	-14.3
1.435	40.9	31.4	0.4	41.3	31.8	56.0	46.0	-14.7	-14.2
3.458	40.8	31.5	0.6	41.4	32.1	56.0	46.0	-14.6	-13.9
3.505	40.8	31.0	0.6	41.4	31.6	56.0	46.0	-14.6	-14.4
3.548	40.4	31.1	0.6	41.0	31.7	56.0	46.0	-15.0	-14.3

Mode: USB Mode


L1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.513	45.9	31.2	0.3	46.2	31.5	56.0	46.0	-9.8	-14.5
0.751	44.2	31.2	0.3	44.5	31.5	56.0	46.0	-11.5	-14.5
1.134	44.9	30.8	0.3	45.2	31.1	56.0	46.0	-10.8	-14.9
1.403	44.7	30.7	0.4	45.1	31.1	56.0	46.0	-10.9	-14.9
1.821	44.0	31.2	0.5	44.5	31.7	56.0	46.0	-11.5	-14.3
3.349	42.9	31.4	0.6	43.5	32.0	56.0	46.0	-12.5	-14.0
3.372	44.1	31.2	0.6	44.7	31.8	56.0	46.0	-11.3	-14.2
3.556	43.0	31.0	0.6	43.6	31.6	56.0	46.0	-12.4	-14.4
3.802	44.5	31.8	0.6	45.1	32.4	56.0	46.0	-10.9	-13.6

Note : The expanded uncertainty of the conducted emission tests is 2.45 dB


Mode: USB Mode

N1



Mode: USB Mode

L1



Operation Mode : SD Card ModeTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Mode: SD Card Mode

N1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
	0.521	42.9		31.1	0.3	43.2	31.4	56.0	46.0
0.759	42.3	30.3	0.3	42.6	30.6	56.0	46.0	-13.4	-15.4
1.040	40.7	30.4	0.3	41.0	30.7	56.0	46.0	-15.0	-15.3
1.161	41.7	30.5	0.3	42.0	30.8	56.0	46.0	-14.0	-15.2
1.388	41.1	30.1	0.4	41.5	30.5	56.0	46.0	-14.5	-15.5
3.239	40.2	30.1	0.6	40.8	30.7	56.0	46.0	-15.2	-15.3
3.450	40.5	30.8	0.6	41.1	31.4	56.0	46.0	-14.9	-14.6

Mode: SD Card Mode


L1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
	0.521	45.7		30.1	0.3	46.0	30.4	56.0	46.0
0.775	44.8	32.3	0.3	45.1	32.6	56.0	46.0	-10.9	-13.4
1.157	45.2	31.3	0.3	45.5	31.6	56.0	46.0	-10.5	-14.4
1.144	43.0	32.3	0.3	43.3	32.6	56.0	46.0	-12.7	-13.4
1.532	43.0	31.5	0.4	43.4	31.9	56.0	46.0	-12.6	-14.1
1.798	43.9	31.0	0.5	44.4	31.5	56.0	46.0	-11.6	-14.5
1.841	43.6	30.1	0.5	44.1	30.6	56.0	46.0	-11.9	-15.4
3.665	44.6	30.2	0.6	45.2	30.8	56.0	46.0	-10.8	-15.2
3.704	43.6	31.1	0.6	44.2	31.7	56.0	46.0	-11.8	-14.3
3.755	43.6	32.2	0.6	44.2	32.8	56.0	46.0	-11.8	-13.2

Note : The expanded uncertainty of the conducted emission tests is 2.45 dB


Mode: SD Card Mode

N1



Mode: SD Card Mode

L1



Operation Mode : Internet ModeTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Mode: Internet Mode

N1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
	0.525	42.9		30.8	0.3	43.2	31.1	56.0	46.0
0.759	42.4	31.4	0.3	42.7	31.7	56.0	46.0	-13.3	-14.3
0.782	42.4	30.4	0.3	42.7	30.7	56.0	46.0	-13.3	-15.3
1.005	41.4	31.4	0.3	41.7	31.7	56.0	46.0	-14.3	-14.3
1.122	41.6	30.8	0.3	41.9	31.1	56.0	46.0	-14.1	-14.9
3.103	39.7	30.7	0.6	40.3	31.3	56.0	46.0	-15.7	-14.7
3.263	40.1	30.9	0.6	40.7	31.5	56.0	46.0	-15.3	-14.5
3.384	41.4	31.4	0.6	42.0	32.0	56.0	46.0	-14.0	-14.0

Mode: Internet Mode


L1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
	0.513	45.9		30.9	0.3	46.2	31.2	56.0	46.0
1.153	45.4	31.4	0.3	45.7	31.7	56.0	46.0	-10.3	-14.3
1.403	44.7	31.3	0.4	45.1	31.7	56.0	46.0	-10.9	-14.3
3.333	43.5	30.4	0.6	44.1	31.0	56.0	46.0	-11.9	-15.0
3.415	43.0	31.3	0.6	43.6	31.9	56.0	46.0	-12.4	-14.1
3.708	42.0	31.5	0.6	42.6	32.1	56.0	46.0	-13.4	-13.9
3.732	43.1	30.8	0.6	43.7	31.4	56.0	46.0	-12.3	-14.6
3.798	44.5	31.4	0.6	45.1	32.0	56.0	46.0	-10.9	-14.0
3.849	43.8	30.7	0.6	44.4	31.3	56.0	46.0	-11.6	-14.7

Note : The expanded uncertainty of the conducted emission tests is 2.45 dB


Mode: Internet Mode

N1



Mode: Internet Mode

L1



Operation Mode : AUX ModeTest Date : Feb. 19, 2009Temperature : 20 °CHumidity : 65 %

Mode: AUX Mode

N1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
	0.747	42.4		31.5	0.3	42.7	31.8	56.0	46.0
1.130	41.9	31.4	0.3	42.2	31.7	56.0	46.0	-13.8	-14.3
1.153	42.1	31.8	0.3	42.4	32.1	56.0	46.0	-13.6	-13.9
1.173	42.2	30.4	0.3	42.5	30.7	56.0	46.0	-13.5	-15.3
1.380	41.0	30.9	0.4	41.4	31.3	56.0	46.0	-14.6	-14.7
3.396	41.2	31.4	0.6	41.8	32.0	56.0	46.0	-14.2	-14.0
3.489	41.2	30.5	0.6	41.8	31.1	56.0	46.0	-14.2	-14.9
3.536	40.5	31.4	0.6	41.1	32.0	56.0	46.0	-14.9	-14.0

Mode: AUX Mode


L1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
	1.146	45.4		30.8	0.3	45.7	31.1	56.0	46.0
1.751	44.1	31.4	0.5	44.6	31.9	56.0	46.0	-11.4	-14.1
1.782	44.0	30.4	0.5	44.5	30.9	56.0	46.0	-11.5	-15.1
1.833	44.2	30.9	0.5	44.7	31.4	56.0	46.0	-11.3	-14.6
3.357	45.2	30.7	0.6	45.8	31.3	56.0	46.0	-10.2	-14.7
3.474	43.1	30.7	0.6	43.7	31.3	56.0	46.0	-12.3	-14.7
3.501	44.4	30.8	0.6	45.0	31.4	56.0	46.0	-11.0	-14.6
3.614	42.6	31.5	0.6	43.2	32.1	56.0	46.0	-12.8	-13.9

Note : The expanded uncertainty of the conducted emission tests is 2.45 dB


Mode: AUX Mode

N1



Mode: AUX Mode

L1



Operation Mode : FM ModeTest Date : Feb. 19, 2009 Temperature : 20 °C Humidity : 65 %

Mode: FM Mode

N1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
	0.771	42.7		31.3	0.3	43.0	31.6	56.0	46.0
1.427	40.9	31.0	0.4	41.3	31.4	56.0	46.0	-14.7	-14.6
3.150	41.2	30.8	0.6	41.8	31.4	56.0	46.0	-14.2	-14.6
3.192	38.7	30.7	0.6	39.3	31.3	56.0	46.0	-16.7	-14.7
3.239	40.5	30.9	0.6	41.1	31.5	56.0	46.0	-14.9	-14.5
3.263	40.1	31.4	0.6	40.7	32.0	56.0	46.0	-15.3	-14.0
3.501	40.7	30.8	0.6	41.3	31.4	56.0	46.0	-14.7	-14.6

Mode: FM Mode


L1

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
	1.138	44.8		30.9	0.3	45.1	31.2	56.0	46.0
1.388	44.1	31.4	0.4	44.5	31.8	56.0	46.0	-11.5	-14.2
1.431	44.4	30.8	0.4	44.8	31.2	56.0	46.0	-11.2	-14.8
1.763	43.9	31.4	0.5	44.4	31.9	56.0	46.0	-11.6	-14.1
3.278	42.8	30.5	0.6	43.4	31.1	56.0	46.0	-12.6	-14.9
3.345	43.3	30.5	0.6	43.9	31.1	56.0	46.0	-12.1	-14.9
3.403	45.7	31.0	0.6	46.3	31.6	56.0	46.0	-9.7	-14.4
3.646	42.3	31.8	0.6	42.9	32.4	56.0	46.0	-13.1	-13.6

Note : The expanded uncertainty of the conducted emission tests is 2.45 dB


Mode: FM Mode

N1



Mode: FM Mode

L1



5.4 Result Data Calculation

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

$$\mathbf{RESULT = READING + LISN FACTOR}$$

Assume a receiver reading of 22.5 dB μ V is obtained, and LISN Factor is 0.1 dB, then the total of disturbance voltage is 22.6 dB μ V.

$$\text{RESULT} = 22.5 + 0.1 = 22.6 \text{ dB } \mu \text{ V}$$

$$\begin{aligned} \text{Level in } \mu \text{ V} &= \text{Common Antilogarithm}[(22.6 \text{ dB } \mu \text{ V})/20] \\ &= 13.48 \mu \text{ V} \end{aligned}$$

5.5 Conducted Measurement Equipment

The following test equipment are used during the conducted test .

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	ESCI	2009/02/04	2010/02/04
LISN	EMCO	3625/2	2009/02/06	2010/02/06
LISN	Rohde & Schwarz	ESH2-Z5	2008/06/27	2009/06/26

5.6 Photos of Conduction Measuring Setup



6 ANTENNA REQUIREMENT

6.1 Standard Applicable

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to §15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.2 Antenna Construction and Directional Gain

A 4.3 dBi antenna is used. Please see construction Photos of Exhibit B and the antenna specifications of Exhibits L for details.

The conducted output power needs not to be reduced

7 EMISSION BANDWIDTH MEASUREMENT


7.1 Standard Applicable

According to 15.247(a)(2), for direct sequence system, the minimum 6dB bandwidth shall be at least 500 kHz.

7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Figure 4: Emission bandwidth measurement configuration.



7.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2008/09/11	2009/09/11

7.4 Measurement Data

Test Date : Feb. 20, 2009 Temperature : 20 °C Humidity : 65 %


A 802.11b

- a) Channel Low: 6 dB Emission Bandwidth is 8.8 MHz
- b) Channel Mid: 6 dB Emission Bandwidth is 10.1 MHz
- c) Channel High: 6 dB Emission Bandwidth is 10.1 MHz


B 802.11g

- a) Channel Low: 6 dB Emission Bandwidth is 16.5 MHz
- b) Channel Mid: 6 dB Emission Bandwidth is 16.5 MHz
- c) Channel High: 6 dB Emission Bandwidth is 16.5 MHz

Note : The expanded uncertainty of the emission bandwidth tests is 1500Hz.



Date: 20.FEB.2009 03:35:13




Date: 20.FEB.2009 03:35:59


802.11g




*RBW 100 kHz Delta 1 [T1]
*VBW 300 kHz 0.02 dB
Ref 10 dBm Att 30 dB SWT 5 ms 16.500000000 MHz



Date: 20.FEB.2009 03:37:21



Date: 20.FEB.2009 03:38:33



Date: 20.FEB.2009 03:40:16

8 OUTPUT POWER MEASUREMENT


8.1 Standard Applicable

For direct sequence system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz and VBW to 1 MHz.
4. Use channel power function and record the level displayed.
5. Repeat above procedures until all frequencies measured were complete.

Figure 5: Output power and measurement configuration.



8.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2008/09/11	2009/09/11

8.4 Measurement Data

Test Date : Feb. 20, 2009 Temperature : 20 °C Humidity : 65 %

A 802.11b

- a) Channel Low: Output Peak Power is 18.15 dBm **65.313** mW
- b) Channel Mid: Output Peak Power is 18.04 dBm **63.680** mW
- c) Channel High: Output Peak Power is 17.77 dBm **59.841** mW

B 802.11g


- a) Channel Low: Output Peak Power is 15.19 dBm **33.037** mW
- b) Channel Mid: Output Peak Power is 15.36 dBm **34.356** mW
- c) Channel High: Output Peak Power is 15.12 dBm **32.509** mW

Note : The expanded uncertainty of the output power tests is 2dB.


802.11b




* RBW 1 MHz
* VBW 3 MHz
SWT 2.5 ms



Date: 20.FEB.2009 03:32:26



Date: 20.FEB.2009 03:32:55




Date: 20.FEB.2009 03:33:15


802.11g




* RBW 1 MHz
* VBW 3 MHz
SWT 2.5 ms



Date: 20.FEB.2009 03:29:38



Date: 20.FEB.2009 03:30:10



Date: 20.FEB.2009 03:30:41

9 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT

9.1 Standard Applicable

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set both RBW of spectrum analyzer to 100kHz and VBW to 1 MHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

9.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2008/09/11	2009/09/11

9.4 Measurement Data

Test Date : Feb. 20, 2009 Temperature : 20 °C Humidity : 65 %

A 802.11b

- a) Lower Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.
- b) Upper Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.

B 802.11g


- a) Lower Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.
- b) Upper Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.

Note : The expanded uncertainty of the 100 khz bandwidth of band edges tests is 2dB.

802.11b




*RBW 100 kHz Marker 1 [T1]
*VBW 300 kHz -53.09 dBm
Ref 10 dBm Att 30 dB SWT 15 ms 2.360060000 GHz



Date: 20.FEB.2009 03:49:34




Ref 10 dBm Att 30 dB SWT 20 ms
*RBW 100 kHz Marker 1 [T1]
*VBW 300 kHz -56.59 dBm
2.515840000 GHz



Date: 20.FEB.2009 03:50:29



Ref 10 dBm Att 30 dB SWT 20 ms
*RBW 100 kHz Marker 1 [T1]
*VBW 300 kHz -54.98 dBm
2.547200000 GHz



Date: 20.FEB.2009 03:51:21

10 POWER DENSITY MEASUREMENT

10.1 Standard Applicable

According to 15.247(d), for direct sequence systems, the transmitted power density averaged over any 1 second interval shall not be greater than 8 dBm in any 3 kHz bandwidth within these bands.

10.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set EUT to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of spectrum analyzer on highest level appearing on spectral display within a 300 kHz frequency span.
4. Set the spectrum analyzer on a 3 kHz resolution bandwidth and 300 kHz video bandwidth as well as max hold function.
5. Repeat above procedures until all measured frequencies were complete.

10.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2008/09/11	2009/09/11

10.4 Measurement Data

Test Date : Feb. 20, 2009 Temperature : 20 °C Humidity : 65 %

A 802.11b

- a) Channel Low: Maximun Power Density of 3 kHz Bandwidth is -8.18 dBm
- b) Channel Mid: Maximun Power Density of 3 kHz Bandwidth is -9.29 dBm
- c) Channel High: Maximun Power Density of 3 kHz Bandwidth is -8.52 dBm

B 802.11g

- a) Channel Low: Maximun Power Density of 3 kHz Bandwidth is -12.34 dBm
- b) Channel Mid: Maximun Power Density of 3 kHz Bandwidth is -12.08 dBm
- c) Channel High: Maximun Power Density of 3 kHz Bandwidth is -12.51 dBm

Note : The expanded uncertainty of the power density tests is 2dB.


802.11b




*RBW 3 kHz Marker 1 [T1]
*VBW 100 kHz -8.18 dBm
*SWT 100 s 2.410551800 GHz

Ref 10 dBm


Att 30 dB



Date: 20.FEB.2009 03:41:33



Date: 20.FEB.2009 03:42:34



Date: 20.FEB.2009 03:43:47

802.11g




*RBW 3 kHz Marker 1 [T1]
*VBW 100 kHz -12.34 dBm
*SWT 100 s 2.410747600 GHz


Ref 0 dBm

Att 20 dB


1 RM*
VIEW



Date: 20.FEB.2009 03:45:16



Date: 20.FEB.2009 03:46:37



Date: 20.FEB.2009 03:47:51

11. OUT-OF-BAND CONDUCTED EMISSION MEASUREMENT

11.1 Standard Applicable

According to 15.247(c), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

11.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Use the following spectrum analyzer settings:
 - Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
 - RBW = 100 kHz
 - VBW \geq RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold.
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all measured frequencies were complete.

11.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2008/09/11	2009/09/11

11.4 Measurement Data

Test Date : Feb. 20, 2009 Temperature : 20 °C Humidity : 65 %

A 802.11b

Model : Channel Low

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Model : Channel Mid

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Model : Channel High

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Test Date : Feb. 20, 2009 Temperature : 20 °C Humidity : 65 %

B 802.11g**Model : Channel Low**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Model : Channel Mid

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.


Model : Channel High

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Note : The expanded uncertainty of the out-of-band conducted emission tests is 2dB.




*RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz -33.97 dBm
Ref 20 dBm *Att 20 dB SWT 2.2 s 24.824000000 GHz






Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz 10.07 dBm
SWT 200 ms 2.440000000 GHz






Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1] 8.83 dBm
*VBW 100 kHz SWT 200 ms 2.464000000 GHz






Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz -33.01 dBm
SWT 2.2 s 20.248000000 GHz






Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz -33.63 dBm
SWT 2.2 s 24.912000000 GHz






Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz 8.09 dBm
SWT 200 ms 2.440000000 GHz






Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz -33.49 dBm
SWT 2.2 s 24.736000000 GHz





Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz 4.17 dBm
SWT 200 ms 2.460000000 GHz






*RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz -32.95 dBm
SWT 2.2 s 21.700000000 GHz

Ref 20 dBm

*Att 20 dB

1 PK
VIEW



Start 3 GHz

2.2 GHz/

Stop 25 GHz