

FCC MPE Evaluation (FCC ID: BYM7000A)

RF Exposure Requirements:	47 CFR §1.1307(b)
RF Radiation Exposure Limits:	47 CFR §1.1310
RF Radiation Exposure Guidelines:	FCC OST/OET Bulletin Number 65
EUT Frequency Band:	5180-5825MHz
Limits for General Population/Uncontrolled Exposure in the band of:	300 - 1500 MHz
Power Density Limit:	f/1500 mW/cm ²
Limits for General Population/Uncontrolled Exposure in the band of:	1500 - 100,000 MHz
Power Density Limit:	1 mW / cm ²

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$
Where, S = Power Density
P = Power Input to Antenna
G = Antenna Gain
R = distance to the center of radiated antenna

Prediction distance 20 cm

EUT: Base Transceiver

Radio	Frequency (MHz)	Max Conducted Output Power (dBm)	Antenna Gain (dBi)	Separation distance (cm)	Power Density (mW/ cm ²)	MPE Limit (mW/ cm ²)
5GHz	5180-5240	24.69	3	20	0.1169	1
5GHz	5260-5320	22.71	3	20	0.0741	1
5GHz	5500-5720	22.28	3	20	0.0671	1
5GHz	5745-5825	24.04	3	20	0.1006	1

The above results show that the device complies with the MPE requirement.

Completed By: Lining Li

Vista Laboratories, Inc.

1261 Puerta Del Sol, San Clemente, CA 92673

Date: 05/23/2024