		ELECTRONICS INC. Certificate of Calibration		TEST NUMBER 320557
Manufacture	r Hewlett Packard Corp		Report #:	320557
Description:	Analyzer, Spectrum		P.O. #:	48654
Model #:	8594E		Procedure:	SureCal
Serial #:	3325A00532		Asset #:	R-03764
Customer:	HM Electronics			
	14110 Stowe Drive			
	Poway, CA 92064			•
accordance with r constants, consens that corresponds t reported herein ap otherwise noted.C	the above instrument was calibrated in c eferenced procedures. Standards used to standards or derived by the ratio type o a probability of approximately 95%(2s oply only to the calibration of the item de ustomer has been contacted concerning duced, except in full, without the express	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and	re certified by or traceable to N. certanties are determined as re other processwas used for this ons are performed to manufactu documentation has been receiv	IST, natural physical equired with a distribution calibration, the results urer's specifications, unless
accordance with r constants, consensi- that corresponds to reported herein ap otherwise noted. C shall not be repro- Condition Re Condition Re Femperature	eferenced procedures. Standards used to us standards or derived by the ratio type o a probability of approximately 95%(2s puly only to the calibration of the item de ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techma	re certified by or traceable to N. certanties are determined as re other processwas used for this ons are performed to manufactu documentation has been receiv	IST, natural physical equired with a distribution calibration, the results urer's specifications, unless
accordance with r constants, consensi- that corresponds to reported herein ap otherwise noted. C shall not be repro- Condition Re Condition Re Temperature	eferenced procedures. Standards used to us standards or derived by the ratio type o a probability of approximately 95%(2s puly only to the calibration of the item de ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techma d Problem	re certified by or traceable to N. certanties are determined as re other processwas used for this of ions are performed to manufact documentation has been receiv asterElectronics. Calibration Cycle: Calibration Date: Next Due Date: Certified By:	IST, natural physical equired with a distribution calibration, the results were's specifications, unless and and is on file. This form 12 Months 04/14/2011 04/14/2012
accordance with r constants, consensi- that corresponds to reported herein ap otherwise noted. C shall not be repro- Condition Re Condition Re Temperature	eferenced procedures. Standards used to hus standards or derived by the ratio type o a probability of approximately 95%(2s oply only to the calibration of the item de ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Notee turned: In Tolerance : 23° C hidity: 45%	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techmu d Problem <u>Standards Uti</u>	re certified by or traceable to N. cortanties are determined as re other processwas used for this of ons are performed to manufactu documentation has been receiv asterElectronics. Calibration Cycle: Calibration Date: Next Due Date: Certified By: Lized	IIST, natural physical equired with a distribution calibration, the results urer's specifications, unless red and is on file. This form 12 Months 04/14/2011 04/14/2012 Williamson, Breeanne
accordance with r constants, consen- that corresponds to reported herein ap otherwise noted. C shall not be repro- condition Re Condition Re Condition Re Relative Hun	eferenced procedures. Standards used to us standards or derived by the ratio type o a probability of approximately 95%(2s puly only to the calibration of the item de ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techma d Problem	re certified by or traceable to N. certanties are determined as re other processwas used for this of ions are performed to manufact documentation has been receiv asterElectronics. Calibration Cycle: Calibration Date: Next Due Date: Certified By:	IST, natural physical equired with a distribution calibration, the results were's specifications, unless and and is on file. This form 12 Months 04/14/2011 04/14/2012
accordance with r constants, consens that corresponds to reported herein ap otherwise noted. C shall not be reprov Condition Re Condition Re Condition Re Relative Hun <u>Standard #</u>	eferenced procedures. Standards used to hus standards or derived by the ratio type o a probability of approximately 95%(2s oply only to the calibration of the item de ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C hidity: 45% <u>Manufacturer</u>	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techmu d Problem <u>Standards Util</u> <u>Model #</u>	re certified by or traceable to N. certanties are determined as re other processwas used for this ions are performed to manufact documentation has been receiv asterElectronics. Calibration Cycle: Calibration Date: Next Due Date: Certified By: lized	IIST, natural physical equired with a distribution calibration, the results were's specifications, unless and and is on file. This form 12 Months 04/14/2011 04/14/2012 Williamson, Breeanne <u>Test Report #</u>
accordance with r constants, consen- that corresponds to reported herein ap otherwise noted. C shall not be reprod Condition Re Condition Re Condition Re Condition Re Standard # 5401	eferenced procedures. Standards used to hus standards or derived by the ratio type o a probability of approximately 95%(2s oply only to the calibration of the item de ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C hidity: 45% <u>Manufacturer</u> Hewlett Packard Corp	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techmu d Problem <u>Standards Util</u> <u>Model #</u> 8482A	re certified by or traceable to N. cortanties are determined as re other processwas used for this of ons are performed to manufactu documentation has been receiv asterElectronics. Calibration Cycle: Calibration Date: Next Due Date: Certified By: <u>Due Date</u> 7/15/2011	IIST, natural physical equired with a distribution calibration, the results were's specifications, unless and and is on file. This form 12 Months 04/14/2011 04/14/2012 Williamson, Breeanne <u>Test Report #</u> 306458
accordance with r constants, consen- that corresponds to reported herein ap otherwise noted. C shall not be reprod Condition Re Condition Re Condition Re Relative Hum <u>Standard #</u> 5401 5428 5240 5345	eferenced procedures. Standards used to hus standards or derived by the ratio type o a probability of approximately 95%(2s oply only to the calibration of the item de ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C hidity: 45% <u>Manufacturer</u> Hewlett Packard Corp Hewlett Packard Corp Hewlett Packard Corp Hewlett Packard Corp Hewlett Packard Corp Hewlett Packard Corp	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techmu d Problem <u>Standards Util</u> <u>Model #</u> 8482A 8565E 83650B 436A	re certified by or traceable to N. cortanties are determined as re- other processwas used for this of ions are performed to manufactu- documentation has been receive asterElectronics. Calibration Dycle: Calibration Date: Next Due Date: Certified By: <u>Due Date</u> 7/15/2011 1/28/2012 6/7/2011 3/23/2012	IST, natural physical equired with a distribution calibration, the results urer's specifications, unless red and is on file. This form 12 Months 04/14/2011 04/14/2012 Williamson, Breeanne <u>Test Report #</u> 306458 315260 303538 320280
accordance with r constants, consen- that corresponds to reported herein ap otherwise noted. C shall not be reprod Condition Re Condition Re Condition Re Relative Hun Standard # 5401 5428 5240 5345 5492	eferenced procedures. Standards used to hus standards or derived by the ratio type of a probability of approximately 95%(2s oply only to the calibration of the item def ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C hidity: 45% <u>Manufacturer</u> Hewlett Packard Corp Hewlett Packard Corp	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techma d Problem <u>Standards Util</u> <u>Model #</u> 8482A 8565E 83650B 436A 8116A	re certified by or traceable to N. cortanties are determined as re- other processwas used for this of ions are performed to manufactu- documentation has been receive asterElectronics. Calibration Date: Calibration Date: Next Due Date: Certified By: <u>Due Date</u> 7/15/2011 1/28/2012 6/7/2011 3/23/2012 11/11/2011	IST, natural physical equired with a distribution calibration, the results urer's specifications, unless red and is on file. This form 12 Months 04/14/2011 04/14/2012 Williamson, Breeanne Test Report # 306458 315260 303538 320280 312658
accordance with r constants, consen- that corresponds to reported herein ap otherwise noted. C shall not be reprov Condition Re Condition Re Condition Re Relative Hun Standard # 5401 5428 5240 5345 5492 801	eferenced procedures. Standards used to hus standards or derived by the ratio type of a probability of approximately 95%(2s oply only to the calibration of the item de ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C hidity: 45% <u>Manufacturer</u> Hewlett Packard Corp Hewlett Packard Corp	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techmu d Problem <u>Standards Util</u> <u>Model #</u> 8482A 8565E 83650B 436A 8116A 8487A	re certified by or traceable to N. cortanties are determined as re- other processwas used for this of ions are performed to manufactu- documentation has been receive asterElectronics. Calibration Date: Calibration Date: Next Due Date: Certified By: <u>Due Date</u> 7/15/2011 1/28/2012 6/7/2011 3/23/2012 11/11/2011 4/6/2012	IST, natural physical equired with a distribution calibration, the results urer's specifications, unless red and is on file. This form 12 Months 04/14/2011 04/14/2012 Williamson, Breeanne <u>Test Report #</u> 306458 315260 303538 320280 312658 321056
accordance with r constants, consen- that corresponds to reported herein ap otherwise noted. C shall not be reprov Condition Re Condition Re Condition Re Relative Hum Standard # 5401 5428 5240 5345 5492 801 5349	eferenced procedures. Standards used to hus standards or derived by the ratio type of a probability of approximately 95%(2s only to the calibration of the item defended ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C hidity: 45% <u>Manufacturer</u> Hewlett Packard Corp Hewlett Packard Corp	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techmu d Problem <u>Standards Util</u> <u>Model #</u> 8482A 8565E 83650B 436A 8116A 8487A 3335A	re certified by or traceable to N. cortanties are determined as re- other processwas used for this of ons are performed to manufactu- documentation has been receive asterElectronics. Calibration Date: Next Due Date: Certified By: <u>Due Date</u> 7/15/2011 1/28/2012 6/7/2011 3/23/2012 11/11/2011 4/6/2012 4/19/2011	IST, natural physical equired with a distribution calibration, the results urer's specifications, unless red and is on file. This form 12 Months 04/14/2011 04/14/2012 Williamson, Breeanne <u>Test Report #</u> 306458 315260 303538 320280 312658 321056 281968
accordance with r constants, consen- that corresponds to reported herein ap otherwise noted. C shall not be reprov Condition Re Condition Re Condition Re Relative Hun Standard # 5401 5428 5240 5345 5492 801	eferenced procedures. Standards used to hus standards or derived by the ratio type of a probability of approximately 95%(2s oply only to the calibration of the item de ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C hidity: 45% <u>Manufacturer</u> Hewlett Packard Corp Hewlett Packard Corp	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techmu d Problem <u>Standards Util</u> <u>Model #</u> 8482A 8565E 83650B 436A 8116A 8487A	re certified by or traceable to N. cortanties are determined as re- other processwas used for this of ions are performed to manufactu- documentation has been receive asterElectronics. Calibration Date: Calibration Date: Next Due Date: Certified By: <u>Due Date</u> 7/15/2011 1/28/2012 6/7/2011 3/23/2012 11/11/2011 4/6/2012	IST, natural physical equired with a distribution calibration, the results urer's specifications, unless red and is on file. This form 12 Months 04/14/2011 04/14/2012 Williamson, Breeanne <u>Test Report #</u> 306458 315260 303538 320280 312658 321056
accordance with r constants, consen- that corresponds to reported herein ap otherwise noted. C shall not be reprov Condition Re Condition Re Condition Re Relative Hum Standard # 5401 5428 5240 5345 5492 801 5349 5501	eferenced procedures. Standards used to hus standards or derived by the ratio type of a probability of approximately 95%(2s only to the calibration of the item defended ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C hidity: 45% <u>Manufacturer</u> Hewlett Packard Corp Hewlett Packard Corp	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techmu d Problem <u>Standards Util</u> <u>Model #</u> 8482A 8565E 83650B 436A 8116A 8487A 3335A 53132A	re certified by or traceable to N. cortanties are determined as re- other processwas used for this of ons are performed to manufactu- documentation has been receive asterElectronics. Calibration Cycle: Calibration Date: Next Due Date: Certified By: <u>Due Date</u> 7/15/2011 1/28/2012 6/7/2011 3/23/2012 11/11/2011 4/6/2012 4/19/2011 12/7/2011	IST, natural physical equired with a distribution calibration, the results urer's specifications, unless red and is on file. This form 12 Months 04/14/2011 04/14/2012 Williamson, Breeanne <u>Test Report #</u> 306458 315260 303538 320280 312658 321056 281968 314200
accordance with r constants, consen- that corresponds to reported herein ap otherwise noted. C shall not be reprov Condition Re Condition Re Condition Re Condition Re Relative Hum Standard # 5401 5428 5240 5345 5492 801 5349 5501 5347 760 5403	eferenced procedures. Standards used to hus standards or derived by the ratio type of a probability of approximately 95%(2s only only to the calibration of the item defended ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C didity: 45% <u>Manufacturer</u> Hewlett Packard Corp Hewlett Packard Corp	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techmu d Problem <u>Standards Util</u> <u>Model #</u> 8482A 8565E 83650B 436A 8116A 8487A 3335A 53132A 8484A 8340B 11667B	re certified by or traceable to N. cortanties are determined as re- other processwas used for this of ions are performed to manufactu- documentation has been receive asterElectronics. Calibration Cycle: Calibration Date: Next Due Date: Certified By:	IST, natural physical equired with a distribution calibration, the results urer's specifications, unless red and is on file. This form 12 Months 04/14/2011 04/14/2012 Williamson, Breeanne Test Report # 306458 315260 303538 320280 312658 321056 281968 314200 320990
accordance with r constants, consen- that corresponds to reported herein ap otherwise noted. C shall not be reprov Condition Re Condition Re Condition Re Condition Re Relative Hum Standard # 5401 5428 5240 5345 5492 801 5349 5501 5347 760	eferenced procedures. Standards used to hus standards or derived by the ratio type of a probability of approximately 95%(2s only only to the calibration of the item defended ustomer has been contacted concerning duced, except in full, without the express ceived: Customer Noted turned: In Tolerance : 23° C didity: 45% <u>Manufacturer</u> Hewlett Packard Corp Hewlett Packard Corp	o perform this calibration ar e calibrations. Expanded un sigma), no sampling plan or escribed above. All calibrati re-certification interval and ed written consent of Techmu d Problem <u>Standards Util</u> <u>Model #</u> 8482A 8565E 83650B 436A 8116A 8487A 3335A 53132A 8484A 8340B	re certified by or traceable to N. cortanties are determined as re- other processwas used for this of ons are performed to manufactu- documentation has been receive asterElectronics. Calibration Cycle: Calibration Date: Next Due Date: Certified By: <u>Due Date</u> 7/15/2011 1/28/2012 6/7/2011 3/23/2012 11/11/2011 4/6/2012 4/19/2011 12/7/2011 1/27/2011 1/27/2011 1/27/2011	IST, natural physical equired with a distribution calibration, the results urer's specifications, unless red and is on file. This form 12 Months 04/14/2011 04/14/2012 Williamson, Breeanne Test Report # 306458 315260 303538 320280 312658 321056 281968 314200 320990 281985

TEL Benett -2 Quality Inspector

Techmaster Electronics, Inc. 2453 Cades Way, Suite "C" Vista, CA 92081

(760)536-0227