



STC Test Report

Date: 2016-08-08

Page 56 of 61

No.: DMA000094

3.1.8 RF Exposure

Test Requirement: FCC 47CFR 15.247(i)
Test Date: 2016-08-03
Mode of Operation: WiFi mode

Test Method:

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

Test Results:

The EUT complied with the requirement(s) of this section.
EUT meets the requirements of these sections as proven through MPE calculation
The MPE calculation for EUT @ 20cm
Based on the highest P = 72.61 mW

$$\begin{aligned} P_d &= PG / 4\pi R^2 = (72.61 \times 2.51) / 12.566 \times (20)^2 \\ &= (182.251) / 12.566 \times 400 = 182.251 / 5026.4 \\ &= 0.0363 \text{ mW/cm}^2 \end{aligned}$$

where:

- *Pd = power density in mW/cm²
- * G = Antenna numeric gain (2.51); Log G = g/10 (g = 4dBi).
- * P = Conducted RF power to antenna (39.54 mW).
- * R = Minimum allowable distance.(20 cm)

- *The power density Pd = 0.0465mW/cm² is less than 1 mW/cm² (listed MPE limit)
- *The SAR evaluation is not needed (this is a desk top device, R> 20 cm)
- * The EUT(antenna) must be 0.2 meters away from the General Population.

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong
Tel: (852) 2666 1888 Fax: (852) 2664 4353 E-mail: hkstc@hkstc.org Homepage: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage