

## FCC IC Test Report (BT-LE)

**Report No.:** FCC\_IC\_RF\_SL19072201-WIN-001\_BLE

**FCC ID:** C3DBT1000

**IC:** 22428-BT1000

**Test Model:** BT-1000

**Variant Model:** TH-3000

**Received Date:** 08/08/2019

**Test Date:** 08/09/2019 – 09/12/2019

**Issued Date:** 09/23/2019

**Applicant:** Winegard Company

**Address:** 3000 Kirkwood Street, Burlington, IA 52601-2000

**Manufacturer:** Winegard Company

**Address:** 3000 Kirkwood Street, Burlington, IA 52601-2000

**Issued By:** Bureau Veritas Consumer Products Services, Inc.

**Lab Address:** 775 Montague Expressway, Milpitas, CA 95035

**Test Location (1):** 775 Montague Expressway, Milpitas, CA 95035

**FCC Registration /**  
540430

**Designation Number:**

**ISED# / CAB identifier:** 4842D



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

## Table of Contents

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>Release Control Record .....</b>                              | <b>4</b>  |
| <b>1 Certificate of Conformity .....</b>                         | <b>5</b>  |
| <b>2 Summary of Test Results .....</b>                           | <b>6</b>  |
| 2.1 Measurement Uncertainty .....                                | 6         |
| 2.2 Modification Record .....                                    | 6         |
| <b>3 General Information .....</b>                               | <b>7</b>  |
| 3.1 General Description of EUT .....                             | 7         |
| 3.2 Description of Test Modes .....                              | 8         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail .....    | 9         |
| 3.3 Duty Cycle of Test Signal .....                              | 10        |
| 3.4 Description of Support Units .....                           | 11        |
| 3.4.1 Configuration of System under Test .....                   | 11        |
| 3.5 General Description of Applied Standards .....               | 11        |
| <b>4 Test Types and Results .....</b>                            | <b>12</b> |
| 4.1 Radiated Emission and Bandedge Measurement .....             | 12        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement ..... | 12        |
| 4.1.2 Test Instruments .....                                     | 13        |
| 4.1.3 Test Procedures .....                                      | 14        |
| 4.1.4 Deviation from Test Standard .....                         | 14        |
| 4.1.5 Test Setup .....                                           | 15        |
| 4.1.6 EUT Operating Conditions .....                             | 16        |
| 4.1.7 Test Results .....                                         | 17        |
| 4.2 Conducted Emission Measurement .....                         | 22        |
| 4.2.1 Limits of Conducted Emission Measurement .....             | 22        |
| 4.2.2 Test Instruments .....                                     | 22        |
| 4.2.3 Test Procedures .....                                      | 23        |
| 4.2.4 Deviation from Test Standard .....                         | 23        |
| 4.2.5 Test Setup .....                                           | 23        |
| 4.2.6 EUT Operating Conditions .....                             | 23        |
| 4.2.7 Test Results .....                                         | 24        |
| 4.3 6dB & 99% Bandwidth Measurement .....                        | 26        |
| 4.3.1 Limits of 6dB Bandwidth Measurement .....                  | 26        |
| 4.3.2 Test Setup .....                                           | 26        |
| 4.3.3 Test Instruments .....                                     | 26        |
| 4.3.4 Test Procedure .....                                       | 26        |
| 4.3.5 Deviation from Test Standard .....                         | 26        |
| 4.3.6 EUT Operating Conditions .....                             | 26        |
| 4.3.7 Test Result .....                                          | 27        |
| 4.4 Conducted Output Power Measurement .....                     | 29        |
| 4.4.1 Limits of Conducted Output Power Measurement .....         | 29        |
| 4.4.2 Test Setup .....                                           | 29        |
| 4.4.3 Test Instruments .....                                     | 29        |
| 4.4.4 Test Procedures .....                                      | 29        |
| 4.4.5 Deviation from Test Standard .....                         | 29        |
| 4.4.6 EUT Operating Conditions .....                             | 29        |
| 4.4.7 Test Results .....                                         | 30        |
| 4.5 Power Spectral Density Measurement .....                     | 32        |
| 4.5.1 Limits of Power Spectral Density Measurement .....         | 32        |
| 4.5.2 Test Setup .....                                           | 32        |
| 4.5.3 Test Instruments .....                                     | 32        |
| 4.5.4 Test Procedure .....                                       | 32        |

|          |                                                                 |           |
|----------|-----------------------------------------------------------------|-----------|
| 4.5.5    | Deviation from Test Standard .....                              | 32        |
| 4.5.6    | EUT Operating Condition .....                                   | 32        |
| 4.5.7    | Test Results .....                                              | 33        |
| 4.6      | Conducted Out of Band Emission Measurement .....                | 35        |
| 4.6.1    | Limits of Conducted Out of Band Emission Measurement.....       | 35        |
| 4.6.2    | Test Setup.....                                                 | 35        |
| 4.6.3    | Test Instruments .....                                          | 35        |
| 4.6.4    | Test Procedure .....                                            | 35        |
| 4.6.5    | Deviation from Test Standard .....                              | 35        |
| 4.6.6    | EUT Operating Condition .....                                   | 35        |
| 4.6.7    | Test Results .....                                              | 36        |
| <b>5</b> | <b>Pictures of Test Arrangements.....</b>                       | <b>37</b> |
|          | <b>Appendix – Information on the Testing Laboratories .....</b> | <b>38</b> |

### Release Control Record

| Issue No.                        | Description      | Date Issued |
|----------------------------------|------------------|-------------|
| FCC_IC_RF_SL19072201-WIN-001_BLE | Original Release | 09/23/2019  |

## 1 Certificate of Conformity

**Product:** Inline Signal Level Meter

**Brand:** Winegard Company

**Test Model:** BT-1000

**Variant Model:** TH-3000

**Sample Status:** Engineering sample

**Applicant:** Winegard Company

**Test Date:** 08/09/2019 – 09/12/2019

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10: 2013  
RSS 247 Issue 2, February 2017

The above equipment has been tested by **Bureau Veritas Consumer Products Services, Inc., Milpitas Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**



**Date:**

09/23/2019

Rachana Khanduri / Test Engineer

**Approved by :**



**Date:**

09/23/2019

Chen Ge / Engineer Reviewer

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (Section 15.247), RSS 247 Issue 2, February 2017 |                                              |        |                                                                                      |
|--------------------------------------------------------------------------------|----------------------------------------------|--------|--------------------------------------------------------------------------------------|
| FCC IC Clause                                                                  | Test Item                                    | Result | Remarks                                                                              |
| 15.207<br>RSS Gen 8.8                                                          | AC Power Conducted Emission                  | PASS   | Meet the requirement of limit.<br>Minimum passing margin is -7.4 dB at 0.473 MHz.    |
| 15.205<br>&15.209 &<br>15.247(d)<br>RSS247 (5.5)                               | Radiated Emissions and Band Edge Measurement | PASS   | Meet the requirement of limit.<br>Minimum passing margin is -11.35 dB at 935.97 MHz. |
| 15.247(d)<br>RSS247 (5.5)                                                      | Antenna Port Emission                        | PASS   | Meet the requirement of limit.                                                       |
| 15.247(a)(2)<br>RSS247 (5.2.a)                                                 | 6dB Bandwidth                                | PASS   | Meet the requirement of limit.                                                       |
| RSS Gen 6.7                                                                    | 99% Occupied Bandwidth                       | PASS   | Meet the requirement of limit.                                                       |
| 15.247(b)<br>RSS247 (5.4.d)                                                    | Conducted power                              | PASS   | Meet the requirement of limit.                                                       |
| 15.247(e)<br>RSS247 (5.2.b)                                                    | Power Spectral Density                       | PASS   | Meet the requirement of limit.                                                       |
| 15.203                                                                         | Antenna Requirement                          | PASS   | The antenna is permanently attached to the PCB                                       |

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                        | Frequency      | Expanded Uncertainty (k=2) (±) |
|------------------------------------|----------------|--------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz | 3.51dB                         |
| Radiated Emissions up to 1 GHz     | 30MHz ~ 1GHz   | 3.73dB                         |
| Radiated Emissions above 1 GHz     | 1GHz ~ 6GHz    | 4.64dB                         |
|                                    | 6GHz ~ 18GHz   | 4.82dB                         |
|                                    | 18GHz ~ 40GHz  | 4.91dB                         |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                           |                                     |
|---------------------------|-------------------------------------|
| Product                   | Inline Signal Level Meter           |
| Brand                     | Winegard Company                    |
| Test Model                | BT-1000                             |
| Variant model             | TH-3000                             |
| Identification No. of EUT | 004                                 |
| Status of EUT             | ENGINEERING SAMPLE                  |
| Power Supply Rating       | 100-240VAC-50/60Hz                  |
| Modulation Type           | GFSK                                |
| Modulation Technology     | DTS                                 |
| Transfer Rate             | Up to 1Mbps                         |
| Operating Frequency       | 2.402 ~ 2.480GHz                    |
| Number of Channel         | 40                                  |
| Output Power              | 1.99 dBm                            |
| Antenna Type              | Meandered Inverted-F Antenna (MIFA) |
| Antenna Gain (dBi)        | 0 dBi                               |
| Antenna Connector         | -                                   |

The models are electrically identical and there is no difference in the RF characteristics.  
The only difference between BT-1000 and TH-3000 are as below:

**BT-1000:** The “DC Pass” configuration allows DC current (if present) to pass through the device from the RF OUTPUT to RF INPUT and travel up the coax to the TV antenna.

**TH-3000:** All other configurations have no DC path from RF OUTPUT to RF INPUT but instead supply 5V DC over coax to the RF INPUT. The 5V DC originates at the USB type C connection.

### 3.2 Description of Test Modes

40 channels are provided to this EUT:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| 0       | 2402            | 10      | 2422            | 20      | 2442            | 30      | 2462            |
| 1       | 2404            | 11      | 2424            | 21      | 2444            | 31      | 2464            |
| 2       | 2406            | 12      | 2426            | 22      | 2446            | 32      | 2466            |
| 3       | 2408            | 13      | 2428            | 23      | 2448            | 33      | 2468            |
| 4       | 2410            | 14      | 2430            | 24      | 2450            | 34      | 2470            |
| 5       | 2412            | 15      | 2432            | 25      | 2452            | 35      | 2472            |
| 6       | 2414            | 16      | 2434            | 26      | 2454            | 36      | 2474            |
| 7       | 2416            | 17      | 2436            | 27      | 2456            | 37      | 2476            |
| 8       | 2418            | 18      | 2438            | 28      | 2458            | 38      | 2478            |
| 9       | 2420            | 19      | 2440            | 29      | 2460            | 39      | 2480            |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT CONFIGURE MODE | APPLICABLE TO |       |     |      | DESCRIPTION |
|--------------------|---------------|-------|-----|------|-------------|
|                    | RE $\geq$ 1G  | RE<1G | PLC | APCM |             |
| -                  | √             | √     | √   | √    | -           |

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz & Bandedge Measurement  
**RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission  
**APCM**: Antenna Port Conducted Measurement

**NOTE:** The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane**.

**NOTE:** "-" means no effect.

#### **Radiated Emission Test (Above 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE | DATA RATE (Mbps) |
|-------------------|----------------|-----------------|------------------|
| 0 to 39           | 0,19,39        | GFSK            | 1                |

#### **Radiated Emission Test (Below 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE | DATA RATE (Mbps) |
|-------------------|----------------|-----------------|------------------|
| 0 to 39           | 0,19,39        | GFSK            | 1                |

#### **Power Line Conducted Emission Test:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE | DATA RATE (Mbps) |
|-------------------|----------------|-----------------|------------------|
| 0 to 39           | 19             | GFSK            | 1                |

#### **Antenna Port Conducted Measurement:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.


| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE | DATA RATE (Mbps) |
|-------------------|----------------|-----------------|------------------|
| 0 to 39           | 19             | GFSK            | 1                |

### Test Condition:

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | INPUT POWER  | TESTED BY        |
|---------------|--------------------------|--------------|------------------|
| RE≥1G         | 25deg. C, 65%RH          | 120Vac, 60Hz | Rachana Khanduri |
| RE<1G         | 25deg. C, 65%RH          | 120Vac, 60Hz | Rachana Khanduri |
| PLC           | 25deg. C, 68%RH          | 120Vac, 60Hz | Rachana Khanduri |
| APCM          | 21deg. C, 60%RH          | 120Vac, 60Hz | Rachana Khanduri |

### 3.3 Duty Cycle of Test Signal

Duty cycle of test signal is  $(621-243) / (867-243) = 60\%$ . Duty factor:  $10 * \log (1/0.6) = 2.22$



### 3.4 Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| ID | Product | Brand | Model No. | Serial No. | FCC ID | Remarks |
|----|---------|-------|-----------|------------|--------|---------|
| A. | -       | -     | -         | -          | -      | -       |

| ID | Descriptions     | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks              |
|----|------------------|------|------------|--------------------|--------------|----------------------|
| 1. | USB Power Supply | 1    | 2          | N                  | 0            | Provided by Customer |

Note: The core(s) is (are) originally attached to the cable(s).

#### 3.4.1 Configuration of System under Test



### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**  
**KDB 558074 D01 15.247 Meas Guidance v05r02**  
**ANSI C63.10-2013**  
**RSS 247 Issue 2, February 2017**  
**RSS Gen Issue 5, March 2019**

All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

#### NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 Test Instruments

| DESCRIPTION & MANUFACTURER           | MODEL NO.   | SERIAL NO.  | DATE OF CALIBRATION | DUE DATE OF CALIBRATION |
|--------------------------------------|-------------|-------------|---------------------|-------------------------|
| EMI Test Receiver<br>ROHDE & SCHWARZ | ESIB 40     | 100179      | 08/28/2018          | 08/28/2019*             |
| Spectrum Analyzer<br>KEYSIGHT        | N9030B      | MY57140374  | 07/22/2019          | 07/22/2020              |
| Hybrid Antenna<br>SUNAR              | JB6         | A111717     | 03/09/2019          | 03/09/2020              |
| DRG Horn Antenna<br>ETS LINDGREN     | 3117        | 214309      | 11/22/2018          | 11/22/2019              |
| Preamplifier<br>RF-LAMBDA            | RAMP00M50GA | 17032300047 | 09/19/2018          | 09/19/2019              |
| Preamplifier<br>RF-BAY               | LPA-6-30    | 11170602    | 05/06/2019          | 05/06/2020              |

\*Calibration extended by 3 months.

#### 4.1.3 Test Procedures

##### **For Radiated emission below 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### **NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30MHz.

##### **For Radiated emission above 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### **Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle  $< 98\%$ ) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



### For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Connected the EUT with the USB Power Supply.
- Controlling software has been activated to set the EUT on specific status.

#### 4.1.7 Test Results

##### BELOW 1GHz WORST-CASE DATA:

##### BT-LE (GFSK)


|                 |               |                   |            |
|-----------------|---------------|-------------------|------------|
| CHANNEL         | TX Channel 19 | DETECTOR FUNCTION | Quasi Peak |
| FREQUENCY RANGE | 30MHz – 1GHz  |                   |            |

##### ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m

| No | Freq.<br>[MHz] | Raw<br>(dB) | Cable Loss<br>(dB) | AF<br>(dB) | Level<br>(dBuV/m) | Measurement Type | Pol | Hgt<br>(cm) | Azt<br>Deg | Limit<br>(dBuV/m) | Margin<br>(dB) | Pass /Fail |
|----|----------------|-------------|--------------------|------------|-------------------|------------------|-----|-------------|------------|-------------------|----------------|------------|
| 1  | 30             | 24.56       | 11.12              | -11.48     | 24.19             | Quasi Max        | V   | 125         | 60         | 40                | -15.81         | Pass       |
| 2  | 76.71594       | 40.68       | 11.64              | -27.94     | 24.38             | Quasi Max        | V   | 121         | 182        | 40                | -15.62         | Pass       |
| 3  | 97.66375       | 34.45       | 11.86              | -26.22     | 20.09             | Quasi Max        | H   | 158         | 346        | 43.5              | -23.41         | Pass       |
| 4  | 196.5203       | 35.25       | 12.59              | -24.39     | 23.44             | Quasi Max        | H   | 130         | 213        | 43.5              | -20.06         | Pass       |
| 5  | 35.21563       | 21.82       | 11.2               | -16.13     | 16.9              | Quasi Max        | V   | 104         | 42         | 40                | -23.1          | Pass       |
| 6  | 102.2797       | 34.04       | 11.9               | -25.14     | 20.8              | Quasi Max        | H   | 152         | 58         | 43.5              | -22.7          | Pass       |

##### REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Cable Loss (dB) + AF (dB)
2. AF (dB) = Antenna Factor (dB) – Preamplifier Gain (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.



**ABOVE 1GHz TEST DATA:**
**BT-LE (GFSK)**

|                        |              |                              |                 |
|------------------------|--------------|------------------------------|-----------------|
| <b>CHANNEL</b>         | TX Channel 0 | <b>DETECTOR<br/>FUNCTION</b> | Peak<br>Average |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              |                 |

**ANTENNA POLARITY & test distance: HORIZONTAL& VERTICAL at 3 m**

| No | Freq.    | Raw   | Cable Loss | AF     | Level    | Measurement Type | Pol | Hgt  | Azt | Limit    | Margin | Pass /Fail |
|----|----------|-------|------------|--------|----------|------------------|-----|------|-----|----------|--------|------------|
|    | [MHz]    | (dB)  | (dB)       | (dB)   | (dBuV/m) |                  |     | (cm) | Deg | (dBuV/m) | (dB)   |            |
| 1  | 4805.925 | 50.92 | 5.8        | -11.05 | 45.67    | Peak Max         | V   | 151  | 183 | 74       | -28.33 | Pass       |
| 2  | 4805.925 | 38.73 | 5.8        | -11.05 | 33.48    | Average Max      | V   | 151  | 183 | 54       | -20.52 | Pass       |
| 3  | 7205.908 | 63.41 | 6.74       | -7.4   | 62.76    | Peak Max         | H   | 120  | 75  | 74       | -11.24 | Pass       |
| 4  | 7205.908 | 36.35 | 6.74       | -7.4   | 35.7     | Average Max      | H   | 120  | 75  | 54       | -18.3  | Pass       |
| 5  | 16896.2  | 45.5  | 9.61       | 1.8    | 56.91    | Peak Max         | V   | 135  | 26  | 74       | -17.09 | Pass       |
| 6  | 16896.2  | 33.3  | 9.61       | 1.8    | 44.71    | Average Max      | V   | 135  | 26  | 54       | -9.29  | Pass       |

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Cable Loss (dB) + AF (dB)
2. AF (dB) = Antenna Factor (dB) – Preamplifier Gain (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.

|                        |               |                              |                 |
|------------------------|---------------|------------------------------|-----------------|
| <b>CHANNEL</b>         | TX Channel 19 | <b>DETECTOR<br/>FUNCTION</b> | Peak<br>Average |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                              |                 |

**ANTENNA POLARITY & test distance: HORIZONTAL& VERTICAL at 3 m**

| No | Freq.    | Raw   | Cable<br>Loss | AF     | Level    | Measurement<br>Type | Pol | Hgt  | Azt | Limit    | Margin | Pass<br>/Fail |
|----|----------|-------|---------------|--------|----------|---------------------|-----|------|-----|----------|--------|---------------|
|    | [MHz]    | (dB)  | (dB)          | (dB)   | (dBuV/m) |                     |     | (cm) | Deg | (dBuV/m) | (dB)   |               |
| 1  | 4880.433 | 51.6  | 5.5           | -11.05 | 46.04    | Peak Max            | V   | 100  | 23  | 74       | -27.96 | Pass          |
| 2  | 4880.433 | 38.84 | 5.5           | -11.05 | 33.28    | Average Max         | V   | 100  | 23  | 54       | -20.72 | Pass          |
| 3  | 7278.105 | 55.72 | 6.47          | -7.33  | 54.85    | Peak Max            | H   | 118  | 0   | 74       | -19.15 | Pass          |
| 4  | 7278.105 | 35.7  | 6.47          | -7.33  | 34.84    | Average Max         | H   | 118  | 0   | 54       | -19.16 | Pass          |
| 5  | 10243.3  | 47.38 | 7.49          | -4.2   | 50.68    | Peak Max            | V   | 121  | 5   | 74       | -23.33 | Pass          |
| 6  | 10243.3  | 33.95 | 7.49          | -4.2   | 37.25    | Average Max         | V   | 121  | 5   | 54       | -16.75 | Pass          |

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Cable Loss (dB) + AF (dB)
2. AF (dB) = Antenna Factor (dB) – Preamplifier Gain (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.

|                        |               |                              |                 |
|------------------------|---------------|------------------------------|-----------------|
| <b>CHANNEL</b>         | TX Channel 39 | <b>DETECTOR<br/>FUNCTION</b> | Peak<br>Average |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                              |                 |


**ANTENNA POLARITY & test distance: HORIZONTAL& VERTICAL at 3 m**

| No | Freq.    | Raw   | Cable<br>Loss | AF     | Level    | Measurement<br>Type | Pol | Hgt  | Azt | Limit    | Margin | Pass<br>/Fail |
|----|----------|-------|---------------|--------|----------|---------------------|-----|------|-----|----------|--------|---------------|
|    | [MHz]    | (dB)  | (dB)          | (dB)   | (dBuV/m) |                     |     | (cm) | Deg | (dBuV/m) | (dB)   |               |
| 1  | 1899.754 | 55.21 | 3.23          | -13.42 | 45.02    | Peak Max            | V   | 101  | 199 | 74       | -28.98 | Pass          |
| 2  | 1899.754 | 41.74 | 3.23          | -13.42 | 31.55    | Average Max         | V   | 101  | 199 | 54       | -22.45 | Pass          |
| 3  | 4964.596 | 50.44 | 5.5           | -11.06 | 44.88    | Peak Max            | H   | 166  | 257 | 74       | -29.12 | Pass          |
| 4  | 4964.596 | 38.55 | 5.5           | -11.06 | 32.99    | Average Max         | H   | 166  | 257 | 54       | -21.01 | Pass          |
| 5  | 7440.143 | 67.23 | 6.53          | -7.19  | 66.57    | Peak Max            | V   | 167  | 281 | 74       | -7.43  | Pass          |
| 6  | 7440.143 | 36.68 | 6.53          | -7.19  | 36.03    | Average Max         | V   | 167  | 281 | 54       | -17.97 | Pass          |


**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Cable Loss (dB) + AF (dB)
2. AF (dB) = Antenna Factor (dB) – Preamplifier Gain (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.

## RESTRICTED BAND (LOW CHANNEL)



## RESTRICTED BAND (HIGH CHANNEL)



## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

| Description & Manufacturer           | Model No. | Serial No. | Date Of Calibration | Due Date Of Calibration |
|--------------------------------------|-----------|------------|---------------------|-------------------------|
| EMI Test Receiver<br>ROHDE & SCHWARZ | ESIB 40   | 100179     | 08/28/2018          | 08/28/2019*             |
| Transient Limiter<br>ELECTRO-METRICS | EM-7600-5 | 106        | 12/31/2018          | 12/31/2019              |
| LISN<br>EMCO                         | 3816/2NM  | 214372     | 01/10/2019          | 01/10/2020              |

\*Calibration extended by 3 months.

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note:** 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions


Same as 4.1.6.

#### 4.2.7 Test Results

| Phase |          |       | Line (L)  |         |        | Detector Function |      | Quasi-Peak / Average |        |            |
|-------|----------|-------|-----------|---------|--------|-------------------|------|----------------------|--------|------------|
| No    | Freq.    | Raw   | Cale Loss | Factors | Level  | Measurement Type  | Line | Limit                | Margin | Pass /Fail |
|       | [MHz]    | (dB)  | (dB)      | (dB)    | (dBuV) |                   |      | (dBuV)               | (dB)   |            |
| 1     | 1.891455 | 35.61 | 7.84      | 0.07    | 43.53  | Quasi Peak        | Line | 56                   | -12.47 | Pass       |
| 2     | 1.898297 | 34.22 | 7.85      | 0.07    | 42.14  | Quasi Peak        | Line | 56                   | -13.86 | Pass       |
| 3     | 0.966619 | 29.5  | 7.65      | 0.04    | 37.19  | Quasi Peak        | Line | 56                   | -18.81 | Pass       |
| 4     | 0.362212 | 27.2  | 7.28      | 0.04    | 34.52  | Quasi Peak        | Line | 58.68                | -24.15 | Pass       |
| 5     | 4.20384  | 23.8  | 8.02      | 0.07    | 31.89  | Quasi Peak        | Line | 56                   | -24.11 | Pass       |
| 6     | 9.850327 | 23.27 | 8.26      | 0.22    | 31.74  | Quasi Peak        | Line | 60                   | -28.26 | Pass       |
| 7     | 1.891455 | 27.36 | 7.84      | 0.07    | 35.27  | Average           | Line | 46                   | -10.73 | Pass       |
| 8     | 1.898297 | 26.95 | 7.85      | 0.07    | 34.87  | Average           | Line | 46                   | -11.13 | Pass       |
| 9     | 0.966619 | 19.91 | 7.65      | 0.04    | 27.6   | Average           | Line | 46                   | -18.4  | Pass       |
| 10    | 0.362212 | 21.95 | 7.28      | 0.04    | 29.27  | Average           | Line | 48.68                | -19.41 | Pass       |
| 11    | 4.20384  | 11.72 | 8.02      | 0.07    | 19.82  | Average           | Line | 46                   | -26.18 | Pass       |
| 12    | 9.850327 | 13.04 | 8.26      | 0.22    | 21.51  | Average           | Line | 50                   | -28.49 | Pass       |

#### REMARKS:

1. The emission levels of other frequencies were very low against the limit.
2. Margin value = Emission level - Limit value
3. Emission Level = Correction Factor + Raw Value + Factors Value.




| Phase | Neutral (N) | Detector Function | Quasi-Peak / Average |
|-------|-------------|-------------------|----------------------|
|-------|-------------|-------------------|----------------------|

| No | Freq.<br>[MHz] | Raw<br>(dB) | Cale<br>Loss<br>(dB) | Factors<br>(dB) | Level<br>(dBuV) | Measurement<br>Type | Line    | Limit<br>(dBuV) | Margin<br>(dB) | Pass /Fail |
|----|----------------|-------------|----------------------|-----------------|-----------------|---------------------|---------|-----------------|----------------|------------|
| 1  | 1.910453       | 38.92       | 7.85                 | 0.06            | 46.83           | Quasi Peak          | Neutral | 56              | -9.17          | Pass       |
| 2  | 1.899042       | 36.56       | 7.85                 | 0.06            | 44.47           | Quasi Peak          | Neutral | 56              | -11.53         | Pass       |
| 3  | 1.941703       | 35.64       | 7.85                 | 0.06            | 43.56           | Quasi Peak          | Neutral | 56              | -12.44         | Pass       |
| 4  | 12.57764       | 27.4        | 8.73                 | 0.31            | 36.44           | Quasi Peak          | Neutral | 60              | -23.56         | Pass       |
| 5  | 4.957389       | 22.29       | 8.13                 | 0.09            | 30.52           | Quasi Peak          | Neutral | 56              | -25.48         | Pass       |
| 6  | 0.358315       | 29.71       | 7.28                 | 0.03            | 37.02           | Quasi Peak          | Neutral | 58.77           | -21.75         | Pass       |
| 7  | 1.910453       | 26.61       | 7.85                 | 0.06            | 34.51           | Average             | Neutral | 46              | -11.49         | Pass       |
| 8  | 1.899042       | 25.85       | 7.85                 | 0.06            | 33.76           | Average             | Neutral | 46              | -12.24         | Pass       |
| 9  | 1.941703       | 29.8        | 7.85                 | 0.06            | 37.71           | Average             | Neutral | 46              | -8.29          | Pass       |
| 10 | 12.57764       | 16.66       | 8.73                 | 0.31            | 25.71           | Average             | Neutral | 50              | -24.29         | Pass       |
| 11 | 4.957389       | 14.99       | 8.13                 | 0.09            | 23.22           | Average             | Neutral | 46              | -22.78         | Pass       |
| 12 | 0.358315       | 24.58       | 7.28                 | 0.03            | 31.89           | Average             | Neutral | 48.77           | -16.88         | Pass       |

#### REMARKS:

1. The emission levels of other frequencies were very low against the limit.
2. Margin value = Emission level - Limit value
3. Emission Level = Correction Factor + Raw Value + Factors Value.




### 4.3 6dB & 99% Bandwidth Measurement

#### 4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 Deviation from Test Standard

No deviation.


#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Result

| Channel | Frequency (MHz) | 99% Occupied Bandwidth (MHz) | 6dB Bandwidth (MHz) | 6dB Bandwidth Limit (MHz) | Pass / Fail |
|---------|-----------------|------------------------------|---------------------|---------------------------|-------------|
| 0       | 2402            | 1.09                         | 0.707               | 0.5                       | PASS        |
| 19      | 2440            | 1.09                         | 0.699               | 0.5                       | PASS        |
| 39      | 2480            | 1.09                         | 0.711               | 0.5                       | PASS        |

#### Test Plots:






#### 4.4 Conducted Output Power Measurement

##### 4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

##### 4.4.2 Test Setup



##### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

##### 4.4.4 Test Procedures

- a. Set the RBW  $\geq$  DTS bandwidth.
- b. Set VBW  $\geq 3 \times$  RBW.
- c. Set span  $\geq 3 \times$  RBW
- d. Sweep time = auto couple.
- e. Detector = peak.
- f. Trace mode = max hold.
- g. Allow trace to fully stabilize.
- h. Use peak marker function to determine the peak amplitude level.

##### 4.4.5 Deviation from Test Standard

No deviation.


##### 4.4.6 EUT Operating Conditions


Same as Item 4.3.6.

#### 4.4.7 Test Results

| Channel | Frequency (MHz) | Conducted Power (dBm) | Limit (dBm) | Pass/Fail |
|---------|-----------------|-----------------------|-------------|-----------|
| 0       | 2402            | 1.83                  | 30          | Pass      |
| 19      | 2440            | 1.92                  | 30          | Pass      |
| 39      | 2480            | 1.99                  | 30          | Pass      |

#### Test Plots:






## 4.5 Power Spectral Density Measurement

### 4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz.

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set the VBW  $\geq 3 \times \text{RBW}$ .
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

### 4.5.5 Deviation from Test Standard

No deviation.


### 4.5.6 EUT Operating Condition


Same as Item 4.3.6

#### 4.5.7 Test Results

| Channel | Frequency (MHz) | PSD (dBm/3kHz) | Limit (dBm/3kHz) | Pass/Fail |
|---------|-----------------|----------------|------------------|-----------|
| 0       | 2402            | -13.16         | 8                | Pass      |
| 19      | 2440            | -12.69         | 8                | Pass      |
| 39      | 2480            | -12.78         | 8                | Pass      |

#### Test Plots:






## 4.6 Conducted Out of Band Emission Measurement

### 4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.


### 4.6.5 Deviation from Test Standard

No deviation.

### 4.6.6 EUT Operating Condition

Same as Item 4.3.6

#### 4.6.7 Test Results



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

Bureau Veritas is a global leader in testing, inspection and certification (TIC) services. We help businesses improve safety, sustainability and productivity; and our clients include the majority of leading brands in retail, manufacturing and other industries. With a presence in every major country around the world, our quality assurance and compliance solutions are vital in helping our customers enhance product quality and concept-to-consumer journeys. We also assist with increasing speed to market, profitability and brand equity throughout the supply chain. Bureau Veritas is a leading wireless/IoT testing, inspection, audit and certification provider, with a global network of test laboratories to support the IoT industry in areas of connectivity, security, interoperability as well as quality, health & safety, and environmental/chemical requirements.

If you have any comments, please feel free to contact us at the following:

**Milpitas EMC/RF/Safety/Telecom Lab**

775 Montague Expressway, Milpitas, CA 95035  
Tel: +1 408 526 1188

**Sunnyvale OTA/Bluetooth Lab**

1293 Anvilwood Avenue, Sunnyvale, CA  
94089  
Tel: +1 669 600 5293

**Littleton EMC/RF/Safety/Environmental Lab**

1 Distribution Center Cir #1, Littleton, MA 01460  
Tel: +1 978 486 8880

**Irvine OTA/PTCRB/Bluetooth/V2X Lab**

15 Musick, Irvine, CA 92618  
Tel: +1 949 716 6512

**Email:** [sales.eaw@us.bureauveritas.com](mailto:sales.eaw@us.bureauveritas.com)

**Web Site:** [www.cpsusa-bureauveritas.com](http://www.cpsusa-bureauveritas.com)

The address and road map of all our labs can be found in our web site also.

--- END ---