



FCC TEST REPORT

REPORT NO.: RF960531L09

MODEL NO.: 1116

RECEIVED: May 23, 2007

TESTED: May 23 ~ Jun. 04, 2007

ISSUED: Jun. 07, 2007

APPLICANT: Microsoft Corporation

ADDRESS: One Microsoft Way, Redmond WA 98052-6399, U.S.A

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang
244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 85 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



NO. 2177-01



0528



TABLE OF CONTENTS

1.	CERTIFICATION.....	4
2.	SUMMARY OF TEST RESULTS.....	5
2.1	MEASUREMENT UNCERTAINTY	6
3.	GENERAL INFORMATION.....	7
3.1	GENERAL DESCRIPTION OF EUT	7
3.2	DESCRIPTION OF TEST MODES	9
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	10
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	11
3.2.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	13
3.2.4	DESCRIPTION OF SUPPORT UNITS	13
4.	TEST TYPES AND RESULTS.....	14
4.1	CONDUCTED EMISSION MEASUREMENT	14
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	14
4.1.2	TEST INSTRUMENTS.....	14
4.1.3	TEST PROCEDURES	15
4.1.4	DEVIATION FROM TEST STANDARD	15
4.1.5	TEST SETUP	16
4.1.6	EUT OPERATING CONDITIONS	16
4.1.7	TEST RESULTS	17
4.2	RADIATED EMISSION MEASUREMENT	29
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT.....	29
4.2.2	TEST INSTRUMENTS.....	30
4.2.3	TEST PROCEDURES	31
4.2.4	DEVIATION FROM TEST STANDARD	31
4.2.5	TEST SETUP.....	32
4.2.6	EUT OPERATING CONDITIONS	32
4.2.7	TEST RESULTS	33
4.3	NUMBER OF HOPPING FREQUENCY USED.....	41
4.3.1	LIMIT OF HOPPING FREQUENCY USED.....	41
4.3.2	TEST INSTRUMENTS.....	41
4.3.3	TEST PROCEDURES	41
4.3.4	DEVIATION FROM TEST STANDARD	42
4.3.5	TEST SETUP.....	42
4.3.6	TEST RESULTS	42
4.4	DWELL TIME ON EACH CHANNEL.....	45
4.4.1	LIMIT OF DWELL TIME USED	45
4.4.2	TEST INSTRUMENTS.....	45
4.4.3	TEST PROCEDURES	45
4.4.4	DEVIATION FROM TEST STANDARD	45



4.4.5	TEST SETUP.....	46
4.4.6	TEST RESULTS	46
4.5	CHANNEL BANDWIDTH	50
4.5.1	LIMITS OF CHANNEL BANDWIDTH	50
4.5.2	TEST INSTRUMENTS.....	50
4.5.3	TEST PROCEDURE.....	50
4.5.4	DEVIATION FROM TEST STANDARD	51
4.5.5	TEST SETUP.....	51
4.5.6	EUT OPERATING CONDITION.....	51
4.5.7	TEST RESULTS	51
4.6	HOPPING CHANNEL SEPARATION	57
4.6.1	LIMIT OF HOPPING CHANNEL SEPARATION	57
4.6.2	TEST INSTRUMENTS.....	57
4.6.3	TEST PROCEDURES	57
4.6.4	DEVIATION FROM TEST STANDARD	58
4.6.5	TEST SETUP.....	58
4.6.6	TEST RESULTS	58
4.7	MAXIMUM PEAK OUTPUT POWER.....	64
4.7.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	64
4.7.2	TEST INSTRUMENTS.....	64
4.7.3	TEST PROCEDURES	64
4.7.4	DEVIATION FROM TEST STANDARD	64
4.7.5	TEST SETUP.....	65
4.7.6	EUT OPERATING CONDITION.....	65
4.7.7	TEST RESULTS	65
4.8	BAND EDGES MEASUREMENT.....	71
4.8.1	LIMITS OF BAND EDGES MEASUREMENT	71
4.8.2	TEST INSTRUMENTS.....	71
4.8.3	TEST PROCEDURE.....	71
4.8.4	DEVIATION FROM TEST STANDARD	71
4.8.5	EUT OPERATING CONDITION.....	71
4.8.6	TEST RESULTS	72
4.9	ANTENNA REQUIREMENT.....	82
4.9.1	STANDARD APPLICABLE	82
4.9.2	ANTENNA CONNECTED CONSTRUCTION	82
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	83
6.	INFORMATION ON THE TESTING LABORATORIES.....	84
	APPENDIX-A.....	A-1



1. CERTIFICATION

PRODUCT: Microsoft® 2.4 GHz Transceiver with Memory v1.0
MODEL NO.: 1116
BRAND: Microsoft®
APPLICANT: Microsoft Corporation
TESTED: May 23 ~ Jun. 04, 2007
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: **FCC Part 15, Subpart C (Section 15.247),**
ANSI C63.4-2003

The above equipment (model: 1116) have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Wendy Liao , **DATE:** Jun. 07, 2007
Wendy Liao / Senior Specialist

TECHNICAL
ACCEPTANCE : Long Chen , **DATE:** Jun. 07, 2007
Responsible for RF Long Chen / Senior Engineer

APPROVED BY : Gary Chang , **DATE:** Jun. 07, 2007
Gary Chang / Supervisor

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -11.23dB at 0.173MHz.
15.247(a)(1)(iii)	Number of Hopping Frequency Used Spec.: At least 15 channels	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel Spec. : Max. 0.4 second within 31.6 second	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation Spec. : Min. 25 kHz or 2/3*20 dB bandwidth, whichever is greater (see Note) 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Spec.: max. 21dBm (see Note)	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions Spec.: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -6.06dB at 152.39MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz ~ 30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~ 1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Microsoft® 2.4 GHz Transceiver with Memory v1.0
MODEL NO.	1116
FCC ID	C3K1116
POWER SUPPLY	5Vdc from host equipment
MODULATION TYPE	GFSK,π/4-DQPSK, 8DPSK
RADIO TECHNOLOGY	FHSS
TRANSFER RATE	531.2kbps
FREQUENCY RANGE	2400 ~ 2483.5 MHz
NUMBER OF CHANNEL	79
OUTPUT POWER	2.328mW
ANTENNA TYPE	PCB antenna with -0.66dBi gain
DATA CABLE	NA
I/O PORTS	USB
ACCESSORY DEVICES	NA

NOTE:

1. Bluetooth technology is used in this EUT.
2. Configuration Information:

Configuration #:		Comments: EV2 phase Receiver unit with EMC fixes for formal report			
Manufacturer	Component type	Part no.	Revision no.	Description	BOM (if known)
Microsoft	BT Transceiver			Model: 1116	
Boardcom	BT IC	11300838200		BCM2046, BGA, 95, FLASH	11300838200
SST	FLASH	11300839200		SST39VF200A, TFBGA48, 2MBITS	11300839200
Hynix ST	NAND FLASH	11300840200		NAND FLASH 1GBYTES, TSOP, 48	11300840200
Prolific	Flash Controller	11300843200		PL2528, LQFP, 64	11300843200
KYE	PCB Assy	20001044200	02	GUSANO, BT DONGLE, RF, PL2528, HANDSOLDER	20001044200
ROM SHINE	PCB	10230736200	09	GUSANO MEM, PL2528, 4L, 36.2X13.6, OM-060072	10230736200
ROM SHINE	PCB	10230734200	08	GUSANO RF, BCM2046, 4L, 38.0X13.6, OM-060072	10230734200

Host System Used for EV2 Testing		Comments: EMI		
Manufacturer	Equipment Type	Part no.	Serial No.	Description
DELL	NOTEBOOK COMPUTER	D600		

Host System Used for EV2 Testing		Comments: EMS		
Manufacturer	Equipment Type	Part no.	Serial No.	Description
DELL	NOTEBOOK COMPUTER	PP05L	20375526736	



Definition of configuration #: The configuration number (#) is used for traceability to a particular BOM (Bill of Materials). It is an easy way to readily identify and convey the construction of a without having to include all of the details of a BOM on every test data sheet. If two sets of test data have test samples with the same configuration # then the construction details of those test samples can readily be determined (as long as the configuration # correctly corresponds to a BOM) and that these two test samples have been constructed identically.

Detailed information on the configuration of the tested samples is required in order to track performance changes across various revisions of the hardware and to document that the samples tested are representative of the final configuration that will be manufactured in production.

Any prototype or pre-production components must be clearly identified in the configuration table.

3. Four samples tested as below:

SAMPLE	SERIAL NO
1	GU-EV2-125
2	GU-EV2-095
3	GU-EV2-333
4	GU-EV2-450

4. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.


3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:


CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2431	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

MODE A



MODE B



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
A	√	√	-	-	Without charger function
B	√	√	√	√	With charger function

Where **PLC**: Power Line Conducted Emission **RE<1G**: Radiated Emission below 1GHz
RE≥1G: Radiated Emission above 1GHz **APCM**: Antenna Port Conducted Measurement

NOTE: "-" means no effect

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, packet types of the antenna and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	SERIAL NO OF SAMPLE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATI ON TYPE	PACKET TYPE
A	GU-EV2-125	0 to 78	0, 39, 78	FHSS	8DPSK	DH1
B	GU-EV2-125	0 to 78	0, 39, 78	FHSS	8DPSK	DH1

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, packet types and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	SERIAL NO OF SAMPLE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATI ON TYPE	PACKET TYPE
A	GU-EV2-125	0 to 78	78	FHSS	8DPSK	DH1
B	GU-EV2-125	0 to 78	78	FHSS	8DPSK	DH1

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, packet types and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	SERIAL NO OF SAMPLE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
B	GU-EV2-125	0 to 78	0, 39, 78	FHSS	GFSK	DH1
B	GU-EV2-125	0 to 78	0, 39, 78	FHSS	8DPSK	DH1

BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types of the antenna and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	SERIAL NO OF SAMPLE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
B	GU-EV2-095	0 to 78	0, 78	FHSS	GFSK	DH1
B	GU-EV2-333	0 to 78	0, 78	FHSS	GFSK	DH1
B	GU-EV2-450	0 to 78	0, 78	FHSS	GFSK	DH1
B	GU-EV2-095	0 to 78	0, 78	FHSS	8DPSK	DH1
B	GU-EV2-333	0 to 78	0, 78	FHSS	8DPSK	DH1
B	GU-EV2-450	0 to 78	0, 78	FHSS	8DPSK	DH1

ANTENNA PORT CONDUCTED MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types of the antenna and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	SERIAL NO OF SAMPLE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
B	GU-EV2-125	0 to 78	0, 39, 78	FHSS	GFSK	DH1
B	GU-EV2-125	0 to 78	0, 39, 78	FHSS	8DPSK	DH1

3.2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	16484462992	E2K24CLNS
2	PRINTER	EPSON	LQ-300+	DCGY054147	FCC DoC Approved
3	MODEM	ACEEX	1414V/3	0401008269	IFAXDM1414
4	Microsoft® Mobile Memory Mouse 8000	Microsoft®	1115	272	C3K1115

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m shielded cable
3	1.2m shielded cable
4	0.9m non-shielded cable

NOTE: 1. All power cords of the above support units are non shielded (1.8m).
2. The item 4 is provided by our client.

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Sep. 25, 2007
RF signal cable Woken	5D-FB	Cable-HYCO3-01	Jan. 06, 2008
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Jan. 08, 2008
LISN ROHDE & SCHWARZ	ESH3-Z5	100311	Jan. 16, 2008
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Plugged EUT into a notebook system and placed on a testing table.
- b. The notebook system ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the system in full functions.


4.1.7 TEST RESULTS

CONDUCTED WORST CASE DATA

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	PHASE	Line 1
MODULATION TYPE	8DPSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A	TESTED BY	Morgan Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.158	0.10	47.96	-	48.06	-	65.58
2	0.224	0.10	44.04	-	44.14	-	62.66	52.66	-18.52	-
3	0.349	0.10	33.70	-	33.80	-	58.98	48.98	-25.18	-
4	0.689	0.10	32.40	-	32.50	-	56.00	46.00	-23.50	-
5	2.078	0.22	28.71	-	28.93	-	56.00	46.00	-27.07	-
6	10.730	0.35	35.36	-	35.71	-	60.00	50.00	-24.29	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	PHASE	Line 2
MODULATION TYPE	8DPSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A	TESTED BY	Morgan Chen

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.162	0.10	44.26	-	44.36	-	65.38
2	0.228	0.10	43.89	-	43.99	-	62.52	52.52	-18.53	-
3	0.357	0.10	36.24	-	36.34	-	58.80	48.80	-22.46	-
4	0.677	0.15	33.29	-	33.44	-	56.00	46.00	-22.56	-
5	2.152	0.22	27.39	-	27.61	-	56.00	46.00	-28.39	-
6	9.980	0.43	37.07	-	37.50	-	60.00	50.00	-22.50	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	PHASE	Line 1
MODULATION TYPE	8DPSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A	TESTED BY	Morgan Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.166	0.10	42.07	-	42.17	-	65.18	55.18	-23.01	-
2	0.228	0.10	43.06	-	43.16	-	62.52	52.52	-19.36	-
3	0.353	0.10	37.17	-	37.27	-	58.89	48.89	-21.62	-
4	0.697	0.10	32.14	-	32.24	-	56.00	46.00	-23.76	-
5	2.246	0.23	28.44	-	28.67	-	56.00	46.00	-27.33	-
6	10.238	0.34	36.58	-	36.92	-	60.00	50.00	-23.08	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	PHASE	Line 2
MODULATION TYPE	8DPSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A	TESTED BY	Morgan Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.150	0.10	47.62	-	47.72	-	66.00
2	0.232	0.10	43.23	-	43.33	-	62.38	52.38	-19.05	-
3	0.353	0.10	37.47	-	37.57	-	58.89	48.89	-21.32	-
4	0.673	0.15	33.10	-	33.25	-	56.00	46.00	-22.75	-
5	2.430	0.23	27.43	-	27.66	-	56.00	46.00	-28.34	-
6	10.457	0.43	35.85	-	36.28	-	60.00	50.00	-23.72	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	PHASE	Line 1
MODULATION TYPE	8DPSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A	TESTED BY	Morgan Chen

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin [dB]	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.150	0.10	47.26	-	47.36	-	66.00
2	0.252	0.10	39.28	-	39.38	-	61.71	51.71	-22.33	-
3	0.357	0.10	36.52	-	36.62	-	58.80	48.80	-22.18	-
4	0.689	0.10	32.57	-	32.67	-	56.00	46.00	-23.33	-
5	2.156	0.22	28.98	-	29.20	-	56.00	46.00	-26.80	-
6	10.566	0.35	36.46	-	36.81	-	60.00	50.00	-23.19	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	PHASE	Line 2
MODULATION TYPE	8DPSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A	TESTED BY	Morgan Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.162	0.10	45.14	-	45.24	-	65.38
2	0.220	0.10	43.75	-	43.85	-	62.81	52.81	-18.96	-
3	0.357	0.10	36.78	-	36.88	-	58.80	48.80	-21.92	-
4	0.685	0.15	33.73	-	33.88	-	56.00	46.00	-22.12	-
5	2.121	0.22	28.64	-	28.86	-	56.00	46.00	-27.14	-
6	10.277	0.43	37.59	-	38.02	-	60.00	50.00	-21.98	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	PHASE	Line 1
MODULATION TYPE	8DPSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	TESTED BY	Match Tsui

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.172	0.10	52.82	-	52.92	-	64.86	54.86	-11.94	-
2	0.232	0.10	45.02	-	45.12	-	62.38	52.38	-17.26	-
3	0.291	0.10	40.21	-	40.31	-	60.51	50.51	-20.20	-
4	2.145	0.22	34.10	-	34.32	-	56.00	46.00	-21.68	-
5	3.855	0.28	30.83	-	31.11	-	56.00	46.00	-24.89	-
6	18.902	0.55	29.29	-	29.84	-	60.00	50.00	-30.16	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	PHASE	Line 2
MODULATION TYPE	8DPSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	TESTED BY	Match Tsui

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.173	0.10	53.46	-	53.56	-	64.79
2	0.232	0.10	46.14	-	46.24	-	62.38	52.38	-16.14	-
3	0.349	0.10	35.52	-	35.62	-	58.98	48.98	-23.36	-
4	2.090	0.22	31.23	-	31.45	-	56.00	46.00	-24.55	-
5	3.977	0.28	32.81	-	33.09	-	56.00	46.00	-22.91	-
6	18.867	0.55	29.29	-	29.84	-	60.00	50.00	-30.16	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	PHASE	Line 1
MODULATION TYPE	8DPSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	TESTED BY	Match Tsui

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	52.48	-	52.58	-	64.79	54.79	-12.21	-
2	0.232	0.10	44.56	-	44.66	-	62.38	52.38	-17.72	-
3	0.291	0.10	39.43	-	39.53	-	60.51	50.51	-20.98	-
4	1.969	0.22	35.82	-	36.04	-	56.00	46.00	-19.96	-
5	4.047	0.28	38.10	-	38.38	-	56.00	46.00	-17.62	-
6	18.813	0.55	29.49	-	30.04	-	60.00	50.00	-29.96	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	PHASE	Line 2
MODULATION TYPE	8DPSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	TESTED BY	Match Tsui

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	52.68	-	52.78	-	64.79	54.79	-12.01	-
2	0.232	0.10	44.40	-	44.50	-	62.38	52.38	-17.88	-
3	0.291	0.10	40.51	-	40.61	-	60.51	50.51	-19.90	-
4	1.621	0.22	32.65	-	32.87	-	56.00	46.00	-23.13	-
5	3.824	0.27	35.80	-	36.07	-	56.00	46.00	-19.93	-
6	18.773	0.55	29.03	-	29.58	-	60.00	50.00	-30.42	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	PHASE	Line 1
MODULATION TYPE	8DPSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	TESTED BY	Match Tsui

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.173	0.10	51.73	-	51.83	-	64.79
2	0.228	0.10	42.63	-	42.73	-	62.52	52.52	-19.79	-
3	0.291	0.10	38.85	-	38.95	-	60.51	50.51	-21.56	-
4	2.367	0.23	31.18	-	31.41	-	56.00	46.00	-24.59	-
5	3.988	0.28	36.13	-	36.41	-	56.00	46.00	-19.59	-
6	18.703	0.55	30.60	-	31.15	-	60.00	50.00	-28.85	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	PHASE	Line 2
MODULATION TYPE	8DPSK	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	TESTED BY	Match Tsui

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.177	0.10	48.96	-	49.06	-	64.61
2	0.232	0.10	44.00	-	44.10	-	62.37	52.37	-18.27	-
3	0.290	0.10	40.17	-	40.27	-	60.52	50.52	-20.25	-
4	1.734	0.22	33.39	-	33.61	-	56.00	46.00	-22.39	-
5	3.992	0.28	35.36	-	35.64	-	56.00	46.00	-20.36	-
6	18.566	0.54	28.50	-	29.04	-	60.00	50.00	-30.96	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Aug. 04, 2007
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100269	Aug. 07, 2007
BILOG Antenna SCHWARZBECK	VULB9168	9168-153	Jan. 04, 2008
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-563	Jul. 26, 2007
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170242	Jan. 16, 2008
Preamplifier Agilent	8449B	3008A01911	Sep. 13, 2007
Preamplifier Agilent	8447D	2944A10638	Dec. 20, 2007
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	218188/218189	Nov. 14, 2007
RF signal cable Worken	8D-FB	Cable-HYCH9-01	Aug. 16, 2007
Software	ADT_Radiated_V7.6	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA
Turn Table EMCO	2087-2.03	NA	NA
Antenna Tower & Turn Table Controller EMCO	2090	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 9.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The IC Site Registration No. is IC3789B-9.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

RADIATED WORST CASE DATA: BELOW 1GHz

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	8DPSK	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	26 deg. C, 71%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A	TESTED BY	Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	199.05	28.75 QP	43.50	-14.75	1.00 H	247	18.36	10.40
2	498.47	28.51 QP	46.00	-17.49	1.50 H	118	9.80	18.71
3	533.47	28.72 QP	46.00	-17.28	1.50 H	25	9.18	19.54
4	665.68	28.83 QP	46.00	-17.17	1.50 H	352	7.14	21.69
5	700.68	30.34 QP	46.00	-15.66	1.00 H	106	8.33	22.01
6	739.57	31.59 QP	46.00	-14.41	1.00 H	106	8.64	22.94
7	759.01	29.02 QP	46.00	-16.98	1.00 H	106	5.62	23.40
8	799.84	28.71 QP	46.00	-17.29	1.00 H	10	4.35	24.36
9	961.21	36.54 QP	54.00	-17.46	1.50 H	58	10.77	25.77

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	37.68	24.16 QP	40.00	-15.84	1.00 V	25	11.99	12.17
2	199.05	27.65 QP	43.50	-15.85	1.00 V	127	17.25	10.40
3	531.53	30.10 QP	46.00	-15.90	1.00 V	286	10.60	19.49
4	665.68	39.74 QP	46.00	-6.26	2.00 V	175	18.05	21.69
5	700.68	31.11 QP	46.00	-14.89	1.50 V	328	9.10	22.01
6	739.57	30.62 QP	46.00	-15.38	1.00 V	163	7.67	22.94
7	904.83	39.02 QP	46.00	-6.98	2.00 V	259	13.67	25.36
8	908.72	34.95 QP	46.00	-11.05	2.00 V	118	9.56	25.39

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	8DPSK	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	26 deg. C, 70%RH, 1004.1hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	TESTED BY	Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	96.01	35.92 QP	43.50	-7.58	2.50 H	223	26.83	9.10
2	152.39	37.44 QP	43.50	-6.06	2.50 H	241	23.82	13.62
3	162.11	36.08 QP	43.50	-7.42	1.50 H	34	22.77	13.31
4	199.05	28.56 QP	43.50	-14.94	1.50 H	10	18.16	10.40
5	533.47	30.68 QP	46.00	-15.32	1.00 H	169	11.14	19.54
6	601.52	32.57 QP	46.00	-13.43	1.00 H	286	11.46	21.11
7	720.12	31.14 QP	46.00	-14.86	1.00 H	220	8.67	22.48
8	739.57	31.90 QP	46.00	-14.10	1.00 H	85	8.95	22.94
9	780.40	30.48 QP	46.00	-15.52	1.00 H	220	6.58	23.91
10	799.84	31.16 QP	46.00	-14.84	1.00 H	154	6.80	24.36
11	832.89	30.79 QP	46.00	-15.21	1.50 H	229	6.11	24.68

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	113.50	35.45 QP	43.50	-8.05	1.00 V	10	24.67	10.78
2	156.28	31.14 QP	43.50	-12.36	2.00 V	322	17.61	13.54
3	166.00	28.97 QP	43.50	-14.53	2.00 V	313	15.94	13.03
4	199.05	28.00 QP	43.50	-15.50	2.00 V	337	17.60	10.40
5	700.68	31.94 QP	46.00	-14.06	1.00 V	166	9.93	22.01
6	832.89	30.58 QP	46.00	-15.42	2.00 V	337	5.90	24.68
7	945.66	36.50 QP	46.00	-9.50	1.00 V	286	10.81	25.69

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

RADIATED WORST CASE DATA: ABOVE 1GHz

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	GFSK	DETECTOR FUNCTION	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26 deg. C, 71%RH, 1004.1hPa
TEST MODE	B	TESTED BY	Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2370.00	41.22 PK	74.00	-32.78	1.08 H	43	9.98	31.24
2	2370.00	31.72 AV	54.00	-22.28	1.08 H	43	0.48	31.24
3	*2402.00	92.55 PK			1.08 H	42	61.34	31.21
4	*2402.00	54.49 AV			1.08 H	42	23.28	31.21
5	4804.00	54.30 PK	74.00	-19.70	1.03 H	178	17.86	36.44
6	4804.00	16.24 AV	54.00	-37.76	1.03 H	178	-20.20	36.44

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2370.00	33.41 PK	74.00	-40.59	1.21 V	339	2.17	31.24
2	2370.00	23.91 AV	54.00	-30.09	1.21 V	339	-7.33	31.24
3	*2402.00	84.74 PK			1.21 V	339	53.53	31.21
4	*2402.00	46.68 AV			1.21 V	339	15.47	31.21
5	4804.00	50.93 PK	74.00	-23.07	1.00 V	179	14.49	36.44
6	4804.00	12.87 AV	54.00	-41.13	1.00 V	179	-23.57	36.44

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The DH1 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 2 per 1.25ms per channel. Therefore, the duty cycle be equal to: $20\log(1.25/100) = -38.06$ dB.
 6. Average value = peak reading – 38.06.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	GFSK	DETECTOR FUNCTION	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26 deg. C, 71%RH, 1004.1hPa
TEST MODE	B	TESTED BY	Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	93.75 PK			1.05 H	39	62.53	31.22
2	*2441.00	55.69 AV			1.05 H	39	24.47	31.22
3	4882.00	53.46 PK	74.00	-20.54	1.00 H	252	16.87	36.59
4	4882.00	15.40 AV	54.00	-38.60	1.00 H	252	-21.19	36.59

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	85.64 PK			1.16 V	102	54.42	31.22
2	*2441.00	47.58 AV			1.16 V	102	16.36	31.22
3	4882.00	50.72 PK	74.00	-23.28	1.00 V	311	14.13	36.59
4	4882.00	12.66 AV	54.00	-41.34	1.00 V	311	-23.93	36.59

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The DH1 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 2 per 1.25ms per channel. Therefore, the duty cycle be equal to: $20\log(1.25/100) = -38.06$ dB.
 6. Average value = peak reading – 38.06.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	GFSK	DETECTOR FUNCTION	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26 deg. C, 71%RH, 1004.1hPa
TEST MODE	B	TESTED BY	Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	94.31 PK			1.02 H	38	63.08	31.23
2	*2480.00	56.25 AV			1.02 H	38	25.02	31.23
3	2483.50	34.30 PK	74.00	-39.70	1.02 H	38	3.06	31.24
4	2483.50	24.80 AV	54.00	-29.20	1.02 H	38	-6.44	31.24
5	4960.00	51.22 PK	74.00	-22.78	1.06 H	21	14.47	36.74
6	4960.00	13.16 AV	54.00	-40.84	1.06 H	21	-23.59	36.74

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	86.09 PK			1.16 V	18	54.86	31.23
2	*2480.00	48.03 AV			1.16 V	18	16.80	31.23
3	2483.50	26.08 PK	74.00	-47.92	1.16 V	18	-5.16	31.24
4	2483.50	16.58 AV	54.00	-37.42	1.16 V	18	-14.66	31.24
5	4960.00	50.55 PK	74.00	-23.45	1.05 V	186	13.80	36.74
6	4960.00	12.49 AV	54.00	-41.51	1.05 V	186	-24.26	36.74

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The DH1 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 2 per 1.25ms per channel. Therefore, the duty cycle be equal to: $20\log(1.25/100) = -38.06$ dB.
 6. Average value = peak reading – 38.06.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	8DPSK	DETECTOR FUNCTION	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26 deg. C, 71%RH, 1004.1hPa
TEST MODE	B	TESTED BY	Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2370.00	40.45 PK	74.00	-33.55	1.06 H	18	9.21	31.24
2	2370.00	30.95 AV	54.00	-23.05	1.06 H	18	-0.29	31.24
3	*2402.00	94.52 PK			1.06 H	18	63.31	31.21
4	*2402.00	56.46 AV			1.06 H	18	25.25	31.21
5	4804.00	54.18 PK	74.00	-19.82	1.08 H	22	17.74	36.44
6	4804.00	16.12 AV	54.00	-37.88	1.08 H	22	-20.32	36.44

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2370.00	31.57 PK	74.00	-42.43	1.00 V	160	0.33	31.24
2	2370.00	22.07 AV	54.00	-31.93	1.00 V	160	-9.17	31.24
3	*2402.00	85.64 PK			1.00 V	160	54.43	31.21
4	*2402.00	47.58 AV			1.00 V	160	16.37	31.21
5	4804.00	50.56 PK	74.00	-23.44	1.03 V	285	14.12	36.44
6	4804.00	12.50 AV	54.00	-41.50	1.03 V	285	-23.94	36.44

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The DH1 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 2 per 1.25ms per channel. Therefore, the duty cycle be equal to: $20\log(1.25/100) = -38.06$ dB.
 6. Average value = peak reading – 38.06.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	8DPSK	DETECTOR FUNCTION	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26 deg. C, 71%RH, 1004.1hPa
TEST MODE	B	TESTED BY	Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	95.26 PK			1.07 H	31	64.04	31.22
2	*2441.00	57.20 AV			1.07 H	31	25.98	31.22
3	4882.00	54.02 PK	74.00	-19.98	1.00 H	267	17.43	36.59
4	4882.00	15.96 AV	54.00	-38.04	1.00 H	267	-20.63	36.59

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	86.32 PK			1.01 V	199	55.10	31.22
2	*2441.00	48.26 AV			1.01 V	199	17.04	31.22
3	4882.00	50.30 PK	74.00	-23.70	1.08 V	167	13.71	36.59
4	4882.00	12.24 AV	54.00	-41.76	1.08 V	167	-24.35	36.59

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The DH1 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 2 per 1.25ms per channel. Therefore, the duty cycle be equal to: $20\log(1.25/100) = -38.06$ dB.
 6. Average value = peak reading –38.06.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	8DPSK	DETECTOR FUNCTION	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26 deg. C, 71%RH, 1004.1hPa
TEST MODE	B	TESTED BY	Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	96.44 PK			1.03 H	35	65.21	31.23
2	*2480.00	58.38 AV			1.03 H	35	27.15	31.23
3	2483.50	41.65 PK	74.00	-32.35	1.03 H	35	10.41	31.24
4	2483.50	32.15 AV	54.00	-21.85	1.03 H	35	0.91	31.24
5	4960.00	53.72 PK	74.00	-20.28	1.04 H	27	16.98	36.74
6	4960.00	15.16 AV	54.00	-38.84	1.04 H	27	-21.58	36.74

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	87.45 PK			1.03 V	192	56.22	31.23
2	*2480.00	49.39 AV			1.03 V	192	18.16	31.23
3	2483.50	32.66 PK	74.00	-41.34	1.03 V	192	1.42	31.24
4	2483.50	23.16 AV	54.00	-30.84	1.03 V	192	-8.08	31.24
5	4960.00	49.57 PK	74.00	-24.43	1.00 V	301	12.83	36.74
6	4960.00	11.51 AV	54.00	-42.49	1.00 V	301	-25.23	36.74

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The DH1 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 2 per 1.25ms per channel. Therefore, the duty cycle be equal to: $20\log(1.25/100) = -38.06$ dB.
 6. Average value = peak reading – 38.06.



4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP





4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.





FOR GFSK





FOR 8DPSK





4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation.

4.4.5 TEST SETUP





4.4.6 TEST RESULTS

FOR GFSK

MODE	NUMBER OF TRANSMISSION IN A 31.6 (79HOPPING * 0.4)	LENGTH OF TRANSMISSION TIME (msec)	RESULT (msec)	LIMIT (msec)
DH1	$51 \text{ (times / 5 sec)} * 6.32 = 322.32 \text{ times}$	0.528	170.185	400

NOTE: Test plots of the transmitting time slot are shown on next page.

DH1





FOR 8DPSK

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	$50(\text{times} / 5 \text{ sec}) * 6.32 = 316.00 \text{ times}$	0.594	187.704	400

NOTE: Test plots of the transmitting time slot are shown on next page.

DH1





4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation.

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 TEST RESULTS


FOR GFSK

MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 1004.1hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Morgan Chen


CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.945
39	2441	0.945
78	2480	0.955




CH 0



CH 39



CH 78






FOR 8DPSK

MODULATION TYPE	8DPSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 1004.1hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Morgan Chen


CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.350
39	2441	1.350
78	2480	1.355



CH 0




CH 39





CH 78





4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.6.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation.

4.6.5 TEST SETUP



4.6.6 TEST RESULTS

FOR GFSK


MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 1004.1hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Morgan Chen

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.007	0.945	0.630	PASS
39	2441	1.005	0.945	0.630	PASS
78	2480	1.005	0.955	0.637	PASS


NOTE: The minimum limit is two-third 20dB bandwidth. Test results please refer to next two pages.




CH 0



CH 39



CH 78





FOR 8DPSK


MODULATION TYPE	8DPSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 1004.1hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Morgan Chen

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.001	1.350	0.900	PASS
39	2441	1.006	1.350	0.900	PASS
78	2480	1.004	1.355	0.903	PASS


NOTE: The minimum limit is two-third 20dB bandwidth. Test results please refer to next two pages.



CH 0




CH 39





CH 78





4.7 MAXIMUM PEAK OUTPUT POWER

4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 125mW.

4.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.7.3 TEST PROCEDURES

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation

4.7.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.7.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 TEST RESULTS


FOR GFSK

MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 1004.1hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Morgan Chen


CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	1.169	0.680	125	PASS
39	2441	1.265	1.020	125	PASS
78	2480	1.256	0.990	125	PASS



CH 0




CH 39





CH 78






FOR 8DPSK

MODULATION TYPE	8DPSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 68%RH, 1004.1hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Morgan Chen


CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	2.234	3.490	125	PASS
39	2441	2.328	3.670	125	PASS
78	2480	2.218	3.460	125	PASS




CH 0



CH 39



CH 78





4.8 BAND EDGES MEASUREMENT

4.8.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz RBW).

4.8.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

4.8.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.6 TEST RESULTS

The spectrum plots are attached on the following 4 images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

FOR GFSK

MODE B (SERIAL NO OF SAMPLE: GU-EV2-333)

NOTE 1:

The band edge emission plot on the next page shows 49.31dBc between carrier maximum power and local maximum emission in restrict band (2.36900000GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 92.55dBuV/m (Peak), so the maximum field strength in restrict band is $92.55 - 49.31 = 43.24$ dBuV/m, which is under 74 dBuV/m limit.

Average value = $43.24 - 38.06 = 5.18$ dBuV/m, which is under 54dBuV/m limit.

*The DH1 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 2$ per 1.25ms per channel. Therefore, the duty cycle be equal to: $20\log(1.25/100) = -38.06$ dB.

Average value = peak reading -38.06 .

NOTE 2:

The band edge emission plot on the next second page shows 49.85dBc between carrier maximum power and local maximum emission in restrict band (2.49660000GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 94.31dBuV/m (Peak), so the maximum field strength in restrict band is $94.31 - 49.85 = 44.46$ dBuV/m, which is under 74 dBuV/m limit.



Average value = $44.46 - 38.06 = 6.40$ dBuV/m, which is under 54dBuV/m limit.



*The DH1 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 2$ per 1.25ms per channel. Therefore, the duty cycle be equal to: $20\log(1.25/100) = -38.06$ dB.

Average value = peak reading -38.06 .





SERIAL NO OF SAMPLE: GU-EV2-333









SERIAL NO OF SAMPLE: GU-EV2-095





SERIAL NO OF SAMPLE: GU-EV2-450



FOR 8DPSK

MODE B (SERIAL NO OF SAMPLE: GU-EV2-333)

NOTE 1:

The band edge emission plot on the next page shows 47.12dBc between carrier maximum power and local maximum emission in restrict band (2.31940000GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 94.52dBuV/m (Peak), so the maximum field strength in restrict band is $94.52 - 47.12 = 47.40$ dBuV/m, which is under 74 dBuV/m limit.

Average value = $47.40 - 38.06 = 9.34$ dBuV/m, which is under 54dBuV/m limit.

*The DH1 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 2$ per 1.25ms per channel. Therefore, the duty cycle be equal to: $20\log(1.25/100) = -38.06$ dB.

Average value = peak reading -38.06 .

NOTE 2:

The band edge emission plot on the next second page shows 48.29dBc between carrier maximum power and local maximum emission in restrict band (2.48980000GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 96.44dBuV/m (Peak), so the maximum field strength in restrict band is $96.44 - 48.29 = 48.15$ dBuV/m, which is under 74 dBuV/m limit.



Average value = $48.15 - 38.06 = 10.09$ dBuV/m, which is under 54dBuV/m limit.



*The DH1 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 2$ per 1.25ms per channel. Therefore, the duty cycle be equal to: $20\log(1.25/100) = -38.06$ dB.

Average value = peak reading -38.06 .





SERIAL NO OF SAMPLE: GU-EV2-333









SERIAL NO OF SAMPLE: GU-EV2-095





SERIAL NO OF SAMPLE: GU-EV2-450



4.9 ANTENNA REQUIREMENT

4.9.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.9.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is PCB antenna without antenna connector. The maximum gain of this antenna is -0.66dBi.

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, NCC
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.