



RF EXPOSURE REPORT

REPORT NO.: SA971208H05

MODEL NO.: 1387

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT : MICROSOFT CORPORATION

ADDRESS : ONE MICROSOFT WAY REDMOND, WA
98052-6399

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB LOCATION: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307,
Taiwan, R.O.C.



No SAR Evaluation Required if power is below the following threshold:

Tunable Range		Center of Tunable Band (GHz)	60/f SAR Limitation (mW)
F(GHz) Low	F(GHz) High		
2.403	2.480	2.444	24.19

Maximum measured transmitter power (EIRP):

Peak Field Strength (dBuV/m)	Pout (dBm)	Pout (mW)
86.3	-8.9	0.129

Remark: converted to a peak field strength level at 3 meters using
 $E(\text{dBuV/m}) = P(\text{dBm}; \text{EIRP}) + 95.2$

Threshold for no SAR evaluation is 24.19 mW

Maximum TX Power is 0.129 mW EIRP

Conclusion: No SAR evaluation required since maximum Transmitter Pout (EIRP) is below FCC threshold