



FCC TEST REPORT

REPORT NO. : RF981109L10

MODEL NO. : 1446

RECEIVED : Nov. 09, 2009

TESTED : Nov. 09 ~ Nov. 30, 2009

ISSUED : Dec. 14, 2009

APPLICANT : Microsoft Corporation

ADDRESS : One Microsoft Way, Redmond WA 98052-6399,
U.S.A

ISSUED BY : Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS : No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION : No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 41 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF or any government agency. The test results in the report only apply to the tested sample.



Table of Contents

1.	CERTIFICATION	3
2.	SUMMARY OF TEST RESULTS	4
2.1	MEASUREMENT UNCERTAINTY	4
3.	GENERAL INFORMATION.....	5
3.1	GENERAL DESCRIPTION OF EUT	5
3.2	DESCRIPTION OF TEST MODES.....	6
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	6
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	9
3.4	DESCRIPTION OF SUPPORT UNITS	9
4.	TEST TYPES AND RESULTS	10
4.1	RADIATED EMISSION MEASUREMENT	10
4.1.1	LIMITS OF RADIATED EMISSION MEASUREMENT.....	10
4.1.2	TEST INSTRUMENTS	11
4.1.3	TEST PROCEDURES	12
4.1.4	DEVIATION FROM TEST STANDARD	12
4.1.5	TEST SETUP	13
4.1.6	EUT OPERATING CONDITIONS	13
4.1.7	TEST RESULTS	14
4.2	CONDUCTED EMISSION MEASUREMENT	27
4.2.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	27
4.2.2	TEST INSTRUMENTS	27
4.2.3	TEST PROCEDURES	28
4.2.4	DEVIATION FROM TEST STANDARD	28
4.2.5	TEST SETUP	29
4.2.6	EUT OPERATING CONDITIONS	29
4.2.7	TEST RESULTS	30
4.3	BAND EDGES MEASUREMENT	36
4.3.1	LIMITS OF BAND EDGES MEASUREMENT	36
4.3.2	TEST INSTRUMENTS	36
4.3.3	TEST PROCEDURE	36
4.3.4	DEVIATION FROM TEST STANDARD	36
4.3.5	EUT OPERATING CONDITION	36
4.3.6	TEST RESULTS	37
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	39
6.	INFORMATION ON THE TESTING LABORATORIES	40
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	41



1. CERTIFICATION

PRODUCT: Wireless Transceiver
MODEL NO.: 1446
BRAND: Microsoft
APPLICANT: Microsoft Corporation
TESTED: Nov. 09 ~ Nov. 30, 2009
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: **FCC Part 15, Subpart C (Section 15.249)**
ANSI C63.4-2003

The above equipment (model: 1446) have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Andrea Hsia , **DATE** : Dec. 14, 2009
Andrea Hsia / Specialist

TECHNICAL ACCEPTANCE : Long Chen , **DATE** : Dec. 14, 2009
Responsible for RF Long Chen / Senior Engineer

APPROVED BY : Gary Chang , **DATE** : Dec. 14, 2009
Gary Chang / Assistant Manager

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.249)			
STANDARD PARAGRAPH	TEST TYPE	RESULT	REMARK
15.207	Conducted Emission Test	PASS	Meet the requirement of limit. Minimum passing margin is -10.93dB at 3.742MHz.
15.209 15.249 15.249 (d)	Radiated Emission Test Band Edge Measurement Limit: 50dB less than the peak value of fundamental frequency or meet radiated emission limit in section 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -8.5dB at 55.18MHz.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.34 dB
	200MHz ~1000MHz	3.35 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless Transceiver
MODEL NO.	1446
FCC ID	C3K1446
POWER SUPPLY	5Vdc
MODULATION TYPE	GFSK
OPERATING FREQUENCY	2403 ~ 2480 MHz
NUMBER OF CHANNEL	24
ANTENNA TYPE	Chip antenna with 0.83dBi gain
ANTENNA CONNECTOR	NA
DATA CABLE	NA
I/O PORT	USB
ACCESSORY DEVICES	NA

NOTE:

1. The following samples are provided for final test.

Sample	Serial No.
Sample 1	D186
Sample 2	D198
Sample 3	D247


2. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

24 channels are provided to this EUT.

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
1	2403	7	2425	13	2448	19	2470
2	2405	8	2427	14	2450	20	2472
3	2417	9	2429	15	2452	21	2474
4	2419	10	2431	16	2454	22	2476
5	2421	11	2444	17	2456	23	2478
6	2423	12	2446	18	2468	24	2480

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE \geq 1G	RE $<$ 1G	PLC	BM	
A	√	√	√	-	Serial No.: D186
B	√	√	√	√	Serial No.: D198
C	√	√	√	-	Serial No.: D247

Where **RE \geq 1G**: Radiated Emission above 1GHz

RE $<$ 1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

BM: Band edge Measurement

NOTE: "-": Means no effect.

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
A, B, C	1 to 24	1, 11, 24	GFSK

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
A, B, C	1 to 24	1	GFSK

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
A, B, C	1 to 24	1	GFSK

BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
B	1 to 24	1, 24	GFSK

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE \geq 1G	26deg. C, 65%RH, 1008 hPa	5Vdc	Brad Wu
RE $<$ 1G	26deg. C, 65%RH, 1008 hPa	5Vdc	Brad Wu
PLC	23deg. C, 65%RH, 1006 hPa	5Vdc	Kevin Liang
BM	26deg. C, 65%RH, 1008 hPa	5Vdc	Brad Wu

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (Section 15.249)

ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	12130898320	E2K24CLNS
2	PRINTER	EPSON	LQ-300+	DCGY054146	FCC DoC Approved
3	MODEM	ACEEX	1414V/3	0401008260	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.8m braid shielded wire, DB25 connector, w/o core.
3	1.2m braid shielded wire, DB25 & DB9 connector, w/o core.

NOTE: All power cords of the above support units are non-shielded (1.8m).

4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209, 15.249 as following:

15.209 Limit		
Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3
15.249 Limit		
Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
902 ~ 928 MHz	50	500
2400 ~ 2483.5 MHz	50	500
5725 ~ 5875 MHz	50	500
24 ~ 24.25 GHz	250	2500

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESI7	100033	Jul. 06, 2009	Jul. 05, 2010
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100076	May 26, 2009	May 25, 2010
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Apr. 27, 2009	Apr. 26, 2010
HORN Antenna SCHWARZBECK	9120D	9120D-209	Jul. 01, 2009	Jun. 30, 2010
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170243	Dec. 25, 2008	Dec. 24, 2009
Preamplifier Agilent	8447D	2944A10633	Nov. 10, 2009	Nov. 09, 2010
Preamplifier Agilent	8449B	3008A01964	Nov. 09, 2009	Nov. 08, 2010
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	238141/4	May 13, 2009	May 12, 2010
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	12738/6	May 13, 2009	May 12, 2010
Software ADT.	ADT_Radiated_ V7.6.15.9.2	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA	NA
Turn Table ADT.	TT100.	TT93021703	NA	NA
Turn Table Controller ADT.	SC100.	SC93021703	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 3.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Site Registration No. is 988962.
 5. The IC Site Registration No. is IC 7450F-3.

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- Plugged the EUT to the notebook and placed on a testing table.
- Set the EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



4.1.7 TEST RESULTS

ABOVE 1GHz DATA

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1000 hPa	TEST MODE	A
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.2 PK	74.0	-23.8	1.03 H	183	19.74	30.43
2	2390.00	27.6 AV	54.0	-26.4	1.03 H	183	-2.85	30.43
3	2398.00	59.3 PK	74.0	-14.7	1.03 H	183	28.88	30.46
4	2398.00	28.5 AV	54.0	-25.5	1.03 H	183	-1.96	30.46
5	2400.00	42.6 PK	74.0	-31.4	1.03 H	183	12.14	30.47
6	2400.00	8.7 AV	54.0	-45.3	1.03 H	183	-21.77	30.47
7	*2403.00	86.3 PK	114.0	-27.7	1.03 H	183	55.81	30.48
8	*2403.00	52.4 AV	94.0	-41.6	1.03 H	183	21.90	30.48
9	4806.00	50.2 PK	74.0	-23.8	1.12 H	18	14.16	36.08
10	4806.00	16.3 AV	54.0	-37.7	1.12 H	18	-19.75	36.08

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.0 PK	74.0	-24.0	1.00 V	275	19.60	30.43
2	2390.00	27.4 AV	54.0	-26.6	1.00 V	275	-3.08	30.43
3	2398.00	59.0 PK	74.0	-15.0	1.00 V	275	28.58	30.46
4	2398.00	28.2 AV	54.0	-25.8	1.00 V	275	-2.30	30.46
5	2400.00	41.6 PK	74.0	-32.4	1.00 V	275	11.12	30.47
6	2400.00	7.7 AV	54.0	-46.3	1.00 V	275	-22.79	30.47
7	*2403.00	85.3 PK	114.0	-28.7	1.00 V	275	54.79	30.48
8	*2403.00	51.4 AV	94.0	-42.6	1.00 V	275	20.88	30.48
9	4806.00	50.7 PK	74.0	-23.3	1.04 V	226	14.60	36.08
10	4806.00	16.8 AV	54.0	-37.2	1.04 V	226	-19.31	36.08

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency
 6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (2.015 \text{ ms} / 100 \text{ ms}) = -33.9 \text{ dB}$
 Please see page 23 for plotted duty.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1000 hPa	TEST MODE	A
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	87.5 PK	114.0	-26.5	1.01 H	168	56.83	30.62
2	*2444.00	53.6 AV	94.0	-40.4	1.01 H	168	22.92	30.62
3	4888.00	51.7 PK	74.0	-22.3	1.09 H	266	15.53	36.12
4	4888.00	17.8 AV	54.0	-36.2	1.09 H	266	-18.38	36.12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	86.6 PK	114.0	-27.4	1.01 V	271	55.97	30.62
2	*2444.00	52.7 AV	94.0	-41.3	1.01 V	271	22.06	30.62
3	4888.00	51.4 PK	74.0	-22.6	1.01 V	266	15.31	36.12
4	4888.00	17.5 AV	54.0	-36.5	1.01 V	266	-18.60	36.12

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency
 6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (2.015 \text{ ms} / 100 \text{ ms}) = -33.9 \text{ dB}$
 Please see page 23 for plotted duty.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 24	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1000 hPa	TEST MODE	A
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	86.8 PK	114.0	-27.2	1.00 H	159	56.10	30.74
2	*2480.00	52.9 AV	94.0	-41.1	1.00 H	159	22.19	30.74
3	2483.50	44.2 PK	74.0	-29.8	1.00 H	159	13.48	30.75
4	2483.50	10.3 AV	54.0	-43.7	1.00 H	159	-20.43	30.75
5	2485.50	57.0 PK	74.0	-17.0	1.00 H	159	26.25	30.76
6	2485.50	27.7 AV	54.0	-26.3	1.00 H	159	-3.04	30.76
7	4960.00	51.9 PK	74.0	-22.1	1.08 H	221	15.53	36.33
8	4960.00	18.0 AV	54.0	-36.0	1.08 H	221	-18.38	36.33
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	85.6 PK	114.0	-28.4	1.02 V	281	54.88	30.74
2	*2480.00	51.7 AV	94.0	-42.3	1.02 V	281	20.97	30.74
3	2483.50	43.0 PK	74.0	-31.0	1.02 V	281	12.26	30.75
4	2483.50	9.1 AV	54.0	-44.9	1.02 V	281	-21.65	30.75
5	2485.50	56.7 PK	74.0	-17.3	1.02 V	281	25.93	30.76
6	2485.50	27.4 AV	54.0	-26.6	1.02 V	281	-3.33	30.76
7	4960.00	50.9 PK	74.0	-23.1	1.04 V	226	14.61	36.33
8	4960.00	17.0 AV	54.0	-37.0	1.04 V	226	-19.30	36.33

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency
6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (2.015 \text{ ms} / 100 \text{ ms}) = -33.9 \text{ dB}$
 Please see page 23 for plotted duty.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1000 hPa	TEST MODE	B
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.6 PK	74.0	-23.4	1.00 H	168	20.13	30.43
2	2390.00	27.9 AV	54.0	-26.1	1.00 H	168	-2.58	30.43
3	2398.00	60.1 PK	74.0	-13.9	1.00 H	168	29.66	30.46
4	2398.00	28.8 AV	54.0	-25.2	1.00 H	168	-1.62	30.46
5	2400.00	44.5 PK	74.0	-29.5	1.00 H	168	14.06	30.47
6	2400.00	10.6 AV	54.0	-43.4	1.00 H	168	-19.85	30.47
7	*2403.00	87.8 PK	114.0	-26.2	1.00 H	168	57.30	30.48
8	*2403.00	53.9 AV	94.0	-40.1	1.00 H	168	23.39	30.48
9	4806.00	51.4 PK	74.0	-22.6	1.09 H	56	15.28	36.08
10	4806.00	17.5 AV	54.0	-36.5	1.09 H	56	-18.63	36.08
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.5 PK	74.0	-23.5	1.01 V	278	20.02	30.43
2	2390.00	27.8 AV	54.0	-26.2	1.01 V	278	-2.61	30.43
3	2398.00	59.7 PK	74.0	-14.3	1.01 V	278	29.22	30.46
4	2398.00	28.4 AV	54.0	-25.6	1.01 V	278	-2.08	30.46
5	2400.00	43.2 PK	74.0	-30.8	1.01 V	278	12.74	30.47
6	2400.00	9.3 AV	54.0	-44.7	1.01 V	278	-21.17	30.47
7	*2403.00	86.5 PK	114.0	-27.5	1.01 V	278	55.98	30.48
8	*2403.00	52.6 AV	94.0	-41.4	1.01 V	278	22.07	30.48
9	4806.00	50.9 PK	74.0	-23.1	1.06 V	229	14.86	36.08
10	4806.00	17.0 AV	54.0	-37.0	1.06 V	229	-19.05	36.08

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency
 6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (2.015 \text{ ms} / 100 \text{ ms}) = -33.9 \text{ dB}$
 Please see page 23 for plotted duty.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1000 hPa	TEST MODE	B
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	87.9 PK	114.0	-26.1	1.01 H	171	57.30	30.62
2	*2444.00	54.0 AV	94.0	-40.0	1.01 H	171	23.39	30.62
3	4888.00	51.5 PK	74.0	-22.5	1.03 H	24	15.37	36.12
4	4888.00	17.6 AV	54.0	-36.4	1.03 H	24	-18.54	36.12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	86.7 PK	114.0	-27.3	1.02 V	281	56.07	30.62
2	*2444.00	52.8 AV	94.0	-41.2	1.02 V	281	22.16	30.62
3	4888.00	51.3 PK	74.0	-22.7	1.05 V	234	15.14	36.12
4	4888.00	17.4 AV	54.0	-36.6	1.05 V	234	-18.77	36.12

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency
 6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (2.015 \text{ ms} / 100 \text{ ms}) = -33.9 \text{ dB}$
 Please see page 23 for plotted duty.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 24	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1000 hPa	TEST MODE	B
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	87.7 PK	114.0	-26.3	1.03 H	165	56.91	30.74
2	*2480.00	53.8 AV	94.0	-40.2	1.03 H	165	23.00	30.74
3	2483.50	45.3 PK	74.0	-28.7	1.03 H	165	14.55	30.75
4	2483.50	11.4 AV	54.0	-42.6	1.03 H	165	-19.36	30.75
5	2485.50	57.4 PK	74.0	-16.6	1.03 H	165	26.60	30.76
6	2485.50	28.0 AV	54.0	-26.0	1.03 H	165	-2.72	30.76
7	4960.00	52.2 PK	74.0	-21.8	1.04 H	223	15.83	36.33
8	4960.00	18.3 AV	54.0	-35.7	1.04 H	223	-18.08	36.33
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	86.4 PK	114.0	-27.6	1.03 V	286	55.69	30.74
2	*2480.00	52.5 AV	94.0	-41.5	1.03 V	286	21.78	30.74
3	2483.50	44.1 PK	74.0	-29.9	1.03 V	286	13.33	30.75
4	2483.50	10.2 AV	54.0	-43.8	1.03 V	286	-20.58	30.75
5	2485.50	56.8 PK	74.0	-17.2	1.03 V	286	26.08	30.76
6	2485.50	27.6 AV	54.0	-26.4	1.03 V	286	-3.18	30.76
7	4960.00	51.5 PK	74.0	-22.5	1.14 V	28	15.12	36.33
8	4960.00	17.6 AV	54.0	-36.4	1.14 V	28	-18.79	36.33

REMARKS:

- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- The other emission levels were very low against the limit.
- Margin value = Emission level – Limit value.
- " * " : Fundamental frequency
- The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (2.015 \text{ ms} / 100 \text{ ms}) = -33.9 \text{ dB}$
 Please see page 23 for plotted duty.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1000 hPa	TEST MODE	C
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.4 PK	74.0	-23.6	1.00 H	162	19.99	30.43
2	2390.00	27.7 AV	54.0	-26.3	1.00 H	162	-2.74	30.43
3	2398.00	60.1 PK	74.0	-13.9	1.00 H	162	29.59	30.46
4	2398.00	28.8 AV	54.0	-25.2	1.00 H	162	-1.67	30.46
5	2400.00	43.8 PK	74.0	-30.2	1.00 H	162	13.30	30.47
6	2400.00	9.9 AV	54.0	-44.1	1.00 H	162	-20.61	30.47
7	*2403.00	87.2 PK	114.0	-26.8	1.00 H	162	56.74	30.48
8	*2403.00	53.3 AV	94.0	-40.7	1.00 H	162	22.83	30.48
9	4806.00	51.4 PK	74.0	-22.6	1.04 H	221	15.36	36.08
10	4806.00	17.5 AV	54.0	-36.5	1.04 H	221	-18.55	36.08

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.3 PK	74.0	-23.7	1.02 V	281	19.89	30.43
2	2390.00	27.6 AV	54.0	-26.4	1.02 V	281	-2.82	30.43
3	2398.00	59.5 PK	74.0	-14.5	1.02 V	281	28.99	30.46
4	2398.00	28.2 AV	54.0	-25.8	1.02 V	281	-2.22	30.46
5	2400.00	42.7 PK	74.0	-31.3	1.02 V	281	12.23	30.47
6	2400.00	8.8 AV	54.0	-45.2	1.02 V	281	-21.68	30.47
7	*2403.00	86.2 PK	114.0	-27.8	1.02 V	281	55.67	30.48
8	*2403.00	52.3 AV	94.0	-41.7	1.02 V	281	21.76	30.48
9	4806.00	51.6 PK	74.0	-22.4	1.01 V	234	15.48	36.08
10	4806.00	17.7 AV	54.0	-36.3	1.01 V	234	-18.43	36.08

- REMARKS:**
- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 - Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 - The other emission levels were very low against the limit.
 - Margin value = Emission level – Limit value.
 - * * : Fundamental frequency
 - The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (2.015 \text{ ms} / 100 \text{ ms}) = -33.9 \text{ dB}$
 Please see page 23 for plotted duty.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1000 hPa	TEST MODE	C
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	87.7 PK	114.0	-26.3	1.02 H	175	57.06	30.62
2	*2444.00	53.8 AV	94.0	-40.2	1.02 H	175	23.15	30.62
3	4888.00	51.7 PK	74.0	-22.3	1.04 H	135	15.53	36.12
4	4888.00	17.8 AV	54.0	-36.2	1.04 H	135	-18.38	36.12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2444.00	86.5 PK	114.0	-27.5	1.03 V	276	55.83	30.62
2	*2444.00	52.6 AV	94.0	-41.4	1.03 V	276	21.92	30.62
3	4888.00	51.4 PK	74.0	-22.6	1.06 V	191	15.32	36.12
4	4888.00	17.5 AV	54.0	-36.5	1.06 V	191	-18.59	36.12

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency
 6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (2.015 \text{ ms} / 100 \text{ ms}) = -33.9 \text{ dB}$
 Please see page 23 for plotted duty.





EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 24	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH 1000 hPa	TEST MODE	C
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	87.4 PK	114.0	-26.6	1.02 H	168	56.70	30.74
2	*2480.00	53.5 AV	94.0	-40.5	1.02 H	168	22.79	30.74
3	2483.50	44.9 PK	74.0	-29.1	1.02 H	168	14.13	30.75
4	2483.50	11.0 AV	54.0	-43.0	1.02 H	168	-19.78	30.75
5	2485.50	57.1 PK	74.0	-16.9	1.02 H	168	26.38	30.76
6	2485.50	27.9 AV	54.0	-26.1	1.02 H	168	-2.90	30.76
7	4960.00	52.5 PK	74.0	-21.5	1.06 H	219	16.12	36.33
8	4960.00	18.6 AV	54.0	-35.4	1.06 H	219	-17.79	36.33
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	86.2 PK	114.0	-27.8	1.01 V	281	55.47	30.74
2	*2480.00	52.3 AV	94.0	-41.7	1.01 V	281	21.56	30.74
3	2483.50	43.7 PK	74.0	-30.3	1.01 V	281	12.90	30.75
4	2483.50	9.8 AV	54.0	-44.2	1.01 V	281	-21.01	30.75
5	2485.50	56.7 PK	74.0	-17.3	1.01 V	281	25.95	30.76
6	2485.50	27.4 AV	54.0	-26.6	1.01 V	281	-3.33	30.76
7	4960.00	51.3 PK	74.0	-22.7	1.01 V	22	14.93	36.33
8	4960.00	17.4 AV	54.0	-36.6	1.01 V	22	-18.98	36.33

REMARKS:

- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- The other emission levels were very low against the limit.
- Margin value = Emission level – Limit value.
- " * " : Fundamental frequency
- The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (2.015 \text{ ms} / 100 \text{ ms}) = -33.9 \text{ dB}$
 Please see page 23 for plotted duty.



$$20 \log (\text{Duty cycle}) = 20 \log (0.155 \cdot 13 \text{ ms} / 100 \text{ ms}) = -33.9 \text{ dB}$$



BELOW 1GHz WORST-CASE DATA

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 999 hPa	TEST MODE	A
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	193.22	26.0 QP	43.5	-17.5	1.50 H	277	15.14	10.84
2	319.60	24.9 QP	46.0	-21.2	1.00 H	229	10.26	14.60
3	399.31	30.3 QP	46.0	-15.7	1.50 H	172	12.28	18.02
4	572.36	26.5 QP	46.0	-19.5	2.00 H	223	4.58	21.89
5	799.84	33.7 QP	46.0	-12.3	1.00 H	7	7.67	26.02
6	904.83	34.5 QP	46.0	-11.5	2.00 H	94	6.50	27.97
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	55.18	31.5 QP	40.0	-8.5	1.00 V	10	18.50	13.03
2	195.16	27.9 QP	43.5	-15.6	1.00 V	172	17.15	10.73
3	339.04	27.4 QP	46.0	-18.6	1.50 V	304	11.94	15.46
4	399.31	29.8 QP	46.0	-16.2	1.50 V	298	11.77	18.02
5	795.95	36.4 QP	46.0	-9.6	1.50 V	337	10.40	25.98
6	959.27	36.5 QP	46.0	-9.5	2.00 V	304	7.88	28.60

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 999 hPa	TEST MODE	B
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	195.16	24.9 QP	43.5	-18.6	1.50 H	286	14.19	10.73
2	399.31	27.9 QP	46.0	-18.1	2.00 H	100	9.88	18.02
3	580.13	26.0 QP	46.0	-20.1	2.00 H	127	3.92	22.03
4	640.41	27.0 QP	46.0	-19.0	1.50 H	238	3.49	23.53
5	799.84	34.8 QP	46.0	-11.2	1.50 H	94	8.79	26.02
6	959.27	32.8 QP	46.0	-13.3	2.00 H	67	4.15	28.60
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	31.3 QP	40.0	-8.8	1.00 V	337	18.29	12.96
2	339.04	28.4 QP	46.0	-17.6	1.50 V	202	12.91	15.46
3	397.37	29.4 QP	46.0	-16.6	2.00 V	166	11.50	17.94
4	710.40	29.9 QP	46.0	-16.1	1.50 V	307	4.74	25.13
5	797.89	36.3 QP	46.0	-9.7	1.00 V	193	10.27	26.00
6	974.82	37.3 QP	54.0	-16.7	1.00 V	268	8.61	28.67

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH 999 hPa	TEST MODE	C
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	191.28	24.2 QP	43.5	-19.3	1.50 H	121	13.23	10.95
2	319.60	24.4 QP	46.0	-21.6	1.00 H	214	9.77	14.60
3	399.31	26.3 QP	46.0	-19.7	1.50 H	163	8.27	18.02
4	572.36	26.0 QP	46.0	-20.0	2.00 H	220	4.15	21.89
5	795.95	32.8 QP	46.0	-13.2	1.50 H	10	6.78	25.98
6	914.55	36.7 QP	46.0	-9.3	2.00 H	154	8.58	28.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	30.2 QP	40.0	-9.8	1.00 V	343	17.25	12.96
2	187.39	28.4 QP	43.5	-15.1	1.00 V	178	17.20	11.16
3	399.31	26.3 QP	46.0	-19.8	1.00 V	187	8.23	18.02
4	638.46	28.3 QP	46.0	-17.7	1.50 V	160	4.81	23.47
5	797.89	35.8 QP	46.0	-10.2	2.00 V	178	9.79	26.00
6	957.33	36.8 QP	46.0	-9.2	1.00 V	73	8.25	28.59

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Sep. 24, 2009	Sep. 23, 2010
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 31, 2008	Dec. 30, 2009
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Dec. 29, 2008	Dec. 28, 2009
LISN ROHDE & SCHWARZ	ESH3-Z5	100311	Jul. 29, 2009	Jul. 28, 2010
Software ADT	ADT_Cond_ V7.3.7	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.

4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.


4.2.7 TEST RESULTS

CONDUCTED WORST-CASE DATA

CHANNEL	Channel 1	PHASE	Line 1
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.167	0.13	48.70	-	48.83	-	65.10	55.10	-16.27	-
2	0.267	0.13	39.84	-	39.97	-	61.21	51.21	-21.23	-
3	2.156	0.20	40.33	-	40.53	-	56.00	46.00	-15.47	-
4	3.742	0.27	44.80	-	45.07	-	56.00	46.00	-10.93	-
5	4.023	0.28	43.33	-	43.61	-	56.00	46.00	-12.39	-
6	10.093	0.43	34.34	-	34.77	-	60.00	50.00	-25.23	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



CHANNEL	Channel 1	PHASE	Line 2
TEST MODE	A		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor (dB)	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.13	51.48	-	51.61	-	64.98	54.98	-13.37	-
2	0.283	0.14	38.26	-	38.40	-	60.73	50.73	-22.33	-
3	0.912	0.17	28.71	-	28.88	-	56.00	46.00	-27.12	-
4	3.179	0.26	40.48	-	40.74	-	56.00	46.00	-15.26	-
5	3.861	0.29	37.95	-	38.24	-	56.00	46.00	-17.76	-
6	9.688	0.49	29.50	-	29.99	-	60.00	50.00	-30.01	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



CHANNEL	Channel 1	PHASE	Line 1
TEST MODE	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	0.13	49.10	-	49.23	-	65.58	55.58	-16.35	-
2	0.263	0.13	42.82	-	42.95	-	61.33	51.33	-18.37	-
3	2.270	0.20	37.17	-	37.37	-	56.00	46.00	-18.63	-
4	3.515	0.26	37.98	-	38.24	-	56.00	46.00	-17.76	-
5	4.879	0.30	33.60	-	33.90	-	56.00	46.00	-22.10	-
6	9.816	0.43	30.75	-	31.18	-	60.00	50.00	-28.82	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



CHANNEL	Channel 1	PHASE	Line 2
TEST MODE	B		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor (dB)	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.13	48.84	-	48.97	-	64.98	54.98	-16.01	-
2	0.263	0.14	41.59	-	41.73	-	61.33	51.33	-19.60	-
3	3.117	0.26	38.41	-	38.67	-	56.00	46.00	-17.33	-
4	3.574	0.28	37.87	-	38.15	-	56.00	46.00	-17.85	-
5	5.957	0.37	26.40	-	26.77	-	60.00	50.00	-33.23	-
6	10.270	0.51	28.92	-	29.43	-	60.00	50.00	-30.57	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



CHANNEL	Channel 1	PHASE	Line 1
TEST MODE	C		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.13	47.98	-	48.11	-	64.98	54.98	-16.87	-
2	0.267	0.13	39.44	-	39.57	-	61.20	51.20	-21.63	-
3	1.758	0.19	36.22	-	36.41	-	56.00	46.00	-19.59	-
4	3.689	0.27	39.93	-	40.20	-	56.00	46.00	-15.80	-
5	5.449	0.32	28.94	-	29.26	-	60.00	50.00	-30.74	-
6	10.273	0.44	31.32	-	31.76	-	60.00	50.00	-28.24	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






A D T

CHANNEL	Channel 1	PHASE	Line 2
TEST MODE	C		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor (dB)	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	0.13	49.01	-	49.14	-	65.58	55.58	-16.44	-
2	0.228	0.13	39.90	-	40.03	-	62.52	52.52	-22.49	-
3	1.984	0.20	36.04	-	36.24	-	56.00	46.00	-19.76	-
4	4.082	0.30	34.39	-	34.69	-	56.00	46.00	-21.31	-
5	9.473	0.48	27.02	-	27.50	-	60.00	50.00	-32.50	-
6	14.008	0.63	27.77	-	28.40	-	60.00	50.00	-31.60	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.3 BAND EDGES MEASUREMENT

4.3.1 LIMITS OF BAND EDGES MEASUREMENT

Below –50dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
R&S SPECTRUM ANALYZER	FSP40	100040	Jul. 07, 2009	Jul. 06, 2010

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots are attached on the following pages.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.



4.3.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest and highest channel frequencies individually.

4.3.6 TEST RESULTS


The spectrum plots are attached on the following 4 images. D1 line indicates the highest level, and D2 line indicates the 50dB offset below D1. It shows compliance with the requirement in part 15.249 (d).

TEST MODE B






A D T



A D T



A D T



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, NVLAP
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA, CSA
R.O.C.	TAF, BSMI, NCC
Netherlands	Telefication
Singapore	GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab
Tel: 886-3-3183232
Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also

7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--- END ---