



A D T

# FCC TEST REPORT

**REPORT NO.:** RF120307D12

**MODEL NO.:** 1521

**FCC ID:** C3K1521

**RECEIVED:** Mar. 7, 2012

**TESTED:** Mar. 9, 2012

**ISSUED:** Mar. 26, 2012

**APPLICANT:** MICROSOFT CORPORATION

**ADDRESS:** ONE MICROSOFT WAY REDMOND, WA  
98052-6399, U.S.A

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)  
Ltd., Taoyuan Branch

**LAB LOCATION:** No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New  
Taipei City, Taiwan ( R.O.C. )

This test report consists of 48 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.





# TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	4
1. CERTIFICATION.....	5
2. SUMMARY OF TEST RESULTS .....	6
2.1 MEASUREMENT UNCERTAINTY .....	6
3. GENERAL INFORMATION .....	7
3.1 GENERAL DESCRIPTION OF EUT .....	7
3.2 DESCRIPTION OF TEST MODES .....	8
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....	8
3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	9
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	11
3.5 DESCRIPTION OF SUPPORT UNITS.....	11
4. TEST TYPES AND RESULTS.....	12
4.1 CONDUCTED EMISSION MEASUREMENT.....	12
4.2 RADIATED EMISSION MEASUREMENT .....	12
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	12
4.2.2 TEST INSTRUMENTS.....	13
4.2.3 TEST PROCEDURES .....	14
4.2.4 DEVIATION FROM TEST STANDARD .....	14
4.2.5 TEST SETUP.....	15
4.2.6 EUT OPERATING CONDITIONS.....	15
4.2.7 TEST RESULTS .....	16
4.3 NUMBER OF HOPPING FREQUENCY USED.....	29
4.3.1 LIMIT OF HOPPING FREQUENCY USED .....	29
4.3.2 TEST INSTRUMENTS.....	29
4.3.3 TEST PROCEDURES .....	29
4.3.4 DEVIATION FROM TEST STANDARD .....	30
4.3.5 TEST SETUP.....	30
4.3.6 TEST RESULTS .....	30
4.4 DWELL TIME ON EACH CHANNEL.....	32
4.4.1 LIMIT OF DWELL TIME USED .....	32
4.4.2 TEST INSTRUMENTS.....	32
4.4.3 TEST PROCEDURES .....	32
4.4.4 DEVIATION FROM TEST STANDARD .....	32
4.4.5 TEST SETUP.....	33
4.4.6 TEST RESULTS .....	33
4.5 CHANNEL BANDWIDTH.....	35
4.5.1 LIMITS OF CHANNEL BANDWIDTH.....	35
4.5.2 TEST INSTRUMENTS.....	35
4.5.3 TEST PROCEDURE .....	35
4.5.4 DEVIATION FROM TEST STANDARD .....	36
4.5.5 TEST SETUP.....	36
4.5.6 EUT OPERATING CONDITION.....	36
4.5.7 TEST RESULTS .....	37



4.6	HOPPING CHANNEL SEPARATION .....	38
4.6.1	LIMIT OF HOPPING CHANNEL SEPARATION .....	38
4.6.2	TEST INSTRUMENTS .....	38
4.6.3	TEST PROCEDURES .....	38
4.6.4	DEVIATION FROM TEST STANDARD .....	38
4.6.5	TEST SETUP .....	38
4.6.6	TEST RESULTS .....	39
4.7	MAXIMUM PEAK OUTPUT POWER .....	40
4.7.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	40
4.7.2	TEST INSTRUMENTS .....	40
4.7.3	TEST PROCEDURES .....	40
4.7.4	DEVIATION FROM TEST STANDARD .....	40
4.7.5	TEST SETUP .....	41
4.7.6	EUT OPERATING CONDITION .....	41
4.7.7	TEST RESULTS .....	42
4.8	CONDUCTED OUT OF BAND EMISSION MEASUREMENT .....	43
4.8.1	LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT .....	43
4.8.2	TEST INSTRUMENTS .....	43
4.8.3	TEST PROCEDURE .....	43
4.8.4	DEVIATION FROM TEST STANDARD .....	43
4.8.5	EUT OPERATING CONDITION .....	43
4.8.6	TEST RESULTS .....	44
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	46
6.	INFORMATION ON THE TESTING LABORATORIES .....	47
7.	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	48



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120307D12	Original release	Mar. 26, 2012



## 1. CERTIFICATION

**PRODUCT:** Microsoft Wireless Keyboard  
**BRAND NAME:** Microsoft  
**MODEL NO.:** 1521  
**APPLICANT:** MICROSOFT CORPORATION  
**TESTED:** Mar. 9, 2012  
**TEST ITEM:** ENGINEERING SAMPLE  
**STANDARDS:** FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10-2009

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :** Celia Chen , **DATE:** Mar. 26. 2012  
( Celia Chen / Senior Specialist )

**APPROVED BY :** Ken Liu , **DATE:** Mar. 26. 2012  
( Ken Liu / Manager )

## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	N/A	Power supply is 3Vdc from batteries
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -10.4dB at 2390.00MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

**NOTE:** If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	30MHz ~ 1GHz	3.87 dB
	Above 1GHz	3.36 dB



### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Microsoft Wireless Keyboard
<b>MODEL NO.</b>	1521
<b>FCC ID</b>	C3K1521
<b>POWER SUPPLY</b>	3Vdc from batteries
<b>MODULATION TYPE</b>	GFSK
<b>RADIO TECHNOLOGY</b>	FHSS
<b>TRANSFER RATE</b>	723.2Kbps
<b>OPERATING FREQUENCY</b>	2402 ~ 2480MHz
<b>NUMBER OF CHANNEL</b>	79
<b>OUTPUT POWER</b>	0.6mW
<b>ANTENNA TYPE</b>	Printed antenna with -6.04dBi gain
<b>ANTENNA CONNECTOR</b>	N/A
<b>DATA CABLE</b>	N/A
<b>I/O PORTS</b>	N/A
<b>ASSOCIATED DEVICES</b>	N/A

**NOTE:**

1. The EUT is a Microsoft Wireless Keyboard.
2. The EUT has serial samples, which are defined as their serial numbers as follows:

<b>Model No.</b>	<b>Serial no.</b>
1521	EV2-009, EV2-025, EV2-032, EV2-061


3. For more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

#### 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST







### 3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	Applicable to				Description
	PLC	RE<1G	RE <sup>&gt;1G</sup>	APCM	
-	-	√	√	√	-

Where **PLC:** Power Line Conducted Emission

**RE<1G:** Radiated Emission below 1GHz

**RE<sup>>1G</sup>:** Radiated Emission above 1GHz

**APCM:** Antenna Port Conducted Measurement

**NOTE:** "-" means no effect.

**NOTE:** No need to concern of Conducted Emission due to the EUT is powered by batteries.

#### RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

SERIAL NO.	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
EV2-009, EV2-025, EV2-032	0 to 78	78	FHSS	GFSK	DH5

#### RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

SERIAL NO.	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
EV2-009, EV2-025, EV2-032	0 to 78	0, 39, 78	FHSS	GFSK	DH5



A D T

### **BANDEDGE MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

SERIAL NO.	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
EV2-061	0 to 78	0, 78	FHSS	GFSK	DH5

### **ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

SERIAL NO.	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
EV2-061	0 to 78	0, 39, 78	FHSS	GFSK	DH5

### **TEST CONDITION:**

APPLICABLE TO	SERIAL NO.	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE <sup>3</sup> 1G	EV2-009, EV2-025, EV2-032	16deg. C, 75% RH	3Vdc	Chad Lee
RE<1G	EV2-009, EV2-025, EV2-032	16deg. C, 68% RH	3Vdc	Chad Lee
APCM	EV2-061	16deg. C, 80% RH	3Vdc	Jun Wu

**Note:** The above four samples were pre-tested, for the **RE>1G & RE<1G** tests, the worst emission level was found on serial no.: EV2-009, EV2-025, EV2-032 and for the **APCM** tests, the worst emission level was found on serial no.: EV2-061.

### **3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (Section 15.247)**

**ANSI C63.10-2009**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

### **3.5 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit.

## 4. TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

N/A

### 4.2 RADIATED EMISSION MEASUREMENT

#### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



## 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
HP Preamplifier	8447D	2432A03504	Feb. 29, 2012	Feb. 28, 2013
HP Preamplifier	8449B	3008A01201	Feb. 29, 2012	Feb. 28, 2013
Agilent Spectrum Analyzer	E4446A	MY46180403	Jun. 22, 2011	Jun. 21, 2012
ROHDE & SCHWARZ Test Receiver	ESCS 30	838251/021	Oct. 14, 2011	Oct. 13, 2012
Schwarzbeck Antenna	VULB 9168	137	Apr. 12, 2011	Apr. 11, 2012
Schwarzbeck Antenna	VHBA 9123	480	May 06, 2011	May 05, 2012
ADT. Turn Table	TT100	0306	NA	NA
ADT. Tower	AT100	0306	NA	NA
Software	ADT_Radiated_V 7.6.15.9.2	NA	NA	NA
SUHNER RF cable	SF102	CABLE-CH6	Aug. 19, 2011	Aug. 18, 2012
Schwarzbeck Horn Antenna	BBHA 9120-D1	D130	May 16, 2011	May 15, 2012
Highpass filter Wainwright Instruments	WHK 3.1/18G-10SS	SN 8	NA	NA
SPECTRUM ANALYZER	FSP 40	100036	Apr. 29, 2011	Apr. 28, 2012

- NOTE:**
1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
  2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  3. The test was performed in Chamber No. 6.
  4. The Industry Canada Reference No. IC 7450E-6.
  5. The FCC Site Registration No. is 447212.

### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak method or average method as specified and then reported in data sheet.


#### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

## 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

## 4.2.6 EUT OPERATING CONDITIONS

Set the EUT under transmission/receiving condition continuously at specific channel frequency.

## 4.2.7 TEST RESULTS

### ABOVE 1GHz DATA (For Fundamental, Harmonics)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 75%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-025		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.4 PK	74.0	-18.6	1.00 H	262	25.13	30.24
2	<b>2390.00</b>	<b>43.6 AV</b>	<b>54.0</b>	<b>-10.4</b>	<b>1.00 H</b>	<b>262</b>	<b>13.36</b>	<b>30.24</b>
3	#2400.00	45.8 PK	70.2	-24.4	1.00 H	262	15.53	30.29
4	#2400.00	15.7 AV	40.1	-24.4	1.00 H	262	-14.57	30.29
5	*2402.00	90.2 PK			1.00 H	262	59.92	30.30
6	*2402.00	60.1 AV			1.00 H	262	29.82	30.30
7	4804.00	44.2 PK	74.0	-29.8	1.00 H	6	7.61	36.59
8	4804.00	14.1 AV	54.0	-39.9	1.00 H	6	-22.49	36.59
9	#7206.00	52.6 PK	70.2	-17.7	1.00 H	0	10.11	42.46
10	#7206.00	22.5 AV	40.1	-17.7	1.00 H	0	-19.99	42.46

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 75%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-025		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.4 PK	74.0	-19.6	1.00 V	261	24.14	30.24
2	2390.00	42.6 AV	54.0	-11.4	1.00 V	261	12.36	30.24
3	#2400.00	44.4 PK	68.8	-24.4	1.00 V	261	14.13	30.29
4	#2400.00	14.3 AV	38.7	-24.4	1.00 V	261	-15.97	30.29
5	*2402.00	88.8 PK			1.00 V	261	58.52	30.30
6	*2402.00	58.7 AV			1.00 V	261	28.42	30.30
7	4804.00	45.1 PK	74.0	-28.9	1.00 V	131	8.52	36.59
8	4804.00	15.0 AV	54.0	-39.0	1.00 V	131	-21.58	36.59
9	#7206.00	54.9 PK	68.8	-13.9	1.00 V	357	12.43	42.46
10	#7206.00	24.8 AV	38.7	-13.9	1.00 V	357	-17.67	42.46

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .
  8. "#":The radiated frequency is out the restricted band.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 75%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-025		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	86.2 PK			1.00 H	255	55.73	30.43
2	*2441.00	56.1 AV			1.00 H	255	25.63	30.43
3	4882.00	45.3 PK	74.0	-28.7	1.00 H	6	8.51	36.79
4	4882.00	15.2 AV	54.0	-38.8	1.00 H	6	-21.59	36.79
5	7323.00	50.5 PK	74.0	-23.5	1.00 H	318	7.84	42.69
6	7323.00	20.4 AV	54.0	-33.6	1.00 H	318	-22.26	42.69
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	85.4 PK			1.00 V	89	54.96	30.43
2	*2441.00	55.3 AV			1.00 V	89	24.86	30.43
3	4882.00	46.1 PK	74.0	-28.0	1.00 V	161	9.26	36.79
4	4882.00	16.0 AV	54.0	-38.1	1.00 V	161	-20.84	36.79
5	7323.00	56.6 PK	74.0	-17.4	1.00 V	9	13.92	42.69
6	7323.00	26.5 AV	54.0	-27.5	1.00 V	9	-16.18	42.69

- REMARKS:**
- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  - Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  - The other emission levels were very low against the limit.
  - Margin value = Emission level – Limit value.
  - \* \*: Fundamental frequency.
  - The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  - Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 75%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-025		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	86.7 PK			1.00 H	296	56.13	30.56
2	*2480.00	56.6 AV			1.00 H	296	26.03	30.56
3	2483.50	43.5 PK	74.0	-30.5	1.00 H	296	12.92	30.57
4	2483.50	13.4 AV	54.0	-40.6	1.00 H	296	-17.18	30.57
5	4960.00	44.3 PK	74.0	-29.7	1.00 H	64	7.29	36.99
6	4960.00	14.1 AV	54.0	-39.9	1.00 H	64	-22.85	36.99
7	7440.00	54.1 PK	74.0	-19.9	1.00 H	357	11.18	42.88
8	7440.00	24.0 AV	54.0	-30.0	1.00 H	357	-18.92	42.88
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	84.0 PK			1.00 V	97	53.43	30.56
2	*2480.00	53.9 AV			1.00 V	97	23.33	30.56
3	2483.50	40.8 PK	74.0	-33.2	1.00 V	97	10.22	30.57
4	2483.50	10.7 AV	54.0	-43.3	1.00 V	97	-19.88	30.57
5	4960.00	46.9 PK	74.0	-27.1	1.00 V	223	9.94	36.99
6	4960.00	16.8 AV	54.0	-37.2	1.00 V	223	-20.16	36.99
7	7440.00	57.4 PK	74.0	-16.6	1.00 V	6	14.51	42.88
8	7440.00	27.3 AV	54.0	-26.7	1.00 V	6	-15.59	42.88

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

**ABOVE 1GHz DATA (For Spurious Emission)**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 75%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-009		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4804.00	45.2 PK	74.0	-28.8	1.00 H	6	8.60	36.59
2	4804.00	15.1 AV	54.0	-38.9	1.00 H	6	-21.50	36.59
3	7206.00	52.0 PK	74.0	-22.0	1.00 H	62	9.57	42.46
4	7206.00	21.9 AV	54.0	-32.1	1.00 H	62	-20.53	42.46
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4804.00	47.7 PK	74.0	-26.3	1.00 V	182	11.13	36.59
2	4804.00	17.6 AV	54.0	-36.4	1.00 V	182	-18.97	36.59
3	7206.00	54.3 PK	74.0	-19.7	1.00 V	8	11.82	42.46
4	7206.00	24.2 AV	54.0	-29.8	1.00 V	8	-18.28	42.46

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  6. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 75%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-009		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4882.00	45.0 PK	74.0	-29.1	1.00 H	14	8.16	36.79
2	4882.00	14.9 AV	54.0	-39.2	1.00 H	14	-21.94	36.79
3	7323.00	51.1 PK	74.0	-22.9	1.00 H	6	8.40	42.69
4	7323.00	21.0 AV	54.0	-33.0	1.00 H	6	-21.70	42.69
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4882.00	45.6 PK	74.0	-28.4	1.00 V	6	8.78	36.79
2	4882.00	15.5 AV	54.0	-38.5	1.00 V	6	-21.32	36.79
3	7323.00	54.2 PK	74.0	-19.9	1.00 V	11	11.46	42.69
4	7323.00	24.1 AV	54.0	-30.0	1.00 V	11	-18.64	42.69

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  6. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 75%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-009		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4960.00	45.0 PK	74.0	-29.1	1.00 H	6	7.96	36.99
2	4960.00	14.9 AV	54.0	-39.2	1.00 H	6	-22.14	36.99
3	7440.00	52.5 PK	74.0	-21.5	1.00 H	12	9.64	42.88
4	7440.00	22.4 AV	54.0	-31.6	1.00 H	12	-20.46	42.88
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4960.00	45.7 PK	74.0	-28.3	1.00 V	357	8.67	36.99
2	4960.00	15.6 AV	54.0	-38.4	1.00 V	357	-21.43	36.99
3	7440.00	55.9 PK	74.0	-18.1	1.00 V	180	13.02	42.88
4	7440.00	25.8 AV	54.0	-28.2	1.00 V	180	-17.08	42.88

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  6. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 75%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-032		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4804.00	45.6 PK	74.0	-28.4	1.00 H	8	9.01	36.59
2	4804.00	15.5 AV	54.0	-38.5	1.00 H	8	-21.09	36.59
3	7206.00	50.6 PK	74.0	-23.4	1.00 H	6	8.16	42.46
4	7206.00	20.5 AV	54.0	-33.5	1.00 H	6	-21.94	42.46
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4804.00	47.5 PK	74.0	-26.5	1.00 V	45	10.88	36.59
2	4804.00	17.4 AV	54.0	-36.6	1.00 V	45	-19.22	36.59
3	7206.00	53.6 PK	74.0	-20.4	1.00 V	1	11.17	42.46
4	7206.00	23.5 AV	54.0	-30.5	1.00 V	1	-18.93	42.46

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  6. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 75%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-032		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4882.00	44.8 PK	74.0	-29.2	1.00 H	6	8.01	36.79
2	4882.00	14.7 AV	54.0	-39.3	1.00 H	6	-22.09	36.79
3	7323.00	51.1 PK	74.0	-22.9	1.00 H	16	8.40	42.69
4	7323.00	21.0 AV	54.0	-33.0	1.00 H	16	-21.70	42.69
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4882.00	45.9 PK	74.0	-28.1	1.00 V	284	9.11	36.79
2	4882.00	15.8 AV	54.0	-38.2	1.00 V	284	-20.99	36.79
3	7323.00	53.4 PK	74.0	-20.6	1.00 V	6	10.75	42.69
4	7323.00	23.3 AV	54.0	-30.7	1.00 V	6	-19.35	42.69

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
  6. Average value = peak reading +  $20\log(\text{duty cycle})$ .





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 75%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-032		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4960.00	45.2 PK	74.0	-28.8	1.00 H	16	8.20	36.99
2	4960.00	15.1 AV	54.0	-38.9	1.00 H	16	-21.90	36.99
3	7440.00	53.1 PK	74.0	-20.9	1.00 H	6	10.24	42.88
4	7440.00	23.0 AV	54.0	-31.0	1.00 H	6	-19.86	42.88
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4960.00	45.4 PK	74.0	-28.6	1.00 V	6	8.40	36.99
2	4960.00	15.3 AV	54.0	-38.7	1.00 V	6	-21.70	36.99
3	7440.00	58.7 PK	74.0	-15.3	1.00 V	244	15.79	42.88
4	7440.00	28.6 AV	54.0	-25.4	1.00 V	244	-14.31	42.88

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1 \text{ dB}$ .
  6. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

**BELOW 1GHz WORST-CASE DATA**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	16deg. C, 68%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-025		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	62.28	24.2 QP	40.0	-15.8	1.17 H	232	11.02	13.14
2	81.65	22.2 QP	40.0	-17.9	1.85 H	265	12.21	9.94
3	117.15	24.5 QP	43.5	-19.0	1.23 H	172	12.58	11.88
4	832.15	26.5 QP	46.0	-19.5	1.41 H	253	-0.53	27.02
5	862.81	27.8 QP	46.0	-18.3	1.79 H	256	0.37	27.38
6	877.34	27.3 QP	46.0	-18.7	1.62 H	271	-0.22	27.54
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	39.68	29.0 QP	40.0	-11.0	1.15 V	307	14.74	14.22
2	88.10	31.0 QP	43.5	-12.5	1.69 V	46	22.17	8.86
3	117.15	26.1 QP	43.5	-17.4	1.84 V	169	14.24	11.88
4	138.14	28.5 QP	43.5	-15.0	1.32 V	226	15.01	13.53
5	189.78	29.8 QP	43.5	-13.8	1.00 V	220	17.52	12.23
6	857.97	27.7 QP	46.0	-18.3	1.50 V	184	0.40	27.33

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	16deg. C, 68%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-009		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	39.68	22.6 QP	40.0	-17.4	1.12 H	37	8.39	14.22
2	75.19	21.9 QP	40.0	-18.1	1.08 H	322	10.47	11.39
3	791.80	26.6 QP	46.0	-19.4	1.35 H	139	0.15	26.41
4	827.30	26.8 QP	46.0	-19.2	1.74 H	193	-0.12	26.95
5	866.04	27.0 QP	46.0	-19.0	1.81 H	4	-0.42	27.41
6	928.99	28.0 QP	46.0	-18.0	1.06 H	346	-0.12	28.16
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	42.91	29.3 QP	40.0	-10.7	1.15 V	133	15.18	14.15
2	73.58	29.5 QP	40.0	-10.5	1.69 V	13	17.69	11.79
3	113.93	27.7 QP	43.5	-15.8	1.82 V	331	16.26	11.43
4	152.66	25.8 QP	43.5	-17.7	1.31 V	343	11.36	14.46
5	799.87	26.2 QP	46.0	-19.8	1.47 V	4	-0.43	26.61
6	822.46	26.4 QP	46.0	-19.7	1.55 V	10	-0.54	26.89

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	16deg. C, 68%RH	TESTED BY	Chad Lee
SERIAL NO.	EV2-032		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	62.28	22.2 QP	40.0	-17.8	1.56 H	196	9.07	13.14
2	76.81	22.5 QP	40.0	-17.5	1.84 H	13	11.46	11.00
3	138.14	23.5 QP	43.5	-20.0	1.71 H	199	9.97	13.53
4	801.48	26.0 QP	46.0	-20.0	1.00 H	58	-0.60	26.63
5	819.23	26.6 QP	46.0	-19.4	1.00 H	118	-0.24	26.85
6	867.65	26.9 QP	46.0	-19.1	1.15 H	49	-0.52	27.43
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	39.68	28.4 QP	40.0	-11.6	1.15 V	10	14.21	14.22
2	97.79	31.1 QP	43.5	-12.4	1.22 V	103	21.83	9.27
3	151.05	25.3 QP	43.5	-18.2	1.48 V	142	10.83	14.45
4	801.48	26.3 QP	46.0	-19.8	1.32 V	103	-0.38	26.63
5	812.78	26.8 QP	46.0	-19.2	1.68 V	115	0.05	26.77
6	859.58	27.5 QP	46.0	-18.5	1.71 V	331	0.14	27.34

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.

## **4.3 NUMBER OF HOPPING FREQUENCY USED**

### **4.3.1 LIMIT OF HOPPING FREQUENCY USED**

At least 15 channels frequencies, and should be equally spaced.

### **4.3.2 TEST INSTRUMENTS**

Refer to section 4.2.2 to get information of above instrument.


### **4.3.3 TEST PROCEDURES**

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.3.5 TEST SETUP





#### 4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.



A D T

SERIAL NO.: EV2-061



## **4.4 DWELL TIME ON EACH CHANNEL**

### **4.4.1 LIMIT OF DWELL TIME USED**

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### **4.4.2 TEST INSTRUMENTS**

Refer to section 4.2.2 to get information of above instrument.

### **4.4.3 TEST PROCEDURES**


- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

### **4.4.4 DEVIATION FROM TEST STANDARD**

No deviation.



#### 4.4.5 TEST SETUP



#### 4.4.6 TEST RESULTS

SERIAL NO.: EV2-061



Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	51 (times / 5 sec) *6.32=322.32 times	0.492	158.58144	400
DH3	25 (times / 5 sec) *6.32=158.00 times	1.752	276.81600	400
DH5	17 (times / 5 sec) *6.32=107.44 times	3.000	322.32000	400

**NOTE:** Test plots of the transmitting time slot are shown on next 3 pages for test channel 39.





A D T



### DH1



### DH3



### DH5



## **4.5 CHANNEL BANDWIDTH**

### **4.5.1 LIMITS OF CHANNEL BANDWIDTH**

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

### **4.5.2 TEST INSTRUMENTS**

Refer to section 4.2.2 to get information of above instrument.


### **4.5.3 TEST PROCEDURE**

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

#### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.5.5 TEST SETUP



#### 4.5.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.




A D T

### 4.5.7 TEST RESULTS

SERIAL NO.: EV2-061

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.10
39	2441	1.04
78	2480	1.03

#### CH 0



## 4.6 HOPPING CHANNEL SEPARATION

### 4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

### 4.6.2 TEST INSTRUMENTS

Refer to section 4.2.2 to get information of above instrument.


### 4.6.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

### 4.6.4 DEVIATION FROM TEST STANDARD

No deviation.

### 4.6.5 TEST SETUP




### 4.6.6 TEST RESULTS

SERIAL NO.: EV2-061

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.10	0.73	PASS
39	2441	1.00	1.04	0.69	PASS
78	2480	1.00	1.03	0.69	PASS

**NOTE:** The minimum limit is two-third 20dB bandwidth. Test results please refer to following plot.

#### CH 39



## **4.7 MAXIMUM PEAK OUTPUT POWER**

### **4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT**

The Maximum Peak Output Power Measurement is 125mW.

### **4.7.2 TEST INSTRUMENTS**

Refer to section 4.2.2 to get information of above instrument.

### **4.7.3 TEST PROCEDURES**


- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3 MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

### **4.7.4 DEVIATION FROM TEST STANDARD**

No deviation



#### 4.7.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

#### 4.7.6 EUT OPERATING CONDITION


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

### 4.7.7 TEST RESULTS

SERIAL NO.: EV2-061

CHANNEL	CHANNEL FREQUENCY (MHz)	OUTPUT POWER (dBm)	OUTPUT POWER (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	-3.3	0.5	125	PASS
39	2441	-3.0	0.5	125	PASS
78	2480	-2.5	<b>0.6</b>	125	PASS

#### CH 78



## **4.8 CONDUCTED OUT OF BAND EMISSION MEASUREMENT**

### **4.8.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT**

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100KHz RBW).

### **4.8.2 TEST INSTRUMENTS**

Refer to section 4.2.2 to get information of above instrument.

### **4.8.3 TEST PROCEDURE**

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

### **4.8.4 DEVIATION FROM TEST STANDARD**

No deviation.

### **4.8.5 EUT OPERATING CONDITION**


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

### 4.8.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

The spectrum plots (RBW = 100kHz, VBW = 300kHz) are attached on the following pages.


SERIAL NO.: EV2-061






A D T

### Hopping enabled \_ Low Channel



### Hopping enabled \_ High Channel



## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



## 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation and authorization certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5.phtml](http://www.adt.com.tw/index.5.phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Telecom Lab:**

Tel: 886-3-3183232

Fax: 886-3-3185050

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



A D T

## **7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No modifications were made to the EUT by the lab during the test.

**---END---**