

RF EXPOSURE REPORT

REPORT NO.: SA120307D12

MODEL NO.: 1521

FCC ID: C3K1521

RECEIVED: Mar. 7, 2012

TESTED: Mar. 9, 2012

ISSUED: Mar. 26, 2012

APPLICANT: MICROSOFT CORPORATION

ADDRESS: ONE MICROSOFT WAY REDMOND, WA 98052-6399,

U.S.A

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

LAB LOCATION: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New

Taipei City, Taiwan (R.O.C.)

This test report consists of 5 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

RELEAS	SE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	CONCLUSION	5



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA120307D12	Original release	Mar. 26, 2012

Report No: SA120307D12 3 Report Format Version 4.0.0



1. CERTIFICATION

PRODUCT: Microsoft Wireless Keyboard

BRAND NAME: Microsoft

MODEL NO.: 1521

APPLICANT: MICROSOFT CORPORATION

TESTED: Mar. 9, 2012

TEST ITEM: **ENGINEERING SAMPLE**

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

, DATE: Mar. 26.2012



2. CONCLUSION

No Evaluation Required if power is below this threshold:

F(G	Hz)	mW	
Low	2.402	24.58	
High	2.480	24.50	

Maximum measured transmitter power:

Pout (dBm	Pout (mW)	
Conducted Power	-2.5	0.6
EIRP Power	-8.5	0.1

*Note: The antenna is Printed antenna with -6.04dBi gain

Threshold for no SAR evaluation is 24.58mW Transmitter power is 0.6mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END---