



A D T

FCC TEST REPORT

REPORT NO.: RF130107C26
MODEL NO.: 1569
FCC ID: C3K1569
RECEIVED: Jan. 08, 2013
TESTED: Jan. 08 ~ Jan. 09, 2013
ISSUED: Jan. 14, 2013

APPLICANT: Microsoft Corporation

ADDRESS: One Microsoft Way, Redmond WA 98052-6399,
U.S.A.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



Table of Contents

| | |
|--|----|
| RELEASE CONTROL RECORD..... | 3 |
| 1. CERTIFICATION | 4 |
| 2. SUMMARY OF TEST RESULTS..... | 5 |
| 2.1 MEASUREMENT UNCERTAINTY | 5 |
| 3. GENERAL INFORMATION | 6 |
| 3.1 GENERAL DESCRIPTION OF EUT..... | 6 |
| 3.2 DESCRIPTION OF TEST MODES..... | 7 |
| 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL | 8 |
| 3.3 DESCRIPTION OF SUPPORT UNITS..... | 9 |
| 3.3.1 CONFIGURATION OF SYSTEM UNDER TEST..... | 9 |
| 3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS..... | 10 |
| 4. TEST TYPES AND RESULTS..... | 11 |
| 4.1 RADIATED EMISSION and band edge MEASUREMENT..... | 11 |
| 4.1.1 LIMITS OF RADIATED EMISSION AND BAND EDGE MEASUREMENT | 11 |
| 4.1.2 TEST INSTRUMENTS | 12 |
| 4.1.3 TEST PROCEDURES | 13 |
| 4.1.4 DEVIATION FROM TEST STANDARD | 13 |
| 4.1.5 TEST SETUP | 14 |
| 4.1.6 EUT OPERATING CONDITIONS..... | 14 |
| 4.1.7 TEST RESULTS | 15 |
| 5. PHOTOGRAPHS OF THE TEST CONFIGURATION | 28 |
| 6. INFORMATION ON THE TESTING LABORATORIES..... | 29 |
| 7. APPENDIX A – MODIFICATION RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB..... | 30 |



RELEASE CONTROL RECORD

| ISSUE NO. | REASON FOR CHANGE | DATE ISSUED |
|-------------|-------------------|---------------|
| RF130107C26 | Original release | Jan. 14, 2013 |



1. CERTIFICATION

PRODUCT: Wireless Mouse

MODEL NO.: 1569

BRAND: Microsoft

APPLICANT: Microsoft Corporation

TESTED: Jan. 08 ~ Jan. 09, 2013

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 15, Subpart C (Section 15.249)

ANSI C63.10-2009

The above equipment (model: 1569) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Celine Chou , **DATE** : Jan. 14, 2013
Celine Chou / Specialist

APPROVED BY : Ken Liu , **DATE** : Jan. 14, 2013
Ken Liu / Manager



2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.249) | | | |
|---|--|--------|--|
| STANDARD PARAGRAPH | TEST TYPE | RESULT | REMARK |
| 15.207 | Conducted Emission Test | NA | Power supply is 1.5Vdc from batteries. |
| 15.209 15.249 15.249 (d) | Radiated Emission Test Band Edge Measurement Limit: 50dB less than the peak value of fundamental frequency or meet radiated emission limit in section 15.209 | PASS | Meet the requirement of limit. Minimum passing margin is -7.6dB at 256.16MHz. |

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT | FREQUENCY | UNCERTAINTY |
|-------------------|-----------------|-------------|
| Radiated emission | 30MHz ~ 200MHz | 3.34 dB |
| | 200MHz ~1000MHz | 3.35 dB |
| | 1GHz ~ 18GHz | 2.26 dB |
| | 18GHz ~ 40GHz | 1.94 dB |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

| | |
|----------------------------|--------------------------------|
| EUT | Wireless Mouse |
| MODEL NO. | 1569 |
| POWER SUPPLY | 1.5Vdc (battery) |
| MODULATION TYPE | GFSK |
| OPERATING FREQUENCY | 2403 ~ 2480MHz |
| NUMBER OF CHANNEL | 24 |
| ANTENNA TYPE | PIFA antenna with 4.14dBi gain |
| DATA CABLE | N/A |
| I/O PORT | N/A |
| ACCESSORY DEVICES | N/A |

NOTE:

1. The EUT has transmitter and receiver functions.
2. The following samples are provided for final test.

| SAMPLE | SERIAL NO. |
|---------------|-------------------|
| Sample A | 671 |
| Sample B | 674 |
| Sample C | 677 |

3. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

24 channels are provided to this EUT:

| Index | Channel Group | Frequency (MHz) | Index | Channel Group | Frequency (MHz) |
|-------|---------------|-----------------|-------|---------------|-----------------|
| 0 | Subset A | 2403 | 1 | Subset A | 2419 |
| 4 | Subset B | 2429 | 5 | Subset B | 2450 |
| 8 | Subset C | 2421 | 9 | Subset C | 2431 |
| 12 | Subset D | 2405 | 13 | Subset D | 2425 |
| 16 | Subset E | 2423 | 17 | Subset E | 2446 |
| 20 | Subset F | 2417 | 21 | Subset F | 2427 |

| Index | Channel Group | Frequency (MHz) | Index | Channel Group | Frequency (MHz) |
|-------|---------------|-----------------|-------|---------------|-----------------|
| 2 | Subset A | 2478 | 3 | Subset A | 2468 |
| 6 | Subset B | 2470 | 7 | Subset B | 2480 |
| 10 | Subset C | 2472 | 11 | Subset C | 2454 |
| 14 | Subset D | 2444 | 15 | Subset D | 2452 |
| 18 | Subset E | 2456 | 19 | Subset E | 2474 |
| 22 | Subset F | 2448 | 23 | Subset F | 2476 |

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

| EUT CONFIGURE MODE | APPLICABLE TO | | | | DESCRIPTION |
|--------------------|---------------|-----------|----|----|-----------------|
| | RE \geq 1G | RE $<$ 1G | BM | FF | |
| A | √ | √ | - | - | Serial No.: 671 |
| B | √ | √ | - | - | Serial No.: 674 |
| C | √ | √ | √ | √ | Serial No.: 677 |

Where **RE $<$ 1G**: Radiated Emission below 1GHz **RE \geq 1G**: Radiated Emission above 1GHz
BM: Bandedge Measurement **FF**: Fundamental Frequency

NOTE: "-" means no effect.

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | AVAILABLE CHANNEL | TESTED FREQUENCY (MHZ) | MODULATION TYPE |
|--------------------|-------------------|------------------------|-----------------|
| A, B, C | 2403 to 2480 | 2403, 2444, 2480 | GFSK |

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | AVAILABLE CHANNEL | TESTED FREQUENCY (MHZ) | MODULATION TYPE |
|--------------------|-------------------|------------------------|-----------------|
| A, B, C | 2403 to 2480 | 2403 | GFSK |

BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | AVAILABLE CHANNEL | TESTED FREQUENCY (MHZ) | MODULATION TYPE |
|--------------------|-------------------|------------------------|-----------------|
| C | 2403 to 2480 | 2403, 2480 | GFSK |



FUNDAMENTAL MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | AVAILABLE CHANNEL | TESTED FREQUENCY (MHZ) | MODULATION TYPE |
|--------------------|-------------------|------------------------|-----------------|
| C | 2403 to 2480 | 2403, 2480 | GFSK |


TEST CONDITION:

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | INPUT POWER | TESTED BY |
|---------------|--------------------------|-------------|-----------|
| RE \geq 1G | 25deg. C, 65%RH | 1.5Vdc | Chris Lin |
| RE $<$ 1G | 25deg. C, 65%RH | 1.5Vdc | Chris Lin |
| BM | 25deg. C, 65%RH | 1.5Vdc | Chris Lin |
| FF | 25deg. C, 65%RH | 1.5Vdc | Chris Lin |

3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit.

3.3.1 CONFIGURATION OF SYSTEM UNDER TEST





3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (Section 15.249)

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION AND BAND EDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BAND EDGE MEASUREMENT

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following

| Fundamental Frequency | Field Strength of Fundamental (millivolts/meter) | Field Strength of Harmonics (microvolts/meter) |
|-----------------------|--|--|
| 902 ~ 928 MHz | 50 | 500 |
| 2400 ~ 2483.5 MHz | 50 | 500 |
| 5725 ~ 5875 MHz | 50 | 500 |
| 24 ~ 24.25 GHz | 250 | 2500 |

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits as below table, whichever is the lesser attenuation

| Frequencies (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490 | 2400/F(kHz) | 300 |
| 0.490 ~ 1.705 | 24000/F(kHz) | 30 |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 | 3 |
| 88 ~ 216 | 150 | 3 |
| 216 ~ 960 | 200 | 3 |
| Above 960 | 500 | 3 |

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | DATE OF CALIBRATION | DUE DATE OF CALIBRATION |
|--|------------------------------|------------------|---------------------|-------------------------|
| Test Receiver ROHDE & SCHWARZ | ESIB7 | 100212 | Aug. 06, 2012 | Aug. 05, 2013 |
| Spectrum Analyzer ROHDE & SCHWARZ | FSP40 | 100039 | Feb. 03, 2012 | Feb. 02, 2013 |
| BILOG Antenna SCHWARZBECK | VULB9168 | 9168-160 | Apr. 06, 2012 | Apr. 05, 2013 |
| HORN Antenna SCHWARZBECK | 9120D | 209 | Sep. 03, 2012 | Sep. 02, 2013 |
| HORN Antenna SCHWARZBECK | BBHA 9170 | 148 | Jul. 11, 2012 | Jul. 10, 2013 |
| Loop Antenna | HFH2-Z2 | 100070 | Jan. 31, 2012 | Jan. 30, 2014 |
| Preamplifier Agilent | 8447D | 2944A10633 | Oct. 25, 2012 | Oct. 24, 2013 |
| Preamplifier Agilent | 8449B | 3008A01964 | Oct. 25, 2012 | Oct. 24, 2013 |
| RF signal cable HUBER+SUHNNER | SUCOFLEX 104 | 250723/4 | Aug. 28, 2012 | Aug. 27, 2013 |
| RF signal cable HUBER+SUHNNER | SUCOFLEX 106 | 12738/6+309224/4 | Aug. 28, 2012 | Aug. 27, 2013 |
| Software ADT. | ADT_Radiated_ V7.6.15.9.2 | NA | NA | NA |
| Antenna Tower inn-co GmbH | MA 4000 | 013303 | NA | NA |
| Antenna Tower Controller inn-co GmbH | CO2000 | 017303 | NA | NA |
| Turn Table ADT. | TT100 | TT93021703 | NA | NA |
| Turn Table Controller ADT. | SC100 | SC93021703 | NA | NA |

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. The test was performed in HwaYa Chamber 3.
 4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 5. The FCC Site Registration No. is 988962.
 6. The IC Site Registration No. is IC 7450F-3.

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

Set the EUT under transmission condition continuously at specific channel frequency.



A D T

4.1.7 TEST RESULTS

ABOVE 1GHz DATA

| EUT TEST CONDITION | | MEASUREMENT DETAIL | |
|--------------------------|-----------------|--------------------|---------------------------|
| TESTED FREQUENCY | 2403 MHz | FREQUENCY RANGE | 1 ~ 25GHz |
| INPUT POWER | 1.5Vdc | DETECTOR FUNCTION | Peak (PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY | Chris Lin |
| TEST MODE | A | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4806.00 | 49.6 PK | 74.0 | -24.4 | 1.11 H | 300 | 10.90 | 38.70 |
| 2 | 4806.00 | 19.1 AV | 54.0 | -34.9 | 1.11 H | 300 | -19.60 | 38.70 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4906.00 | 49.3 PK | 74.0 | -24.7 | 1.07 V | 63 | 10.30 | 39.00 |
| 2 | 4906.00 | 18.8 AV | 54.0 | -35.2 | 1.07 V | 63 | -20.20 | 39.00 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (12 * 0.248 \text{ ms} / 100 \text{ ms}) = -30.5 \text{ dB}$
Please see page 24 for plotted duty.



| EUT TEST CONDITION | | MEASUREMENT DETAIL | |
|--------------------------|-----------------|--------------------|---------------------------|
| TESTED FREQUENCY | 2444 MHz | FREQUENCY RANGE | 1 ~ 25GHz |
| INPUT POWER | 1.5Vdc | DETECTOR FUNCTION | Peak (PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY | Chris Lin |
| TEST MODE | A | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4888.00 | 50.0 PK | 74.0 | -24.0 | 1.05 H | 23 | 11.00 | 39.00 |
| 2 | 4888.00 | 19.5 AV | 54.0 | -34.5 | 1.05 H | 23 | -19.50 | 39.00 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4888.00 | 51.1 PK | 74.0 | -22.9 | 1.05 V | 74 | 12.10 | 39.00 |
| 2 | 4888.00 | 20.6 AV | 54.0 | -33.4 | 1.05 V | 74 | -18.40 | 39.00 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (12 * 0.248 \text{ ms} / 100 \text{ ms}) = -30.5 \text{ dB}$
Please see page 24 for plotted duty.



| EUT TEST CONDITION | | MEASUREMENT DETAIL | |
|--------------------------|-----------------|--------------------|---------------------------|
| TESTED FREQUENCY | 2480 MHz | FREQUENCY RANGE | 1 ~ 25GHz |
| INPUT POWER | 1.5Vdc | DETECTOR FUNCTION | Peak (PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY | Chris Lin |
| TEST MODE | A | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4960.00 | 50.5 PK | 74.0 | -23.5 | 1.14 H | 89 | 11.30 | 39.20 |
| 2 | 4960.00 | 20.0 AV | 54.0 | -34.0 | 1.14 H | 89 | -19.20 | 39.20 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4960.00 | 50.1 PK | 74.0 | -23.9 | 1.16 V | 87 | 10.90 | 39.20 |
| 2 | 4960.00 | 19.6 AV | 54.0 | -34.4 | 1.16 V | 87 | -19.60 | 39.20 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (12 * 0.248 \text{ ms} / 100 \text{ ms}) = -30.5 \text{ dB}$
Please see page 24 for plotted duty.



A D T

| EUT TEST CONDITION | | MEASUREMENT DETAIL | |
|--------------------------|-----------------|--------------------|---------------------------|
| TESTED FREQUENCY | 2403 MHz | FREQUENCY RANGE | 1 ~ 25GHz |
| INPUT POWER | 1.5Vdc | DETECTOR FUNCTION | Peak (PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY | Chris Lin |
| TEST MODE | B | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4806.00 | 49.7 PK | 74.0 | -24.3 | 1.05 H | 87 | 11.00 | 38.70 |
| 2 | 4806.00 | 19.2 AV | 54.0 | -34.8 | 1.05 H | 87 | -19.50 | 38.70 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4806.00 | 50.5 PK | 74.0 | -23.5 | 1.28 V | 360 | 11.80 | 38.70 |
| 2 | 4806.00 | 20.0 AV | 54.0 | -34.0 | 1.28 V | 360 | -18.70 | 38.70 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
$$20 \log (\text{Duty cycle}) = 20 \log (12 * 0.248 \text{ ms} / 100 \text{ ms}) = -30.5 \text{ dB}$$

Please see page 24 for plotted duty.



| EUT TEST CONDITION | | MEASUREMENT DETAIL | |
|--------------------------|-----------------|--------------------|---------------------------|
| TESTED FREQUENCY | 2444 MHz | FREQUENCY RANGE | 1 ~ 25GHz |
| INPUT POWER | 1.5Vdc | DETECTOR FUNCTION | Peak (PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY | Chris Lin |
| TEST MODE | B | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4888.00 | 50.3 PK | 74.0 | -23.7 | 1.17 H | 25 | 11.30 | 39.00 |
| 2 | 4888.00 | 19.8 AV | 54.0 | -34.2 | 1.17 H | 25 | -19.20 | 39.00 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4888.00 | 49.6 PK | 74.0 | -24.4 | 1.10 V | 47 | 10.60 | 39.00 |
| 2 | 4888.00 | 19.1 AV | 54.0 | -34.9 | 1.10 V | 47 | -19.90 | 39.00 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (12 * 0.248 \text{ ms} / 100 \text{ ms}) = -30.5 \text{ dB}$
Please see page 24 for plotted duty.



| EUT TEST CONDITION | | MEASUREMENT DETAIL | |
|--------------------------|-----------------|--------------------|---------------------------|
| TESTED FREQUENCY | 2480 MHz | FREQUENCY RANGE | 1 ~ 25GHz |
| INPUT POWER | 1.5Vdc | DETECTOR FUNCTION | Peak (PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY | Chris Lin |
| TEST MODE | B | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4960.00 | 49.6 PK | 74.0 | -24.4 | 1.16 H | 45 | 10.40 | 39.20 |
| 2 | 4960.00 | 19.1 AV | 54.0 | -34.9 | 1.16 H | 45 | -20.10 | 39.20 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4960.00 | 51.1 PK | 74.0 | -22.9 | 1.18 V | 56 | 11.90 | 39.20 |
| 2 | 4960.00 | 20.6 AV | 54.0 | -33.4 | 1.18 V | 56 | -18.60 | 39.20 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (12 * 0.248 \text{ ms} / 100 \text{ ms}) = -30.5 \text{ dB}$
Please see page 24 for plotted duty.



| EUT TEST CONDITION | | MEASUREMENT DETAIL | |
|--------------------------|-----------------|--------------------|---------------------------|
| TESTED FREQUENCY | 2403 MHz | FREQUENCY RANGE | 1 ~ 25GHz |
| INPUT POWER | 1.5Vdc | DETECTOR FUNCTION | Peak (PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY | Chris Lin |
| TEST MODE | C | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 2390.00 | 38.4 PK | 74.0 | -35.6 | 1.74 H | 96 | 6.30 | 32.10 |
| 2 | 2390.00 | 29.3 AV | 54.0 | -24.7 | 1.74 H | 96 | -2.80 | 32.10 |
| 3 | 2400.00 | 46.1 PK | 74.0 | -27.9 | 1.18 H | 52 | 14.00 | 32.10 |
| 4 | 2400.00 | 15.6 AV | 54.0 | -38.4 | 1.18 H | 52 | -16.50 | 32.10 |
| 5 | *2403.00 | 91.1 PK | 114.0 | -22.9 | 1.38 H | 333 | 58.90 | 32.20 |
| 6 | *2403.00 | 60.6 AV | 94.0 | -33.4 | 1.38 H | 333 | 28.40 | 32.20 |
| 7 | 4806.00 | 49.1 PK | 74.0 | -24.9 | 1.31 H | 360 | 10.40 | 38.70 |
| 8 | 4806.00 | 18.6 AV | 54.0 | -35.4 | 1.31 H | 360 | -20.10 | 38.70 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 2390.00 | 41.0 PK | 74.0 | -33.0 | 1.12 V | 129 | 8.90 | 32.10 |
| 2 | 2390.00 | 26.8 AV | 54.0 | -27.2 | 1.12 V | 129 | -5.30 | 32.10 |
| 3 | 2400.00 | 37.4 PK | 74.0 | -36.6 | 1.12 V | 129 | 5.30 | 32.10 |
| 4 | 2400.00 | 6.9 AV | 54.0 | -47.1 | 1.12 V | 129 | -25.20 | 32.10 |
| 5 | *2403.00 | 82.4 PK | 114.0 | -31.6 | 1.74 V | 11 | 50.20 | 32.20 |
| 6 | *2403.00 | 51.9 AV | 94.0 | -42.1 | 1.74 V | 11 | 19.70 | 32.20 |
| 7 | 4806.00 | 50.4 PK | 74.0 | -23.6 | 1.29 V | 360 | 11.70 | 38.70 |
| 8 | 4806.00 | 19.9 AV | 54.0 | -34.1 | 1.29 V | 360 | -18.80 | 38.70 |

- REMARKS:**
- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 - Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 - The other emission levels were very low against the limit.
 - Margin value = Emission level – Limit value.
 - * * : Fundamental frequency
 - The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (12 * 0.248 \text{ ms} / 100 \text{ ms}) = -30.5 \text{ dB}$
Please see page 24 for plotted duty.



| EUT TEST CONDITION | | MEASUREMENT DETAIL | |
|--------------------------|-----------------|--------------------|---------------------------|
| TESTED FREQUENCY | 2444 MHz | FREQUENCY RANGE | 1 ~ 25GHz |
| INPUT POWER | 1.5Vdc | DETECTOR FUNCTION | Peak (PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY | Chris Lin |
| TEST MODE | C | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | *2444.00 | 92.1 PK | 114.0 | -21.9 | 1.30 H | 323 | 59.80 | 32.30 |
| 2 | *2444.00 | 61.6 AV | 94.0 | -32.4 | 1.30 H | 323 | 29.30 | 32.30 |
| 3 | 4888.00 | 49.4 PK | 74.0 | -24.6 | 1.00 H | 350 | 10.40 | 39.00 |
| 4 | 4888.00 | 18.9 AV | 54.0 | -35.1 | 1.00 H | 350 | -20.10 | 39.00 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | *2444.00 | 83.2 PK | 114.0 | -30.8 | 1.19 V | 0 | 50.90 | 32.30 |
| 2 | *2444.00 | 52.7 AV | 94.0 | -41.3 | 1.19 V | 0 | 20.40 | 32.30 |
| 3 | 4888.00 | 50.6 PK | 74.0 | -23.4 | 1.22 V | 5 | 11.60 | 39.00 |
| 4 | 4888.00 | 20.1 AV | 54.0 | -33.9 | 1.22 V | 5 | -18.90 | 39.00 |

REMARKS:

- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- The other emission levels were very low against the limit.
- Margin value = Emission level – Limit value.
- “ * “ : Fundamental frequency
- The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (12 * 0.248 \text{ ms} / 100 \text{ ms}) = -30.5 \text{ dB}$
Please see page 24 for plotted duty.





| EUT TEST CONDITION | | MEASUREMENT DETAIL | |
|--------------------------|-----------------|--------------------|---------------------------|
| TESTED FREQUENCY | 2480 MHz | FREQUENCY RANGE | 1 ~ 25GHz |
| INPUT POWER | 1.5Vdc | DETECTOR FUNCTION | Peak (PK) Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY | Chris Lin |
| TEST MODE | C | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | *2480.00 | 90.5 PK | 114.0 | -23.5 | 1.16 H | 320 | 58.20 | 32.30 |
| 2 | *2480.00 | 60.0 AV | 94.0 | -34.0 | 1.16 H | 320 | 27.70 | 32.30 |
| 3 | 2483.50 | 45.5 PK | 74.0 | -28.5 | 1.15 H | 23 | 13.20 | 32.30 |
| 4 | 2483.50 | 15.0 AV | 54.0 | -39.0 | 1.15 H | 23 | -17.30 | 32.30 |
| 5 | 4960.00 | 50.8 PK | 74.0 | -23.2 | 1.09 H | 62 | 11.60 | 39.20 |
| 6 | 4960.00 | 20.3 AV | 54.0 | -33.7 | 1.09 H | 62 | -18.90 | 39.20 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | *2480.00 | 82.6 PK | 114.0 | -31.4 | 1.71 V | 353 | 50.30 | 32.30 |
| 2 | *2480.00 | 52.1 AV | 94.0 | -41.9 | 1.71 V | 353 | 19.80 | 32.30 |
| 3 | 2483.50 | 37.6 PK | 74.0 | -36.4 | 1.00 V | 74 | 5.30 | 32.30 |
| 4 | 2483.50 | 7.1 AV | 54.0 | -46.9 | 1.00 V | 74 | -25.20 | 32.30 |
| 5 | 4960.00 | 50.5 PK | 74.0 | -23.5 | 1.14 V | 85 | 11.30 | 39.20 |
| 6 | 4960.00 | 20.0 AV | 54.0 | -34.0 | 1.14 V | 85 | -19.20 | 39.20 |

- REMARKS:**
- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 - Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 - The other emission levels were very low against the limit.
 - Margin value = Emission level – Limit value.
 - “ * “ : Fundamental frequency
 - The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (12 * 0.248 \text{ ms} / 100 \text{ ms}) = -30.5 \text{ dB}$
Please see page 24 for plotted duty.



A D T



$$20 \log (\text{Duty cycle}) = 20 \log (12 * 0.248 \text{ ms} / 100 \text{ ms}) = -30.5 \text{ dB}$$



A D T

BELOW 1GHz WORST-CASE DATA

| EUT TEST CONDITION | | MEASUREMENT DETAIL | |
|--------------------------|-----------------|--------------------|---------------|
| TESTED FREQUENCY | 2403 MHz | FREQUENCY RANGE | Below 1000MHz |
| INPUT POWER | 1.5Vdc | DETECTOR FUNCTION | Quasi-Peak |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY | Chris Lin |
| TEST MDDE | A | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 57.12 | 30.9 QP | 40.0 | -9.1 | 2.00 H | 358 | 17.30 | 13.60 |
| 2 | 199.05 | 31.1 QP | 43.5 | -12.4 | 1.00 H | 270 | 20.00 | 11.10 |
| 3 | 265.16 | 37.4 QP | 46.0 | -8.6 | 1.00 H | 272 | 23.60 | 13.80 |
| 4 | 381.82 | 33.5 QP | 46.0 | -12.5 | 2.00 H | 178 | 16.40 | 17.10 |
| 5 | 527.64 | 26.7 QP | 46.0 | -19.3 | 1.25 H | 275 | 5.90 | 20.80 |
| 6 | 797.89 | 31.0 QP | 46.0 | -15.0 | 1.50 H | 284 | 5.50 | 25.50 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 166.00 | 27.9 QP | 43.5 | -15.6 | 1.00 V | 258 | 14.20 | 13.70 |
| 2 | 265.16 | 35.8 QP | 46.0 | -10.2 | 1.49 V | 202 | 22.00 | 13.80 |
| 3 | 385.70 | 31.9 QP | 46.0 | -14.1 | 1.00 V | 293 | 14.70 | 17.20 |
| 4 | 624.85 | 25.4 QP | 46.0 | -20.6 | 1.49 V | 217 | 2.60 | 22.80 |
| 5 | 797.89 | 30.8 QP | 46.0 | -15.2 | 1.24 V | 255 | 5.30 | 25.50 |
| 6 | 900.94 | 26.8 QP | 46.0 | -19.2 | 1.24 V | 346 | -0.20 | 27.00 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



| EUT TEST CONDITION | | MEASUREMENT DETAIL | |
|--------------------------|-----------------|--------------------|---------------|
| TESTED FREQUENCY | 2403 MHz | FREQUENCY RANGE | Below 1000MHz |
| INPUT POWER | 1.5Vdc | DETECTOR FUNCTION | Quasi-Peak |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY | Chris Lin |
| TEST MDDE | B | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 57.12 | 30.5 QP | 40.0 | -9.5 | 1.99 H | 205 | 16.90 | 13.60 |
| 2 | 265.16 | 38.4 QP | 46.0 | -7.6 | 1.00 H | 260 | 24.60 | 13.80 |
| 3 | 374.04 | 33.4 QP | 46.0 | -12.6 | 1.00 H | 163 | 16.50 | 16.90 |
| 4 | 527.64 | 27.7 QP | 46.0 | -18.3 | 1.24 H | 292 | 6.90 | 20.80 |
| 5 | 708.46 | 24.0 QP | 46.0 | -22.0 | 1.24 H | 4 | 0.20 | 23.80 |
| 6 | 797.89 | 31.1 QP | 46.0 | -14.9 | 1.50 H | 288 | 5.60 | 25.50 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 166.00 | 27.5 QP | 43.5 | -16.0 | 1.00 V | 238 | 13.80 | 13.70 |
| 2 | 265.16 | 35.7 QP | 46.0 | -10.3 | 1.50 V | 332 | 21.90 | 13.80 |
| 3 | 385.70 | 31.6 QP | 46.0 | -14.4 | 1.00 V | 294 | 14.40 | 17.20 |
| 4 | 624.85 | 25.2 QP | 46.0 | -20.8 | 1.00 V | 179 | 2.40 | 22.80 |
| 5 | 797.89 | 31.3 QP | 46.0 | -14.7 | 1.25 V | 178 | 5.80 | 25.50 |
| 6 | 900.94 | 27.3 QP | 46.0 | -18.7 | 1.25 V | 206 | 0.30 | 27.00 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



| EUT TEST CONDITION | | MEASUREMENT DETAIL | |
|--------------------------|-----------------|--------------------|---------------|
| TESTED FREQUENCY | 2403 MHz | FREQUENCY RANGE | Below 1000MHz |
| INPUT POWER | 1.5Vdc | DETECTOR FUNCTION | Quasi-Peak |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY | Chris Lin |
| TEST MDDE | C | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 57.12 | 30.7 QP | 40.0 | -9.3 | 2.00 H | 244 | 17.10 | 13.60 |
| 2 | 199.05 | 31.3 QP | 43.5 | -12.2 | 1.00 H | 265 | 20.20 | 11.10 |
| 3 | 265.16 | 38.1 QP | 46.0 | -7.9 | 1.00 H | 262 | 24.30 | 13.80 |
| 4 | 379.87 | 33.3 QP | 46.0 | -12.7 | 2.00 H | 181 | 16.30 | 17.00 |
| 5 | 527.64 | 26.5 QP | 46.0 | -19.5 | 1.25 H | 281 | 5.70 | 20.80 |
| 6 | 797.89 | 29.0 QP | 46.0 | -17.0 | 1.00 H | 15 | 3.50 | 25.50 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 199.05 | 29.5 QP | 43.5 | -14.0 | 1.00 V | 57 | 18.40 | 11.10 |
| 2 | 265.16 | 35.9 QP | 46.0 | -10.1 | 1.50 V | 202 | 22.10 | 13.80 |
| 3 | 389.59 | 31.7 QP | 46.0 | -14.3 | 1.00 V | 298 | 14.40 | 17.30 |
| 4 | 529.58 | 24.1 QP | 46.0 | -21.9 | 1.00 V | 345 | 3.30 | 20.80 |
| 5 | 624.85 | 24.7 QP | 46.0 | -21.3 | 1.00 V | 177 | 1.90 | 22.80 |
| 6 | 799.84 | 31.7 QP | 46.0 | -14.3 | 1.24 V | 192 | 6.10 | 25.60 |

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

7. APPENDIX A – MODIFICATION RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---