



RF EXPOSURE REPORT

REPORT NO.: SA140430E05 R1

MODEL NO.: 1653

FCC ID: C3K1653

RECEIVED: Apr. 30, 2014

TESTED: July 11, 2014

ISSUED: Sep. 02, 2014

APPLICANT: Microsoft Corporation

ADDRESS: One Microsoft Way Redmond WA 98052

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT.....	5
3. MPE CALCULATION FORMULA	5
4. CLASSIFICATION.....	5
5. ANTENNA GAIN.....	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	7

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA140430E05	Original release	Aug. 06, 2014
SA140430E05 R1	Modified section 5: Connector Type.	Sep. 02, 2014





A D T

1. CERTIFICATION

PRODUCT: 802.11a/b/g/n 2T2R dual-band wireless LAN radio
BRAND NAME: Microsoft
MODEL NO.: 1653
TEST SAMPLE: ENGINEERING SAMPLE
APPLICANT: Microsoft Corporation
TESTED DATE: July 11, 2014
STANDARDS: FCC Part 2 (Section 2.1091)
IEEE C95.1

The above equipment (Model: 1653) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE:** Sep. 02, 2014
(Elsie Hsu, Specialist)

APPROVED BY :  , **DATE:** Sep. 02, 2014
(May Chen, Manager)

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Accessory Radio							
Ant. No.	Brand	Model	Ant. Gain(dBi) <including cable loss>	Frequency range (GHz ~ GHz)	Ant. Type	Connector Type	Cable Length (mm)
1	Microsoft	NA	2.2	2.4~2.5	PCB	i-PEX	295
	Microsoft	NA	3.14	5.15~5.85	PCB	i-PEX	295
Network Radio							
Ant. No.	Transmitter Circuit	Brand	Model	Ant. Gain(dBi) <including cable loss>	Frequency range (GHz ~ GHz)	Ant. Type	Connector Type
1	Chain (0)	Microsoft	NA	4.79	2.4~2.5	PCB	NA
				3.49	5.15~5.85		
2	Chain (1)	Microsoft	NA	1.87	2.4~2.5	PCB	NA
				2.63	5.15~5.85		

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

For Accessory Radio:

15.247(2.4GHz):

FREQUENCY- (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	588.844	2.2	20	0.19441	1

15.407(5GHz_ U-NII-1):

FREQUENCY (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm ²)
5180 ~ 5240	34.041	3.14	20	0.01396	1

15.407(5GHz_ U-NII-3):

FREQUENCY (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm ²)
5745 ~ 5825	36.898	3.14	20	0.01513	1

For Network Radio:

15.247(2.4GHz):

FREQUENCY– (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	629.359	6.46	20	0.55415	1

Note: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 6.46\text{dBi}$

15.407(5GHz_ U-NII-1):

FREQUENCY (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm ²)
5180 ~ 5240	168.582	6.08	20	0.13600	1

Note: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 6.08\text{dBi}$

15.407(5GHz_ U-NII-3):

FREQUENCY (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm ²)
5745 ~ 5825	119.519	6.08	20	0.09642	1

Note: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 6.08\text{dBi}$

CONCLUSION:

The (WiFi) Accessory Radio (1x1) and Features (WiFi) Network Radio (2x2) can transmit simultaneously as below table, the formula of calculated the MPE is:

Condition	Technology	
	Networking Radio(2x2)	Accessory radio(1x1)
1	2.4GHz Band	5GHz U-NII-1 Band
2	2.4GHz Band	5GHz U-NII-3 Band
3	5GHz U-NII-1 Band	2.4GHz Band
4	5GHz U-NII-1 Band	5GHz U-NII-3 Band
5	5GHz U-NII-3 Band	2.4GHz Band
6	5GHz U-NII-3 Band	5GHz U-NII-1 Band

$$CPD_1 / LPD_1 + CPD_2 / LPD_2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

For Network Radio (2.4G) + Accessory Radio (5G_U-NII-1):

Therefore, the worst-case situation is $0.55415 / 1 + 0.01396 / 1 = 0.568$, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

For Network Radio (2.4G) + Accessory Radio (5G_U-NII-3):

Therefore, the worst-case situation is $0.55415 / 1 + 0.01513 / 1 = 0.569$, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

For Network Radio (5G_U-NII-1) + Accessory Radio (2.4G):

Therefore, the worst-case situation is $0.13600 / 1 + 0.19441 / 1 = 0.330$, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

For Network Radio (5G_U-NII-1) + Accessory Radio (5G_U-NII-3):

Therefore, the worst-case situation is $0.13600 / 1 + 0.01513 / 1 = 0.151$, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

For Network Radio (5G_U-NII-3) + Accessory Radio (2.4G):

Therefore, the worst-case situation is $0.09642 / 1 + 0.19441 / 1 = 0.291$, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

For Network Radio (5G_U-NII-3) + Accessory Radio (5G_U-NII-1):

Therefore, the worst-case situation is $0.09642 / 1 + 0.01396 / 1 = 0.110$, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---