

RADIO TEST REPORT

For

MODEL NO.: 1707 FCC ID: C3K1707 IC ID: 3048A-1707

Test Report No. R-TR371-FCCIC-DFS-2 Issue Date: 14 Oct 2016

FCC CFR47 Part 15 Subpart E Innovation, Science and Economic Development Canada RSS-247 Issue 1

> Prepared by Microsoft EMC Laboratory 17760 NE 67th Ct, Redmond WA, 98052, U.S.A. 425-421-9799 <u>sajose@microsoft.com</u>





1 Record of Revisions

Revision	Date	Section	Page(s)	Summary of Changes	Author/Revised By:
1.0	09/23/2016	All	All	Version 1.0	Daniel Salinas
2.0	10/14/2016	4 5	7 10	Updated Product description. Updated EUT description from "slave" to "client".	Daniel Salinas
	1				



Table of Contents

1	Rec	ord of Revisions	2
2	Dev	iations from Standards	6
3	Fac	ilities and Accreditations	6
	3.1	Test Facility	6
	3.2	Accreditations	6
4	Pro	duct Description	7
	4.1	Test Configurations	8
	4.2	Environmental Conditions	8
	4.3	Antenna Requirements	8
	4.4	Equipment Modifications	9
	4.5	Dates of Testing	9
5	Tes	t Results Summary	10
6	Tes	t Equipment List	11
7	Tes	t Method	12
	7.1	Antenna port conducted measurements	12
	7.2	Test Setup Diagrams	12
	7.3	Radar Waveform Verification	13
	7.4	Channel Loading	16
	7.4.	1 Test Method	16
8	Tes	t Results	18
	8.1	Channel Move Time	18
	8.1.	1 Test Requirement:	18
	8.1.	2 Test Method:	18
	8.1.	3 Limits:	18
	8.1.	4 Test Results:	18
	8.1.	5 Test Data	
	8.1. 8.2	5 Test Data Channel Closing Transmission Time	
	8.1. 8.2 8.2.	 5 Test Data Channel Closing Transmission Time 1 Test Requirement: 	
	8.1. 8.2 8.2. 8.2.	 5 Test Data Channel Closing Transmission Time 1 Test Requirement: 2 Test Method: 	
	8.1. 8.2 8.2. 8.2. 8.2.	 5 Test Data Channel Closing Transmission Time 1 Test Requirement: 2 Test Method: 3 Limits: 	
	8.1. 8.2 8.2. 8.2. 8.2. 8.2.	 5 Test Data Channel Closing Transmission Time 1 Test Requirement: 2 Test Method: 3 Limits: 4 Test Results: 	



8.3	Non	n-Occupancy Period	.24
8.3	.1	Test Requirement:	.24
8.3	.2	Test Method:	.24
8.3	.3	Limits:	.24
8.3	.4	Test Results:	.24
8.3	.5	Test Data:	.24



Test Report Attestation

Microsoft Corporation Model: 1707

FCC ID: C3K1707 IC ID: 3048A-1707

Applicable Standards

Specification	Test Result
FCC 47CFR Rule Parts 15.407 (DFS)	Pass
Innovation, Science and Economic Development Canada RSS-247 Issue 1 (DFS)	Pass

Microsoft EMC Laboratory attests that the product model identified in this report has been tested to and meets the requirements identified in the above standards. The test results in this report solely pertains to the specific sample tested, under the conditions and operating modes as provided by the customer.

This report shall not be used to claim product certification, approval, or endorsement by A2LA or any agency of any Government. Reproduction, duplication or publication of extracts from this test report is prohibited and requires prior written approval of Microsoft EMC Laboratory.

This report replaces the previously issued report #R-TR371-FCCIC-DFS-1 issued by Microsoft EMC labs on 9/2/32016.

Written By: Daniel Salinas Radio Test Lead

Reviewed/ Issued By: Sajay Jose EMC/RF Compliance Lab Manager



2 Deviations from Standards

None.

3 Facilities and Accreditations

3.1 Test Facility

All test facilities used to collect the test data are located at Microsoft EMC Laboratory,

17760 NE 67th Ct, Redmond WA, 98052, USA

3.2 Accreditations

The lab is established and follows procedures as outlined in IEC/ISO 17025 and A2LA accreditation requirements. A2LA Accredited Testing Certificate Number: 3472.01 FCC Registration Number: US1141 IC Site Registration Numbers: 3048A-3, 3048A-4

4 Product Description

Company Name:	Microsoft Corporation	
Address:	One Microsoft Way	
City, State, Zip:	Redmond, WA 98052-6399	
Customer Contact:	Jennifer Liu	
Functional Description of the EUT:	PC with IEEE 802.11a/b/g/n/ac MIMO supporting 20/40/80 MHz bandwidths, Bluetooth and additional 802.11n Radio.	
Model:	1707	
FCC ID:	C3K1707	
IC ID:	3048A-1707	
Radio under test:	IEEE 802.11a/n/ac with 20MHz, 40MHz and 80MHz Signal Bandwidths	
Modulation(s):	OFDM – BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM	
EUT Classification:	UNII Client Device without radar detection	
RF Conducted port impedance:	50 Ω in the frequency range of operation	
Antenna Gain Measurement Verification:	N/A – Measurements were performed using conducted test methods	
Transmit Power Control:	The EUT does not implement TPC	
Wireless Bridge or Mesh Capability:	The device does not implement bridge or mesh modes.	
Power – Cycle Time:	N/A. The EUT is a client device without radar detection	
Radar Waveform Information:	The EUT does not detect or store information regarding radar waveforms	
Equipment Design State:	Prototype/Production Equivalent	
Equipment Condition:	Good	
Test Sample Details:	RF Conducted Test Sample SN: 000008661958	



4.1 Test Configurations

The device was setup in normal operation and connected wirelessly to an 802.11 access point on 20 MHz and 40 MHz bandwidth channels. The EUT supports 80 MHz bandwidths, which were excluded from measurements (based on guidance from KDB 905462 D03 v01r01). A host laptop was configured to transmit traffic by using an .MP4 video file to the EUT. Iperf was used to generate a continuous amount of traffic while the video was streamed simultaneously to meet channel loading conditions and allow for random pinging intervals and dynamically allocate the talk/listen ratio.

Aeroflex PXI 3001C DFS test system was used to monitor traffic and generate radar pulses. Measurements were performed on the main antenna, Chain B of the EUT. DFS signals were injected into 5 GHz Tx/Rx port B of the Master device.

4.2 Environmental Conditions

Ambient air temperature of the test site was within the range of 10 °C to 40 °C (50 °F to 104 °F) unless the EUT specified testing over a different temperature range. Humidity levels were in the range of 10% to 90% relative humidity. Testing conditions were within tolerance and any deviations required from the EUT are reported.

4.3 Antenna Requirements

The antennas are internal, permanently attached and there are no provisions for connection to an external antenna.

Antenna Gain					
Frequency Band (MHz)	Chain A MIMO Wi-Fi Antenna Peak Gain (dBi)	Chain B Main Antenna Wi-Fi Peak Gain (dBi)			
UNII Band 1- 5150 to 5250	5.59	5.37			
UNII Band 2a – 5250 to 5350	6.41	6.19			
UNII Band 2c – 5470 to 5725	6.89	6.71			
UNII Band 3 – 5725 to 5850	5.05	5.56			

Simultaneous transmission on both transmit chains was observed to be the worst case mode of operation for all test cases. Since the transmit signals are completely uncorrelated, the combined gain is calculated using the following formula as specified in KDB 662911 D01 Multiple Transmitter Output v02r01:

Directional gain = $10\log \left[(10^{G1/10} + 10^{G2/10} + ... + 10^{GN/10})/N_{ANT} \right] dBi$

Combined Directional Antenna Gain			
Frequency Band	Combined Directional Gain		
UNII Band 1- 5150 to 5250	5.48		
UNII Band 2a – 5250 to 5350	6.3		
UNII Band 2c – 5470 to 5725	6.8		
UNII Band 3 – 5725 to 5850	5.31		



4.4 Equipment Modifications

No modifications were made during testing.

4.5 Dates of Testing

Testing was performed from July 22th – August 4, 2016.



5 Test Results Summary

Test Description	FCC CFR 47/ ISED Rule Part	Limit	Test Result
In-Service Monitoring	15.407(h)(2)(iv) RSS-247 [6.3]	Monitor co-channel radar	N/A*
Channel Availability Check	15.407 (h)(2)(ii) RSS-247 [6.3]	60s detection	N/A*
Channel Move Time	15.407 (h)(2)(iii) RSS-247 [6.3]	10s	Pass
Channel Closing Transmission Time	15.407 (h)(2)(iii) RSS-247 [6.3]	200ms +aggregate 60ms over remaining 10s period	Pass
Non-occupancy Period	15.407 (h)(2)(iv) RSS-247 [6.3]	30 minutes	Pass

*Note: The EUT is a Client device without radar detection.



6 Test Equipment List

Manufacturer	Description	Model #	Asset #	FCC ID	Calibration Due
Aeroflex	PXI Chassis	3001C	RF-132	N/A	05/27/2017
Cisco	Cisco Aironet ISO Access Point	AIR-AP1252AG- A-K9	RF-331	LDK 102061 LDK 102062	N/A*
Agilent	Spectrum Analyzer	N9030A	EMC-607	N/A	05/26/2017
Agilent	Microwave Analyzer	N9918A	EMC-728	N/A	04/13/2017
MegaPhase	RF Cable	KB18-S1S1-79	EMC- 1042	N/A	N/A*
Rosenberger	RF Cable	L72-449-1830	EMC-123	N/A	N/A*
Argosy	RF Cable	B101	RF-271	N/A	N/A [*]
Rosenberger	RF Cable	L72-450-1830	RF-106	N/A	N/A*
Pasternack	RF Cable	PE304-200CM	RF-445	N/A	N/A*
Matura	RF-Cable	MXHQ87WA3000	RF-392	N/A	N/A*
Fairview Microwave	10dB Attenuator	SA18N5W	RF-418	N/A	N/A [*]
Pasternack	3dB Attenuator	7092-3	RF-154	N/A	N/A*
Pasternack	Attenuator	PE7005-20	RF-085	N/A	N/A*
Pasternack	6dB Attenuator	PE7087-6	RF-436	N/A	N/A*
Pasternack	3dB Attenuator	PE7092-3	RF-440	N/A	N/A*
Pasternack	20dB Attenuator	PE7087-20	RF-334	N/A	N/A [*]
Pasternack	20dB Attenuator	PE7005-20	RF-082	N/A	N/A*
Pasternack	6dB Attenuator	PE7087-6	RF-437	N/A	N/A*
L-Com	RF Combiner	SC5802N	RF-048	N/A	N/A*
L-Com	RF Combiner	SC5802N	RF-049	N/A	N/A*



7 Test Method

7.1 Antenna port conducted measurements

Antenna port conducted measurements were performed on a bench-top setup consisting of a spectrum analyzer, splitters/combiners (as necessary), attenuators, and pre-characterized RF cables. The Aeroflex PXI 3001C DFS test system monitored traffic and generated radar bursts.

The correction factors between the EUT, support equipment, radar test generator and the spectrum analyzer are added internally in the Aeroflex test system.



7.2 Test Setup Diagrams

Figure 1. Test Setup for Antenna Port Conducted Measurements

7.3 Radar Waveform Verification



Device Type	Device	Min. Output Power (dBm)	Max Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Required Radar Detection Threshold Level (dBm)
Master	CISCO AIR-AP1252AG-A-K9	-1	20	6	26	-63
Client	Microsoft Model 1707	5.5	18.5	6.8	25.3	N/A

DFS Measurement	Radar Type
Channel Move Time	0
Channel Closing Transmission Time	0
Non-Occupancy Period	0

Rader Type	Frequency (MHz)	Level (dBm)	Pulse count	Pulse width (µs)	Pulse Repetition Interval (ms)
0	5520	-63.06	18	1.020	1.428
0	5310	-63.54	18	1.057	1.428

Note: 80 MHz bandwidths were not tested, due to the lack of 80 MHz Master devices available on the market (based on guidance from KDB 905462 D03 v01r01).



	sctrum Analyzer - Swept	SA							- 6 -
X	RF 50 Ω	DC		SENSE:INT	AL	IGN AUTO		10:31:41	AM Aug 04, 2016
Marker 1	9.13800 ms		PNO: Fast 🔸	Trig Delay Trig: Video #Atten: 0 c	2.000 ms B	Avg Type:	Log-Pwr	Th	DET P NNNN
10 dB/div	Ref -40.00 dE	3m						Mkr1 -63	9.138 ms 3.06 dBn
Log									
-50.0			.1						
-50.0									TRIG LM
-70.0 shi wike		et for reduce			UNION OF A		needolooyd yf		and Markinson
-80.0									
-90.0									
-100									
-110									
-120									
-130									
	520000000 CH	7							Span 0 Hz
Center 5.5 Res BW 8	MHz	2	#VB	W 50 MHz			Sweep	30.00 ms	(30000 pts

Figure 3. Radar Burst Level at -63dBm: Radar Type 0 (5520 MHz 20 MHz BW)



Figure 4. Radar Pulse width: Radar Type 0 (5520 MHz 20 MHz BW)



Figure 5. Radar Pulse Repetition Interval: Radar Type 0 (5520 MHz 20 MHz BW)



Marker 1 22.9180 ms PHO: Fast Hours and Hours and H	Agilent Spect	rum Analyzer - Swept S/	A							
Mining Fig. 22.9 Too Fins PRO: Finst Trig: Video Wig Type Color Mkr1 22.92 mm 000 Mkr1 22.92 mm -63.54 dBn -63.54 dBn -63.54 dBn -63.54 dBn 000 Mkr1 22.92 mm -63.54 dBn -63.56 dBn		RF 50 Q DC			SENSE:INT	4 500 me	IGNAUTO	og.Pwr	03:32:19	PM 3ul22, 2016
Mkr1 22.92 mt Common and and the second	Marker	22.9160 ms	P	NO: Fast 🔸	Trig: Video #Atten: 0 d	B	Ang type.	Log-i mi		DET P N N N N
00 00<	10.101.0	D-6 50 00 dD							Mkr1	22.92 ms
40.0 1 1 1 1 1 1000000000000000000000000000000000000		Rer -SU.UU dBr	n							
4000 40000 4000 <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>.1</td><td></td><td></td></t<>								.1		
2000 20000 20000	-60.0							••••		TRIG LVI
Openalistic description Description <thdescription< td=""><td>-70.0</td><td></td><td>Land Land La</td><td></td><td></td><td></td><td>1 1 1 1 1</td><td>that a</td><td></td><td>4</td></thdescription<>	-70.0		Land Land La				1 1 1 1 1	that a		4
301 100 <td>IN STATE</td> <td>Internation and a second state</td> <td>adificial constraint</td> <td>de la companya Nova</td> <td>ale de la construction de la constru</td> <td>Anihard Lines</td> <td>ind and a little build</td> <td>and the second second</td> <td>antiklinis bis bi an</td> <td>in makenandelet</td>	IN STATE	Internation and a second state	adificial constraint	de la companya Nova	ale de la construction de la constru	Anihard Lines	ind and a little build	and the second	antiklinis bis bi an	in makenandelet
300	-ab.u pite-ab	Indefinition of the state	other privile and a	in the states	dia di kitata a	AND A DECK	and the light	and the second second	uppen (ppl age	indu alim
100	-90.0									
110 110 110 110 120 110 110 110 130 110 110 110 140 110 110 110 140 110 110 110 140 110 110 110 140 110 110 110 140 110 110 110 140 110 110 110 140 110 110 110 140 110 110 110 140 110 110 110 140 110 110 110 140 110 110 110 140 110 110 110 110 140 110 110 110 110 110 140 110 110 110 110 110 110 140 110 110 110 110 110 110 <td< td=""><td>.100</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>	.100									
.110										
1:00	-110									
.100	-120									
100 100 <td></td>										
Span 0 Hz Span 0 Hz <t< td=""><td>-130</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>	-130									
Center 5.310000000 GHz Span 0 Hz Res BW 8 MHz #VBW 50 MHz Sweep 30.00 ms (30000 pts	-140									
Center 5.31000000 GHz Span 0 Hz Res BW 8 MHz #VBW 50 MHz Sweep 30.00 ms (30000 pts)										
Res BW 8 MHZ #VBW 50 MHZ Sweep 30.00 ms (30000 pts	Center 5.	310000000 GHz								Span 0 Hz
	Res BW	5 MHZ		#VB	W SU MHZ			Sweep	30.00 ms	(30000 pts

Figure 6. Radar Burst Level at -63dBm: Radar Type 0 (5310 MHz 40 MHz BW)



Figure 7. Radar Pulse width: Radar Type 0 (5310 MHz 40 MHz BW)



Figure 8. Radar Pulse Repetition Interval: Radar Type 0 (5310 MHz 40 MHz BW)

7.4 Channel Loading

7.4.1 Test Method

Channel Loading measurements were taken with a spectrum analyzer. A .csv file was generated and Channel Loading was calculated using that measured data.

Channel Loading is calculated using the following formula:

Channal Loading (04)	(%) -	On Time	v100
Chunnel Louding (%)	_	(On Time + Off Time)	×100

Frequency (MHz)	Signal Bandwidth (MHz)	Total On Time (ms)	On Time + Off Time (ms)	Channel Loading (%)
5520	20	26.57	100	26.57
5310	40	41.65	100	41.65



Figure 9. Channel Loading (5520 MHz 20 MHz BW)





Figure 10. Channel Loading (5310 MHz 40 MHz BW)



8 Test Results

8.1 Channel Move Time

8.1.1 **Test Requirement:**

FCC CFR 47 Rule Part 15.407 (h)(2)(iv)

ISED Canada RSS-247 [6.3]

8.1.2 Test Method:

Measurements were performed according to the procedures defined in KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

8.1.3 Limits:

After a radar signal is detected, the device shall cease all transmissions on the operating channel within 10 seconds.

8.1.4 Test Results:

Pass.

The EUT ceased transmission on the channel within 200 ms and there was less than an aggregate of 60ms transmission time in a 10s period.

8.1.5 **Test Data**

8.1.5.1 Channel Move Time

Frequency (MHz)	Signal Bandwidth (MHz)	Channel Move Time (s)	Limit (s)	Result
5520	20	0.66	10	Pass
5310	40	0.10	10	Pass



FCC ID: C3K1707 IC ID: 3048A-1707



Figure 11. Channel Move Time 20 MHz Bandwidth



FCC ID: C3K1707 IC ID: 3048A-1707



Figure 12. Channel Move Time 40 MHz Bandwidth



8.2 Channel Closing Transmission Time

8.2.1 Test Requirement: FCC CFR 47 Rule Part 15.407 (h)(2)(iii)

ISED Canada RSS-247 [6.3]

8.2.2 Test Method:

Measurements were performed according to the procedures defined in KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

8.2.3 Limits:

After the radar burst has been applied, the EUT shall cease normal transmission on the channel within 200 ms starting at the beginning of the channel move time. Control signaling required to facilitate a channel move (an aggregate of 60 ms) over the remaining 10-second period of the channel move time is permissible.

8.2.4 **Test Results:**

Pass.

The EUT ceased transmission on the channel within the allotted time.

8.2.5 Test Data

Channel Bandwidth (MHz)	Channel Closing Transmission Time (ms)	Channel Closing Transmission Time Limit + Aggregate Control Signaling Time Limit (ms)	Result
20	0.261	200 +60	Pass
40	0.006	200 +60	Pass





Figure 13. Channel Closing Transmission Time (5520 MHz 20 MHz BW)



FCC ID: C3K1707 IC ID: 3048A-1707



Transmission Level

Figure 14. Channel Closing Transmission Time (5310 MHz 40 MHz BW)



8.3 Non-Occupancy Period

8.3.1 Test Requirement: FCC CFR 47 Rule Part 15.407 (h)(2)(iv)

ISED Canada RSS-247 [6.3]

8.3.2 Test Method:

Measurements were performed according to the procedures defined in KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

8.3.3 Limits:

A channel that has been flagged as containing a radar system, either by a channel availability check or in-service monitoring, is subject to a non-occupancy period of at least 30 minutes. The non-occupancy period starts at the time when the radar system is detected.

8.3.4 **Test Results:**

Pass.

After radar was detected by the master device, the EUT did not transmit on the tested channel for at least 30 minutes.

8.3.5 **Test Data:**

Plot shown for 2000 seconds sweep time.



Figure 15. 30 Minute Non-Occupancy Period



End of Report